

# MATERIAL SAFETY DATA SHEET

**Product Trade Name:** **OPTIFLO-II DELAYED RELEASE BREAKER**

**Revision Date:** 20-Dec-2012

## **1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**

**Statement of Hazardous Nature** Hazardous according to the criteria of NOHSC, Dangerous Goods according to the criteria of ADG.

**Manufacturer/Supplier** Halliburton Australia Pty. Ltd.  
15 Marriott Road  
Jandakot  
WA 6164  
Australia

ACN Number: 009 000 775  
Telephone Number: 61 (08) 9455 8300  
Fax Number: 61 (08) 9455 5300

**Product Emergency Telephone**  
Australia: 08-64244950  
Papua New Guinea: 05 1 281 575 5000  
New Zealand: 06-7559274

**Fire, Police & Ambulance - Emergency Telephone**  
Australia: 000  
Papua New Guinea: 000  
New Zealand: 111

### **Identification of Substances or Preparation**

**Product Trade Name:** OPTIFLO-II DELAYED RELEASE BREAKER

**Synonyms:** None

**Chemical Family:** Oxidant

**UN Number:**, UN1444

**Dangerous Goods Class:** 5.1

**Subsidiary Risk:** None

**Hazchem Code:** 2W

**Poisons Schedule:** None Allocated

**Application:** Breaker

**Prepared By** Chemical Compliance

Telephone: 1-580-251-4335

e-mail: fdunexchem@halliburton.com

## **2. COMPOSITION/INFORMATION ON INGREDIENTS**

Substances	CAS Number	PERCENT	Australia NOHSC	New Zealand WES	ACGIH TLV-TWA
Ammonium persulfate	7727-54-0	60 - 100%	0.01 mg/m <sup>3</sup>	Not applicable	0.1 mg/m <sup>3</sup>
Crystalline silica, quartz	14808-60-7	5 - 10%	TWA: 0.1 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup>	TWA: 0.025 mg/m <sup>3</sup>

## Non-Hazardous Substance to Total of 100%

### 3. HAZARDS IDENTIFICATION

#### Hazard Overview

##### **CAUTION! - ACUTE HEALTH HAZARD**

May cause eye, skin, and respiratory irritation. May cause allergic skin and respiratory reaction. May be harmful if swallowed. Oxidizer.

##### **DANGER! - CHRONIC HEALTH HAZARD**

Breathing crystalline silica can cause lung disease, including silicosis and lung cancer. Crystalline silica has also been associated with scleroderma and kidney disease.

This product contains quartz, cristobalite, and/or tridymite which may become airborne without a visible cloud. Avoid breathing dust. Avoid creating dusty conditions. Use only with adequate ventilation to keep exposures below recommended exposure limits. Wear a NIOSH certified, European Standard EN 149, or equivalent respirator when using this product. Review the Material Safety Data Sheet (MSDS) for this product, which has been provided to your employer.

#### Risk Phrases

R8 Contact with combustible material may cause fire.

R22 Harmful if swallowed.

R36/37/38 Irritating to eyes, respiratory system and skin.

R42/43 May cause sensitization by inhalation and skin contact.

#### HSNO Classification

Not Determined

### 4. FIRST AID MEASURES

#### Inhalation

If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

#### Skin

In case of contact, immediately flush skin with plenty of soap and water for at least 15 minutes. Get medical attention. Remove contaminated clothing and launder before reuse.

#### Eyes

In case of contact, or suspected contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention immediately after flushing.

#### Ingestion

Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.

#### Notes to Physician

Not Applicable

### 5. FIRE FIGHTING MEASURES

#### Suitable Extinguishing Media

Water fog, carbon dioxide, foam, dry chemical.

#### Extinguishing media which must not be used for safety reasons

#### Special Exposure Hazards

Oxidizer. May ignite combustibles. Decomposition in fire may produce toxic gases.

#### Special Protective Equipment for Fire-Fighters

Full protective clothing and approved self-contained breathing apparatus required for fire fighting personnel.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautionary Measures** Use appropriate protective equipment. Avoid creating and breathing dust.

**Environmental Precautionary Measures** Prevent from entering sewers, waterways, or low areas.

**Procedure for Cleaning / Absorption** Collect using dustless method and hold for appropriate disposal. Consider possible toxic or fire hazards associated with contaminating substances and use appropriate methods for collection, storage and disposal.

## 7. HANDLING AND STORAGE

**Handling Precautions**

Avoid contact with eyes, skin, or clothing. Wash hands after use. Launder contaminated clothing before reuse. This product contains quartz, cristobalite, and/or tridymite which may become airborne without a visible cloud. Avoid breathing dust. Avoid creating dusty conditions. Use only with adequate ventilation to keep exposure below recommended exposure limits. Wear a NIOSH certified, European Standard En 149, or equivalent respirator when using this product. Material is slippery when wet.

**Storage Information**

Store away from reducing agents. Store away from combustibles. Store in a cool, dry location. Store between 20 F (-6 C) and 100 F (38 C). Use good housekeeping in storage and work areas to prevent accumulation of dust. Close container when not in use. Product has a shelf life of 12 months.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Engineering Controls**

Use approved industrial ventilation and local exhaust as required to maintain exposures below applicable exposure limits.

**Respiratory Protection**

Wear a NIOSH certified, European Standard EN 149 (FFP2/FFP3), or equivalent respirator when using this product.

**Hand Protection**

Impervious rubber gloves.

**Skin Protection**

Rubber apron. Wear clothing appropriate for the work environment. Dusty clothing should be laundered before reuse. Use precautionary measures to avoid creating dust when removing or laundering clothing.

**Eye Protection**

Chemical goggles; also wear a face shield if splashing hazard exists.

**Other Precautions**

Eyewash fountains and safety showers must be easily accessible.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical State:**

Solid

**Color:**

Off white to tan

**Odor:**

Mild acrid

**pH:**

5

**Specific Gravity @ 20 C (Water=1):**

1.98

**Density @ 20 C (kg/l):**

Not Determined

**Bulk Density @ 20 C (kg/m<sup>3</sup>):**

Not Determined

**Boiling Point/Range (C):**

Not Determined

**Freezing Point/Range (C):**

Not Determined

**Pour Point/Range (C):**

Not Determined

**Flash Point/Range (C):**

Not Determined

**Flash Point Method:**

Not Determined

**Autoignition Temperature (C):**

Not Determined

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Flammability Limits in Air - Lower (g/m <sup>3</sup> ):	Not Determined
Flammability Limits in Air - Lower (%):	Not Determined
Flammability Limits in Air - Upper (g/m <sup>3</sup> ):	Not Determined
Flammability Limits in Air - Upper (%):	Not Determined
Vapor Pressure @ 20 C (mmHg):	Not Determined
Vapor Density (Air=1):	Not Determined
Percent Volatiles:	Not Determined
Evaporation Rate (Butyl Acetate=1):	Not Determined
Solubility in Water (g/100ml):	79
Solubility in Solvents (g/100ml):	Not Determined
VOCs (g/l):	Not Determined
Viscosity, Dynamic @ 20 C (centipoise):	Not Determined
Viscosity, Kinematic @ 20 C (centistokes):	Not Determined
Partition Coefficient/n-Octanol/Water:	Not Determined
Molecular Weight (g/mole):	228.22
Decomposition Temperature (C):	Not Determined

## 10. STABILITY AND REACTIVITY

Stability Data:	Stable
Hazardous Polymerization:	Will Not Occur
Conditions to Avoid	Avoid contact with readily oxidizable materials.
Incompatibility (Materials to Avoid)	Organic matter. All flammables, especially petroleum products, asphalt & other volatile flammables. Amphoteric metals such as aluminum, magnesium, lead, tin, or zinc. Strong acids. Avoid halogens.
Hazardous Decomposition Products	Toxic fumes. Ammonia. Sulfuric acid. Amorphous silica may transform at elevated temperatures to tridymite (870 C) or cristobalite (1470 C).
Additional Guidelines	Not Applicable

## 11. TOXICOLOGICAL INFORMATION

Principle Route of Exposure	Eye or skin contact, inhalation.
<u>Symptoms related to exposure</u> Inhalation	May cause allergic respiratory reaction. Inhaled crystalline silica in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (IARC, Group 1). There is sufficient evidence in experimental animals for the carcinogenicity of tridymite (IARC, Group 2A).  Breathing silica dust may cause irritation of the nose, throat, and respiratory passages. Breathing silica dust may not cause noticeable injury or illness even though permanent lung damage may be occurring. Inhalation of dust may also have serious chronic health effects (See "Chronic Effects/Carcinogenicity" subsection below).
Skin Contact	May cause skin irritation. May cause an allergic skin reaction.
Eye Contact	May cause eye irritation.
Ingestion	Causes burns of the mouth, throat and stomach.
Aggravated Medical Conditions	Individuals with respiratory disease, including but not limited to asthma and bronchitis, or subject to eye irritation, should not be exposed to quartz dust.

**Chronic Effects/Carcinogenicity** Silicosis: Excessive inhalation of respirable crystalline silica dust may cause a progressive, disabling, and sometimes-fatal lung disease called silicosis. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness, and reduced pulmonary function. This disease is exacerbated by smoking. Individuals with silicosis are predisposed to develop tuberculosis.

Cancer Status: The International Agency for Research on Cancer (IARC) has determined that crystalline silica inhaled in the form of quartz or cristobalite from occupational sources can cause lung cancer in humans (Group 1 - carcinogenic to humans) and has determined that there is sufficient evidence in experimental animals for the carcinogenicity of tridymite (Group 2A - possible carcinogen to humans). Refer to [IARC Monograph 68, Silica, Some Silicates and Organic Fibres](#) (June 1997) in conjunction with the use of these minerals. The National Toxicology Program classifies respirable crystalline silica as "Known to be a human carcinogen". Refer to the 9th Report on Carcinogens (2000). The American Conference of Governmental Industrial Hygienists (ACGIH) classifies crystalline silica, quartz, as a suspected human carcinogen (A2).

There is some evidence that breathing respirable crystalline silica or the disease silicosis is associated with an increased incidence of significant disease endpoints such as scleroderma (an immune system disorder manifested by scarring of the lungs, skin, and other internal organs) and kidney disease.

#### Other Information

For further information consult "Adverse Effects of Crystalline Silica Exposure" published by the American Thoracic Society Medical Section of the American Lung Association, American Journal of Respiratory and Critical Care Medicine, Volume 155, pages 761-768 (1997).

#### Toxicity Tests

<b>Oral Toxicity:</b>	LD50: 820 mg/kg (Rat)
<b>Dermal Toxicity:</b>	Not determined
<b>Inhalation Toxicity:</b>	Not determined
<b>Primary Irritation Effect:</b>	Not determined
<b>Carcinogenicity</b>	Refer to <a href="#">IARC Monograph 68, Silica, Some Silicates and Organic Fibres</a> (June 1997).
<b>Genotoxicity:</b>	Not determined
<b>Reproductive / Developmental Toxicity:</b>	Not determined

## 12. ECOLOGICAL INFORMATION

<b>Mobility (Water/Soil/Air)</b>	Not determined
<b>Persistence/Degradability</b>	Readily biodegradable
<b>Bio-accumulation</b>	Not determined

#### Ecotoxicological Information

<b>Acute Fish Toxicity:</b>	Not determined
<b>Acute Crustaceans Toxicity:</b>	Not determined

<b>Acute Algae Toxicity:</b>	Not determined
<b>Chemical Fate Information</b>	Not determined
<b>Other Information</b>	Not applicable

## **13. DISPOSAL CONSIDERATIONS**

<b>Disposal Method</b>	Disposal should be made in accordance with federal, state, and local regulations.
<b>Contaminated Packaging</b>	This bag may contain residue of a hazardous material. Some authorities may regulate such containers as hazardous waste. Dispose of container according to national or local regulations.

## **14. TRANSPORT INFORMATION**

### **Land Transportation**

#### **ADR**

UN1444,Ammonium Persulfate, 5.1, III

### **Air Transportation**

#### **ICAO/IATA**

UN1444,Ammonium Persulfate, 5.1, III

### **Sea Transportation**

#### **IMDG**

UN1444,Ammonium Persulfate, 5.1, III  
EmS F-A, S-Q

### **Other Transportation Information**

**Labels:** Oxidizer

## **15. REGULATORY INFORMATION**

### **Chemical Inventories**

<b>Australian AICS Inventory</b>	Product contains one or more components not listed on inventory.
<b>New Zealand Inventory of Chemicals</b>	This product does not comply with NZIOC
<b>US TSCA Inventory</b>	All components listed on inventory or are exempt.
<b>EINECS Inventory</b>	This product, and all its components, complies with EINECS

**Classification**  
O - Oxidizing.  
Xn - Harmful.

**Risk Phrases**  
R8 Contact with combustible material may cause fire.  
R22 Harmful if swallowed.  
R36/37/38 Irritating to eyes, respiratory system and skin.  
R42/43 May cause sensitization by inhalation and skin contact.

**Safety Phrases**

S2 Keep out of reach of children.  
S22 Do not breathe dust.  
S24 Avoid contact with skin.  
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
S37 Wear suitable gloves.

**16. OTHER INFORMATION**

**The following sections have been revised since the last issue of this SDS**  
Not applicable

**Contact****Australian Poisons Information Centre**

24 Hour Service: - 13 11 26  
Police or Fire Brigade: - 000 (exchange): - 1100

**New Zealand National Poisons Centre**

0800 764 766

**Additional Information**

For additional information on the use of this product, contact your local Halliburton representative.

For questions about the Safety Data Sheet for this or other Halliburton products, contact Chemical Compliance at 1-580-251-4335.

**Disclaimer Statement**

This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the sole responsibility of the user.

**\*\*\*END OF MSDS\*\*\***