



Chem-shop™

MATERIAL SAFETY DATA SHEET

SECTION I · PRODUCT IDENTIFICATION

Product Name: PAINT & VARNISH STRIPPER
Product Number: 101-6570
Product Type: AEROSOL
Supplier's Name: Frank's Maintenance Products Inc.
Supplier's Address: 1299 Strasburg Road, Kitchener, ON N2R 1H2

Formula: Proprietary
Date Prepared: Nov. 1, 2012
Emergency Phone: (613) 996-6666
Information Phone: (519) 748-4433

HMIS Rating (Based on Aerosol Conc.):
0-Minimal 1- Slight 2- Moderate
3- Serious 4- Extreme
HEALTH: 3 FIRE: 3 REACTIVITY: 1
Personal Protection : H

TDG: CONSUMER COMMODITY · ORM-D WHMIS: Class A, Class B - Div 5, Class D - Div 1B, Class D - Div 2B

SECTION II · HAZARDOUS INGREDIENTS

CHEMICAL NAME	CAS #	%WT	TWA/TLV	LD 50	LC 50
Methylene Chloride	75-09-2	50-60	25 ppm	167 mg/kg Oral Rat	19049 ppm Rat 4hr
Toluene	108-88-3	01-10	100 ppm	2500 mg/kg Oral Rat	8000 ppm Rat 4hr
Methanol	67-56-1	01-05	200 ppm	870 mg/kg Oral Mouse	64000 ppm Rat 4hr
Ethanol	64-17-5	01-10	400ppm	N/D	N/D
Liquified Petroleum Gas	68476-86-8	10-20	1000 ppm	N/D	N/D

SECTION III · PHYSICAL DATA

Data Below Based On Aerosol Concentrate Only:

Boiling Point: 40°C
pH: N/A
Solubility In Water: Slight
Appearance/Odor: Clear Liquid, Mild Sweet Odor

Data Below Based On Total Contents:

Vapor Pressure of can (psig @20°C): 50
Total VOC %: ~ 39.8%

Vapor Density(Air=1): >1
Specific Gravity (H₂O=1)@23°C: 1.130

SECTION IV · FIRE AND EXPLOSION DATA

Flash Point (of Concentrate Only): 24°C (T.O.C.)
Extinguishing Media: Foam, CO₂, Dry Media

Special Fire Fighting Procedures: Wear self-contained breathing apparatus and protective clothing. Cool fire exposed containers to prevent rupturing.
Unusual Fire and Explosion Hazards: Exposure to temperature above 49° C may cause bursting.

Flammability (as per Flame Projection Test): Flammable Spray

SECTION V · REACTIVITY DATA

Stability: Material Stable.

Incompatibility: Avoid contact with strong oxidizing agents, strong acids and bases, and selected Amines.

Hazardous Decomposition Products: Hydrogen Chloride, Phosgene.

Hazardous Polymerization: Will not Occur.

SECTION VI · STORAGE AND HANDLING

KEEP OUT OF REACH OF CHILDREN.

For Industrial and Institutional use only.

Store in a cool, dry area away from heat or open flame.

Do not store at temperatures above 49° C

NFPA Code 30B Rating: Level 1 Aerosol.

SECTION VII · HEALTH AND FIRST AID

PRIMARY ROUTES OF ENTRY & EFFECTS OF OVER EXPOSURE:

Eyes: May cause slight irritation but does not injure eye tissue.

Skin: Frequent or prolonged contact may cause irritation.

Inhalation: Inhalation of mist can cause irritation of nasal and respiratory passages. Abusive or excessive inhalation may cause irritation to the upper respiratory tract, dizziness, nausea and other central nervous system effects.

Ingestion: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis..

Carcinogenicity - Hazardous by WHMIS Criteria*; Reproductive Effects - N/D; Teratogenicity - N/D; Mutagenicity - N/D; Synergistic Material - N/D

* If this product is handled with good industrial hygiene practice it will not present a carcinogenic risk in the work place.

FIRST AID PROCEDURES:

Eyes: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

Skin: Wash with soap and water. If irritation persists seek medical attention.

Inhalation: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.

Ingestion: Do not induce vomiting. Seek medical attention immediately.

SECTION VIII · SPECIAL PROTECTION DATA

Respiratory Protection: None needed for proper use in accordance with label directions.

Ventilation: Provide local exhaust to keep TLV of Section II ingredients below acceptable limits.

Protective Gloves: None needed for proper use in accordance with label directions. Use chemical resistant gloves if hand contact will be made.

Eye Protection: None needed unless it is anticipated that a splash or spray back will occur, then wear safety glasses or chemical proof goggles.

SECTION IX · SPILL OR LEAK PROTECTION

STEPS TO BE TAKE IN CASE OF SPILL OR LEAK: Allow propellant to evaporate. Maintain local exhaust and adequate ventilation. No smoking. Keep sparks, heat sources and open flame far away from spill or leak. Cover with absorbent material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbent material in accordance with Federal, Provincial and local laws.

WASTE DISPOSAL METHOD: Aerosol cans, when emptied and depressurized through normal use, pose no disposal hazard and should be recycled. Consult Federal, Provincial and local authorities for approved procedures.

N/A= NOT APPLICABLE · N/E=NOT ESTABLISHED · N/D=NOT DETERMINED · <=LESS THAN · >=MORE THAN

NOTICE: The information contained on this Material Safety Data Sheet is considered accurate as of the date of publication. It is not necessarily all inclusive nor fully adequate in every circumstance. The suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements. No warranty, express or implied, of merchantability, fitness, accuracy of data, or the results to be obtained from the use thereof is made. The vendor assumes no responsibility for injury or damages resulting from the inappropriate use of this product.

