

SAFETY DATA SHEET
FOR PAINTS COATINGS AND RELATED MATERIALS

02/26/2015

Section 1: Identification

Product code and name: 102 Tektone Hi Hide
Interior Flat Paint

passonno paints
500 Broadway
Watervliet NY 12189
(518)273-3822

Section 2: Hazard identification



WARNING!

May be harmful if inhaled, swallowed or if contacted with skin. Causes eye irritation.
Refer to Section 4 for first aid measures.

Section 3: Composition on Ingredients

Titanium Dioxide	664-67-7	13.2%	Anhydrous Aluminum Silicate	66402-68-4	12.4%
Calcium Carbonate	1317-65-3	8.9%	Nepheline Syenite	37244-96-5	4.4%
Ethylene Glycol	107-21-1	2.1%	Attapugite Clay	8031-18-3	0.4%
Trime-1,3-Pentanediol, Monoisobutyrate				25265-77-4	0.2%
2-Amino-2-Methyl-1-Propanol				124-68-5	0.1%
Sodium Nitrite	7632-00-0	0.1%			

Section 4: First Aid Measures

Eyes: Overexposure can result in sever irritation, tearing, redness or blurred vision. Continuously flush with clean cool water for 10 – 15 minutes. Occasionally pull back eyelids while flushing with water.

Skin: Irritation, prolonged exposure may cause defatting and dermatitis. Clean with “waterless” hand-cleaner followed by washing with soap and water.

Breathing: Excessive inhalation may cause dizziness, nausea, weakness, fatigue, unconsciousness or asphyxiation. If affected person is conscious remove to fresh air. If breathing is difficult, administer oxygen. If unconscious, apply artificial respiration and seek immediate medical assistance.

Ingestion: Can cause gastrointestinal irritation, nausea, vomiting or diarrhea. DO NOT INDUCE VOMITING. Secure immediate medical assistance.

Section 5: Fire-Fighting Measures

Extinguishing media: CO2, Foam, dry chemical

Unusual fire and explosion hazards: Keep away from heat, sparks and open flame.

Special fire fighting procedures: Fight as a volatile fire. Use water only to keep closed fire exposed paint containers cool to reduce internal pressure.

Section 6: Accidental Release Measures

Steps to be taken in case material is released or spilled: Remove sources of ignition and provide ventilation. Large spills may be scooped up with non-sparking tools. Provide respiratory protection if required. Small quantities may be picked up with absorbent material.

Section 7: Handling and Storage

Handling: Wear appropriate person protective gear as defined in section 8. Eating, drinking and smoking should be prohibited. Avoid breathing vapor or mist. Do not swallow or get on skin or in eyes. Use with adequate ventilation. Keep in original container, keeping lid tightly closed when not in use. Do not reuse container.

Storage: Store in accordance with appropriate regulations, in original container away from excessive heat or cold. Keep container closed until ready for use. Do not store in unlabelled containers. Protect from freezing.

Section 8: Exposure Controls/Personal Protection

	CAS#	TWA		STEL		Vapor	LEL
		PPM	mg/M3	PPM	mg/M3	Pressure	
Ethylene Glycol	107-21-1	C50	C127			01.mmHg@20 ⁰ C	3.2%

Respiratory protection: Approved mask or respirator for organic vapors and dusts as necessary.

Ventilation: Designed and maintained to provide volume and pattern to prevent vapor concentration in excess of TLV or STEL.

Protective gloves: Neoprene rubber gloves

Eye protection: Goggles or side shield spectacles.

Other protective equipment: Eye wash station and safety showers should be available.

Section 9: Physical and Chemical Properties

Boiling range:300-385⁰F

Weight/Gallon:11.3lbs.

Percent volatile by volume:69.1

Evaporation rate: Slower than ether.

Vapor density: Heavier than air

VOC: Less than 100 gms/l

Section 10: Stability and Reactivity

Stability: Stable

Conditions to avoid: not applicable

Incompatibility: Avoid contact with or storage near strong oxidizing agents.

Hazardous Decomposition Products: Usual products of combustion – CO, CO₂, smoke and toxic hydrocarbons.

Hazardous Polymerization: Will not occur.

Section 11: Toxicological Information

Ethylene Glycol 107-21-1

Sodium Nitrite

7632-00-0

Toxic chemicals subject to reporting requirements of Sect 313 of Emergency Planning & Community Right to Know Act of 1986 (40CFR372).

Likely routes of exposure: Inhalation, ingestion, skin and eye contact.

Delayed, immediate or chronic effects: Unknown.

Description of symptoms: Refer to Section 4 First Aid Measures.

Components known to be human carcinogens: None

Components anticipated to be human carcinogens: None

Section 12: Ecological Information

No information is available.

Section 13: Disposal Considerations

Dispose of waste paint in accordance to federal, state and local regulations.

Section 14: Transport Information

Proper shipping name: Paint

Section 15: Regulatory Information

No information is available.

Section 16: Other Information



The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of the need that information is current, applicable and suitable to their circumstances.