Osmose MATERIAL SAFETY DATA SHEET

MATERIAL SAFETY DATA SHEET: POLE WRAP

SECTION I

MSDS NUMBER:	112-Osm	
MSDS CODE:	Osm	1 1 2 2 2 2
SYNONYMS:	Patox II	
MANUFACTURED BY:	Osmose, Inc.	
DIVISION:	Utilities Division	
EPA REGISTRATION NUMBER:	3008-52	
VENDOR:	N/A	<u> </u>
EMERGENCY PHONE:	CHEMTREC: 1(800) 424-9300	
OTHER CALLS:	(716) 882-5905	
ADDRESS:	980 Ellicott Street, Buffalo, NY 14209	
MSDS PREPARED BY:	Teri Muchow	
DATE PREPARED:	June 11, 1990	
DATE LAST REVISED:	July 12, 2000	

ADDITIONAL INFORMATION

CHEMTREC'S EMERGENCY TELEPHONE NUMBER IS TO BE USED ONLY IN THE EVENT OF CHEMICAL EMERGENCIES INVOLVING A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT INVOLVING CHEMICALS.

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

TRADE NAME: Pole Wrap					
INGREDIENT NAME	******************************	OSI IA ÇEL	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	OTHER	% 70.6
Sodium Fluoride	7681-49-4	2.5 mg/M° as F	2.5 mg/M° as F	RQ = 1000 pounds	70.6

SECTION III - CHEMICAL CHARACTERISTICS

BOILING POINT	MELTING POINT	FREEZING POINT	SPECIFIC GRAVITY (H ₂ 0 = 1)	PERCENT VOLATILE BY VOLUME	THEORETICAL VOC CONTENT (PERCENT OF WEIGHT)		
N/A	1818°F	N/A	N/A	N/A	N/A		
WEIGHT PER GALLON	pH:	VAPOR PRESSURE	VAPOR DENSITY	DENSITY	EVAPORATION RATE BASIS (N-BUAC) = 1		
N/A	N/A	N/A	N/A	Not Available	N/A		
SOLUBILITY IN V	SOLUBILITY IN WATER: 4.4% at 75°F			REACTIVITY IN WATER: N/A			
APPEARANCE A	ND ODOR:	Gray bandage, odorl	ess.				

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT METHOD N/A N/A		N/A		R (%) AUTOIGNITION TEMPERATE N/A	
NFPA CODES	HEALTH.	1	HMIS CODES:	HEALTH	
	FLAMMABILITY	0		FLAMMABILITY	0
	REACTIVITY	0		REACTIVITY	0
	OTHER	N/A		PROTECTION	В

SPECIAL FIRE FIGHTING PROCEDURES: Toxic vapors given off in fire. Wear full protective clothing and self-contained breathing apparatus. UNUSUAL FIRE AND EXPLOSION HAZARDS: May burn, but does not ignite readily.

SECTION V - REACTIVITY DATA

IS THIS CHEMICAL STABLE UNDER NORMAL CONDITIONS OF HANDLING/STORAGE (Y/N)? Y CONDITIONS TO AVOID (REGARDING STABILITY): N/A INCOMPATIBILITY (MATERIALS TO AVOID): Acids HAZARDOUS DECOMPOSITION PRODUCTS: Toxic fumes of F and Na₂O HAZARDOUS POLYMERIZATION POSSIBLE (Y/N)? N CONDITIONS TO AVOID (REGARDING POLYMERIZATION): N/A

Osmose MATERIAL SAFETY DATA SHEET

SECTION VI - HEALTH HAZARDS

ROUTES OF ENTRY: Skin.

SIGNS AND SYMPTOMS OF ACUTE OVEREXPOSURE: May be fatal if swallowed. Possible skin irritation. Contact with eye will cause irritation. Due to physical nature of this product, oral, eye and inhalation exposure unlikely.

CHRONIC OVEREXPOSURE: N/A

CHEMICAL LISTED AS A CARCINOGEN OR POTENTIAL CARCINOGEN?:

NATIONAL TOXICOLOGY PROGRAM (Y/N): N

IARC MONOGRAPHS (Y/N): N

OSHA (Y/N): N

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: N/A

TOXICITY DATA

Dermai LD50	> 2000 mg/Kg
Eye Irritation	Moderately Irritating
Skin Irritation	Non-irritant
Skin Sensitization	NOT a skin sensitizer



EMERGENCY AND FIRST AID PROCEDURES



① EMERGENCY PHONE NUMBER OF MANUFACTURER: CHEMTREC 1(800) 424-9300

1. INHALATION:

Remove victim to fresh air. Apply respiration if indicated. Call a physician immediately.

2. EYE CONTACT:

Flush eyes with plenty of water. Call a physician immediately.

3. SKIN CONTACT:

Remove contaminated clothing and wash affected area with soap and water.

4. INGESTION:

Call a physician or Poison Control Center. Drink 1 or 2 glasses of water and induce vomiting by touching back of throat

with finger. Do not induce vomiting on or give anything to an unconscious person.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

USDOT SHIPPING DESCRIPTION: Sodium fluoride, solid, 6.1, UN1690, III

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store in dry area. Do not store near open flames. Use good personal hygiene. Applicators must not eat, drink, or use tobacco products during those parts of the application process that may expose them to the wood treatment formulation.

OTHER PRECAUTIONS: Read and follow label instructions.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: N/A - Due to physical nature of product. WASTE DISPOSAL METHODS: Bury in approved landfill. Dispose in accordance with all Federal, State and local laws.

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION: Normally not necessary due to physical nature of product.

VENTILATION REQUIREMENTS: Local exhaust is sufficient.

PROTECTIVE GLOVES: Rubber

EYE PROTECTION: Wear protective eyewear (goggles, face shield or safety glasses).

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: N/A

WORK/HYGIENIC PRACTICES: Follow good work practices. Wash hands before eating, smoking or using tobacco products. Remove contaminated clothing and wash clothing before reuse.

SECTION IX - REGULATORY INFORMATION:

STATE OF CALIFORNIA PROPOSITION 65:

WARNING - This product contains chemicals known to the State of California to cause cancer.

SARA/TITLE III ;SECTION 312 - HAZARD CATEGORIES:

Immediate (Acute) Health: Yes

Reactive Hazard: No

Delayed (Chronic) Health: No

Sudden Release of Pressure: No

Fire Hazard: No

SECTION 302:

N/A

SECTION 304:


Sodium fluoride has a reportable quantity of 1,000 pounds.

SECTION 311 & 312:

Report if inventory equals or exceeds 10,000 pounds on any given day.

Osmose MATERIAL SAFETY DATA SHEET

HAZARDOUS MATERIALS INFORMATION SYSTEM (HMIS) PERSONAL PROTECTION INDEX



N/A = Not Applicable

12020

NOTICE:

The information herein is given in good faith but no warranty, expressed or implied, is made, and Osmose, Inc. expressly disclaims liability from reliance on such information.

Information on this form is furnished for the purpose of compliance with the Occupational Safety and Health Act of 1970 and shall not be used for any other purpose. Use or dissemination of all or any part of this information for any other purpose may result in a violation of law or constitute grounds for legal action.

CIRCATORY TELETION RESTROYS TELETION RESPRICTS
SER PROTECTION TELETION TELE

E OF C

				-
•				
•				
•				
		49.		
	with the state of			
				,