

Material Safety Data Sheet

May be used to comply with OSHA=s
Hazard Communication Standard
29 CFR 1910.1200 Standard must be
consulted for specific requirements.

U.S. Department of Labor

Occupational Safety & Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

Identity (as used on label & list)		HMIS / NFPA HAZARD ID SYSTEM PEEL COAT TYPE I-II-III-IV
EVANS STRIPCOAT - TYPE IV	K-25, K-25S	
Section I		
Manufacturers Name EVANS COATING LLC	Emergency Telephone Number 248-583-9890	HEALTH: 1
Address (Number-Street City-State -Zip Code) 1330 SOUTER TROY, MI 48083	Telephone Number for Information 248-583-9890	FLAMMABILITY 1
	Date Prepared 2-1-2011	REACTIVITY: 0
	Signature of Preparer (optional)	PERSONAL PROTECTION: B

Section II - Hazardous Ingredients / Identity Information

Hazardous Components (Specific Chemical: Common Names)	OSHA PEL	ACGIH TLV	Other Limits Recommended	% Optional
THIS PRODUCT CONTAINS NO KNOWN HAZARDOUS COMPONENTS AS DEFINED IN ACCORDANCE WITH 29 CFR 1910.1200. THE				
PRECISE COMPOSITION OF THIS MIXTURE IS PROPRIETARY INFORMATION. A MORE COMPLETE DISCLOSURE IS AVAILABLE IN THE				
EVENT OF A MEDICAL EMERGENCY.				

CHEMICAL FAMILY = OIL MODIFIED BLOCK COPOLYMER RUBBER

CHEMICAL NAME = THERMOPLASTIC RUBBER

Section III - Physical / Chemical Characteristics

Boiling Point	OVER 700°F	Specific Gravity (H ₂ O = 1)	1
Vapor Pressure (mm Hg)	N/A	Melting Point	OVER 200°F
Vapor Density (AIR = 1)	N/A	Evaporation Rate (Butyl Acetate = 1)	N/A

Solubility in Water	INSOLUBLE		
Appearance and Odor	100% SOLID THERMOPLASTIC - WAX LIKE - WITH OIL ODOR		

Section IV - Fire & Explosion Hazard Data

Flash Point (Method Used) - 395EF OPEN CUP	Flammable Limits - N/A	LEL - N/A	UEL - N/A
--	------------------------	-----------	-----------

Extinguishing Media - WATER FOG - DRY CHEMICAL - FOAM & CO₂

Special Fire Fighting Procedures - TREAT AS AN OIL FIRE

Unusual Fire & Explosion Hazards - IF HEATED ABOVE THE FLASH POINT, THIS PRODUCT WILL RELEASE FLAMMABLE

VAPORS WHICH CAN BURN OR BE EXPLOSIVE

PAGE 1 OF 2

Section V - Reactivity Data

Stability	Unstable		Conditions to Avoid: DIPPING IN EXCESS OF FLASH POINT
	Stable	X	

Incompatibility (Materials to Avoid): **STRONG ACIDS AND ALKALIS**

Hazardous Decomposition or Byproducts: **NONE KNOWN**

Hazardous Polymerization	May Occur		Conditions to Avoid: DIPPING IN EXCESS OF FLASH POINT
	Will Not Occur	X	

Section VI - Health Hazard Data

Route(s) of Entry:	Inhalation	-	Skin	-	Ingestion ?
NO RESPIRATORY IRRITATION EXPECTED	-	MELTED COMPOUND CAN BURN	-	NON-HAZARDOUS AT ROOM TEMPERATURE	

Health Hazards (Acute & Chronic)

Carcinogenicity:	N/A	NTP ?	N/A	IARC Monographs ?	N/A	OSHA Regulated ?	N/A
------------------	-----	-------	-----	-------------------	-----	------------------	-----

Signs and Symptoms of Exposure: N/A

Medical Conditions Generally Aggravated by Exposure: N/A

Emergency and First Aid Procedures: **APPLIED AT 350EF - IF IT COMES IN CONTACT WITH THE SKIN, TREAT AS AN OIL BURN**

Section VII - Precautions for Safe Handling and Use

Steps to be Taken in Case Material is Released or Spilled: N/A = SOLID

Waste Disposal Method: **SAME AS WAX OR OIL = INCINERATION OR LANDFILL TO COMPLY WITH FEDERAL,
STATE & LOCAL REGULATION**

Precautions to be Taken in Handling and Storing: **STORE IN A COOL / DRY AREA**

Other Precautions: **NONE**

Section VIII - Control Measures

Respiratory Protection (Specify Type): **NONE NEEDED**

Ventilation	Local Exhaust: IF ODOR IS OBJECTIONABLE	Special: N/A
	Mechanical (General)	Other: N/A

Protective Gloves: **WHILE DIPPING**

Eye Protection: **SPLASH GOGGLES**

Other Protective Clothing or Equipment: **NONE**

Work / Hygienic Practices: **N/A**
