SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

CHEMICAL NAME: Methacrylate Copolymer

PRODUCT NAME: PINK

Manufacturer's Name : EZ Flow Nail Systems Address : 13720 Rosecrans Ave

City, State, Zip: Santa Fe Springs, CA 90670

Business Telephone : 562-229-0337 Emergency Telephone : 800-535-5053

PREPARATION/UPDATE DATE: 01/30/01

PRINT DATE: 8/16/02

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

FOR POLYMER:

ITEM	CHEMICAL NAME	CAS NUMBER:	WT/WT %
01	Particulates Not Otherwise Classified	NE	60.0-100.0
02	Residual Monomers	NA	05-5.0
03	Benzoyl Peroxide	94-36-0	1.0-5.0
04	Azo Dye	59487-23-9	0.5-1.5

ACGIH		OSHA		Company		
ITEM	TLV-TWA	TLV-STEL	PEL TWA	PEL CEILING	Recommendation	SKIN
01	10 mg/m ³	NE	15 mg/m ³	NE	NE	NE
02	NA	NA	NA	NA	NA	NA
03	5 m/m ³	NE	5 m/m ³	NE	5 m/m ³	NE
04	NF	NF	NF	NF	NF	NF

FOR DECOMPOSITION PRODUCTS:

ITEM	CHEMICAL NAME	CAS NUMBER:	WT/WT %
05	Methyl Methacrylate Monomer	80-62-6	60.0-100.0
06	Ethyl Methacrylate Monomer	97-63-2	60.0-100.0

ACGIH		OSHA		Company		
ITEM	TLV-TWA	TLV-STEL	PEL TWA	PEL CEILING	Recommendation	SKIN
05	100 ppm	NE	100 ppm	NE	100 ppm	NE
06	100 ppm	NE	100 ppm	NE	100 ppm	NE

See Section 16 for Abbreviations.

SECTION 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

WARNING: For Polymer: May irritate eyes, skin and respiratory tract.

For Polymer:

OSHA classifies this material as Particulates, Not

Otherwise Classified.

Eyes: May be irritated by gross overexposure, no matter how

generated. Keep dust out of eyes.

Skin May be irritated by gross overexposure, no matter how

generated. May cause dryness.

Respiratory Tract May be irritated by gross overexposure, no matter how

generated.

For Benzoyl Peroxide: Eyes: May cause irritation or damage.

Skin: Prolonged and/or repeated skin contact may cause

irritation, defatting, dermatitis and sensitization.

Inhalation: May cause irritation of nose, throat and lungs.

Ingestion: May produce muscular weakness.

For Azo Dye: Eyes: May cause mechanical irritation, although found to be non-

irritating when tested on the eyes of rabbits.

Ingestion: Extreme quantities may cause discomfort to the digestive

tract.

Respiratory Tract: May cause mechanical irritation.

Skin: Found to be non-irritating when tested on the skin of

rabbits.

For Decomposition Products:

Methyl Methacrylate:

Acute Hazards: Eyes: May irritate.

Respiratory Tract: May irritate.

Skin: May cause rashes.

Symptoms: Headaches, nausea, staggering gait, confusion, drowsiness

and unconsciousness.

Chronic Hazards: Eyes: May cause eye corrosion and permanent injury.

Liver and Kidneys: May cause changes in liver and kidney function or damage.

Nervous System: Repeated and prolonged over exposure may cause

permanent damage.

Skin: May cause allergic skin rashes.

SECTION 3 - HAZARDS IDENTIFICATION CONTINUED

For Decomposition Products Continued:

Ethyl Methacrylate:

Acute Hazards: Eyes: Eye contact may cause irritation with discomfort, tearing, or

blurring of vision.

Respiratory Tract: Inhalation may cause irritation of the respiratory tract with

coughing, of nonspecific discomfort, such as nausea,

headache and or weakness.

Skin: Effects in humans include skin irritation with discomfort or

allergic skin rashes.

Digestive Tract: Ingestion may cause anesthetic effects such as dizziness,

headache, confusion, incoordination, and loss of

consciousness

Symptoms: May include burning sensation, coughing, wheezing,

laryngitis, shortness of breath, headache, nausea and

vomiting.

Chronic Hazards: Skin: May cause allergic skin rashes.

Animal Studies: Administered lethal oral doses include weakness, labored

and irregular respiration, drop in arterial blood pressure and

coma.

CARCINOGENICITY: IARC lists Benzoyl Peroxide as not classifiable as to

carcinogenicity to humans. None of the other components of this material are listed by IARC, NTP, OSHA, or ACGIH

as carcinogens.

PRIMARY ROUTES OF ENTRY: Inhalation, Skin or Eyes.

SECTION 4 - FIRST AID MEASURES

EMERGENCY AND FIRST AID PROCEDURES:

INHALATION: Remove to fresh air. Get medical help if discomfort persists.

EYES: Flush with water for 15 minutes, including under eyelids. Get medical help if

discomfort persists.

SKIN: Wash with soap and water. Get medical help if discomfort persists.

INGESTION: Rinse mouth out with water. Call doctor if amount was large.

CLOTHING: Wash thoroughly before reuse.

TREATMENT: Treat symptoms after thorough decontamination.

SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT: 304 °C, 580 °F

FLAMMABLE LIMIT, AIR VOL% LOWER: NA

UPPER: NA

AUTOIGNITION TEMPERATURE: NE

EXPLOSION HAZARD:

EXTINGUISHER METHOD: Water, carbon dioxide, dry chemical.

FIRE AND EXPLOSION HAZARDS: Polymer dust is combustible. The explosive limits of the polymer

particles suspended in air are approximately those of coal dust.

SPECIAL FIRE FIGHTING PROCEDURES: Avoid extinguishing methods which may generate dust clouds.

Water stream can disperse dust into air, producing a fire hazard and

possible explosion hazard if exposed to ignition source.
Firefighters should wear self-contained breathing apparatus.

SENSITIVE TO MECHANICAL IMPACT: For Polymer: No. For Benzoyl Peroxide Component: Yes

SENSITIVE TO STATIC DISCHARGE: For Polymer: No. For Benzoyl Peroxide Component: Yes

SECTION 6 - ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE: Sweep up to avoid slipping hazard. Keep airborne particulates at a

minimum when cleaning up spills.

SECTION 7- HANDLING AND STORAGE

PRECAUTIONS FOR HANDLING: Use in well ventilated areas. Wear gloves when handling powder.

PRECAUTIONS FOR STORAGE: Store in cool dry place. Keep container closed to prevent water

absorption and contamination.

SECTION 8 - EXPOSURE CONTROL/PERSONAL PROTECTION

VENTILATION: Use good, local exhaust at processing equipment, including buffers,

sanders, grinders and polishers.

RESPIRATORY PROTECTION: Use type for Particulates Not Otherwise Classified, if needed.

EYE PROTECTION: Safety glasses or chemical splash goggles.

PROTECTIVE GLOVES: Impervious, nitrile, if hot plastic is handled.

OTHER PROTECTIVE EQUIPMENT: Provide eyewash, safety shower and impervious clothing are

recommended. High temperature processing equipment should be

well ventilated.

INDUSTRIAL HYGIENE PRACTICES: Wash face and hands thoroughly with soap and water after use and

before eating, drinking, smoking or applying cosmetics.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Fine pink powder.

ODOR: Faint odor in bulk.

pH: ND **ODOR THRESHOLD:** ND **BOILING POINT:** NA FREEZING POINT: ND VISCOSITY: NA **SPECIFIC GRAVITY** (H₂O=1): 1.25 **VAPOR PRESSURE:** NA **PERCENT VOLATILE W/W%:** NA **VAPOR DENSITY** (AIR=1): NA **EVAPORATION RATE** (BuAc =1): 3.0 **SOLUBILITY IN WATER:** Insoluble.

COEFFICIENT OF WATER/OIL DISTRIBUTION: ND

SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID: Heating above 240 °C, 464 °F.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Methacrylate Monomer and Oxides of Carbon when burned.

HAZARDOUS POLYMERIZATION: MAY OCCUR: WILL NOT OCCUR: X

STABILITY: UNSTABLE: STABLE: X

SECTION 11- TOXICOLOGICAL PROPERTIES

TARGET ORGANS:

For Polymer; None Listed.
For Benzoyl Peroxide: Skin and eyes.
For Azo Dye: None Listed.

For Decomposition Products:

Methyl Methacrylate: Nose, Liver and kidneys.

Ethyl Methacrylate: None Listed.

SECTION 11- TOXICOLOGICAL PROPERTIES CONTINUED

MUTAGENICITY DATA:

For Polymer: None Listed.

For Benzoyl Peroxide:

For Decomposition Products:

Methyl Methacrylate:

Ovary Hamster Cytogenetic Analysis: 1600 mg/L.
Inhalation Rat Cytogenetic Analysis: 4 mg/m³/16W.
Lymphocyte Mouse Gene Mutation in Mammalian Cells: 704 mg/L.
Lymphocyte Mouse Microsomal Assay: 500 mg/L.

Ovary, Hamster Sister Chromatid Exchange: 1500 mg/L.

Ethyl Methacrylate: None Listed.

REPRODUCTIVE TOXICITY DATA:

For Polymer: None Listed. For Decomposition Products: None Listed.

Methyl Methacrylate:

Inhalation Rat TC_{Lo} : 109 gm/m³/17M.

Inhalation Rat TC_{Lo} : 109 gm/m³/54M, 6-15 days of pregnancy. Inhalation Rat TC_{Lo} : 54mg/m³/24H, 8 weeks of pregnancy. Inhalation Rat TC_{Lo} : 4480 mg/m³/2H, 6-18 days of pregnancy.

Ethyl Methacrylate:

TUMOROGENIC DATA:

For Polymer: None Listed.

For Benzoyl Peroxide:

Skin Mouse TD_{Lo}: 24 gm/kg/30W.

SECTION 11- TOXICOLOGICAL PROPERTIES CONTINUED

TOXICITY DATA:

For Polymer: None Listed.

For Benzoyl Peroxide:

Inhalation Rat LC₅₀: 24.3 mg/L/4hr. Intraperitoneal Mouse 250 mg/kg. LD_{Lo}: Oral Rat LD₅₀: 7710 mg/kg.

For Azo Dye:

Oral Rat >10,000 mg/kg. LD₅₀: Ames Test

Negative

For Decomposition Products:

Methyl Methacrylate:

LD₅₀: Acute Oral Rat 7990 mg/kg. LD₅₀: Acute Dermal Rabbit 35,500 mg/kg.

Acute Inhalation Rat LC₅₀: >12,500 to 16,500 ppm for 0.5 hours.

Inhalation Human TC_{Lo}: 125 ppm. TC_{Lo}: Inhalation Human 60 mg/m³.

Human Patch Test: Approximate one-third of subjects developed mild redness at the

site of application. Twenty percent showed sensitivity when tested

10 days later.

Ethyl Methacrylate:

8300 ppm/4H. LC₅₀: Inhalation Rat Intraperitoneal Mouse LD₅₀: 1369 mg/kg. Intraperitoneal Rat LD₅₀: 1223 mg/kg. Oral Mouse LD₅₀: 7836 mg/kg. Oral Rat LD₅₀: 14800 mg/kg. Oral Rabbit 3630 mg/kg. LD₅₀: Subcutaneous Rat 25 gm/kg. LD_{Lo:}

SECTION 12 - ECOLOGICAL INFORMATION

AQUATIC TOXICITY:

None Listed. For Polymer:

For Decomposition Products:

Methyl Methacrylate:

Flathead Minnows TLm_{96H}: 100-1000 ppm. TLm_{24H}: Goldfish 420 ppm. Bluegills 368 ppm. TLm_{24H}: Ethyl Methacrylate: None Listed.

ECOLOGICAL TOXICITY:

Not Known. For Polymer: For Benzoyl Peroxide: Not Known.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose in a landfill or incinerate according to Federal, State, and

Local regulations.

DISPOSAL OF EMPTY CONTAINERS: Reuse of empty drums or containers is not recommended.

Employees should be advised of the potential hazards, due to residual material, associated with empty containers. It is our policy to discourage the reuse of empty containers and to dispose of all empty containers properly, in accordance with Federal, State and

Local regulations.

SECTION 14 - TRANSPORTATION

DOT/UN SHIPPING NAME: SYNTHETIC GUM RESIN GRANULAR, NOIBN

DOT/UN CLASS: NA/UN NUMBER: PACKING GROUP:

NAERG: LABEL:

NMFC ITEM #: 46030

SCHEDULE B: 3906.90.6000

IMDG CLASS: IMDG PG:

CERLA RQ: For Decomposition Products:

Methyl Methacrylate Monomer: 1000 lb. Ethyl Methacrylate Monomer: 1000 lb.

SECTION 15 - REGULATORY INFORMATION ITEM **TSCA EINECS** CAA **RCRA** CERCLA 313 03 Χ Χ Χ Χ Χ 04 Χ Χ 05 Χ Χ Χ U 162 06 Χ Χ Χ Χ Χ U 118 ITEM **CWA** PA NJ CA 65 WHMIS DAK 03 Χ 05 Χ Χ Χ 50 ppm Χ Χ 06 Χ

TSCA: FOR USE IN FDA REGULATED PRODUCTS ONLY

CANADIAN WHMIS: This product has been classified in accordance with the hazardous criteria of the CPR and the MSDS contains all the information required by the CPR.

SECTION 16 - OTHER INFORMATION

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM (HMIS) RATING:

HEALTH: 1
FLAMMABILITY: 1
REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: Gloves and Safety Glasses or Chemical Splash Goggles.

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) HAZARD IDENTIFICATION RATING:

HEALTH: 1
FLAMMABILITY: 1
REACTIVITY: 0

ABBREVIATIONS:

NA Not Applicable ND Not Determined NE Not Established CPR Controlled Products Regulation parts per million Gallon ppm G Milligram L Liter mg Gram Mole mol gm kg Kilogram Micro μ Millimeter Pico mm р

LCLethal ConcentrationLDLethal DoseTCToxic ConcentrationTDToxic Dose

BOD Biological Oxygen Demand COD Chemical Oxygen Demand Lo Lowest ThOD Theoretical Oxygen Demand

TLm Threshold Limit

H Hours M Months D Days Y Years

W Weeks

OSHA Occupational Safety and Health Administration

ACGIH American Conference of Governmental Industrial Hygienist

IARC International Agency for Research for Cancer

TLV Threshold Limit Value
PEL Permissible Exposure Limit

SECTION 16 - OTHER INFORMATION CONTINUED

Prepared By:	Health, Safety and Environment
Reviewed By:	Technical Review
Reviewed By:	Senior Company Officer
Issue Date:	

THIS MATERIAL SAFETY DATA SHEET IS PREPARED IN COMPLIANCE WITH FEDERAL REGULATIONS (29 CFR 1910.1200), THE COMMONWEALTH OF PENNSYLVANIA REGULATIONS (TITLE 34. CHAPTERS 301-323) AND CANADIAN WHMIS REGULATIONS, ANY APPLICABLE STATE AND LOCAL REGULATIONS SHOULD BE CONSULTED. THE ABOVE INFORMATION MAY BE BASED IN PART ON INFORMATION PROVIDED BY COMPONENT SUPPLIERS AND IS BELIEVED TO BE CORRECT AS OF THE DATE HEREOF. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OF THESE DATA, THE RESULTS TO BE OBTAINED FROM THE USE OF THE MATERIAL, OR THE HAZARDS CONNECTED WITH SUCH USE. SINCE THE INFORMATION CONTAINED HEREIN MAY BE APPLIED UNDER CONDITIONS BEYOND OUR CONTROL AND WITH WHICH WE MAY BE UNFAMILIAR, AND SINCE DATA MADE AVAILABLE SUBSEQUENT TO THE DATE HEREOF MAY SUGGEST MODIFICATION OF THE INFORMATION, WE ASSUME NO RESPONSIBILITY FOR THE RESULT OF ITS USE. THIS INFORMATION AND MATERIAL IS FURNISHED ON THE CONDITION THAT THE PERSON RECEIVING IT SHALL MAKE HIS/HER OWN DETERMINATION AS TO THE SUITABILITY OF THE MATERIAL FOR HIS/HER PARTICULAR PURPOSE AND ON THE CONDITION THAT HE/SHE ASSUME THE RISK OF HIS/HER USE THEREOF.