SAFETY DATA SHEET

SECTION 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: QRISTAL H.D. POLYSATIN

Other Names:

Recommended Use: Solventborne urethane-alkyd clear semigloss for brush application

Company Name: Resene Paints Limited New Zealand Address: 32-50 Vogel Street, Naenae, Wellington, NEW ZEALAND

P O Box 38242, Wellington Mail Centre

Phone: (04) 577 0500 Fax: (04) 577 0600

Resene Paints Limited Australia Address 7 Production Avenue, Molendinar, Queensland 4214

P O Box 785, Ashmore City, Queensland 4214

AUSTRALIA

Phone 1800 738 383

Emergency Telephone:

New Zealand 0800 737 363 Available Monday - Friday 8.00am - 4.30pm

New Zealand Poisons Centre: 0800 764 766

Australia 1800 738 383

Australian Poisons Centre: 131 126

SECTION 2. HAZARDS IDENTIFICATION

Hazard Classificaton HAZARDOUS according to NZ HSNO Regulations

Regulated under NZS5433 for land transportation

Risk Phrases Safety Phrases

Substance Classification 3.1C 6.3B 6.5B 6.7B 9.1B

Hazard Statements Flammable liquid and vapour

Causes skin irritation

May cause an allergic skin reaction

Suspected of causing cancer through inhalation. Toxic to aquatic life with long lasting effects

SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

% CAS No Ingredients **TWA** Aromatic Hydrocarbon 30-60 64742-82-1 525 mg/m³ Alkyd Resin 10-30 Not known None Establish OSHA CEL Methyl Ethyl Ketoxime 96-29-7 36 mg/m³ <1

Proprietary ingredients 1-10 various None Establish

SECTION 4. FIRST AID MEASURES

Eyes Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so.

Continue rinsing. If eye irritation persists get medical attention/advice.

Swallowed: Call a POISON CENTRE (NZ 0800 764766) or Australia (131 126) or doctor/physician if you feel

unwell.

Skin IF ON SKIN: Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF skin irritation occurs: Get medical advice/attention.

Inhaled Remove to fresh air and keep at rest in a position comfortable for breathing.

Aggravated medical conditions caused by exposure

Chronic Health Effects

Advice to Doctor

SECTION 5. FIRE FIGHTING MEASURES

Extinguisher Foam, Carbon Dioxide, Dry Chemical

Hazards from

combustion products

Special protective precautions and equipment for firefighters

Fire/Explosion Hazard Auto Ingnition Temperature Lower Explosion Limit Upper Explosion Limit

Hazchem Code Flash Point

3[Y]

SECTION 6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures

Keep spectators away and avoid breathing dust or vapours

Methods and materials for containment and clean up

Minor Spills Clean up spills immediately.

Wear protective clothing and breathing apparatus.

Use absorbent clean up materials, such as fire retardant treated sawdust or diatomaceous earth.

Keep spills (and as much as possible cleaning runoffs) out of municipal sewers and waterways.

Sweep up.

Place in separate container for disposal or recovery.

Major Spills Dike and contain spill with inert materials (eg. Sand).

Keep spills (and as much as possible cleaning runoffs) out of municipal sewers and open bodies of water.

Restrict access to area. No smoking or naked lights.

Clear area of personnel and move upwind.

Alert Fire Brigade and tell them location and nature of hazard.

Consider evacuation (or protect in place).

Stop leak if safe to do so.

Collect recoverable product into labelled containers for recycling.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling Avoid damaging containers. Keep lids on containers when not in use

Conditions for safe storage including any incompatibilities

Storage Temperatures Min 1°C Max 40°C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

National exposure standards for mixture

Component Breathing Zone ppm Breathing Zone mg/m³

Personal Protection

Eye: Safety eyewear with splash guards or side shields to prevent eye contact is recommended when

using any paint.

Hands/Feet Protective clothing. Gloves of neoprene or nitrile rubber - Industrial weight lined

gauntlet recommended.

Other Overalls, impervious clothing, barrier cream, eyewash unit, skin cleansing cream.

Practice good caution and personal cleanliness to avoid skin contact. Avoid breathing vapours of

heated materials. Wash hands thoroughly before handling food.

Respirator

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Clear liquid

Odour pH Vapour Pressure Vapour Density Boiling Point Melt Freeze Solubility Volatile by Weigl Hydrocarbon n/a 5.2 kPa 3.7 137°C Immiscible 56

SECTION 10. STABILITY AND ACTIVITY

Chemical Stability Product is considered stable under normal storage and handling conditions.

Conditions to Avoid Freezing, excessive heat and changes in temperature

Incompatible Material
Hazardous decomposition product Oxides of carbon and nitrogen
Hazardous reactions Hazardous polymerisation will not occur.

QRISTAL H.D. POLYSATIN

TOXICOLOGICAL INFORMATION SECTION 11.

No data available for this product

Refer to individual raw materials

Oral: LD50 mg/kg Component Dermal: LD50 mg/kg Inhale: LC50 ppm

SECTION 12. HAZARDS IDENTIFICATION

No data available for this product

Do not allow the product to enter the environment

Component Fish: LC50 mg/Lt BCF: <100 Kow

DISPOSAL CONSIDERATIONS SECTION 13.

Special precautions for landfill or incineration

Consult manufacturer for recycling options and recycle where possible

Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed

SECTION 14. TRANSPORT INFORMATION

UN Number 1263

UN Proper Paint related material

shipping

Subsidiary risk

Poison Schedule HAZCHEM Code 3[Y]

Packing Group: III Class 3

Special precautions for user

SECTION 15. REGULATORY INFORMATION

Group Standard HSR002662 Surface Coatings & Colourants - Flammable, Toxic[6.7]

Approved Handler Class 6.7A required for any amount

SECTION 16. OTHER INFORMATION

Date of Preparation 25/09/2009

Literature references MSDS's for individual raw material

Abbreviations:

NOHSC National Occupational Health and Safety Commission

Time weighted average **TWA** Short term exposure limit STEL

Chemical Abstract Service registry number CAS Numbe

Threshold limit value

Marine Pollutant □ Marine Pollutant

Safety data sheets are updated frequently. Please ensure that you have a current copy

The information contained herein is based on data considered accurate and reliable to the best of our knowledge and belief as of the date compiled. However no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use hereof. Resene Paints (New Zealand) Limited assumes no responsibility for personal injury or property damage to vendors, users or third parties caused by the material. Such users or vendors assume all risks associated with the use of the material. It is the users responsibility to satisfy themselves as to the suitability and completeness of the information for their own particular use. The users must determine whether the use of the information and data is in accordance with local laws and regulations.