

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Trade name or designation of the mixture      RTS SEALER - GREY

Registration number      -

Synonyms      None.

Product code      RSS-150-G

Issue date      27-April-2015

Version number      01

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses      Automotive Refinish Primer

Uses advised against      None known.

### 1.3. Details of the supplier of the safety data sheet

#### Supplier

Company name      Quest Automotive Products

Address      600 Nova Drive SE  
Massillon, OH 44646  
United States

Division      Massillon

Telephone      General Assistance      (330) 830-6000

e-mail      rpandrus@quest-ap.com

Contact person      Not available.

1.4. Emergency telephone number      CHEMTREC      (800) 424-9300

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

#### Classification according to Directive 67/548/EEC or 1999/45/EC as amended

Classification      F;R11, Carc. Cat. 2;R45, Muta. Cat. 2;R46, Xn;R20/21, Xi;R36, R66

The full text for all R-phrases is displayed in section 16.

#### Classification according to Regulation (EC) No 1272/2008 as amended

##### Physical hazards

Flammable liquids	Category 2	H225 - Highly flammable liquid and vapour.
-------------------	------------	--

##### Health hazards

Acute toxicity, dermal	Category 4	H312 - Harmful in contact with skin.
Acute toxicity, inhalation	Category 4	H332 - Harmful if inhaled.
Skin corrosion/irritation	Category 2	H315 - Causes skin irritation.
Serious eye damage/eye irritation	Category 2	H319 - Causes serious eye irritation.
Germ cell mutagenicity	Category 1B	H340 - May cause genetic defects.
Carcinogenicity	Category 1A	H350 - May cause cancer.
Reproductive toxicity (the unborn child)	Category 2	H361d - Suspected of damaging the unborn child.
Specific target organ toxicity - single exposure	Category 3 narcotic effects	H336 - May cause drowsiness or dizziness.

##### Environmental hazards

Hazardous to the aquatic environment, long-term aquatic hazard	Category 2	H411 - Toxic to aquatic life with long lasting effects.
--	------------	---

### Hazard summary

Physical hazards      Highly flammable.

<b>Health hazards</b>	May cause cancer. May cause heritable genetic damage. Also harmful by inhalation and in contact with skin. Irritating to eyes. Repeated exposure may cause skin dryness or cracking. Occupational exposure to the substance or mixture may cause adverse health effects.
<b>Environmental hazards</b>	Not classified for hazards to the environment.
<b>Specific hazards</b>	Prolonged exposure may cause chronic effects.
<b>Main symptoms</b>	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

## 2.2. Label elements

### Label according to Regulation (EC) No. 1272/2008 as amended

**Contains:** 2-Heptanone, 4-Methyl-2-pentanone, acetone, Cumene, Ethyl benzene, light aromatic solvent naphtha, methyl ethyl ketoxime, Silicon dioxide, Stoddard solvent, Titanium dioxide, Toluene, VM & P NAPHTHA, Xylene

### Hazard pictograms



### Signal word

Danger

### Hazard statements

H225	Highly flammable liquid and vapour.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.
H361d	Suspected of damaging the unborn child.
H411	Toxic to aquatic life with long lasting effects.

### Precautionary statements

#### Prevention

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing mist or vapour.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

#### Response

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a POISON CENTER/doctor if you feel unwell.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P370 + P378	In case of fire: Use appropriate media to extinguish.
P391	Collect spillage.

#### Storage

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

#### Disposal

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
------	---

**Supplemental label information** 45,28 % of the mixture consists of component(s) of unknown acute dermal toxicity. 46,93 % of the mixture consists of component(s) of unknown acute inhalation toxicity. 49,32 % of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment. EUH066 - Repeated exposure may cause skin dryness or cracking. EUH208 - Contains methyl ethyl ketoxime. May produce an allergic reaction.

**2.3. Other hazards** None known.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
acetone	20 - < 30	67-64-1 200-662-2	-	606-001-00-8	#
<b>Classification:</b>	<b>DSD:</b> F;R11, Xi;R36, R66-67				
	<b>CLP:</b> -				
Xylene	20 - < 30	1330-20-7 215-535-7	-	601-022-00-9	#
<b>Classification:</b>	<b>DSD:</b> R10, Xn;R20/21, Xi;R38				C
	<b>CLP:</b> Flam. Liq. 3;H226, Acute Tox. 4;H312, Skin Irrit. 2;H315, Acute Tox. 4;H332, Aquatic Chronic 2;H411				C
Titanium dioxide	5 - < 10	13463-67-7 236-675-5	-	-	
<b>Classification:</b>	<b>DSD:</b> -				
	<b>CLP:</b> Carc. 2;H351				
Toluene	3 - < 5	108-88-3 203-625-9	-	601-021-00-3	#
<b>Classification:</b>	<b>DSD:</b> F;R11, Repr. Cat. 3;R63, Xn;R65-48/20, Xi;R38, R67				
	<b>CLP:</b> Flam. Liq. 2;H225, Asp. Tox. 1;H304, Skin Irrit. 2;H315, STOT SE 3;H336, Repr. 2;H361d, STOT RE 2;H373, Aquatic Chronic 2;H411				
VM & P NAPHTHA	3 - < 5	8032-32-4 232-453-7	-	649-263-00-9	
<b>Classification:</b>	<b>DSD:</b> Carc. Cat. 2;R45, Muta. Cat. 2;R46, Xn;R65				P
	<b>CLP:</b> -				P
2-Heptanone	1 - < 3	110-43-0 203-767-1	-	606-024-00-3	#
<b>Classification:</b>	<b>DSD:</b> R10, Xn;R20/22				
	<b>CLP:</b> -				
4-Methyl-2-pentanone	1 - < 3	108-10-1 203-550-1	-	606-004-00-4	#
<b>Classification:</b>	<b>DSD:</b> F;R11, Xn;R20, Xi;R36/37, R66				
	<b>CLP:</b> -				
Ethyl benzene	< 1	100-41-4 202-849-4	-	601-023-00-4	#
<b>Classification:</b>	<b>DSD:</b> F;R11, Xn;R20				
	<b>CLP:</b> Flam. Liq. 2;H225, Asp. Tox. 1;H304, Acute Tox. 4;H332, Carc. 2;H351, STOT RE 2;H373, Aquatic Chronic 2;H411				

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
light aromatic solvent naphtha	< 0,3	64742-95-6 265-199-0	-	649-356-00-4	
<b>Classification:</b>	<b>DSD:</b>	Carc. Cat. 2;R45, Muta. Cat. 2;R46, Xn;R65			P
	<b>CLP:</b>	Asp. Tox. 1;H304, Muta. 1B;H340, Carc. 1B;H350			P
methyl ethyl ketoxime	< 0,3	96-29-7 202-496-6	-	616-014-00-0	
<b>Classification:</b>	<b>DSD:</b>	Carc. Cat. 3;R40, Xn;R21, Xi;R41, R43			
	<b>CLP:</b>	-			
Cumene	< 0,2	98-82-8 202-704-5	-	601-024-00-X	#
<b>Classification:</b>	<b>DSD:</b>	R10, Xn;R65, Xi;R37, N;R51/53			C
	<b>CLP:</b>	-			C
Silicon dioxide	< 0,2	14808-60-7 238-878-4	-	-	
<b>Classification:</b>	<b>DSD:</b>	-			
	<b>CLP:</b>	-			
Stoddard solvent	< 0,2	8052-41-3 232-489-3	-	649-345-00-4	
<b>Classification:</b>	<b>DSD:</b>	Carc. Cat. 2;R45, Muta. Cat. 2;R46, Xn;R65-48/20			P
	<b>CLP:</b>	-			P

Other components below reportable levels 30 - < 40

#### List of abbreviations and symbols that may be used above

CLP: Regulation No. 1272/2008.

DSD: Directive 67/548/EEC.

M: M-factor

vPvB: very persistent and very bioaccumulative substance.

PBT: persistent, bioaccumulative and toxic substance.

#: This substance has been assigned Community workplace exposure limit(s).

**Composition comments** The full text for all R- and H-phrases is displayed in section 16.

## SECTION 4: First aid measures

<b>General information</b>	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.
<b>4.1. Description of first aid measures</b>	
<b>Inhalation</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a POISON CENTRE or doctor/physician if you feel unwell.
<b>Skin contact</b>	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical advice/attention if you feel unwell. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Rinse mouth. Get medical advice/attention if you feel unwell.
<b>4.2. Most important symptoms and effects, both acute and delayed</b>	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.
<b>4.3. Indication of any immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

## SECTION 5: Firefighting measures

<b>General fire hazards</b>	Highly flammable liquid and vapour.
<b>5.1. Extinguishing media</b>	
<b>Suitable extinguishing media</b>	Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO <sub>2</sub> ).
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>5.2. Special hazards arising from the substance or mixture</b>	Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
<b>5.3. Advice for firefighters</b>	
<b>Special protective equipment for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Special fire fighting procedures</b>	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.

## SECTION 6: Accidental release measures

<b>6.1. Personal precautions, protective equipment and emergency procedures</b>	
<b>For non-emergency personnel</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapours and spray mists. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8.
<b>For emergency responders</b>	Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Use personal protection recommended in Section 8 of the SDS.
<b>6.2. Environmental precautions</b>	Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.
<b>6.3. Methods and material for containment and cleaning up</b>	<p>Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil etc) away from spilled material.</p> <p>Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.</p> <p>Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.</p> <p>Never return spills to original containers for re-use.</p>
<b>6.4. Reference to other sections</b>	For personal protection, see section 8. For waste disposal, see section 13 of the SDS.

## SECTION 7: Handling and storage

<b>7.1. Precautions for safe handling</b>	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid inhalation of vapours and spray mists. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.
<b>7.2. Conditions for safe storage, including any incompatibilities</b>	Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).
<b>7.3. Specific end use(s)</b>	Not available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

##### Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001

Components	Type	Value	Form
2-Heptanone (CAS 110-43-0)	MAK	237 mg/m <sup>3</sup>	
	STEL	50 ppm 473 mg/m <sup>3</sup>	
4-Methyl-2-pentanone (CAS 108-10-1)	MAK	100 ppm 83 mg/m <sup>3</sup>	
	STEL	20 ppm 208 mg/m <sup>3</sup>	
acetone (CAS 67-64-1)	MAK	50 ppm 1200 mg/m <sup>3</sup>	
	STEL	4800 mg/m <sup>3</sup> 2000 ppm	
Cumene (CAS 98-82-8)	MAK	100 mg/m <sup>3</sup> 20 ppm	
	STEL	250 mg/m <sup>3</sup> 20 ppm	
Ethyl benzene (CAS 100-41-4)	Ceiling	880 mg/m <sup>3</sup>	
	MAK	200 ppm 440 mg/m <sup>3</sup> 100 ppm	
Silicon dioxide (CAS 14808-60-7)	MAK	0,15 mg/m <sup>3</sup>	Respirable dust.
Talc (CAS 14807-96-6)	MAK	2 mg/m <sup>3</sup>	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	MAK	5 mg/m <sup>3</sup>	Respirable dust.
Toluene (CAS 108-88-3)	STEL	10 mg/m <sup>3</sup>	Respirable dust.
	MAK	190 mg/m <sup>3</sup> 50 ppm	
Trimethylbenzene (CAS 25551-13-7)	STEL	380 mg/m <sup>3</sup> 100 ppm	
	MAK	100 mg/m <sup>3</sup> 20 ppm	
Xylene (CAS 1330-20-7)	STEL	150 mg/m <sup>3</sup> 30 ppm	
	MAK	221 mg/m <sup>3</sup> 50 ppm	
	STEL	442 mg/m <sup>3</sup> 100 ppm	

##### Belgium. Exposure Limit Values.

Components	Type	Value	Form
2-Heptanone (CAS 110-43-0)	STEL	475 mg/m <sup>3</sup>	
	TWA	100 ppm 238 mg/m <sup>3</sup> 50 ppm	
4-Methyl-2-pentanone (CAS 108-10-1)	STEL	208 mg/m <sup>3</sup>	
	TWA	50 ppm 83 mg/m <sup>3</sup> 20 ppm	
acetone (CAS 67-64-1)	STEL	2420 mg/m <sup>3</sup> 1000 ppm	
	TWA	1210 mg/m <sup>3</sup> 500 ppm	
Cumene (CAS 98-82-8)	STEL	250 mg/m <sup>3</sup>	

**Belgium. Exposure Limit Values.**

Components	Type	Value	Form
Ethyl benzene (CAS 100-41-4)	TWA	50 ppm 100 mg/m3	
	STEL	20 ppm 551 mg/m3	
	TWA	125 ppm 442 mg/m3	
Silicon dioxide (CAS 14808-60-7)	TWA	100 ppm 0,1 mg/m3	Respirable dust.
Stoddard solvent (CAS 8052-41-3)	TWA	533 mg/m3	
Talc (CAS 14807-96-6)	TWA	100 ppm 2 mg/m3	
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
Toluene (CAS 108-88-3)	STEL	384 mg/m3	
	TWA	100 ppm 77 mg/m3	
Trimethylbenzene (CAS 25551-13-7)	TWA	20 ppm 100 mg/m3	
	TWA	20 ppm 1390 mg/m3	
VM & P NAPHTHA (CAS 8032-32-4)	TWA	300 ppm	
Xylene (CAS 1330-20-7)	STEL	442 mg/m3	
	TWA	100 ppm 221 mg/m3	
	TWA	50 ppm	

**Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work**

Components	Type	Value	Form
2-Heptanone (CAS 110-43-0)	STEL	475 mg/m3	
	TWA	100 ppm 238 mg/m3	
4-Methyl-2-pentanone (CAS 108-10-1)	STEL	50 ppm 200 mg/m3	
	TWA	50 mg/m3	
acetone (CAS 67-64-1)	STEL	1400 mg/m3	
	TWA	600 mg/m3	
Cumene (CAS 98-82-8)	STEL	250 mg/m3	
	TWA	50 ppm 100 mg/m3	
Ethyl benzene (CAS 100-41-4)	STEL	20 ppm 545 mg/m3	
	TWA	435 mg/m3	
Silicon dioxide (CAS 14808-60-7)	TWA	0,07 mg/m3	Respirable fraction.
Talc (CAS 14807-96-6)	TWA	1 fibers/cm3	Respirable fraction.
	TWA	6 mg/m3	Inhalable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	3 mg/m3	Respirable fraction.
	TWA	10 mg/m3	Respirable dust.
Toluene (CAS 108-88-3)	STEL	384 mg/m3	
	TWA	100 ppm 192 mg/m3	
VM & P NAPHTHA (CAS 8032-32-4)	STEL	50 ppm 1800 mg/m3	
	TWA	350 mg/m3	
Xylene (CAS 1330-20-7)	STEL	442 mg/m3	

**Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work**

Components	Type	Value	Form
	TWA	100 ppm 221 mg/m3 50 ppm	

**Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09**

Components	Type	Value	Form
2-Heptanone (CAS 110-43-0)	MAC	238 mg/m3	
	STEL	50 ppm 475 mg/m3 100 ppm	
4-Methyl-2-pentanone (CAS 108-10-1)	MAC	83 mg/m3	
	STEL	20 ppm 208 mg/m3	
acetone (CAS 67-64-1)	MAC	50 ppm 1210 mg/m3	
	STEL	500 ppm 3620 mg/m3 1500 ppm	
Cumene (CAS 98-82-8)	MAC	100 mg/m3	
	STEL	20 ppm 250 mg/m3	
Ethyl benzene (CAS 100-41-4)	MAC	50 ppm 442 mg/m3	
	STEL	100 ppm 884 mg/m3	
Silicon dioxide (CAS 14808-60-7)	MAC	200 ppm 0,1 mg/m3	
Talc (CAS 14807-96-6)	MAC	1 mg/m3	Respirable dust.
Titanium dioxide (CAS 13463-67-7)	STEL	4 mg/m3	Respirable dust.
Toluene (CAS 108-88-3)	MAC	10 mg/m3 192 mg/m3	Total dust.
	STEL	50 ppm 384 mg/m3	
Trimethylbenzene (CAS 25551-13-7)	MAC	100 ppm 125 mg/m3	
Xylene (CAS 1330-20-7)	MAC	25 ppm 221 mg/m3	
	STEL	50 ppm 442 mg/m3 100 ppm	

**Cyprus. OELs. Control of factory atmosphere and dangerous substances in factories regulation, PI 311/73, as amended.**

Components	Type	Value	Form
Cumene (CAS 98-82-8)	TWA	245 mg/m3	
		50 ppm	
Talc (CAS 14807-96-6)	TWA	706 part/cm3	
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	

**Czech Republic. OELs. Government Decree 361**

Components	Type	Value	Form
2-Heptanone (CAS 110-43-0)	Ceiling	300 mg/m3	
	TWA	150 mg/m3	
4-Methyl-2-pentanone (CAS 108-10-1)	Ceiling	200 mg/m3	
	TWA	80 mg/m3	
acetone (CAS 67-64-1)	Ceiling	1500 mg/m3	
	TWA	800 mg/m3	

**Czech Republic. OELs. Government Decree 361**

Components	Type	Value	Form
Cumene (CAS 98-82-8)	Ceiling	250 mg/m3	
	TWA	100 mg/m3	
Ethyl benzene (CAS 100-41-4)	Ceiling	500 mg/m3	
	TWA	200 mg/m3	
Silicon dioxide (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable dust.
Talc (CAS 14807-96-6)	TWA	10 mg/m3	Total dust.
		10 mg/m3	Respirable dust.
Toluene (CAS 108-88-3)	Ceiling	500 mg/m3	
	TWA	200 mg/m3	
Xylene (CAS 1330-20-7)	Ceiling	400 mg/m3	
	TWA	200 mg/m3	

**Denmark. Exposure Limit Values**

Components	Type	Value	Form
2-Heptanone (CAS 110-43-0)	TLV	238 mg/m3	
4-Methyl-2-pentanone (CAS 108-10-1)	TLV	50 ppm	
		83 mg/m3	
acetone (CAS 67-64-1)	TLV	20 ppm	
		600 mg/m3	
Cumene (CAS 98-82-8)	TLV	250 ppm	
		100 mg/m3	
Ethyl benzene (CAS 100-41-4)	TLV	20 ppm	
		217 mg/m3	
Silicon dioxide (CAS 14808-60-7)	TLV	50 ppm	
		0,3 mg/m3	Total
Stoddard solvent (CAS 8052-41-3)	TLV	0,1 mg/m3	Respirable.
		145 mg/m3	
Titanium dioxide (CAS 13463-67-7)	TLV	25 ppm	
		6 mg/m3	
Toluene (CAS 108-88-3)	TLV	94 mg/m3	
Trimethylbenzene (CAS 25551-13-7)	TLV	25 ppm	
		100 mg/m3	
Xylene (CAS 1330-20-7)	TLV	20 ppm	
		109 mg/m3	
		25 ppm	

**Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001)**

Components	Type	Value	Form
2-Heptanone (CAS 110-43-0)	STEL	475 mg/m3	
	TWA	100 ppm	
		238 mg/m3	
4-Methyl-2-pentanone (CAS 108-10-1)	STEL	50 ppm	
		208 mg/m3	
	TWA	83 mg/m3	
acetone (CAS 67-64-1)	TWA	20 ppm	
		1210 mg/m3	
Cumene (CAS 98-82-8)	STEL	500 ppm	
		250 mg/m3	
	TWA	50 ppm	
		100 mg/m3	
		20 ppm	

**Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001)**

Components	Type	Value	Form
Ethyl benzene (CAS 100-41-4)	STEL	884 mg/m <sup>3</sup>	
	TWA	200 ppm 442 mg/m <sup>3</sup> 100 ppm	
Silicon dioxide (CAS 14808-60-7)	TWA	0,1 mg/m <sup>3</sup>	Respirable dust.
Stoddard solvent (CAS 8052-41-3)	STEL	600 mg/m <sup>3</sup>	
	TWA	100 ppm 300 mg/m <sup>3</sup> 50 ppm	
Titanium dioxide (CAS 13463-67-7)	TWA	5 mg/m <sup>3</sup>	
Toluene (CAS 108-88-3)	STEL	384 mg/m <sup>3</sup>	
	TWA	100 ppm 192 mg/m <sup>3</sup> 50 ppm	
Xylene (CAS 1330-20-7)	STEL	450 mg/m <sup>3</sup>	
	TWA	100 ppm 200 mg/m <sup>3</sup> 50 ppm	

**Finland. Workplace Exposure Limits**

Components	Type	Value	Form
2-Heptanone (CAS 110-43-0)	STEL	360 mg/m <sup>3</sup>	
	TWA	75 ppm 240 mg/m <sup>3</sup> 50 ppm	
4-Methyl-2-pentanone (CAS 108-10-1)	STEL	210 mg/m <sup>3</sup>	
	TWA	50 ppm 80 mg/m <sup>3</sup> 20 ppm	
acetone (CAS 67-64-1)	STEL	1500 mg/m <sup>3</sup>	
	TWA	630 ppm 1200 mg/m <sup>3</sup> 500 ppm	
Cumene (CAS 98-82-8)	STEL	250 mg/m <sup>3</sup>	
	TWA	50 ppm 100 mg/m <sup>3</sup> 20 ppm	
Ethyl benzene (CAS 100-41-4)	STEL	880 mg/m <sup>3</sup>	
	TWA	200 ppm 220 mg/m <sup>3</sup> 50 ppm	
light aromatic solvent naphtha (CAS 64742-95-6)	TWA	100 mg/m <sup>3</sup>	
Silicon dioxide (CAS 14808-60-7)	TWA	0,05 mg/m <sup>3</sup>	Respirable.
Talc (CAS 14807-96-6)	STEL	2 ppm	Inhalable dust.
		1 ppm	Respirable.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m <sup>3</sup>	Dust.
Toluene (CAS 108-88-3)	STEL	380 mg/m <sup>3</sup>	
	TWA	100 ppm 81 mg/m <sup>3</sup> 25 ppm	
Trimethylbenzene (CAS 25551-13-7)	TWA	100 mg/m <sup>3</sup>	
		20 ppm	
Xylene (CAS 1330-20-7)	STEL	440 mg/m <sup>3</sup>	

**Finland. Workplace Exposure Limits**

Components	Type	Value	Form
	TWA	100 ppm 220 mg/m3 50 ppm	

**France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984**

Components	Type	Value	Form
2-Heptanone (CAS 110-43-0)	VLE	475 mg/m3	
	VME	100 ppm 238 mg/m3 50 ppm	
4-Methyl-2-pentanone (CAS 108-10-1)	VLE	208 mg/m3	
	VME	50 ppm 83 mg/m3	
acetone (CAS 67-64-1)	VLE	20 ppm 2420 mg/m3	
	VME	1000 ppm 1210 mg/m3	
Cumene (CAS 98-82-8)	VLE	500 ppm 250 mg/m3	
	VME	50 ppm 100 mg/m3	
Ethyl benzene (CAS 100-41-4)	VLE	20 ppm 442 mg/m3	
	VME	100 ppm 88,4 mg/m3	
Silicon dioxide (CAS 14808-60-7)	VME	20 ppm 0,1 mg/m3	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	VME	10 mg/m3	
Toluene (CAS 108-88-3)	VLE	384 mg/m3	
	VME	100 ppm 76,8 mg/m3	
Xylene (CAS 1330-20-7)	VLE	20 ppm 442 mg/m3	
	VME	100 ppm 221 mg/m3 50 ppm	

**Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)**

Components	Type	Value
4-Methyl-2-pentanone (CAS 108-10-1)	TWA	83 mg/m3
acetone (CAS 67-64-1)	TWA	20 ppm 1200 mg/m3 500 ppm
Cumene (CAS 98-82-8)	TWA	50 mg/m3 10 ppm
Ethyl benzene (CAS 100-41-4)	TWA	88 mg/m3
Toluene (CAS 108-88-3)	TWA	20 ppm 190 mg/m3 50 ppm
Trimethylbenzene (CAS 25551-13-7)	TWA	100 mg/m3
Xylene (CAS 1330-20-7)	TWA	20 ppm 440 mg/m3 100 ppm

**Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace**

<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
2-Heptanone (CAS 110-43-0)	AGW	238 mg/m3	
4-Methyl-2-pentanone (CAS 108-10-1)	AGW	83 mg/m3	
acetone (CAS 67-64-1)	AGW	20 ppm 1200 mg/m3	
Cumene (CAS 98-82-8)	AGW	500 ppm 100 mg/m3	
Ethyl benzene (CAS 100-41-4)	AGW	20 ppm 88 mg/m3	
methyl ethyl ketoxime (CAS 96-29-7)	AGW	20 ppm 1 mg/m3	
Talc (CAS 14807-96-6)	AGW	0,3 ppm 10 mg/m3	Inhalable fraction.
Titanium dioxide (CAS 13463-67-7)	AGW	1,25 mg/m3 10 mg/m3	Respirable fraction. Inhalable fraction.
Toluene (CAS 108-88-3)	AGW	1,25 mg/m3 190 mg/m3	Respirable fraction.
Trimethylbenzene (CAS 25551-13-7)	AGW	50 ppm 100 mg/m3	
Xylene (CAS 1330-20-7)	AGW	440 mg/m3 100 ppm	

**Greece. OELs (Decree No. 90/1999, as amended)**

<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
2-Heptanone (CAS 110-43-0)	STEL	465 mg/m3	
	TWA	100 ppm 465 mg/m3	
4-Methyl-2-pentanone (CAS 108-10-1)	STEL	100 ppm 410 mg/m3	
	TWA	100 ppm 410 mg/m3	
acetone (CAS 67-64-1)	STEL	100 ppm 3560 mg/m3	
	TWA	1780 mg/m3	
Cumene (CAS 98-82-8)	STEL	370 mg/m3	
	TWA	75 ppm 245 mg/m3	
Ethyl benzene (CAS 100-41-4)	STEL	50 ppm 545 mg/m3	
	TWA	125 ppm 435 mg/m3	
Stoddard solvent (CAS 8052-41-3)	STEL	100 ppm 720 mg/m3	
	TWA	125 ppm 575 mg/m3	
Talc (CAS 14807-96-6)	TWA	100 ppm 2 mg/m3	Respirable.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3 5 mg/m3	Inhalable Respirable.
Toluene (CAS 108-88-3)	STEL	10 mg/m3 384 mg/m3	Inhalable
	TWA	100 ppm 192 mg/m3 50 ppm	

**Greece. OELs (Decree No. 90/1999, as amended)**

Components	Type	Value	Form
Xylene (CAS 1330-20-7)	STEL	650 mg/m3 150 ppm	
	TWA	435 mg/m3 100 ppm	

**Hungary. OELs. Joint Decree on Chemical Safety of Workplaces**

Components	Type	Value	Form
2-Heptanone (CAS 110-43-0)	STEL	476 mg/m3	
	TWA	238 mg/m3	
4-Methyl-2-pentanone (CAS 108-10-1)	STEL	208 mg/m3	
	TWA	83 mg/m3	
acetone (CAS 67-64-1)	STEL	2420 mg/m3	
	TWA	1210 mg/m3	
Cumene (CAS 98-82-8)	STEL	250 mg/m3	
	TWA	100 mg/m3	
Ethyl benzene (CAS 100-41-4)	STEL	884 mg/m3	
	TWA	442 mg/m3	
Silicon dioxide (CAS 14808-60-7)	TWA	0,15 mg/m3	Respirable.
Talc (CAS 14807-96-6)	TWA	2 mg/m3	Respirable.
Toluene (CAS 108-88-3)	STEL	380 mg/m3	
	TWA	190 mg/m3	
Xylene (CAS 1330-20-7)	STEL	442 mg/m3	
	TWA	221 mg/m3	

**Iceland. OELs. Regulation 154/1999 on occupational exposure limits**

Components	Type	Value	Form
2-Heptanone (CAS 110-43-0)	STEL	475 mg/m3	
	TWA	100 ppm 238 mg/m3 50 ppm	
4-Methyl-2-pentanone (CAS 108-10-1)	STEL	208 mg/m3	
	TWA	50 ppm 83 mg/m3 20 ppm	
acetone (CAS 67-64-1)	TWA	600 mg/m3 250 ppm	
	STEL	250 mg/m3	
Cumene (CAS 98-82-8)	TWA	50 ppm 100 mg/m3 20 ppm	
	STEL	884 mg/m3	
Ethyl benzene (CAS 100-41-4)	TWA	200 ppm 200 mg/m3 50 ppm	
	TWA	0,3 mg/m3	Total dust.
Stoddard solvent (CAS 8052-41-3)	TWA	0,1 mg/m3 145 mg/m3	Respirable dust.
	TWA	25 ppm 6 mg/m3	
Titanium dioxide (CAS 13463-67-7)	TWA	6 mg/m3	
	STEL	188 mg/m3 50 ppm	
Toluene (CAS 108-88-3)	TWA	94 mg/m3 25 ppm	
	TWA	100 mg/m3	
Trimethylbenzene (CAS 25551-13-7)	TWA	100 mg/m3	

**Iceland. OELs. Regulation 154/1999 on occupational exposure limits**

Components	Type	Value	Form
Xylene (CAS 1330-20-7)	STEL	20 ppm 442 mg/m3	
	TWA	100 ppm 109 mg/m3 25 ppm	

**Ireland. Occupational Exposure Limits**

Components	Type	Value	Form
2-Heptanone (CAS 110-43-0)	STEL	475 mg/m3	
	TWA	100 ppm 238 mg/m3 50 ppm	
4-Methyl-2-pentanone (CAS 108-10-1)	STEL	208 mg/m3	
	TWA	50 ppm 83 mg/m3	
acetone (CAS 67-64-1)	TWA	20 ppm 1210 mg/m3	
Cumene (CAS 98-82-8)	STEL	500 ppm 250 mg/m3	
	TWA	50 ppm 100 mg/m3	
Ethyl benzene (CAS 100-41-4)	STEL	20 ppm 884 mg/m3	
	TWA	200 ppm 442 mg/m3 100 ppm	
methyl ethyl ketoxime (CAS 96-29-7)	STEL	33 mg/m3	
	TWA	10 ppm 10 mg/m3 3 ppm	
Silicon dioxide (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable dust.
Stoddard solvent (CAS 8052-41-3)	TWA	573 mg/m3	
Talc (CAS 14807-96-6)	TWA	100 ppm 10 mg/m3	Total inhalable dust.
	TWA	0,8 mg/m3	Respirable dust.
Titanium dioxide (CAS 13463-67-7)	TWA	4 mg/m3	Respirable dust.
Toluene (CAS 108-88-3)	TWA	10 mg/m3	Total inhalable dust.
	STEL	384 mg/m3	
Trimethylbenzene (CAS 25551-13-7)	TWA	100 ppm 192 mg/m3 50 ppm	
	TWA	100 mg/m3	
Xylene (CAS 1330-20-7)	STEL	20 ppm 442 mg/m3	
	TWA	100 ppm 221 mg/m3 50 ppm	

**Italy. Occupational Exposure Limits**

Components	Type	Value	Form
2-Heptanone (CAS 110-43-0)	STEL	475 mg/m3	
	TWA	100 ppm 238 mg/m3 50 ppm	
4-Methyl-2-pentanone (CAS 108-10-1)	STEL	208 mg/m3	

**Italy. Occupational Exposure Limits Components**

Components	Type	Value	Form
acetone (CAS 67-64-1)	TWA	50 ppm 83 mg/m3	
	TWA	20 ppm 1210 mg/m3	
	STEL	500 ppm 250 mg/m3	
Cumene (CAS 98-82-8)	TWA	50 ppm 100 mg/m3	
	STEL	20 ppm 884 mg/m3	
	TWA	200 ppm 442 mg/m3	
Ethyl benzene (CAS 100-41-4)	STEL	100 ppm 0,025 mg/m3	Respirable fraction.
	TWA	100 ppm	
Silicon dioxide (CAS 14808-60-7)	TWA	2 mg/m3	Respirable fraction.
Stoddard solvent (CAS 8052-41-3)	TWA	10 mg/m3	
Talc (CAS 14807-96-6)	TWA	192 mg/m3	
Titanium dioxide (CAS 13463-67-7)	TWA	50 ppm	
Toluene (CAS 108-88-3)	TWA	25 ppm	
Trimethylbenzene (CAS 25551-13-7)	STEL	442 mg/m3	
	TWA	100 ppm 221 mg/m3	
Xylene (CAS 1330-20-7)	TWA	50 ppm	

**Latvia. OELs. Occupational exposure limit values of chemical substances in work environment Components**

Components	Type	Value
2-Heptanone (CAS 110-43-0)	STEL	475 mg/m3
	TWA	100 ppm 238 mg/m3
4-Methyl-2-pentanone (CAS 108-10-1)	STEL	50 ppm 208 mg/m3
	TWA	50 ppm 83 mg/m3
acetone (CAS 67-64-1)	TWA	20 ppm 1210 mg/m3
	STEL	500 ppm 250 mg/m3
Cumene (CAS 98-82-8)	TWA	50 ppm 100 mg/m3
	STEL	20 ppm 884 mg/m3
Ethyl benzene (CAS 100-41-4)	TWA	200 ppm 442 mg/m3
	TWA	100 ppm 10 mg/m3
Titanium dioxide (CAS 13463-67-7)	STEL	150 mg/m3
	TWA	40 ppm 50 mg/m3
Toluene (CAS 108-88-3)	TWA	14 ppm 300 mg/m3
	STEL	442 mg/m3
VM & P NAPHTHA (CAS 8032-32-4)	TWA	100 ppm 221 mg/m3
	STEL	442 mg/m3
Xylene (CAS 1330-20-7)	TWA	100 ppm 221 mg/m3
	TWA	221 mg/m3

**Latvia. OELs. Occupational exposure limit values of chemical substances in work environment**

Components	Type	Value	
		50 ppm	
<b>Lithuania. OELs. Limit Values for Chemical Substances, General Requirements</b>			
Components	Type	Value	Form
2-Heptanone (CAS 110-43-0)	STEL	250 mg/m3	
	TWA	50 ppm 120 mg/m3 25 ppm	
4-Methyl-2-pentanone (CAS 108-10-1)	STEL	208 mg/m3	
	TWA	50 ppm 83 mg/m3	
acetone (CAS 67-64-1)	STEL	20 ppm 2420 mg/m3	
	TWA	1000 ppm 1210 mg/m3	
Cumene (CAS 98-82-8)	STEL	500 ppm 170 mg/m3	
	TWA	35 ppm 120 mg/m3 25 ppm	
Ethyl benzene (CAS 100-41-4)	STEL	884 mg/m3	
	TWA	200 ppm 442 mg/m3	
Silicon dioxide (CAS 14808-60-7)	TWA	100 ppm 0,1 mg/m3	Respirable fraction.
Talc (CAS 14807-96-6)	TWA	2 mg/m3 1 mg/m3	Inhalable fraction. Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	5 mg/m3	
Toluene (CAS 108-88-3)	STEL	384 mg/m3	
	TWA	100 ppm 192 mg/m3	
Trimethylbenzene (CAS 25551-13-7)	TWA	50 ppm 100 mg/m3	
	STEL	20 ppm 450 mg/m3	
Xylene (CAS 1330-20-7)	TWA	100 ppm 200 mg/m3 50 ppm	

**Luxembourg. Binding Occupational exposure limit values (Annex I), Memorial A**

Components	Type	Value	
2-Heptanone (CAS 110-43-0)	STEL	475 mg/m3	
	TWA	100 ppm 238 mg/m3 50 ppm	
4-Methyl-2-pentanone (CAS 108-10-1)	STEL	208 mg/m3	
	TWA	50 ppm 83 mg/m3	
acetone (CAS 67-64-1)	TWA	20 ppm 1210 mg/m3	
	STEL	500 ppm 250 mg/m3	
Cumene (CAS 98-82-8)	TWA	50 ppm 100 mg/m3 20 ppm	

**Luxembourg. Binding Occupational exposure limit values (Annex I), Memorial A**

Components	Type	Value
Ethyl benzene (CAS 100-41-4)	STEL	884 mg/m3 200 ppm
	TWA	442 mg/m3 100 ppm
Toluene (CAS 108-88-3)	STEL	384 mg/m3 100 ppm
	TWA	192 mg/m3 50 ppm
Xylene (CAS 1330-20-7)	STEL	442 mg/m3 100 ppm
	TWA	221 mg/m3 50 ppm

**Malta. OELs. Occupational Exposure Limit Values (L.N. 227. of Occupational Health and Safety Authority Act (CAP. 424), Schedules I and V)**

Components	Type	Value
2-Heptanone (CAS 110-43-0)	STEL	475 mg/m3 100 ppm
	TWA	238 mg/m3 50 ppm
4-Methyl-2-pentanone (CAS 108-10-1)	STEL	208 mg/m3 50 ppm
	TWA	83 mg/m3 20 ppm
acetone (CAS 67-64-1)	TWA	1210 mg/m3 500 ppm
Cumene (CAS 98-82-8)	STEL	250 mg/m3 50 ppm
	TWA	100 mg/m3 20 ppm
Ethyl benzene (CAS 100-41-4)	STEL	884 mg/m3 200 ppm
	TWA	442 mg/m3 100 ppm
Toluene (CAS 108-88-3)	STEL	384 mg/m3 100 ppm
	TWA	192 mg/m3 50 ppm
Xylene (CAS 1330-20-7)	STEL	442 mg/m3 100 ppm
	TWA	221 mg/m3 50 ppm

**Netherlands. OELs (binding)**

Components	Type	Value	Form
2-Heptanone (CAS 110-43-0)	TWA	233 mg/m3	
4-Methyl-2-pentanone (CAS 108-10-1)	STEL	208 mg/m3	
	TWA	104 mg/m3	
acetone (CAS 67-64-1)	STEL	2420 mg/m3	
	TWA	1210 mg/m3	
Cumene (CAS 98-82-8)	STEL	250 mg/m3	
	TWA	100 mg/m3	
Ethyl benzene (CAS 100-41-4)	STEL	430 mg/m3	
	TWA	215 mg/m3	
Silicon dioxide (CAS 14808-60-7)	TWA	0,075 mg/m3	Respirable dust.
Talc (CAS 14807-96-6)	TWA	0,25 mg/m3	Respirable dust.

**Netherlands. OELs (binding)**

Components	Type	Value	Form
Toluene (CAS 108-88-3)	STEL	384 mg/m3	
	TWA	150 mg/m3	
Xylene (CAS 1330-20-7)	STEL	442 mg/m3	
	TWA	210 mg/m3	

**Norway. Administrative Norms for Contaminants in the Workplace**

Components	Type	Value	Form
2-Heptanone (CAS 110-43-0)	TLV	115 mg/m3	
		25 ppm	
4-Methyl-2-pentanone (CAS 108-10-1)	STEL	208 mg/m3	
		50 ppm	
	TLV	83 mg/m3	
		20 ppm	
acetone (CAS 67-64-1)	TLV	295 mg/m3	
		125 ppm	
Cumene (CAS 98-82-8)	STEL	250 mg/m3	
		50 ppm	
	TLV	100 mg/m3	
		20 ppm	
Ethyl benzene (CAS 100-41-4)	TLV	20 mg/m3	
		5 ppm	
Silicon dioxide (CAS 14808-60-7)	TLV	0,3 mg/m3	Total dust.
		0,1 mg/m3	Respirable dust.
Talc (CAS 14807-96-6)	TLV	6 mg/m3	Total dust.
		2 mg/m3	Respirable dust.
Titanium dioxide (CAS 13463-67-7)	TLV	5 mg/m3	
Toluene (CAS 108-88-3)	TLV	94 mg/m3	
		25 ppm	
Xylene (CAS 1330-20-7)	TLV	108 mg/m3	
		25 ppm	

**Poland. MACs. Minister of Labour and Social Policy Regarding Maximum Allowable Concentrations and Intensities in Working Environment**

Components	Type	Value	Form
2-Heptanone (CAS 110-43-0)	STEL	475 mg/m3	
	TWA	238 mg/m3	
4-Methyl-2-pentanone (CAS 108-10-1)	STEL	200 mg/m3	
	TWA	83 mg/m3	
acetone (CAS 67-64-1)	STEL	1800 mg/m3	
	TWA	600 mg/m3	
Cumene (CAS 98-82-8)	STEL	250 mg/m3	
	TWA	100 mg/m3	
Ethyl benzene (CAS 100-41-4)	STEL	400 mg/m3	
	TWA	200 mg/m3	
Silicon dioxide (CAS 14808-60-7)	TWA	2 mg/m3	Total dust.
		0,3 mg/m3	Respirable dust.
Stoddard solvent (CAS 8052-41-3)	STEL	900 mg/m3	
	TWA	300 mg/m3	
Talc (CAS 14807-96-6)	TWA	4 mg/m3	Total dust.
		1 mg/m3	Respirable dust.
Titanium dioxide (CAS 13463-67-7)	STEL	30 mg/m3	
	TWA	10 mg/m3	Total dust.
Toluene (CAS 108-88-3)	STEL	200 mg/m3	
	TWA	100 mg/m3	

**Poland. MACs. Minister of Labour and Social Policy Regarding Maximum Allowable Concentrations and Intensities in Working Environment**

Components	Type	Value	Form
Trimethylbenzene (CAS 25551-13-7)	STEL	170 mg/m3	
	TWA	100 mg/m3	
Xylene (CAS 1330-20-7)	TWA	100 mg/m3	

**Portugal. OELs. Decree-Law n. 290/2001 (Journal of the Republic - 1 Series A, n.266)**

Components	Type	Value	Form
2-Heptanone (CAS 110-43-0)	STEL	475 mg/m3	
	TWA	100 ppm 238 mg/m3	
4-Methyl-2-pentanone (CAS 108-10-1)	STEL	50 ppm 208 mg/m3	
	TWA	83 mg/m3 20 ppm	
acetone (CAS 67-64-1)	TWA	1210 mg/m3 500 ppm	
Cumene (CAS 98-82-8)	STEL	250 mg/m3 50 ppm	
	TWA	100 mg/m3 20 ppm	
Ethyl benzene (CAS 100-41-4)	STEL	884 mg/m3	
	TWA	200 ppm 442 mg/m3 100 ppm	
Toluene (CAS 108-88-3)	STEL	384 mg/m3 100 ppm	
	TWA	192 mg/m3 50 ppm	
Xylene (CAS 1330-20-7)	STEL	442 mg/m3 100 ppm	
	TWA	221 mg/m3 50 ppm	

**Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)**

Components	Type	Value	Form
2-Heptanone (CAS 110-43-0)	TWA	50 ppm	
4-Methyl-2-pentanone (CAS 108-10-1)	STEL	75 ppm	
	TWA	50 ppm	
acetone (CAS 67-64-1)	STEL	750 ppm	
	TWA	500 ppm	
Cumene (CAS 98-82-8)	TWA	50 ppm	
Ethyl benzene (CAS 100-41-4)	STEL	125 ppm	
	TWA	100 ppm	
Silicon dioxide (CAS 14808-60-7)	TWA	0,025 mg/m3	Respirable fraction.
Stoddard solvent (CAS 8052-41-3)	TWA	100 ppm	
Talc (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
Toluene (CAS 108-88-3)	TWA	50 ppm	
Trimethylbenzene (CAS 25551-13-7)	TWA	25 ppm	
VM & P NAPHTHA (CAS 8032-32-4)	TWA	300 ppm	
Xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

**Romania. OELs. Protection of workers from exposure to chemical agents at the workplace**

Components	Type	Value	Form
2-Heptanone (CAS 110-43-0)	STEL	475 mg/m3	
	TWA	100 ppm 238 mg/m3 50 ppm	
4-Methyl-2-pentanone (CAS 108-10-1)	STEL	208 mg/m3	
	TWA	50 ppm 200 mg/m3 20 ppm	
acetone (CAS 67-64-1)	TWA	1210 mg/m3 500 ppm	
Cumene (CAS 98-82-8)	STEL	150 mg/m3 30 ppm	
	TWA	100 mg/m3 20 ppm	
Ethyl benzene (CAS 100-41-4)	STEL	884 mg/m3	
	TWA	200 ppm 442 mg/m3 100 ppm	
Silicon dioxide (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable fraction.
Stoddard solvent (CAS 8052-41-3)	STEL	1000 mg/m3	
	TWA	700 mg/m3	
Talc (CAS 14807-96-6)	TWA	2 mg/m3	Inhalable fraction.
Titanium dioxide (CAS 13463-67-7)	STEL	15 mg/m3	
	TWA	10 mg/m3	
Toluene (CAS 108-88-3)	STEL	384 mg/m3 100 ppm	
	TWA	192 mg/m3 50 ppm	
VM & P NAPHTHA (CAS 8032-32-4)	STEL	1000 mg/m3	
	TWA	700 mg/m3	
Xylene (CAS 1330-20-7)	STEL	442 mg/m3 100 ppm	
	TWA	221 mg/m3 50 ppm	

**Romania. OELs/CMRs. Protection of workers from exposure to carcinogen and mutagen agents. Hotarâre Nr. 1093 din 16 august 2006, Annex 3**

Components	Type	Value	Form
Silicon dioxide (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable dust.

**Slovakia. OELs for carcinogens and mutagens. Regulation No. 46/2002 on carcinogenic and mutagenic substances**

Components	Type	Value	Form
Silicon dioxide (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable fraction.

**Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents**

Components	Type	Value	Form
2-Heptanone (CAS 110-43-0)	STEL	475 mg/m3	
	TWA	100 ppm 238 mg/m3 50 ppm	
4-Methyl-2-pentanone (CAS 108-10-1)	STEL	166 mg/m3	
	TWA	40 ppm 83 mg/m3 20 ppm	
acetone (CAS 67-64-1)	TWA	1210 mg/m3	

**Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents**

Components	Type	Value	Form
Cumene (CAS 98-82-8)	STEL	500 ppm 250 mg/m3	
	TWA	50 ppm 100 mg/m3	
Ethyl benzene (CAS 100-41-4)	STEL	20 ppm 884 mg/m3	
	TWA	200 ppm 442 mg/m3	
Stoddard solvent (CAS 8052-41-3)	STEL	100 ppm 600 mg/m3	
	TWA	300 mg/m3 50 ppm	
Talc (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.
		2 mg/m3	Respirable fraction.
		10 mg/m3	Total
Titanium dioxide (CAS 13463-67-7)	TWA	5 mg/m3	
Toluene (CAS 108-88-3)	STEL	384 mg/m3	
	TWA	100 ppm 192 mg/m3	
Xylene (CAS 1330-20-7)	STEL	50 ppm 442 mg/m3	
	TWA	100 ppm 221 mg/m3	
		50 ppm	

**Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)**

Components	Type	Value	Form
2-Heptanone (CAS 110-43-0)	TWA	238 mg/m3	
4-Methyl-2-pentanone (CAS 108-10-1)	TWA	50 ppm 83 mg/m3	
		20 ppm	
acetone (CAS 67-64-1)	TWA	1210 mg/m3	
Cumene (CAS 98-82-8)	TWA	500 ppm 100 mg/m3	
		20 ppm	
Ethyl benzene (CAS 100-41-4)	TWA	442 mg/m3	
		100 ppm	
light aromatic solvent naphtha (CAS 64742-95-6)	TWA	100 mg/m3	
		20 ppm	
Silicon dioxide (CAS 14808-60-7)	TWA	0,15 mg/m3	Respirable fraction.
Talc (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.
Toluene (CAS 108-88-3)	TWA	192 mg/m3	
		50 ppm	
Xylene (CAS 1330-20-7)	TWA	221 mg/m3	
		50 ppm	

**Spain. Occupational Exposure Limits**

Components	Type	Value	Form
2-Heptanone (CAS 110-43-0)	STEL	474 mg/m3	
	TWA	100 ppm 237 mg/m3	
4-Methyl-2-pentanone (CAS 108-10-1)	STEL	50 ppm 208 mg/m3	

**Spain. Occupational Exposure Limits Components**

Components	Type	Value	Form
acetone (CAS 67-64-1)	TWA	50 ppm 83 mg/m3	
	TWA	20 ppm 1210 mg/m3	
Cumene (CAS 98-82-8)	STEL	500 ppm 250 mg/m3	
	TWA	50 ppm 100 mg/m3	
Ethyl benzene (CAS 100-41-4)	STEL	20 ppm 884 mg/m3	
	TWA	200 ppm 441 mg/m3	
Silicon dioxide (CAS 14808-60-7)	TWA	100 ppm 0,1 mg/m3	Respirable fraction.
Talc (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
Toluene (CAS 108-88-3)	STEL	384 mg/m3 100 ppm	
	TWA	192 mg/m3 50 ppm	
Xylene (CAS 1330-20-7)	STEL	442 mg/m3 100 ppm	
	TWA	221 mg/m3 50 ppm	

**Sweden. Occupational Exposure Limit Values Components**

Components	Type	Value	Form
2-Heptanone (CAS 110-43-0)	STEL	250 mg/m3	
	TWA	50 ppm 120 mg/m3 25 ppm	
4-Methyl-2-pentanone (CAS 108-10-1)	STEL	200 mg/m3	
	TWA	50 ppm 100 mg/m3 25 ppm	
acetone (CAS 67-64-1)	STEL	1200 mg/m3 500 ppm	
	TWA	600 mg/m3 250 ppm	
Cumene (CAS 98-82-8)	STEL	170 mg/m3 35 ppm	
	TWA	120 mg/m3 25 ppm	
Ethyl benzene (CAS 100-41-4)	STEL	450 mg/m3	
	TWA	100 ppm 200 mg/m3 50 ppm	
Silicon dioxide (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable dust.
Stoddard solvent (CAS 8052-41-3)	STEL	300 mg/m3	
	TWA	50 ppm 150 mg/m3 25 ppm	
Talc (CAS 14807-96-6)	TWA	2 mg/m3 1 mg/m3	Total dust. Respirable dust.
	TWA	5 mg/m3	Total dust.

**Sweden. Occupational Exposure Limit Values**

Components	Type	Value	Form
Toluene (CAS 108-88-3)	STEL	384 mg/m3 100 ppm	
	TWA	192 mg/m3 50 ppm	
Trimethylbenzene (CAS 25551-13-7)	STEL	170 mg/m3 35 ppm	
	TWA	120 mg/m3 25 ppm	
Xylene (CAS 1330-20-7)	STEL	442 mg/m3 100 ppm	
	TWA	221 mg/m3 50 ppm	

**Switzerland. SUVA Grenzwerte am Arbeitsplatz**

Components	Type	Value	Form
2-Heptanone (CAS 110-43-0)	TWA	235 mg/m3 50 ppm	
4-Methyl-2-pentanone (CAS 108-10-1)	STEL	164 mg/m3 40 ppm	
	TWA	82 mg/m3 20 ppm	
acetone (CAS 67-64-1)	STEL	2400 mg/m3 1000 ppm	
	TWA	1200 mg/m3 500 ppm	
Cumene (CAS 98-82-8)	STEL	400 mg/m3 80 ppm	
	TWA	100 mg/m3 20 ppm	
Ethyl benzene (CAS 100-41-4)	STEL	220 mg/m3 50 ppm	
	TWA	220 mg/m3 50 ppm	
Silicon dioxide (CAS 14808-60-7)	TWA	0,15 mg/m3	Respirable dust.
Talc (CAS 14807-96-6)	TWA	2 mg/m3	Respirable dust.
Titanium dioxide (CAS 13463-67-7)	TWA	3 mg/m3	Respirable dust.
Toluene (CAS 108-88-3)	STEL	760 mg/m3 200 ppm	
	TWA	190 mg/m3 50 ppm	
Trimethylbenzene (CAS 25551-13-7)	STEL	200 mg/m3 40 ppm	
	TWA	100 mg/m3 20 ppm	
Xylene (CAS 1330-20-7)	STEL	870 mg/m3 200 ppm	
	TWA	435 mg/m3 100 ppm	

**UK. EH40 Workplace Exposure Limits (WELs)**

Components	Type	Value	Form
2-Heptanone (CAS 110-43-0)	STEL	475 mg/m3 100 ppm	
	TWA	237 mg/m3 50 ppm	

**UK. EH40 Workplace Exposure Limits (WELs)**

<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
4-Methyl-2-pentanone (CAS 108-10-1)	STEL	416 mg/m3	
	TWA	100 ppm 208 mg/m3	
acetone (CAS 67-64-1)	STEL	50 ppm 3620 mg/m3	
	TWA	1500 ppm 1210 mg/m3	
Cumene (CAS 98-82-8)	STEL	500 ppm 250 mg/m3	
	TWA	50 ppm 125 mg/m3	
Ethyl benzene (CAS 100-41-4)	STEL	25 ppm 552 mg/m3	
	TWA	125 ppm 441 mg/m3	
Silicon dioxide (CAS 14808-60-7)	TWA	100 ppm 0,1 mg/m3	Respirable.
Talc (CAS 14807-96-6)	TWA	1 mg/m3	Respirable dust.
Titanium dioxide (CAS 13463-67-7)	TWA	4 mg/m3	Respirable.
Toluene (CAS 108-88-3)	STEL	10 mg/m3 384 mg/m3	Inhalable
	TWA	100 ppm 191 mg/m3	
Trimethylbenzene (CAS 25551-13-7)	TWA	50 ppm 125 mg/m3	
	STEL	25 ppm 441 mg/m3	
Xylene (CAS 1330-20-7)	TWA	100 ppm 220 mg/m3	
	STEL	50 ppm	

**EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU**

<b>Components</b>	<b>Type</b>	<b>Value</b>
2-Heptanone (CAS 110-43-0)	STEL	475 mg/m3
	TWA	100 ppm 238 mg/m3
4-Methyl-2-pentanone (CAS 108-10-1)	STEL	50 ppm 208 mg/m3
	TWA	83 mg/m3 20 ppm
acetone (CAS 67-64-1)	TWA	1210 mg/m3 500 ppm
Cumene (CAS 98-82-8)	STEL	250 mg/m3 50 ppm
	TWA	100 mg/m3 20 ppm
Ethyl benzene (CAS 100-41-4)	STEL	884 mg/m3
	TWA	200 ppm 442 mg/m3
Toluene (CAS 108-88-3)	STEL	100 ppm 384 mg/m3
	TWA	100 ppm 192 mg/m3
Xylene (CAS 1330-20-7)	STEL	50 ppm 442 mg/m3

Components	Type	Value
	TWA	100 ppm 221 mg/m <sup>3</sup> 50 ppm

**Biological limit values****Czech Republic. Limit Values for Indicators of Biological Exposure Tests in Urine and Blood, Annex 2, Tables 1 and 2, Government Decree 432/2003 Sb.**

Components	Value	Determinant	Specimen	Sampling time
Ethyl benzene (CAS 100-41-4)	1100 µmol/mmol	Mandelic acid	Creatinine in urine	*
	1500 mg/g	Mandelic acid	Creatinine in urine	*
Toluene (CAS 108-88-3)	1000 µmol/mmol	Hippuric acid	Creatinine in urine	*
	1600 mg/g	Hippuric acid	Creatinine in urine	*
Xylene (CAS 1330-20-7)	820 µmol/mmol	Methylhippuric acids	Creatinine in urine	*
	1400 mg/g	Methylhippuric acids	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Finland. HTP-arvot, App 2., Biological Limit Values, (BRA/BGV), Social Affairs and Ministry of Health**

Components	Value	Determinant	Specimen	Sampling time
Ethyl benzene (CAS 100-41-4)	5,2 mmol/l	Mandelic acid	Urine	*
Toluene (CAS 108-88-3)	500 nmol/l	Toluene concentration	Blood	*
Xylene (CAS 1330-20-7)	5 mmol/l	Methylhippuric acids	Urine	*

\* - For sampling details, please see the source document.

**France. Biological indicators of exposure (IBE) (National Institute for Research and Security (INRS, ND 2065))**

Components	Value	Determinant	Specimen	Sampling time
4-Methyl-2-pentanone (CAS 108-10-1)	2 mg/l	Méthylisobutylcétone	Urine	*
acetone (CAS 67-64-1)	100 mg/l	Acétone	Urine	*
Ethyl benzene (CAS 100-41-4)	1500 mg/g	Acide mandélique	Creatinine in urine	*
Toluene (CAS 108-88-3)	2500 mg/g	Acide hippurique	Creatinine in urine	*
	2500 mg/g	Acide hippurique	Creatinine in urine	*
	1 mg/l	Toluène	Venous blood	*
Xylene (CAS 1330-20-7)	1500 mg/g	Acides méthylhippuriques	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Germany. TRGS 903, BAT List (Biological Limit Values)**

Components	Value	Determinant	Specimen	Sampling time
4-Methyl-2-pentanone (CAS 108-10-1)	3,5 mg/l	4-Methylpentan-2-on	Urine	*
acetone (CAS 67-64-1)	80 mg/l	Aceton	Urine	*
Ethyl benzene (CAS 100-41-4)	300 mg/l	Mandelsäure plus Phenylglyoxylsäure	Urine	*
Toluene (CAS 108-88-3)	600 µg/l	Toluol	Blood	*
	1,5 mg/l	o-Kresol (nach Hydrolyse)	Urine	*
Trimethylbenzene (CAS 25551-13-7)	400 mg/g	Dimethylbenzoesäuren (Summe aller Isomeren nach Hydrolyse)	Creatinine in urine	*

**Germany. TRGS 903, BAT List (Biological Limit Values)**

Components	Value	Determinant	Specimen	Sampling time
Xylene (CAS 1330-20-7)	2000 mg/l	Methylhippur-(Tolur-) säure (alle Isomere)	Urine	*
	1,5 mg/l	Xylol	Blood	*

\* - For sampling details, please see the source document.

**Hungary. Chemical Safety at Workplace Ordinance Joint Decree No. 25/2000 (Annex 2): Permissible limit values of biological exposure (effect) indices**

Components	Value	Determinant	Specimen	Sampling time
Ethyl benzene (CAS 100-41-4)	1500 mg/g	mandelic acid	Creatinine in urine	*
	1110 µmol/mmol	mandelic acid	Creatinine in urine	*
Toluene (CAS 108-88-3)	1 mg/g	o-crezol	Creatinine in urine	*
	1,05 µmol/mmol	o-crezol	Creatinine in urine	*
Xylene (CAS 1330-20-7)	1500 mg/g	methyl hippuric acids	Creatinine in urine	*
	860 µmol/mmol	methyl hippuric acids	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Slovakia. BLVs (Biological Limit Value). Regulation no. 355/2006 concerning protection of workers exposed to chemical agents, Annex 2**

Components	Value	Determinant	Specimen	Sampling time
4-Methyl-2-pentanone (CAS 108-10-1)	2,36 mg/g	Methyl isobutyl ketone	Creatinine in urine	*
	3,5 mg/l	Methyl isobutyl ketone	Urine	*
acetone (CAS 67-64-1)	53,36 mg/g	Acetone	Creatinine in urine	*
	80 mg/l	Acetone	Urine	*
Ethyl benzene (CAS 100-41-4)	8,03 mg/g	2-ethylphenol	Creatinine in urine	*
	12 mg/l	2-ethylphenol	Urine	*
Toluene (CAS 108-88-3)	600 µg/l	Toluene	Blood	*
	1600 mg/g	Hippuric acid	Creatinine in urine	*
	1,03 mg/g	o-cresol (Phenol, 2-methyl-)	Creatinine in urine	*
	2401 mg/l	Hippuric acid	Urine	*
	1,5 mg/l	o-cresol (Phenol, 2-methyl-)	Urine	*
Xylene (CAS 1330-20-7)	1334 mg/g	Methylhippuric acids	Creatinine in urine	*
	2000 mg/l	Methylhippuric acids	Urine	*
	1,5 mg/l	Xylene	Blood	*

\* - For sampling details, please see the source document.

**Spain. Biological Limit Values (VLBs), Occupational Exposure Limits for Chemical Agents, Table 4**

Components	Value	Determinant	Specimen	Sampling time
4-Methyl-2-pentanone (CAS 108-10-1)	1 mg/l	Metilisobutilcetona	Urine	*
acetone (CAS 67-64-1)	50 mg/l	Acetona	Urine	*
Ethyl benzene (CAS 100-41-4)	700 mg/g	Suma del ácido mandélico y el ácido fenilglioxílico	Creatinine in urine	*
Toluene (CAS 108-88-3)	1,6 g/g	Ácido hipúrico	Creatinine in urine	*
	0,5 mg/l	o-cresol (Phenol, 2-methyl-)	Urine	*
	0,05 mg/l	Tolueno	Blood	*

**Spain. Biological Limit Values (VLBs), Occupational Exposure Limits for Chemical Agents, Table 4**

Components	Value	Determinant	Specimen	Sampling time
------------	-------	-------------	----------	---------------

Xylene (CAS 1330-20-7)	1 g/g	Ácidos metilhipúricos	Creatinine in urine	*
------------------------	-------	-----------------------	---------------------	---

\* - For sampling details, please see the source document.

**Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA)**

Components	Value	Determinant	Specimen	Sampling time
------------	-------	-------------	----------	---------------

4-Methyl-2-pentanone (CAS 108-10-1)	2 mg/l	4-Methylpentan-2-on	Urine	*
acetone (CAS 67-64-1)	80 mg/l	Aceton	Urine	*
Cumene (CAS 98-82-8)	50 mg/g	2-Phenyl-2-propanol	Creatinine in urine	*
Ethyl benzene (CAS 100-41-4)	800 mg/l	Mandelsäure plus Phenylglyoxylsäure	Urine	*
Toluene (CAS 108-88-3)	600 µg/l	Toluol	Blood	*
	2 g/g	Hippursäure	Creatinine in urine	*
	0,5 mg/l	o-Kresol	Urine	*
Xylene (CAS 1330-20-7)	1,5 g/g	Methyl-Hippursäure	Creatinine in urine	*
	1,5 mg/l	Xylol	Blood	*

\* - For sampling details, please see the source document.

**UK. EH40 Biological Monitoring Guidance Values (BMGVs)**

Components	Value	Determinant	Specimen	Sampling time
------------	-------	-------------	----------	---------------

4-Methyl-2-pentanone (CAS 108-10-1)	20 µmol/l	4-Methylpentan-2-one	Urine	*
Xylene (CAS 1330-20-7)	650 mmol/mol	Methyl hippuric acid	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Recommended monitoring procedures** Follow standard monitoring procedures.

**Derived no-effect level (DNEL)** Not available.

**Predicted no effect concentrations (PNECs)** Not available.

**Exposure guidelines**

**EU Exposure Limit Values: Skin designation**

2-Heptanone (CAS 110-43-0)	Can be absorbed through the skin.
Cumene (CAS 98-82-8)	Can be absorbed through the skin.
Ethyl benzene (CAS 100-41-4)	Can be absorbed through the skin.
Toluene (CAS 108-88-3)	Can be absorbed through the skin.
Xylene (CAS 1330-20-7)	Can be absorbed through the skin.

**8.2. Exposure controls**

**Appropriate engineering controls** Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

**Individual protection measures, such as personal protective equipment**

**General information** Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin protection**

**- Hand protection** Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

**- Other** Wear appropriate chemical resistant clothing.

**Respiratory protection** If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

<b>Thermal hazards</b>	Wear appropriate thermal protective clothing, when necessary.
<b>Hygiene measures</b>	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.
<b>Environmental exposure controls</b>	Inform appropriate managerial or supervisory personnel of all environmental releases.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Appearance

<b>Physical state</b>	Liquid.
<b>Form</b>	Liquid.
<b>Colour</b>	Grey Opaque.
<b>Odour</b>	Solvent.
<b>Odour threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	-94,7 °C (-138,46 °F) estimated
<b>Initial boiling point and boiling range</b>	56,05 °C (132,89 °F) estimated
<b>Flash point</b>	-20,0 °C (-4,0 °F) estimated
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	2,6 % estimated
<b>Flammability limit - upper (%)</b>	12,8 % estimated
<b>Vapour pressure</b>	492,8 hPa estimated
<b>Vapour density</b>	Not available.
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Not available.
<b>Solubility (other)</b>	Not available.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	465 °C (869 °F) estimated
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Explosive properties</b>	Not available.
<b>Oxidizing properties</b>	Not available.

### 9.2. Other information

<b>Density</b>	8,68 lbs/gal
<b>Percent volatile</b>	59,98 %
<b>Specific gravity</b>	1,04
<b>VOC</b>	3,2 lbs/gal Material 4,6 lbs/gal Regulatory 384 g/l Material 553 g/l Regulatory

## SECTION 10: Stability and reactivity

<b>10.1. Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>10.2. Chemical stability</b>	Material is stable under normal conditions.
<b>10.3. Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>10.4. Conditions to avoid</b>	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>10.5. Incompatible materials</b>	Strong acids. Strong oxidising agents. Halogens.

**10.6. Hazardous decomposition products**

No hazardous decomposition products are known.

**SECTION 11: Toxicological information**

**General information** Occupational exposure to the substance or mixture may cause adverse effects.

**Information on likely routes of exposure**

- Inhalation** Harmful if inhaled. May cause drowsiness and dizziness. Headache. Nausea, vomiting. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- Skin contact** Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction.
- Eye contact** Causes serious eye irritation.
- Ingestion** May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.

**Symptoms** Headache. May cause drowsiness and dizziness. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

**11.1. Information on toxicological effects**

**Acute toxicity** Harmful if inhaled. Harmful in contact with skin. Narcotic effects.

Components	Species	Test results
2-Heptanone (CAS 110-43-0)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	12600 mg/kg
<b>Oral</b>		
LD50	Mouse	730 mg/kg
	Rat	1,67 g/kg
4-Methyl-2-pentanone (CAS 108-10-1)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 16000 mg/kg
<b>Inhalation</b>		
LC50	Rat	8,2 mg/l, 4 Hours
<b>Oral</b>		
LD50	Rat	2080 mg/kg
acetone (CAS 67-64-1)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	20000 mg/kg 20 ml/kg
<b>Inhalation</b>		
LC50	Rat	76 mg/l, 4 Hours 50,1 mg/l, 8 Hours
<b>Oral</b>		
LD50	Mouse	3000 mg/kg
	Rabbit	5340 mg/kg
	Rat	5800 mg/kg
Cumene (CAS 98-82-8)		
<b>Acute</b>		
<b>Inhalation</b>		
LC50	Mouse	2000 ppm, 7 Hours 24,7 mg/l, 2 Hours
	Rat	8000 ppm, 4 Hours
<b>Oral</b>		
LD50	Rat	1400 mg/kg

Components	Species	Test results
Ethyl benzene (CAS 100-41-4)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	17800 mg/kg
<b>Oral</b>		
LD50	Rat	3500 mg/kg
Toluene (CAS 108-88-3)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	12124 mg/kg 14,1 ml/kg
<b>Inhalation</b>		
LC50	Mouse	5320 ppm, 8 Hours 400 ppm, 24 Hours
	Rat	26700 ppm, 1 Hours 12200 ppm, 2 Hours 8000 ppm, 4 Hours
<b>Oral</b>		
LD50	Rat	2,6 g/kg
VM & P NAPHTHA (CAS 8032-32-4)		
<b>Acute</b>		
<b>Inhalation</b>		
LC50	Rat	3400 mg/l, 4 Hours
Xylene (CAS 1330-20-7)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 43 g/kg
<b>Inhalation</b>		
LC50	Mouse	3907 mg/l, 6 Hours
	Rat	6350 mg/l, 4 Hours
<b>Oral</b>		
LD50	Mouse	1590 mg/kg
	Rat	3523 - 8600 mg/kg

\* Estimates for product may be based on additional component data not shown.

<b>Skin corrosion/irritation</b>	Causes skin irritation.
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.
<b>Respiratory sensitisation</b>	Due to partial or complete lack of data the classification is not possible.
<b>Skin sensitisation</b>	Due to partial or complete lack of data the classification is not possible.
<b>Germ cell mutagenicity</b>	May cause genetic defects.
<b>Carcinogenicity</b>	May cause cancer.
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>	
4-Methyl-2-pentanone (CAS 108-10-1)	2B Possibly carcinogenic to humans.
Cumene (CAS 98-82-8)	2B Possibly carcinogenic to humans.
Ethyl benzene (CAS 100-41-4)	2B Possibly carcinogenic to humans.
Silicon dioxide (CAS 14808-60-7)	1 Carcinogenic to humans.
Stoddard solvent (CAS 8052-41-3)	3 Not classifiable as to carcinogenicity to humans.
Titanium dioxide (CAS 13463-67-7)	2B Possibly carcinogenic to humans.
Toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.
Xylene (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.
<b>Reproductive toxicity</b>	Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging the unborn child.
<b>Specific target organ toxicity - single exposure</b>	May cause drowsiness and dizziness.

**Specific target organ toxicity - repeated exposure** Due to partial or complete lack of data the classification is not possible.

**Aspiration hazard** Due to partial or complete lack of data the classification is not possible.

**Mixture versus substance information** No information available.

**Other information** May cause allergic respiratory and skin reactions.

## SECTION 12: Ecological information

**12.1. Toxicity** Toxic to aquatic life with long lasting effects.

Components		Species	Test results
2-Heptanone (CAS 110-43-0)			
<b>Aquatic</b>			
Fish	LC50	Fathead minnow ( <i>Pimephales promelas</i> )	126 - 137 mg/l, 96 hours
4-Methyl-2-pentanone (CAS 108-10-1)			
<b>Aquatic</b>			
Fish	LC50	Fathead minnow ( <i>Pimephales promelas</i> )	492 - 593 mg/l, 96 hours
acetone (CAS 67-64-1)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea ( <i>Daphnia magna</i> )	21,6 - 23,9 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout ( <i>Oncorhynchus mykiss</i> )	4740 - 6330 mg/l, 96 hours
Cumene (CAS 98-82-8)			
<b>Aquatic</b>			
Crustacea	EC50	Brine shrimp ( <i>Artemia</i> sp.)	3,55 - 11,29 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout ( <i>Oncorhynchus mykiss</i> )	2,7 mg/l, 96 hours
Ethyl benzene (CAS 100-41-4)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea ( <i>Daphnia magna</i> )	1,37 - 4,4 mg/l, 48 hours
Fish	LC50	Fathead minnow ( <i>Pimephales promelas</i> )	7,5 - 11 mg/l, 96 hours
methyl ethyl ketoxime (CAS 96-29-7)			
<b>Aquatic</b>			
Fish	LC50	Fathead minnow ( <i>Pimephales promelas</i> )	777 - 914 mg/l, 96 hours
Titanium dioxide (CAS 13463-67-7)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea ( <i>Daphnia magna</i> )	> 1000 mg/l, 48 hours
Fish	LC50	Mummichog ( <i>Fundulus heteroclitus</i> )	> 1000 mg/l, 96 hours
Toluene (CAS 108-88-3)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea ( <i>Daphnia magna</i> )	5,46 - 9,83 mg/l, 48 hours
Fish	LC50	Coho salmon,silver salmon ( <i>Oncorhynchus kisutch</i> )	8,11 mg/l, 96 hours
Xylene (CAS 1330-20-7)			
<b>Aquatic</b>			
Fish	LC50	Bluegill ( <i>Lepomis macrochirus</i> )	7,711 - 9,591 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

**12.2. Persistence and degradability** No data is available on the degradability of this product.

### 12.3. Bioaccumulative potential

#### Partition coefficient

##### n-octanol/water (log Kow)

2-Heptanone	1,98
4-Methyl-2-pentanone	1,31
acetone	-0,24
Cumene	3,66
Ethyl benzene	3,15

Stoddard solvent	3,16 - 7,15
Toluene	2,73
Xylene	3,12 - 3,2

<b>Bioconcentration factor (BCF)</b>	Not available.
<b>12.4. Mobility in soil</b>	No data available.
<b>12.5. Results of PBT and vPvB assessment</b>	Not available.
<b>12.6. Other adverse effects</b>	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

<b>Residual waste</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
<b>EU waste code</b>	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Disposal methods/information</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Special precautions</b>	Dispose in accordance with all applicable regulations.

## SECTION 14: Transport information

### ADR

<b>14.1. UN number</b>	UN1263
<b>14.2. UN proper shipping name</b>	Paint, Paint Related Material
<b>14.3. Transport hazard class(es)</b>	
Class	3
Subsidiary risk	-
Label(s)	3
Hazard No. (ADR)	33
Tunnel restriction code	D/E
<b>14.4. Packing group</b>	II
<b>14.5. Environmental hazards</b>	Yes
<b>14.6. Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.

### RID

<b>14.1. UN number</b>	UN1263
<b>14.2. UN proper shipping name</b>	Paint, Paint Related Material
<b>14.3. Transport hazard class(es)</b>	
Class	3
Subsidiary risk	-
Label(s)	3
<b>14.4. Packing group</b>	II
<b>14.5. Environmental hazards</b>	Yes
<b>14.6. Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.

### ADN

<b>14.1. UN number</b>	UN1263
<b>14.2. UN proper shipping name</b>	Paint, Paint Related Material
<b>14.3. Transport hazard class(es)</b>	
Class	3
Subsidiary risk	-
Label(s)	3
<b>14.4. Packing group</b>	II
<b>14.5. Environmental hazards</b>	Yes

**14.6. Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**IATA**

**14.1. UN number** UN1263  
**14.2. UN proper shipping name** Paint, Paint Related Material

**14.3. Transport hazard class(es)**

**Class** 3  
**Subsidiary risk** -

**14.4. Packing group** II

**14.5. Environmental hazards** Yes

**ERG Code** 3H

**14.6. Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**Other information**

**Passenger and cargo aircraft** Allowed.

**Cargo aircraft only** Allowed.

**IMDG**

**14.1. UN number** UN1263  
**14.2. UN proper shipping name** Paint, Paint Related Material

**14.3. Transport hazard class(es)**

**Class** 3  
**Subsidiary risk** -

**14.4. Packing group** II

**14.5. Environmental hazards**

**Marine pollutant** Yes

**EmS** F-E, S-E


**14.6. Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not established.

**ADN; ADR; IATA; IMDG; RID**



**Marine pollutant**



**General information** IMDG Regulated Marine Pollutant.

## SECTION 15: Regulatory information

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

### EU regulations

**Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I, as amended**

Not listed.

**Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex II, as amended**

Not listed.

**Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended**

Not listed.

**Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 1 as amended**

Not listed.

**Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 2 as amended**

Not listed.

**Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 3 as amended**

Not listed.

**Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex V as amended**

Not listed.

**Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended**

Not listed.

**Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA**

Not listed.

#### **Authorisations**

**Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended**

light aromatic solvent naphtha (CAS 64742-95-6)

Stoddard solvent (CAS 8052-41-3)

VM & P NAPHTHA (CAS 8032-32-4)

#### **Restrictions on use**

**Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended**

4-Methyl-2-pentanone (CAS 108-10-1)

acetone (CAS 67-64-1)

Ethyl benzene (CAS 100-41-4)

methyl ethyl ketoxime (CAS 96-29-7)

Toluene (CAS 108-88-3)

**Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended**

light aromatic solvent naphtha (CAS 64742-95-6)

Stoddard solvent (CAS 8052-41-3)

VM & P NAPHTHA (CAS 8032-32-4)

**Directive 92/85/EEC: on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding, as amended**

light aromatic solvent naphtha (CAS 64742-95-6)

methyl ethyl ketoxime (CAS 96-29-7)

Stoddard solvent (CAS 8052-41-3)

Toluene (CAS 108-88-3)

VM & P NAPHTHA (CAS 8032-32-4)

#### **Other EU regulations**

**Directive 2012/18/EU on major accident hazards involving dangerous substances**

2-Heptanone (CAS 110-43-0)

4-Methyl-2-pentanone (CAS 108-10-1)

acetone (CAS 67-64-1)

Cumene (CAS 98-82-8)

Ethyl benzene (CAS 100-41-4)

Toluene (CAS 108-88-3)

Xylene (CAS 1330-20-7)

**Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work, as amended**

2-Heptanone (CAS 110-43-0)

4-Methyl-2-pentanone (CAS 108-10-1)

acetone (CAS 67-64-1)

Cumene (CAS 98-82-8)

Ethyl benzene (CAS 100-41-4)

light aromatic solvent naphtha (CAS 64742-95-6)

methyl ethyl ketoxime (CAS 96-29-7)

Stoddard solvent (CAS 8052-41-3)

Toluene (CAS 108-88-3)

VM & P NAPHTHA (CAS 8032-32-4)

Xylene (CAS 1330-20-7)

## Directive 94/33/EC on the protection of young people at work, as amended

Ethyl benzene (CAS 100-41-4)  
light aromatic solvent naphtha (CAS 64742-95-6)  
methyl ethyl ketoxime (CAS 96-29-7)  
Stoddard solvent (CAS 8052-41-3)  
Toluene (CAS 108-88-3)  
VM & P NAPHTHA (CAS 8032-32-4)

**Other regulations** The product is classified and labelled in accordance with EC directives or respective national laws. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006. Pregnant women should not work with the product, if there is the least risk of exposure.

**National regulations** Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work. Follow national regulation for work with chemical agents.

**15.2. Chemical safety assessment** No Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

**List of abbreviations** Not available.

**References** Not available.

**Information on evaluation method leading to the classification of mixture** The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

### Full text of any statements or R-phrases and H-statements under Sections 2 to 15

R10 Flammable.  
R11 Highly flammable.  
R20 Harmful by inhalation.  
R20/21 Harmful by inhalation and in contact with skin.  
R20/22 Harmful by inhalation and if swallowed.  
R21 Harmful in contact with skin.  
R36 Irritating to eyes.  
R36/37 Irritating to eyes and respiratory system.  
R37 Irritating to respiratory system.  
R38 Irritating to skin.  
R40 Limited evidence of a carcinogenic effect.  
R41 Risk of serious damage to eyes.  
R43 May cause sensitisation by skin contact.  
R45 May cause cancer.  
R46 May cause heritable genetic damage.  
R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.  
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R63 Possible risk of harm to the unborn child.  
R65 Harmful: may cause lung damage if swallowed.  
R66 Repeated exposure may cause skin dryness or cracking.  
R67 Vapours may cause drowsiness and dizziness.  
H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H332 Harmful if inhaled.  
H336 May cause drowsiness or dizziness.  
H340 May cause genetic defects.  
H350 May cause cancer.  
H351 Suspected of causing cancer.  
H361d Suspected of damaging the unborn child.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H411 Toxic to aquatic life with long lasting effects.

**Revision information** None.

**Training information** Follow training instructions when handling this material.

**Disclaimer**

The information in the sheet was written based on the best knowledge and experience currently available. The information contained herein is based on data believed to be reliable and the manufacturer disclaims any liability incurred from the use or reliance upon the same. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This safety information is not a licence to use this material as claimed by any patents of third parties. The user alone must finally determine whether a contemplated use of this material will infringe any such patents, and for obtaining any required licenses.