Fax sent by : 3132559199

GEISLER COMPANY

12-16-08 15:30 Pg: 2/4

14

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: RUSTLICK 606

LONG TERM RUST PREVENTATIVE

HMIS CODES:

Health = 1

FINISHED GOODS:

Flammability = 2

5 GAL = 7105255 GAT. = 71552 Reactivity = 0

SECTION 1 - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: ITW ROCOL NORTH AMERICA

ADDRESS : 3624 West Lake Avenue Glenview, Illinois 60026

EMERGENCY PHONE : 800-4249300 CHEMTREC

INFORMATION PHONE : 800-452-5823

DATE REVISED : 08/08/07

NAME OF PREPARER : Steve Badger II

SUPERCEDES : 1/22/07

SECTION 2 - INGREDIENTS

REPORTABLE COMPONENTS

CAS NUMBER

WEIGHT PERCENT

PETROLEUM HYDROCARBON

64742-47-8

71-90%

COMBUSTIBLE: TLV=300PPM

107-41-5

1-5%

* HEXYLENE GLYCOL TLV:25 ppm CEILING

* Indicates chemical(s) subject to the reporting requirements of OSHA's Hazard Communication Standard 1910.1200.

All ingredients in this product are listed on TSCA.

SECTION 3 - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: 212°F

SPECIFIC GRAVITY (H2O=1): 0.83

VAPOR DENSITY: (Air = 1): >1

EVAPORATION RATE: (BuAc=1): <1

SOLUBILITY IN WATER: Insoluble

APPEARANCE AND ODOR: Reddish brown liquid with mild odor

SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 175°F

METHOD USED: PMCC

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 1.28 UPPER: 8.8

EXTINGUISHING MEDIA: Water No, CO2 Yes, Dry chemical Yes, Foam Yes,

Alcohol foam No.

SPECIAL FIREFIGHTING PROCEDURES: Fire fighters should wear self-contained breathing apparatus in confined areas.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None.

SECTION 5 - REACTIVITY DATA

r: 3/4

STABILITY: Chemically stable.

CONDITIONS TO AVOID: None

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Oxides of carbon.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION 6 - HEALTH MAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: High concentrations of vapors may produce irritation of the respiratory tract, headache, dizziness, and nausea.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Slight irritation.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Slight irritant. INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: No data.

HEALTH HAZARDS (ACUTE AND CHRONIC):

Acute: Slight irritation.

Chronic: Effects are not known.

CARCINOGENICITY: NTP CARCINOGEN: No

TARC MONOGRAPHS: No OSHA REGULATED: No

ACGIH CARCINOGENICITY: No

TOXICITY DATA:

INGREDIENTS	ORAL LD50 (RAT)	DËRMAT, LD50 (Rabbit)	INHALATTON LD50
Hexylene glycol	N/A	N/A	N/A
Petrolem Hydrogarbon	low toxicity	low toxicity	N/A

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Skin disorders.

EMERGENCY AND FIRST AID PROCEDURES:

EYES: Flush well with water. Contact a physician if irritation persists.

SKIN: Wash with soap and water.

INHALATION: No emergency care anticipated under normal conditions.

INGESTION: Do not induce vomiting. Contact a physician. If vomiting

occurs, keep head below hips to prevent aspiration of liquid into lungs.

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Prevent skin and eye contact. Use non-combustible material to confine and/or absorb. Eliminate ignition sources. Ventilate area.

WASTE DISPOSAL METHOD: Remove to a waste disposal facility operating in compliance with federal, state, and local regulations.

Applicable CERCLA/RCRA Hazardous Waste Codes: None PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: If mists are generated in the use of this product; then the following values for petroleum oils apply:

---ACHIG - TLV/TWA = 5 mg/m3/8hr ---OSHA - PEL/TWA = 5 mg/m3/8hr Fax sent by : 3132559199

GEISLER COMPANY

12-16-08 15:30

Pg: 4/4

---ACGIH - TLV/STEL = 10 mg/m3

If mist levels exceed these values, then a respirator should be worn to provide protection to workers.

SHIPPING CLASSIFICATION: Combustible Liquid, non-hazardous, NA1993 (combustible with Flash Point of 175F).

SECTION 8 - CONTROL MEASURES

RESPIRATORY PROTECTION: None required at normal handling temperatures. VENTILATION: Local exhaust is recommended for confined areas. General mechanical ventilation is adequate for normal use.

PROTECTIVE GLOVES: Chemical resistant rubber gloves, such as polyvinyl chloride-coated, and other protective gear as required to minimize skin contact.

EYE PROTECTION: Safety glasses. Splash proof goggles. OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Eye bath and safety shower. WORK/HYGIENIC PRACTICES: Follow current H.M.I S. regulations.

SECTION 9 - REGULATORY INFORMATION

U.S. Federal Regulatory Information:

SARA ETREMELY HAZARDOUS SUBSTANCE: No chemicals in this product exceed the DE Minimus reporting level established on the SARA ETREMELY HAZARDOUS SUBSTANCE LIST.

SARA TITLE III, Section 313: No chemicals in this product exceed the DE Minimus reporting level established by SARA TITLE III, Section 313.

TSCA:

All ingredients are listed in TSCA inventory.

CERCLA:

Not reportable

SECTION 10 - DISCLAIMER

ITW ROCOL NORTH AMERICA bases the information and recommendations in this document on data believed to be correct. No warranty of any kind, however, is made as to the information in this document.