

MATERIAL SAFETY DATA SHEET


MSDS No. AI-60-20653

Revision#: 1

Date of Preparation: 7/29/2003

SECTION I. Product and Company Information

BRAND NAME: BODY DRENCH
PRODUCT NAME: SELF-TANNING SPRAY
PRODUCT IDENTIFICATION: 20653
NATURE OF PRODUCT: SKIN CARE
MANUFACTURER: AMERICAN INTERNATIONAL INDUSTRIES
2220 GASPAR AVE. LOS ANGELES, CA 90040
Tel: (323) 728-2999 FAX: (323) 726-6271
24 Hour Emergency Phone: Chemtrec (800) 424-9300



HMIS	
H	2
F	4
R	0
PPE	C

SECTION II. Information on Hazardous Ingredients

<u>Ingredient Name</u>	<u>Hazardous</u>	<u>Carcinogenic</u>	<u>CAS Number</u>	<u>% Wt. or % Vol</u>	<u>Toxicity Data</u>
Dimethyl Ether	Yes	No	115-10-6	40.00%	None Established
Alcohol Denat.	Yes	No	64-17-5	20.40%	1000 ppm PEL **

** Permissible Exposure Limit * Threshold Limit Value

SECTION III. Physical and Chemical Properties

Appearance	Thin liquid spray	Solubility in Water	Soluble
Color	Brown	Volatiles (By Weight)	92%
Odor	Vanilla	Vapor Pressure (PSIG) @ 70°F	87 (for propellant)
Specific Gravity	0.960 (prior to addition of propellant)	Vapor Density	2.4 (for propellant)

SECTION IV. Fire Fighting Measures

Flash Point	< 73°F (Tag Closed Cup)
Flamability Classification	Extremely Flammable
Extinguishing Media	Use water spray or mist, dry chemical, or Carbon Dioxide.
Fire and Explosion Hazards	Keep containers cool and away from flames, and sources of ignition. Do not crush or puncture containers. Closed containers exposed to excessive heat may rupture.
Special Fire Fighting Procedures	Confine to immediate area; disperse vapor if spill occurs; shut off source. Wear full bunker gear while controlling fire in confined areas.

SECTION V. Stability and Reactivity

Stability	Stable at room temperature in closed containers under normal storage and handling conditions.
Polymerization	Will not occur
Conditions to avoid	Heat, sparks, flame, strong acids and contact with strong oxidizing agents.
Hazardous Decomposition Products	Excessive heat may cause Carbon Monoxide, Carbon Dioxide, and unidentified organic compounds to be released. Asphyxiation by displacement may occur.

SECTION VI. Health Hazard Information

Potential Health Effects

Primary Routes of Entry: Eyes, Skin, Inhalation, Ingestion	
Eye Contact	Liquid and vapor may cause mild to severe eye irritation. Splashes may cause temporary pain and blurred vision.
Skin Contact	Repeated contact may cause irritation and drying of the skin. Contact with propellant may cause freeze burns. Avoid contact with rashes or open sores.
Inhalation	May cause irritation to mucous membranes of the upper respiratory tract. Inhalation of propellant may cause headache, drowsiness, and inability to concentrate, or asphyxiation by oxygen displacement.
Ingestion	May irritate digestive tract and cause intestinal discomfort. May cause depression of Central Nervous System.
Chronic Effects	None known.

MATERIAL SAFETY DATA SHEET

Date of Preparation: 7/29/03

MSDS NO. AI-60-20653

Emergency and First Aid Procedures

Eyes	Irrigate with flowing water immediately and continuously for up to 15 minutes. Consult medical personnel if irritation persists.
Skin	Flush with plenty of tepid water for at least 15 minutes. Treat for frostbite, if necessary, by gently warming area. Consult physician if irritation persists. Launder contaminated clothing before reuse.
Ingestion	DO NOT INDUCE VOMITING! Contact Poison Control Center immediately.
Inhalation	If ill effects occur, remove to fresh air. If breathing has stopped, perform artificial respiration. Seek medical attention as needed.
Note to Physician	No specific antidote. Treat symptomatically. Inhalation hazard. Because inhalation of propellant may cause disturbance of cardiac rhythm, catecholamine drugs, such as epinephrine, should only be used with special caution in situations of emergency life support.

SECTION VII. Spill, Leak, and Disposal Procedures

Steps to be taken in case material is released or spilled

For small spills or leaks, contain spill with inert material; sweep up, and place in a disposal container. For large spills, dike far ahead of spill for later disposal. Disperse vapors with water spray. Do not release into sewers or water-ways.

Waste disposal method

Disposal requirements are dependent on hazard classification and will vary by location and the type of disposal selected. 2-2-0 LABORATORIES suggests that all local, state, and federal regulations concerning health and pollution be reviewed to determine approved disposal methods

SECTION VIII. Exposure Controls / Personal Protection

Ventilation Provide general or local exhaust ventilation systems to maintain airborne concentration of hazardous materials below OSHA PELs (Sec. 2).

Respiratory Protection

Follow OSHA respirator regulations (29 CFR 1910.134). If necessary, wear an SCBA.

Personal Protective Equipment

As necessary, wear protective gloves, boots, aprons, and gauntlets. Wear protective eyeglasses or safety goggles per OSHA regulations (29 CFR 1910.133)

SECTION IX. Other Information

Handling & Storage

Practice good personal hygiene after handling this product. Protect containers from physical damage, shield them from direct sunlight, and store in cool, dry area.

DOT Transport Information (49 CFR 172.101)

Shipping Name: CONSUMER COMMODITY

Hazard Class: ORM-D

UN/NA Number: -----

Disclaimer

This information is given without any warranty or representation. It is believed to be correct, but does not claim to be all-inclusive, and shall be used only as a guide. All, shall not be held liable for any damage resulting from handling or contact with this product. This information is offered solely for your consideration, investigation, and verification.