SAFETY DATA SHEET

M1055 - ANSI - EN





SULFURIC ACID - SPENT

SDS No.: M1055 Rev. Date: 27-Jun-2014 Rev. Num. 12

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Occidental Chemical Corporation **Company Identification:**

> 5005 LBJ Freeway P.O. Box 809050 Dallas, TX 75380-9050

1-800-752-5151

24 Hour Emergency Telephone

Number:

1-800-733-3665 or 1-972-404-3228 (USA); CHEMTREC (within USA and

Canada): 1-800-424-9300; CHEMTREC (outside USA and Canada): +1

703-527-3887; CHEMTREC Contract No: CCN16186

To Request an SDS: MSDS@oxy.com or 1-972-404-3245

Customer Service: 1-800-752-5151 or 1-972-404-3700

Product Identifier: SULFURIC ACID - SPENT

Spent Sulfuric Acid Synonyms:

Product Use: Process cleaner

Uses Advised Against: None identified.

2. HAZARDS IDENTIFICATION

OSHA REGULATORY STATUS: This material is considered hazardous by the OSHA Hazard Communication

Standard (29 CFR 1910.1200).

Print date: 27-Jun-2014 1 of 15

SDS No.: M1055 **Rev. Date**: 27-Jun-2014 **Rev. Num.** 12

EMERGENCY OVERVIEW:

Color: Slight yellow to dark amber

Physical state Liquid Appearance: Turbid

Odor: Pungent, Biting, Organic

Signal Word: <u>DANGER</u>

MAJOR HEALTH HAZARDS: CORROSIVE. CAUSES SEVERE SKIN BURNS AND EYE DAMAGE. CAUSES SERIOUS EYE DAMAGE. FATAL IF INHALED. CAUSES DAMAGE TO RESPIRATORY SYSTEM. CAUSES DAMAGE TO THE RESPIRATORY SYSTEM AND TEETH THROUGH PROLONGED OR REPEATED EXPOSURES. MAY CAUSE CANCER IF INHALED.

PHYSICAL HAZARDS: STRONG OXIDIZER. MAY BE CORROSIVE TO METALS. Contact with metals may evolve flammable hydrogen gas. May spatter or generate heat when mixed with water.

AQUATIC TOXICITY: HARMFUL TO AQUATIC LIFE.

PRECAUTIONARY STATEMENTS: Do not get in eyes, on skin, or on clothing. Wear protective gloves, protective clothing, eye, and face protection as appropriate. Do not breathe mists or spray. Use outdoors or in a well-ventilated area. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Oxidizer, keep separated from incompatible substances.

GHS CLASSIFICATION:

CHE, DHVCICAL HAZADDO.	Corrosive to Metals
011011111010111111111111111111111111111	
GHS: CONTACT HAZARD - SKIN:	Category 1A - Causes severe skin burns and eye damage
GHS: CONTACT HAZARD - EYE:	Category 1 - Causes serious eye damage
GHS: ACUTE TOXICITY -	Category 2 - Fatal if inhaled
INHALATION:	
GHS: TARGET ORGAN	Category 1 - Causes damage to: Respiratory System
TOXICITY (SINGLE EXPOSURE):	
GHS: TARGET ORGAN	Category 1 - Causes damage to respiratory system and teeth through prolonged
	or repeated exposure
EXPOSURE):	
GHS: CARCINOGENICITY:	Category 1 - May cause cancer
GHS: HAZARDOUS TO AQUATIC	Category 3 - Harmful to aquatic life
ENVIRONMENT - ACUTE	
HAZARD:	

UNKNOWN ACUTE TOXICITY:

Not applicable. This product was tested as a whole. This information only pertains to untested mixtures.

GHS SYMBOL:

Corrosive, Health hazards, Skull and Crossbones

Print date: 27-Jun-2014 **2 of 15**

SDS No.: M1055 **Rev. Date**: 27-Jun-2014 **Rev. Num.** 12







GHS SIGNAL WORD: DANGER

GHS HAZARD STATEMENTS:

GHS - Physical Hazard Statement(s)

May be corrosive to metals

GHS - Health Hazard Statement(s)

Fatal if inhaled

Causes severe skin burns and eye damage

Causes serious eye damage

Causes damage to respiratory system

Causes damage to organs through prolonged or repeated exposure (Respiratory System and Teeth)

May cause cancer

GHS - Environmental Hazard Statement(s)

Harmful to aquatic life

GHS - Precautionary Statement(s) - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Do not breathe mists or vapors

In case of inadequate ventilation, wear respiratory protection

Wear protective gloves, protective clothing, eye, and face protection

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Avoid release to the environment

GHS - Precautionary Statement(s) - Response

IF INHALED: Remove person to fresh air and keep comfortable for breathing

Immediately call a POISON CENTER or doctor/physician

Specific treatment is urgent (see Section 4 of SDS or first aid information on this label)

IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower Wash contaminated clothing before reuse

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

IF exposed or concerned: Get medical advice/attention

Get medical advice/attention if you feel unwell

GHS - Precautionary Statement(s) - Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Print date: 27-Jun-2014 3 of 15

SDS No.: M1055 **Rev. Date**: 27-Jun-2014 **Rev. Num.** 12

GHS - Precautionary Statement(s) - Disposal

Dispose of contents and container in accordance with applicable local, regional, national, and/or international regulations

Hazards Not Otherwise Classified (HNOC)

None identified

See Section 11: TOXICOLOGICAL INFORMATION

3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms: Spent Sulfuric Acid

Component	Percent [%]	CAS Number
Sulfuric acid	65 - 85	7664-93-9
Water	15 - 35	7732-18-5

4. FIRST AID MEASURES

INHALATION: If inhaled and adverse effects occur, remove victim to fresh air and keep at rest in a position comfortable for breathing. Evaluate ABC's (is Airway constricted, is Breathing occurring, and is blood Circulating) and treat symptomatically. If you feel unwell, GET MEDICAL ATTENTION IMMEDIATELY.

SKIN CONTACT: If on skin or hair, immediately flush contaminated areas with water. Remove immediately all contaminated clothing, jewelry, and shoes. Rinse skin with large amounts of water. Thoroughly clean and dry contaminated clothing and shoes before reuse. If you feel unwell, immediately contact a poison center, physician, or get medical attention. The specific treatment is dilution with water. There is no antidote.

EYE CONTACT: Immediately flush contaminated eyes with a directed stream of water for as long as possible. Remove contact lenses, if present and easy to do. Continue rinsing. Continued irrigation may be necessary to ensure neutral pH. Water or saline may be used. GET MEDICAL ATTENTION IMMEDIATELY.

INGESTION: If swallowed: Rinse mouth. Do NOT induce vomiting. Give large amounts of water. If vomiting occurs spontaneously, keep airway clear. Give more water when vomiting stops. Never give anything by mouth to an unconscious or convulsive person. GET MEDICAL ATTENTION IMMEDIATELY.

Most Important Symptoms/Effects (Acute and Delayed)

This material may be corrosive to any tissue it comes in contact with. It can cause serious burns and extensive tissue destruction resulting in: liquefaction, necrosis, and/or perforation.

Acute Symptoms/Effects:

Print date: 27-Jun-2014 **4 of 15**

SDS No.: M1055 **Rev. Date**: 27-Jun-2014 **Rev. Num.** 12

Inhalation (Breathing): Respiratory System Effects: Acute inhalation may cause: sever irritation of the respiratory tract with sore throat, coughing, shortness of breath, bronchospasm and pulmonary edema. Causes chemical burn and dehydration of the respiratory tract. Measurements of distress include increased respiration rate and decreased tidal volume, decreased forces expiratory volume, increased airway resistance, and reduced vital capacity. Death has been reported and is usually due to sudden circulatory collapse, glottis or esophageal edema.

Skin: Skin Corrosion: Concentrated sulfuric acid is corrosive to tissue. Concentrated acid destroys tissues as a result of its severe dehydrating action, whereas dilute solutions act as milder irritants due to acid properties. Severe burns have been fatal. Sudden circulatory collapse can occur with shock if large areas of the skin have been burned.

Eye: Serious Eye Damage: Exposure to eyes may cause irritation and burns to the eye lids, conjunctivitis, corneal edema, and corneal burn. Significant and prolonged contact may cause damage to the internal contents of the eye, including perforation of the globe.

Ingestion (Swallowing): Gastrointestinal System Effects: Acute ingestion of concentrated sulfuric acid can cause nausea, vomiting, abdominal pain, perforation of the stomach, gastrointestinal bleeding, edema of the glottis, necrosis and scarring, and sudden circulatory collapse.

Delayed Symptoms/Effects:

- Respiratory System Effects: Both acute high exposures and long-term moderate exposures to mists have been associated with the occurrence of respiratory disease. Long-term exposures have been associated with bronchitis, emphysema, and frequent respiratory infections. Long-term exposure has also been associated with laryngeal and lung cancer in humans
- Skin: Repeated and prolonged skin contact may cause dermatitia
- Eyes: Blindness resulting from corneal burns, damage/loss of internal contents of the eye, and perforation of the globe
- Gastrointestinal System Effects: Delayed effects have been noted and may include: perforation, GI hemorrhage, fistula formation or delayed stricture. Effects are typically more severe in the stomach and intestinal tract than the esophagus

Interaction with Other Chemicals Which Enhance Toxicity: None known.

Medical Conditions Aggravated by Exposure: May aggravate preexisting conditions, such as: eye disorders that decrease tear production or have reduced integrity; skin disorders that compromise the integrity of the skin; and respiratory conditions including asthma and other breathing disorders.

Protection of First-Aiders: Protect yourself by avoiding contact with this material. Use personal protective equipment. Refer to Section 8 for specific personal protective equipment recommendations. Avoid contact with skin and eyes. Do not ingest. At minimum, treating personnel should utilize PPE sufficient for prevention of bloodborne pathogen transmission.

Notes to Physician: Treat as a corrosive substance. Concentrated acid destroys tissue by severe dehydrating action. Sudden circulatory collapse can occur. Sulfuric acid mist may produce bronchoconstriction in asthmatics. Concentrated acid is more toxic than pH alone. Do not attempt to neutralize pH with sodium bicarbonate. Treat via dilution. Water or milk may be used. There is no antidote. Severe burns have been fatal. Treatment is supportive care. Follow normal parameters for airway, breathing, and circulation.

5. FIRE-FIGHTING MEASURES

Fire Hazard: May release toxic gases. Containers may explode when heated or contaminated with water.

Print date: 27-Jun-2014 **5 of 15**

SDS No.: M1055 **Rev. Date**: 27-Jun-2014 **Rev. Num.** 12

Extinguishing Media: Use extinguishing agents appropriate for surrounding fire.

Fire Fighting: Wear special protective clothing as listed in Section 8. Wear NIOSH approved positive-pressure self-contained breathing apparatus operated in pressure demand mode. Move container from fire area if it can be done without risk. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas. Cool containers with water. Do not get water inside container.

Component	Immediately Dangerous to Life/ Health (IDLH)
Sulfuric acid	15 mg/m³ IDLH
7664-93-9	-

Hazardous Combustion Products: Oxides of sulfur

Sensitivity to Mechanical Impact: Not sensitive.

Sensitivity to Static Discharge: Not sensitive.

Lower Flammability Level (air): Not flammable

Upper Flammability Level (air): Not flammable

Flash point: Not flammable

Auto-ignition Temperature: Not applicable

GHS: PHYSICAL HAZARDS:

- Corrosive to Metals

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions:

Evacuation of surrounding area may be necessary for large spills. Keep unnecessary and unprotected persons away. Isolate hazard area and deny entry. Do not get in eyes, on skin or on clothing. Do not breathe fumes, mist, or spray. Wear appropriate personal protective equipment recommended in Section 8, Exposure Controls / Personal Protection, of the SDS.

Methods and Materials for Containment and Cleaning Up:

Completely contain spilled materials with dikes, sandbags, etc. Shut off ventilation system if needed. Reuse or reprocess where possible. Neutralize with soda ash or limestone. Collect with appropriate absorbent and place into suitable container. Liquid material may be removed with a properly rated vacuum truck.

Environmental Precautions:

Keep out of water supplies and sewers. This material is acidic and may lower the pH of the surface waters with low buffering capacity. Releases should be reported, if required, to appropriate agencies.

7. HANDLING AND STORAGE

Print date: 27-Jun-2014 **6 of 15**

SDS No.: M1055 **Rev. Date**: 27-Jun-2014 **Rev. Num.** 12

Precautions for Safe Handling:

Use only equipment and hoses approved for this material. Avoid breathing vapor or mist. Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling. When mixing, slowly add to water to minimize heat generation and spattering. Water or caustic solutions should never be added directly to this product because of violent reaction and spattering.

Safe Storage Conditions:

Store and handle in accordance with all current regulations and standards. Keep container tightly closed and properly labeled. Do not use spark-producing tools as flammable hydrogen gas may be present in the container and head space. Keep separated from incompatible substances (see below or Section 10 of the Safety Data Sheet).

Incompatibilities/ Materials to Avoid:

many organic and inorganic materials including, ammonia, amines, strong alkali, combustible materials, nitrites, reducing agents, metals, carbides, alcohols, chlorates, oxidizing materials, permanganates

GHS: PHYSICAL HAZARDS:

- Corrosive to Metals

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Regulatory Exposure Limit(s): As listed below

OEL: Occupational Exposure Limit; OSHA: United States Occupational Safety and Health Administration; PEL: Permissible Exposure Limit; TWA: Time Weighted Average; STEL: Short Term Exposure Limit

NON-REGULATORY EXPOSURE LIMIT(S): As listed below

- The Non-Regulatory United States Occupational Safety and Health Administration (OSHA) limits, if shown, are the Vacated 1989 PEL's (vacated by 58 FR 35338, June 30, 1993).
- The American Conference of Governmental Industrial Hygienists (ACGIH) is a voluntary organization of professional industrial hygiene personnel in government or educational institutions in the United States. The ACGIH develops and publishes recommended occupational exposure limits each year called Threshold Limit Values (TLVs) for hundreds of chemicals, physical agents, and biological exposure indices.

ENGINEERING CONTROLS: Use closed systems when possible. Provide local exhaust ventilation where vapor or mist may be generated. Ensure compliance with applicable exposure limits.

PERSONAL PROTECTIVE EQUIPMENT:

Eye Protection: Wear chemical safety goggles with a face-shield to protect against eye and skin contact when appropriate. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

Skin and Body Protection: Wear chemical resistant clothing and rubber boots when potential for contact with the material exists.

Hand Protection: Wear appropriate chemical resistant gloves. Consult a glove supplier for assistance in selecting an appropriate chemical resistant glove.

Print date: 27-Jun-2014 **7 of 15**

SDS No.: M1055 **Rev. Date**: 27-Jun-2014 **Rev. Num.** 12

Protective Material Types: Butyl rubber, Polyethylene (PE), Teflon®, Saranex(TM), 4H®/Silver Shield®, CPF®

3, Responder®, Trellchem® HPS, Tychem® 10000, Viton®

Component	Immediately Dangerous to Life/ Health (IDLH)		
Sulfuric acid	15 mg/m³ IDLH		
7664-93-9			

Respiratory Protection: Where vapor or mist concentration exceeds or is likely to exceed applicable exposure limits, a NIOSH approved respirator with acid gas cartridge in combination with a N100, R100 or P100 filter is required. When an air-purifying respirator is not adequate or for spills and/or emergencies of unknown concentrations, a NIOSH approved self-contained breathing apparatus or airline respirator with full-face piece is required. A respiratory protection program that meets 29 CFR 1910.134 must be followed whenever workplace conditions warrant use of a respirator.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state Liquid Appearance: Turbid

Color:Slight yellow to dark amberOdor:Pungent, Biting, Organic

Odor Threshold [ppm]:>1 mg/m³Molecular Weight:98.04Molecular Formula:H2SO4

Boiling Point/Range: 330.1 - 450 °F (165.6 - 232 °C) **Freezing Point/Range:** -63.8 to 50.4 °F (-53.2 to 10.2 °C)

Vapor Pressure: 0.05 psia @ 70 °F

Vapor Density (air=1): >1

Relative Density - Specific 1.58 - 1.75

Gravity (water=1):

Water Solubility: 100% pH: <1
Volatility: <5%

Evaporation Rate (ether=1): No data available **Partition Coefficient** Log Kow = 1.92

(n-octanol/water):

Flash point:

Flammability (solid, gas):

Lower Flammability Level (air):

Upper Flammability Level (air):

Auto-ignition Temperature:

Viscosity:

Not flammable

Not flammable

Not flammable

Not flammable

Not flammable

Not applicable

No data available

10. STABILITY AND REACTIVITY

Print date: 27-Jun-2014 **8 of 15**

SDS No.: M1055 **Rev. Date**: 27-Jun-2014 **Rev. Num.** 12

Reactivity: Highly reactive. Reacts with alkalis and many other substances. Generates heat when diluted with water.

Chemical Stability: Stable at normal temperatures and pressures.

Possibility of Hazardous Reactions:

This product is a strong oxidizer and is highly reactive. Avoid heat, flames, sparks and other sources of ignition. Mixing with water, acid, or incompatible materials may cause splattering and release of large amounts of heat. Will react with some metals forming flammable hydrogen gas.

Conditions to Avoid:

(e.g., static discharge, shock, or vibration) -. None known.

Incompatibilities/ Materials to Avoid:

many organic and inorganic materials including, ammonia, amines, strong alkali, combustible materials, nitrites, reducing agents, metals, carbides, alcohols, chlorates, oxidizing materials, permanganates

Hazardous Decomposition Products: Oxides of sulfur

Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

TOXICITY DATA:

PRODUCT TOXICITY DATA: SULFURIC ACID-SPENT

LD50 Oral:	LD50 Dermal:	LC50 Inhalation:
2140 mg/kg (Rat)	No data available	0.375 mg/L (4 hr - Rat)

COMPONENT TOXICITY DATA:

Component	LD50 Oral:	LD50 Dermal:	LC50 Inhalation:
\$ Sulfuric acid 7664-93-9	2140 mg/kg (Rat)		320 mg/m ³ (2 hr-Mouse) 347 ppm (1 hr-Rat) 510 mg/m ³ (2 hr-Rat)
Water 7732-18-5	90 mL/kg (Rat)		

POTENTIAL HEALTH EFFECTS:

Eye contact: Causes serious eye damage. Corrosive to the eyes and may cause severe

damage including blindness. Eye exposure may cause irritation and burns to the

eye lids, conjunctivitis, corneal edema, and corneal burn.

Print date: 27-Jun-2014 **9 of 15**

SDS No.: M1055 **Rev. Date**: 27-Jun-2014 **Rev. Num.** 12

Skin contact: Can cause severe skin burns. If skin is exposed to mild concentrations, it can

cause redness and irritation. Skin contact with liquid can rapidly cause burns. Concentrated sulfuric acid is corrosive to tissue, causing burns, necrosis, and scarring. Sudden circulatory collapse can occur with shock if large areas of skin

have been burned. Severe burns have been fatal.

Inhalation: Inhalation may cause: severe irritation of the respiratory tract with sore throat,

coughing, shortness of breath, bronchospasm, and pulmonary edema. Exposure can cause chemical burns and dehydration of the respiratory tract. Measurements of distress include increased respiration rate and decreased tidal volume, decreased forces expiratory volume, increased airway resistance, and reduced vital capacity. Death has been reported and is usually due to sudden circulatory

collapse, glottis or esophageal edema.

Ingestion: Corrosive. Ingestion may cause immediate burns of the mouth, esophagus, and

stomach. Ingestion may cause nausea, vomiting, abdominal pain, perforation of the stomach, edema of the glottis, necrosis and scarring, acidosis and sudden

circulatory collapse.

Chronic Effects: Causes damage to the respiratory system and teeth through prolonged or

repeated exposure. May cause cancer. Both acute high exposures and long-term moderate exposures to sulfuric acid mists have been associated with the occurrence of respiratory disease. Long-term exposures have been associated with bronchitis, emphysema, and frequent respiratory infections. Long-term exposure has been associated with laryngeal and lung cancer in humans. Repeated or prolonged skin contact may result in dermatitis. Chronic eye exposure can cause blindness resulting from corneal burns, damage/loss of internal eye contents, and perforation of the globe. Delayed gastrointestinal (GI) effects have been noted as include: perforation, GI hemorrhage, fistula formation, or delayed stricture. Effects are typically more severe in the stomach and intestinal tract than in the esophagus. Sulfuric acid exposure can cause etching of dental enamel of the teeth that are exposed directly to acid mist. Etching typically occurs

after years of occupational exposure.

SIGNS AND SYMPTOMS OF EXPOSURE:

Inhalation (Breathing): Respiratory System Effects: Acute inhalation may cause: sever irritation of the respiratory tract with sore throat, coughing, shortness of breath, bronchospasm and pulmonary edema. Causes chemical burn and dehydration of the respiratory tract. Measurements of distress include increased respiration rate and decreased tidal volume, decreased forces expiratory volume, increased airway resistance, and reduced vital capacity. Death has been reported and is usually due to sudden circulatory collapse, glottis or esophageal edema.

Skin: Skin Corrosion: Concentrated sulfuric acid is corrosive to tissue. Concentrated acid destroys tissues as a result of its severe dehydrating action, whereas dilute solutions act as milder irritants due to acid properties. Severe burns have been fatal. Sudden circulatory collapse can occur with shock if large areas of the skin have been burned.

Eye: Serious Eye Damage: Exposure to eyes may cause irritation and burns to the eye lids, conjunctivitis, corneal edema, and corneal burn. Significant and prolonged contact may cause damage to the internal contents of the eye, including perforation of the globe.

Ingestion (Swallowing): Gastrointestinal System Effects: Acute ingestion of concentrated sulfuric acid can cause nausea, vomiting, abdominal pain, perforation of the stomach, gastrointestinal bleeding, edema of the glottis, necrosis and scarring, and sudden circulatory collapse.

Print date: 27-Jun-2014 10 of 15

SDS No.: M1055 **Rev. Date**: 27-Jun-2014 **Rev. Num.** 12

ACUTE TOXICITY:

Only one acute oral toxicity study is currently available for sulfuric acid. This study indicates an LD50 = 2140 mg/kg in the rat. However, due to irritant and/or corrosive effects of sulfuric acid, the oral route of exposure is not appropriate for testing possible toxic endpoints. Gavage dosing of animals will not represent oral exposures in humans, which itself will be limited. Toxic signs of oral exposure in humans are of irritation/corrosion of the gastrointestinal tract [OECD-SIDS].

Interaction with Other Chemicals Which Enhance Toxicity: None known

GHS HEALTH HAZARDS:

GHS: ACUTE TOXICITY -

Category 2 - Fatal if inhaled

INHALATION:

GHS: CONTACT HAZARD -

Category 1A - Causes severe skin burns and eye damage

SKIN:

GHS: CONTACT HAZARD - EYE: Category 1 - Causes serious eye damage

GHS: CARCINOGENICITY: Category 1 - May cause cancer

Component	NTP:	IARC (GROUP 1):	IARC (GROUP 2):	OSHA:
Sulfuric acid	Known Human Carcinogen	Group 1	Not listed	Listed

SPECIFIC TARGET ORGAN TOXICITY (Single Exposure):

Category 1 - Respiratory System

SPECIFIC TARGET ORGAN TOXICITY (Repeated or Prolonged Exposure):

Category 1 - Respiratory System and Teeth

DEVELOPMENTAL TOXICITY:

Not classified as a developmental or reproductive toxin per GHS criteria. The inhalation of sulfuric acid fumes did not increase congenital anomalies in the offspring of treated pregnant mice or rabbits.

12. ECOLOGICAL INFORMATION

ECOTOXICITY DATA:

Aquatic Toxicity:

The toxicity of sulfuric acid to aquatic life is a function of the resulting pH.

LC50 (bluegill): 3.0 - 3.5 (concentration of hydrogen ion/96 hour)

LC50 (flounder): 100 - 330 ppm/48 hr LC50 (mosquito fish): 42 ppm/96 hr EC50 (shrimp): 70 - 80 ppm/48 hr EC50 (crab): 70 - 80 ppm/48 hr.

FATE AND TRANSPORT:

Print date: 27-Jun-2014 11 of 15

SDS No.: M1055 **Rev. Date**: 27-Jun-2014 **Rev. Num.** 12

BIODEGRADATION: Sulfuric acid will ultimately react with calcium and magnesium in water to form sulfate salts.

13. DISPOSAL CONSIDERATIONS

Waste from material:

Reuse or reprocess, if possible. May be subject to disposal regulations. Dispose in accordance with all applicable regulations.

Container Management:

Dispose of container in accordance with applicable local, regional, national, and/or international regulations. Container rinsate must be disposed of in compliance with applicable regulations.

14. TRANSPORT INFORMATION

U.S. DOT 49 CFR 172.101:

UN NUMBER: UN1832

PROPER SHIPPING NAME: Sulfuric acid, spent

HAZARD CLASS/ DIVISION: 8
PACKING GROUP: ||
LABELING REQUIREMENTS: 8

RQ (lbs): RQ 1,000 Lbs. (Sulfuric acid)

CANADIAN TRANSPORTATION OF DANGEROUS GOODS:

UN NUMBER: UN1832

SHIPPING NAME: Sulfuric acid, spent

CLASS OR DIVISION: 8
PACKING/RISK GROUP: ||
LABELING REQUIREMENTS: 8

15. REGULATORY INFORMATION

U.S. REGULATIONS

OSHA REGULATORY STATUS:

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Print date: 27-Jun-2014 **12 of 15**

SDS No.: M1055 **Rev. Date**: 27-Jun-2014 **Rev. Num.** 12

CERCLA SECTIONS 102a/103 HAZARDOUS SUBSTANCES (40 CFR 302.4):

If a release is reportable under CERCLA section 103, notify the state emergency response commission and local emergency planning committee. In addition, notify the National Response Center at (800) 424-8802 or (202) 426-2675.

Component	CERCLA Reportable Quantities:
Sulfuric acid	1000 lb (final RQ)

SARA EHS Chemical

If a release is reportable under EPCRA, notify the state emergency response commission and local emergency planning committee. If the TPQ is met, facilities are subject to reporting requirements under EPCRA Sections 311 and 312.

Component	EPCRA RQs	Section 302 Threshold Planning Quantity (TPQs)
Sulfuric acid	1000 lb (EPCRA RQ)	1000 lb TPQ

EPCRA SECTIONS 311/312 HAZARD CATEGORIES (40 CFR 370.10):

Acute Health Hazard, Chronic Health Hazard, Reactive Hazard

EPCRA SECTION 313 (40 CFR 372.65):

The following chemicals are listed in 40 CFR 372.65 and may be subject to Community Right-to Know Reporting requirements.

OSHA PROCESS SAFETY (PSM) (29 CFR 1910.119):

Not regulated

NATIONAL INVENTORY STATUS

U.S. INVENTORY STATUS: Toxic Substance Control Act (TSCA): All components are listed or exempt.

TSCA 12(b): This product is not subject to export notification.

<u>Canadian Chemical Inventory:</u> All components of this product are listed on either the DSL or the NDSL.

STATE REGULATIONS

Component	Proposition 65 Cancer WARNING:	Proposition 65 CRT List - Male	Proposition 65 CRT List - Female	Right to Know Hazardous	Hazardous	New Jersey Special Health Hazards Substance List
Sulfuric acid 7664-93-9	Listed	Not Listed	Not Listed	Listed	1761	corrosive; reactive - second degree

Component	Environmental		to Know Special Hazardous	to Know	Rhode Island Right to Know Hazardous Substance List
Sulfuric acid 7664-93-9	Listed	Listed	Not Listed	Present	Listed

CANADIAN REGULATIONS

Print date: 27-Jun-2014 **13 of 15**

SDS No.: M1055 **Rev. Date**: 27-Jun-2014 **Rev. Num.** 12

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

WHMIS - Classifications of Substances:

- D1A Poisonous and Infectious Material; Materials causing immediate and serious toxic effects Very toxic material
- · E Corrosive material

16. OTHER INFORMATION

Prepared by: OxyChem Corporate HESS - Product Stewardship

SDS Revision Date: 27-Jun-2014

HMIS: (SCALE 0-4) (Rated using National Paint & Coatings Association HMIS: Rating Instructions, 2nd Edition)

Health Rating: 3* Flammability Rating: 0 Reactivity Rating: 2

NFPA 704 - Hazard Identification Ratings (SCALE 0-4)

Health Rating: 3 Flammability: 0 Reactivity Rating: 2

Reason for Revision:

- Changed the SDS format to meet the GHS requirements of the revised 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)
- Updated the (M)SDS header
- Updated 24 Hour Emergency Telephone Number: SEE SECTION 1
- Product Identifier has been added or updated: SEE SECTION 1
- Updated Uses Advised Against information: SEE SECTION 1
- Revised Hazard(s) Identification information: SEE SECTION 2
- Emergency Overview was revised: SEE SECTION 2
- Added GHS Information: SEE SECTION 2
- Updated First Aid Measures: SEE SECTION 4
- Modified Fire Fighting Measure Recommendations: SEE SECTION 5
- Revised Accidental Release Measures: SEE SECTION 6
- Revised Handling and Storage Recommendations: SEE SECTION 7
- Updated Physical and Chemical Properties. SEE SECTION 9
- Stability and Reactivity recommendations: SEE SECTION 10
- Toxicological Information has been revised: SEE SECTION 11
- Updated Disposal Considerations. SEE SECTION 13
- Added SDS Revision Date: SEE SECTION 16

Print date: 27-Jun-2014 **14 of 15**

SDS No.: M1055 **Rev. Date:** 27-Jun-2014 **Rev. Num.** 12

IMPORTANT:

The information presented herein, while not guaranteed, was prepared by technical personnel and is true and accurate to the best of our knowledge. NO WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTY OR GUARANTY OF ANY OTHER KIND, EXPRESSED OR IMPLIED, IS MADE REGARDING PERFORMANCE, SAFETY, SUITABILITY, STABILITY OR OTHERWISE. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, storage, disposal and other factors that may involve other or additional legal, environmental, safety or performance considerations, and OxyChem assumes no liability whatsoever for the use of or reliance upon this information. While our technical personnel will be happy to respond to questions, safe handling and use of the product remains the responsibility of the customer. No suggestions for use are intended as, and nothing herein shall be construed as, a recommendation to infringe any existing patents or to violate any Federal, State, local or foreign laws.

OSHA Standard 29 CFR 1910.1200 requires that information be provided to employees regarding the hazards of chemicals by means of a hazard communication program including labeling, safety data sheets, training and access to written records. We request that you, and it is your legal duty to, make all information in this Safety Data Sheet available to your employees

End of Safety Data Sheet

Print date: 27-Jun-2014 15 of 15