

SAFETY DATA SHEET	Revision Date: 01/08/2018
	Print Date: 4/20/2018
	SDS Number: R0252918
SynPower™ SAE 5W-30 Synthetic Motor Oil	Version: 1.4
787007	

29 CFR 1910.1200 (OSHA HazCom 2012) SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

:

Product identifier

Trade name

SynPower™ SAE 5W-30 Synthetic Motor Oil

Details of the supplier of the safety data	Emergency telephone number
sheet	1-800-VALVOLINE (1-800-825-8654)
Valvoline LLC	
100 Valvoline Way	Regulatory Information Number
Lexington, KY 40509	1-800-TEAMVAL (1-800-832-6825)
United States of America (USA)	
1-800-TEAMVAL (1-800-832-6825)	Product Information
· · · · · · · · · · · · · · · · · · ·	1-800-TEAMVAL (1-800-832-6825)

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

GHS label elements

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	Asp. Tox. 1; H304	25.234
Mineral Oil		Asp. Tox. 1; H304	5.871

SECTION 4. FIRST AID MEASURES



Revision Date: 01/08/2018

 SynPower™ SAE 5W-30 Synthetic Motor Oil

 787007

General advice	:	No hazards which require special first aid measures.
If inhaled	:	If breathed in, move person into fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	:	First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
In case of eye contact	:	Remove contact lenses. Protect unharmed eye.
If swallowed	:	Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	:	Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities. Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: acne stomach or intestinal upset (nausea, vomiting, diarrhea) irritation (nose, throat, airways)
Notes to physician	:	No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	 Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO2) Dry chemical
------------------------------	--



SAFETY DATA SHEET	Revision Date: 01/08/2018
	Print Date: 4/20/2018
	SDS Number: R0252918
SynPower™ SAE 5W-30 Synthetic Motor Oil	Version: 1.4
787007	

Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	carbon dioxide and carbon monoxide Hydrocarbons nitrogen oxides (NOx)
Specific extinguishing methods	:	
		Product is compatible with standard fire-fighting agents.
Further information	:	Standard procedure for chemical fires.
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Environmental precautions	: Prevent further leakage or spillage if safe to do so.
Methods and materials for containment and cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.
Other information	: Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	: Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8.
Materials to avoid	: No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type	Control	Basis	
		(Form of	parameters /		



SAFETY DATA SHEET	Revision Date: 01/08/2018
	Print Date: 4/20/2018
	SDS Number: R0252918
SynPower™ SAE 5W-30 Synthetic Motor Oil	Version: 1.4
787007	

		exposure)	Permissible concentration	
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL

Components	CAS-No.	
Mineral Oil		
Engineering measures	General room ventilation should be a conditions of use. However, if unusu exist, provide sufficient mechanical (g exhaust) ventilation to maintain expos guidelines (if applicable) or below lev suspected or apparent adverse effect	al operating condition general and/or local sure below exposure els that cause known
Personal protective equipmen Respiratory protection	No personal respiratory protective eq required.	uipment normally
Eye protection	Not required under normal conditions proof safety goggles if material could into eyes.	
Skin and body protection	Wear as appropriate: Safety shoes Wear resistant gloves (consult your s supplier).	afety equipment
Hygiene measures	General industrial hygiene practice.	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	:	liquid
Colour	:	amber
Odour	:	mild



SAFETY DATA SHEET

Revision Date: 01/08/2018

Print Date: 4/20/2018 SDS Number: R0252918

Version: 1.4

SynPower™ SAE 5W-30 Synthetic Motor Oil 787007

Odour Threshold	: No data available
рН	: No data available
Melting point/freezing point	: No data available
Boiling point/boiling range	: 626 °F / 330 °C (1,013.333333 hPa) Calculated Phase Transition Liquid/Gas
Flash point	: > 390 °F / 199 °C Method: Cleveland open cup
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: 6 %(V) Calculated Explosive Limit
Lower explosion limit	: 1 %(V)
Vapour pressure	Calculated Explosive Limit : 1.3333333 hPa (20 °C) Calculated Vapor Pressure
Relative vapour density	: No data available
Relative density	: No data available
Density	: 0.8473 g/cm3
Solubility(ies) Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n- octanol/water	: No data available
Thermal decomposition	: No data available
Viscosity Viscosity, dynamic	: No data available
Viscosity, kinematic	: 63.17 mm2/s (40 °C)
Oxidizing properties	: No data available

SECTION 10. STABILITY AND REACTIVITY



Revision Date: 01/08/2018

Print Date: 4/20/2018

SDS Number: R0252918

Version: 1.4

787007

SAFETY DATA SHEET

SynPower™ SAE 5W-30 Synthetic Motor Oil

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: Product will not undergo hazardous polymerization.
Conditions to avoid	: None known.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	carbon dioxide and carbon monoxide Hydrocarbons Nitrogen oxides (NOx)

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of	:	Inhalation
exposure		Skin contact
		Eye Contact
		Ingestion

Acute toxicity

Not classified based on available information. <u>Components:</u> Distillates (Petroleum), Hydrotreated Heavy Paraffinic: Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

Skin corrosion/irritation

Not classified based on available information. <u>Components:</u> Distillates (Petroleum), Hydrotreated Heavy Paraffinic: Result: Slight, transient irritation

Serious eye damage/eye irritation

Not classified based on available information. <u>Product:</u> Remarks: Unlikely to cause eye irritation or injury.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic: Result: No eye irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information.



SAFETY DATA SHEET	Revision Date: 01/08/201
	Print Date: 4/20/201
	SDS Number: R025291
SynPower™ SAE 5W-30 Synthetic Motor Oil	Version: 1.
787007	

Germ cell mutagenicity Not classified based on available information. **Carcinogenicity** Not classified based on available information. **Reproductive toxicity** Not classified based on available information. **STOT - single exposure** Not classified based on available information. **STOT - repeated exposure** Not classified based on available information. **Aspiration toxicity** Not classified based on available information. **Product:**

No aspiration toxicity classification

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic: May be fatal if swallowed and enters airways.

Mineral Oil: May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

Carcinogenicity: IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity <u>Product:</u> Ecotoxicology Assessment Acute aquatic toxicity	: Not classified based on available information.
Chronic aquatic toxicity	: Not classified based on available information.
Components:	



SAFETY DATA SHEET	Revision Date: 01/08/2018
	Print Date: 4/20/201
	SDS Number: R025291
SynPower™ SAE 5W-30 Synthetic Motor Oil	Version: 1.4
787007	

Distillates (Petroleum), Hydrotre Toxicity to fish	ated Heavy Paraffinic: : LL50 (Fish): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Aquatic invertebrates): > 10,000 mg/l Exposure time: 48 h
Toxicity to algae	: EL50 (Algae, algal mat (Algae)): > 100 mg/l Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	: NOEC (Fish): 10 mg/l
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Aquatic invertebrates): 10 mg/l
Persistence and degradability <u>Components:</u> No data available Bioaccumulative potential <u>Components:</u> No data available <u>Mobility in soil</u> <u>Components:</u> No data available <u>Other adverse effects</u> No data available <u>Product:</u>	
	: No data available
Components:	
SECTION 13. DISPOSAL CONSIDE	RATIONS
Disposal methods	
General advice	: Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.

SECTION 14. TRANSPORT INFORMATION

International transport regulations REGULATION



SAFETY DATA SHEETRevision Date: 01/08/2018Print Date: 4/20/2018Print Date: 4/20/2018SynPower™ SAE 5W-30 Synthetic Motor OilSDS Number: R0252918787007Version: 1.4

Page: 9

ID	NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT /
						LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

TDG_INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant

no



SAFETY DATA SHEET	Revision Date: 01/08/2018
	Print Date: 4/20/2018
	SDS Number: R0252918
SynPower™ SAE 5W-30 Synthetic Motor Oil	Version: 1.4
787007	

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
TOLUENE	108-88-3	1000	*

*: Calculated RQ exceeds reasonably attainable upper limit. SARA 304 Extremely Hazardous Substances Reportable Quantity This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards	No SARA Hazards
SARA 313	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
California Prop 65	This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.
• •	ct are reported in the following inventories: All components of this product are on the Canadian DSL
AICS	Not in compliance with the inventory
ENCS	Contact your sales representative for additional information.
KECI	On the inventory, or in compliance with the inventory
IECSC	q (quantity restricted)
PICCS	Not in compliance with the inventory
TSCA	On TSCA Inventory

Inventories


AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Valvoline.	Page: 11
SAFETY DATA SHEET	Revision Date: 01/08/2018
	Print Date: 4/20/2018
	SDS Number: R0252918
SynPower™ SAE 5W-30 Synthetic Motor Oil	Version: 1.4
787007	

Revision Date: 01/08/2018



NFPA Flammable and Combustible Liquids Classification Combustible Liquid Class IIIB

Full text of H-Statements

H304

May be fatal if swallowed and enters airways.

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet : ACGIH : American Conference of Industrial Hygienists BEI : Biological Exposure Index CAS : Chemical Abstracts Service (Division of the American Chemical Society). CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.



SAFETY DATA SHEET	Revision Date: 01/08/2018
	Print Date: 4/20/201
	SDS Number: R025291
SynPower™ SAE 5W-30 Synthetic Motor Oil	Version: 1.
787007	

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization" IMDG : International Maritime Code for Dangerous Goods ISO : International Organization for Standardization logPow : octanol-water partition coefficient LCxx : Lethal Concentration, for xx percent of test population LDxx : Lethal Dose, for xx percent of test population. ICxx : Inhibitory Concentration for xx of a substance Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified OECD : Organization for Economic Co-operation and Development **OEL** : Occupational Exposure Limit P-Statement : Precautionary Statement PBT : Persistent, Bioaccumulative and Toxic **PPE : Personal Protective Equipment** STEL : Short-term exposure limit STOT : Specific Target Organ Toxicity TLV : Threshold Limit Value TWA : Time-weighted average vPvB : Very Persistent and Very Bioaccumulative WEL : Workplace Exposure Level CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act **DOT** : Department of Transportation FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act HMIRC : Hazardous Materials Information Review Commission HMIS : Hazardous Materials Identification System NFPA : National Fire Protection Association NIOSH : National Institute for Occupational Safety and Health **OSHA** : Occupational Safety and Health Administration PMRA : Health Canada Pest Management Regulatory Agency RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System