

MATERIAL SAFETY DATA SHEET

Section 1. Product and Company Identification

Product Name: Seche Vite Gel Laquer DATE: 8/24/2010

(Pure, Crème, Debutant, Bella, Memoire, Snap Dragon, Stilleto, REV.

Risque, Signature, Nouveau, Noir, Plum

Formula: 30-1972, 30-1973, 30-1974, 30-1975, 30-1978, 30-1981, 30-

1983, 30-1984, 30-1989, 30-1991, 30-1992, 30-1993

Item#: 83168, 83169, 83170, 83172, 83171, 83173, 83179, 83178,

83174, 83177, 83176, 83175

Manufacturer: American International Industries

2220 Gaspar Ave

Los Angeles, CA 90040


Chem-Tel: (800) 255-3924

Section 2. Composition / Information on Ingredients

Ingredients:				
ingredients.	Component	CAS#	90	Exposure Limits ppm ACGIH-TWA / OSHA-PEL
	Ethyl Acetate	141-78-6	20 - 30	ACGIH-TWA: 400ppm OSHA-PEL: 400ppm
	Butyl Acetate	123-86-4	20 - 30	ACGIH-TWA: 100ppm OSHA-PEL: 150ppm
	Di-Hema Trimethylhexyl Dicarbamate	41137-60-4	15 - 20	None Established
	Isobornyl Acrylate	5888-33-5	10 - 15	None Established
	Nitrocellulose	9004-70-0	5 - 10	ACGIH-TWA: 400ppm
	Isopropyl Alcohol	67-63-0	1 - 5	ACGIH-TWA: 400ppm
	Hydroxycyclohexyl Phenyl Ketone	947-19-3	1 - 5	None Established
	Trimethyl Pentanyl Diisobutyrate	6846-50-0	1 - 5	None Established
	Éthyl Tosylamide	80-39-7	0.5 - 1.5	None Established
	Stearalkonium Bentonite	130501-87-0	0.5 - 1	None Established
	Stearalkonium Hectorite	12691-60-0	0.5 - 1	None Established
	Kaolin	1302-78-9	<1	None Established
	Benzophenone-1	119-61-9	<1	None Established
May Contain:	Polyethylene Terephthalate	25038-59-9	1 - 5	None Established
	Mica	12001-26-2	1 - 2	None Established
	Ferric Ammonium Ferrocyanide	12240-15-2	<1	None Established
	Iron Oxides (CI 77499)	1309-37-1	<1	None Established
	Iron Oxides (CI 77491)	1309-37-1	<1	None Established
	Red 6 (CI 15850)	5858-81-1	<1	None Established
	Red 7 (CI 15850)	5858-81-1	<1.5	None Established
	Red 34 (CI 15880)	6417-83-0	<1	None Established
	Titanium Dioxide (Cl 77891)	13463-67-7	<1	None Established
	Yellow 5 (CI 19140)	81-48-1	<1	None Established

00

AMERICAN INTERNATIONAL INDUSTRIES



MATERIAL SAFETY DATA SHEET

Section 3. Hazardous Identification

Potential Health Effects, Signs and Symptoms of Exposure:

Eye: May cause irritation or burning eyes.

Skin: Repeated or prolonged liquid contact may cause skin irritation with discomfort or dermatitis.

Ingestion: Gastro intestinal distress, call a physician.

Inhalation: May cause nose and throat irritation.

Section 4. First Aid Measures

First Aid for Eye: Immediately flush with water for 15 minutes, including under eyelids. Seek medical attention if

discomfort persists.

First Aid for Skin: Wash off affected areas with plenty of soap and water. If discomfort or irritation persists contact

a physician.

First Aid for Inhalation: Remove to fresh air. Seek medical attention if discomfort persists.

First Aid for Ingestion: Rinse mouth out with water. Only induce vomiting if directed by a physician. Never give

anything by mouth to an unconscious person. Seek prompt medical attention.

Section 5. Fire Fighting Measures

Flash Point (°F/°C): 40°F (4.44°C)TCC

Flammable Limit LEL: 1.7% (vol%): UEL: 12.0%

Auto-ignition Temp.

(vol%)

None Established

Extinguisher Media: Foam, dry chemical or carbon dioxide.


Fire Fighting Full protective equipment, including self contained breathing apparatus is recommended.

Procedures: Water from fog nozzle may be used to cool containers to prevent pressure build up.

Unusual Fire and When heated above the flash point flammable vapors may be emitted. Fine mists or sprays

Explosion Hazards: may be flammable at temperatures below the flash point.

AMERICAN INTERNATIONAL INDUSTRIES



MATERIAL SAFETY DATA SHEET

Section 6. Accidental Release Measures

Spill or Release Procedures:

Highway or railway spills call chemtrec (800) 424-9600 cont. U.S. Collect (202) 483-7616 from Alaska and Hawaii.

Stay upwind and away from spill. Keep all sources of ignition and hot metal surfaces away from spill. Keep out of drains, sewers, or waterways. Use sand or other inert material to dam and contain spill. Do not flush with water; use absorbent pads. For large spills call response team and notify appropriate state/local agencies. Immediately notify the National Response Center (phone number: 800-424-8802) in case if the spill is in excess of EPA reportable quantity.

Section 7. Handling and Storage

Handling & Storing: In accordance with good industrial practice avoid unnecessary personal contact. Wash face

and hands before eating, drinking, or smoking. Store in original container, away from excessive

heat and keep in a dry are.

Section 8. Exposure Controls / Personal Protective Equipment

For Manufacturing Use Only:

Ventilation: Use local Exhaust.

Protective Gloves: Neoprene gloves.

Include splash guards and side shields. Eye Protection:

Respiratory Protection: Use with adequate Ventilation and avoid breathing vapors.

Clothing: Coveralls.

Other Protective Eye bath and shower.

Section 9. Physical and Chemical Properties


Appearance @ 25°C: Colored viscous liquid Viscosity (RAT): Not applicable

Odor @ 25°C: Vapor Pressure: Not Available Sweet Ester Odor Not applicable Vapor Density: Not Available pН Evaporation Rate: Slower than ether

~565 Viscosity:

Ignition: Not applicable **Melting Point:** Not applicable






MATERIAL SAFETY DATA SHEET

Boiling Range:

Not available





MATERIAL SAFETY DATA SHEET

Solubility in Water

Insoluble

Section 10. Stability and Reactivity

Stability:

Stable

Hazardous Decomposition Products:

CO, CO2, Nitrous Oxides, Smoke

Incompatibility (Materials to Avoid):

Acids, Alkalies and Peroxides.

Hazardous Polymerization:

Will not occur

Conditions to Avoid: Do not store over 120°F

Section 11. Toxicological Information

Results of component toxicity test performed:

No data

Human experience:

No data

Section 12. Ecological Information

Ecological Information:

No data

Chemical Fate Information:


No data

Section 13. Disposable Considerations

RCRA 40 CFR 261 Classification:

Federal, State and local laws governing disposal of materials can differ. Ensure proper disposal compliance with proper authorities before disposal. Do not incinerate in closed containers

AMERICAN INTERNATIONAL INDUSTRIES



MATERIAL SAFETY DATA SHEET

Section 14. Transportation Information

<DOT Information>

Proper Shipping Name: Paint

DOT Hazard Class: 3, Flammable Liquid

Packaging Group:

UN ID Number UN 1263

Section 15. Regulatory Information

Additional regulatory information available upon request.

Section 16. Other Information

No additional information available.