according to Regulation (EC) No 1907/2006

#### W & H Service Oil F1 MD400 REF 10940021

Print date: 28.08.2015 Product code: 11AFX10940011 Page 1 of 9

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

W & H Service Oil F1 MD400 REF 10940021

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

No information available.

### 1.3. Details of the supplier of the safety data sheet

Company name: W&H Dentalwerk Bürmoos GmbH

Street: Ignaz-Glaser-Strasse 53

Place: A-5111 Bürmoos

Post-office box:

A Bürmoos

Telephone: +43 6274 6236-0 Telefax: +43 6274 6236-55

e-mail: office@wh.com

Internet: wh.com

**1.4. Emergency telephone** 111 NHS (National Health Service)

number:

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

Indications of danger: F+ - Extremely flammable

R phrases:

Extremely flammable.

## Classification according to Regulation (EC) No. 1272/2008 [CLP]

Hazard categories: Aerosol: Aerosol 1 Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

## 2.2. Label elements

Signal word: Danger Pictograms: GHS02



## **Hazard statements**

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

**Precautionary statements** 

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

according to Regulation (EC) No 1907/2006

#### W & H Service Oil F1 MD400 REF 10940021

Print date: 28.08.2015 Product code: 11AFX10940011 Page 2 of 9

### 2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

## **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

#### Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification according to Directive 67/548/EEC	
Index No	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
REACH No		
500-165-3	Alcohols, C12-13, ethoxylated (1-5 EO)	< 0.1 %
66455-14-9	Xi - Irritant, N - Dangerous for the environment R41-50	
	Eye Dam. 1, Aquatic Acute 1 (M-Factor = 1); H318 H400	

Full text of R, H and EUH phrases: see section 16.

### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

After inhalation

Provide fresh air.

After contact with skin

Wash with plenty of water.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

After ingestion

Rinse mouth immediately and drink plenty of water.

## 4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

# 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

# Suitable extinguishing media

Carbon dioxide (CO2), Foam, Extinguishing powder.

## Unsuitable extinguishing media

Full water jet

# 5.2. Special hazards arising from the substance or mixture

Flammable. Vapours can form explosive mixtures with air.

# 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

## Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

# **SECTION 6: Accidental release measures**

according to Regulation (EC) No 1907/2006

#### W & H Service Oil F1 MD400 REF 10940021

Print date: 28.08.2015 Product code: 11AFX10940011 Page 3 of 9

### 6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition.

#### 6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

#### 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

#### Advice on safe handling

No special measures are necessary.

## Advice on protection against fire and explosion

Do not spray on naked flames or any incandescent material. Protect from sunlight. Do no expose to temperatures exceeding 50°C/122°F. Keep away from sources of ignition. - No smoking. Vapours can form explosive mixtures with air.

#### 7.2. Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

## Advice on storage compatibility

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

# Further information on storage conditions

Protect from frost. Protect against direct sunlight.

## 7.3. Specific end use(s)

No information available.

### **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

### **Exposure limits (EH40)**

	CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
Ī	106-97-8	Butane	600	1450		TWA (8 h)	WEL
l			750	1810		STEL (15 min)	WEL

## Additional advice on limit values

a no restriction

b End of exposure or shift

c in long-term exposure: after several shifts

d prior to next shift

STEL (EC): Short Term Exposure Limit TWA (EC): time-weighted average

U: Urea B: Blood

according to Regulation (EC) No 1907/2006

#### W & H Service Oil F1 MD400 REF 10940021

Print date: 28.08.2015 Product code: 11AFX10940011 Page 4 of 9

### 8.2. Exposure controls

### Protective and hygiene measures

Wash hands before breaks and after work. When using do not eat or drink.

#### Eye/face protection

Wear eye/face protection.

## Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

### Skin protection

Wear suitable protective clothing.

# **Respiratory protection**

In case of inadequate ventilation wear respiratory protection. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Suitable respiratory protective equipment: Combination filter device (DIN EN 141)...

Filtering device with filter or ventilator filtering device of type: AX

Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

### **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state: Aerosol
Colour: slightly yellow
Odour: characteristic

**Test method** 

pH-Value (at 20 °C): not determined DIN 19268

Changes in the physical state

Melting point:

Initial boiling point and boiling range:

Sublimation point:

No information available.

Softening point:

No information available.

Flash point:

-80 °C

Flammability

Solid: not applicable
Gas: not applicable
Lower explosion limits: 1 vol. %
Upper explosion limits: 11 vol. %
Ignition temperature: > 200 °C

**Auto-ignition temperature** 

Solid: not applicable
Gas: not applicable
Decomposition temperature: not determined

**Oxidizing properties** 

Not oxidizing.

according to Regulation (EC) No 1907/2006

#### W & H Service Oil F1 MD400 REF 10940021

Print date: 28.08.2015 Product code: 11AFX10940011 Page 5 of 9

Vapour pressure: not determined
Vapour pressure: No information available.

Density (at 20 °C): 0,8575 g/cm³ DIN 51757

Bulk density:

Water solubility:

No information available.

insoluble

Solubility in other solvents

not determined

Partition coefficient: not determined

Viscosity / dynamic: No information available.

Viscosity / kinematic:

Flow time:

No information available.

No information available.

No information available.

not determined

Evaporation rate:

not determined

Solvent separation test:

Solvent content:

No information available.

No information available.

9.2. Other information

Solid content: not determined

Density Data apply to the technically active substance. pressure - bar (20°C)

### **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

Flammable, Ignition hazard.

## 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

#### 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

### 10.5. Incompatible materials

No information available.

#### 10.6. Hazardous decomposition products

No known hazardous decomposition products.

#### **Further information**

Do not mix with other chemicals.

# **SECTION 11: Toxicological information**

# 11.1. Information on toxicological effects

# Toxicocinetics, metabolism and distribution

No information available.

## **Acute toxicity**

Based on available data, the classification criteria are not met.

according to Regulation (EC) No 1907/2006

#### W & H Service Oil F1 MD400 REF 10940021

Print date: 28.08.2015 Product code: 11AFX10940011 Page 6 of 9

### **Acute toxicity**

CAS No	Chemical name						
	Exposure routes	Method	Dose	Species	Source		
66455-14-9							
	oral	LD50 mg/kg	14685	Rat			
	dermal	LD50 mg/kg	>2000	Rat			
	inhalative (4 h) vapour	LC50	>100 mg/l	Rat			

## Irritation and corrosivity

Based on available data, the classification criteria are not met.

#### Sensitising effects

Based on available data, the classification criteria are not met.

# STOT-single exposure

Based on available data, the classification criteria are not met.

#### Severe effects after repeated or prolonged exposure

Based on available data, the classification criteria are not met.

## Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

# Specific effects in experiment on an animal

No information available.

# Additional information on tests

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

## **SECTION 12: Ecological information**

### 12.1. Toxicity

Aquatic toxicity: The classification criteria for this hazard class are not met by definition.

CAS No	Chemical name							
Aquatic toxicity		Method	Dose	[h]   [d]	Species	Source		
66455-14-9	Alcohols, C12-13, ethoxylated (1-5 EO)							
	Acute fish toxicity	LC50	0,96 mg/l		Pimephales promelas Pimephales promelas			
	Acute algae toxicity	ErC50	0,22 mg/l	96 h	Selenastrum capricornutum			
	Acute crustacea toxicity	EC50	0,46 mg/l	48 h	Daphnia magna			

## 12.2. Persistence and degradability

The product has not been tested.

# 12.3. Bioaccumulative potential

The product has not been tested.

### 12.4. Mobility in soil

The product has not been tested.

according to Regulation (EC) No 1907/2006

#### W & H Service Oil F1 MD400 REF 10940021

Print date: 28.08.2015 Product code: 11AFX10940011 Page 7 of 9

### 12.5. Results of PBT and vPvB assessment

The product has not been tested.

#### 12.6. Other adverse effects

No information available.

### **Further information**

No special environmental measures are necessary.

### **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

#### Advice on disposal

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

### Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances Classified as hazardous waste.

# Waste disposal number of used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances

Classified as hazardous waste.

# Waste disposal number of contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

## Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.

# **SECTION 14: Transport information**

## Land transport (ADR/RID)

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1Classification code:5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1Classification code:5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L

according to Regulation (EC) No 1907/2006

#### W & H Service Oil F1 MD400 REF 10940021

Print date: 28.08.2015 Product code: 11AFX10940011 Page 8 of 9

Marine transport (IMDG)

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1Marine pollutant:no

Special Provisions: 63, 190, 277, 327, 344, 959

Limited quantity: 1000 mL EmS: F-D, S-U

Air transport (ICAO)

**14.1. UN number:** UN 1950

14.2. UN proper shipping name: AEROSOLS, flammable

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1

Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G

IATA-packing instructions - Passenger:

IATA-max. quantity - Passenger:

IATA-packing instructions - Cargo:

IATA-max. quantity - Cargo:

150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Warning: Flammable gases.

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

not applicable

## **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**EU** regulatory information

1999/13/EC (VOC): VOC-CH: 65,52 % w/w

VOC 1999/13/EG: 65,64 % w/w

**Additional information** 

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

**National regulatory information** 

Employment restrictions: Observe employment restrictions for young people.

Water contaminating class (D): 1 - slightly water contaminating

Additional information

94/69/EC (21st ATP). The benzene content of the product is less than 0.1%. It applies the annotation P.

Classification and labeling as carcinogenic is not necessary.

### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

## **SECTION 16: Other information**

according to Regulation (EC) No 1907/2006

#### W & H Service Oil F1 MD400 REF 10940021

Print date: 28.08.2015 Product code: 11AFX10940011 Page 9 of 9

### Changes

This data sheet contains changes from the previous version in section(s): 2,4,9,10,14,15.

#### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European

Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de

fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level

WEL (UK): Workplace Exposure Limits TWA (EC): Time-Weighted Average ATE: Acute Toxicity Estimate

STEL (EC) Short Term Exposure Limit

LC50: Lethal Concentration

EC50: half maximal Effective Concentration

ErC50: means EC50 in terms of reduction of growth rate

### Relevant R phrases (number and full text)

Extremely flammable. 12

41 Risk of serious damage to eyes. 50 Very toxic to aquatic organisms.

#### Relevant H and EUH statements (number and full text)

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H318 Causes serious eve damage. H400 Very toxic to aquatic life.

# **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)