

**SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION.****W. F. Taylor Co., Inc.**

11545 Pacific Avenue  
 Fontana, CA 92337-8228  
 951/360-6677  
 CHEMICAL EMERGENCY HOTLINE 1-800-535-5053

PRODUCT NAME: **SHAW 5000 PRESSURE SENSITIVE ADHESIVE**  
 ITEM NUMBER: 5000-4  
 ITEM DESCRIPTION: Shaw 5000 Pressure Sensitive Adhesive 4-gal  
 PRODUCT DESCRIPTION: LATEX BASED ADHESIVE  
 CHEMICAL FAMILY: ACRYLIC LATEX, RESIN BLEND  
 REVISION DATE: 08/05/09  
 MANUFACTURED FOR: SHAW INDUSTRIES  
 ADDRESS: P.O. DRAWER 2128  
 DALTON, GA  
 PHONE NO.: (800) 441 - 7429  
 EMERGENCY PHONE NO.: (800) 535 - 5053  
 CHEMICAL NAMES, COMMON NAMES: ACRYLIC LATEX, RESIN BLEND  
 TRADE NAME: SHAW SURESET 5000

## HMIS HAZARD RATING

LEAST: 0	HEALTH: 1
SLIGHT: 1	FLAMMABLE: 0
MODERATE: 2	REACTIVITY: 0
HIGH: 3	
EXTREME: 4	

PREPARED BY: DARWIN C. REGIS  
 PREEMPTS PREVIOUS MSDS SHEETS

**SECTION II HAZARDOUS INGREDIENTS**

<u>COMPONENT/CAS #</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>% WT</u>	<u>NOTES</u>
NO HAZARDOUS INGREDIENTS PER CURRENT OSHA REGULATIONS				

**SECTION III PHYSICAL DATA**

BOILING POINT: 212 DEGREES F  
 LBS / GAL: 8.5 - 9.0  
 EVAPORATION RATE: SAME AS WATER  
 VAPOR DENSITY: SAME AS WATER.  
 PERCENT VOLATILE: 47 -50 (BY WEIGHT)  
 COLOR: OFF WHITE  
 ODOR: NIL  
 GRAMS V.O.C. PER LITER OF MATERIAL: less than 0.5

**SECTION IV FIRE AND EXPLOSION HAZARD DATA**

FLASH POINT, PENSKEY-MARTIN C.C.: NA  
 AUTO IGNITION TEMPERATURE, DEGREES F: NA  
 FLAMMABLE LIMITS IN AIR (% BY VOLUME): LEL: NA UEL: NA  
 EXTINGUISHING MEDIA:

(X) WATER SPRAY (X) CARBON DIOXIDE ( ) OTHER  
 (X) FOAM (X) DRY CHEMICAL

PRODUCT NAME: **SHAW 5000 PRESSURE SENSITIVE ADHESIVE**  
ITEM NUMBER: 5000-4  
ITEM DESCRIPTION: Shaw 5000 Pressure Sensitive Adhesive 4-gal  
REVISION DATE: 08/05/09

---

SPECIAL FIRE FIGHTING PROCEDURES: USE SELF CONTAINED BREATHING APPARATUS.  
UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE KNOWN

---

#### **SECTION V HEALTH HAZARD IDENTIFICATION**

##### SYMPTOMS OF OVER EXPOSURE:

INHALATION: MAY CAUSE SLIGHT IRRITATION TO THE UPPER RESPIRATORY TRACT.  
EYES: VAPOR MAY CAUSE IRRITATION.  
SKIN: MAY CAUSE SLIGHT SKIN IRRITATION.  
INGESTION: NOT A LIKELY ROUTE OF ENTRY UNDER PROPER HANDLING CONDITIONS. MAY CAUSE VOMITING. SYMPTOMS MAY BE SAME AS INHALATION.

##### HEALTH EFFECTS OR RISK FROM EXPOSURE:

ACUTE: MAY CAUSE MILD SKIN AND RESPIRATORY TRACT IRRITATION  
CHRONIC: NOT KNOWN

##### FIRST AID PROCEDURES:

EYES CONTACT: WASH WITH WATER AT LEAST 15 MINUTES. IF IRRITATIONS PERSISTS, SEEK MEDICAL ATTENTION.  
SKIN CONTACT: REMOVE FROM SKIN AND WASH WITH SOAP AND WATER. IF IRRITATIONS PERSISTS, SEEK MEDICAL ATTENTION.  
INHALATION: REMOVE TO FRESH AIR, ADMINISTER OXYGEN. IF NECESSARY, SEEK MEDICAL ATTENTION.  
INGESTION: IF SWALLOWED, CALL PHYSICIAN.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: NONE KNOWN

---

#### **SECTION VI REACTIVITY DATA**

STABILITY: STABLE  
CONDITIONS TO AVOID: PROTECT FROM FREEZING.  
INCOMPATIBILITY (MATERIALS TO AVOID): OXIDIZING MATERIALS  
HAZARDOUS DECOMPOSITION PRODUCTS (INCLUDING COMBUSTION PRODUCTS): OXIDES OF CARBON, WATER, AND ORGANIC COMPOUNDS OF UNKNOWN STRUCTURE  
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

---

#### **SECTION VII SPILL OR LEAK PROCEDURES**

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED  
KEEP OUT OF SEWER SYSTEMS TO PREVENT BLOCKAGE DUE TO POLYMER DEPOSITS. USE ABSORBENT MATERIAL TO COLLECT AND/OR SCRAPE UP EXCESS AND PLACE INTO CLOSED DOT APPROVED CONTAINERS FOR DISPOSAL.

WASTE DISPOSAL: ABIDE BY ALL STATE, FEDERAL AND LOCAL REGULATIONS.

---

#### **SECTION VIII SPECIAL PROTECTION INFORMATION**

VENTILATION AND ENGINEERING CONTROLS: USE LOCAL EXHAUST. DO NOT USE CLOSED AIR-CIRCULATING SYSTEM. OPEN WINDOWS AND DOORS IF NECESSARY.  
RESPIRATORY PROTECTION: NIOSH RESPIRATOR MAY BE REQUIRED.  
PROTECTIVE GLOVES: CHEMICAL RESISTANT GLOVES  
EYE PROTECTION: CHEMICAL GOGGLES OR FACE SHIELD  
OTHER CLOTHING AND EQUIPMENT: IF CLOTHING BECOMES CONTAMINATED, REMOVE AND CLEAN BEFORE REWEARING.  
WORK PRACTICES, HYGIENIC PRACTICES: FOLLOW LABEL INSTRUCTIONS.  
PROTECTIVE MEASURES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT: USE GOGGLES AND GLOVES WHEN CLEANING ADHESIVE FROM EQUIPMENT. MAINTAIN PROPER VENTILATION.

---

PRODUCT NAME: **SHAW 5000 PRESSURE SENSITIVE ADHESIVE**  
ITEM NUMBER: 5000-4  
ITEM DESCRIPTION: Shaw 5000 Pressure Sensitive Adhesive 4-gal  
REVISION DATE: 08/05/09

---

#### **SECTION IX SPECIAL PRECAUTIONS**

KEEP OUT OF THE REACH OF CHILDREN. DO NOT INDUCE VOMITING IF INGESTED. AVOID BREATHING BUILDUP OF VAPORS. USE WITH ADEQUATE VENTILATION.  
PROTECT AGAINST PHYSICAL DAMAGE. STORE IN A COOL DRY PLACE (50 - 90 DEGREES F). KEEP AWAY FROM HEAT AND SPARKS. KEEP FROM FREEZING.

---

#### **SECTION X TOXICOLOGICAL PROPERTIES**

CHRONIC/SUBCHRONIC DATA:

SMALL AMOUNTS OF VINYL ACETATE MAY BE CONTAINED IN THIS PRODUCT. ACGIH EVALUATED VINYL ACETATE AS AN A3(1993) ANIMAL CARCINOGEN. AVAILABLE EVIDENCE SUGGESTS THE AGENT IS NOT LIKELY TO CAUSE CANCER IN HUMANS EXCEPT UNDER UNCOMMON OR UNLIKELY ROUTES OF EXPOSURE. INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC) PUBLISHED A MONOGRAPH ON VINYL ACETATE (1995) WHICH INDICATES "THERE IS INADEQUATE EVIDENCE IN HUMANS FOR CARCINOGENITY OF VINYL ACETATE". BECAUSE VINYL ACETATE IS METABOLIZED TO ACETALDEHYDE WHICH IS IARC 2B CLASSIFICATION (POSSIBLE CARCINOGEN TO HUMAN), IT ALSO HAS BEEN LISTED UNDER 2B.

---

#### **SECTION XI REGULATORY INFORMATION**

OSHA HAZARD COMMUNICATION STANDARD(29CFR 1910.1200)HAZARD CLASS(ES): NONE

SARA TITLE III SECTION 312 HAZARD CLASS: NONE

EPA SARA TITLE III SECTION 313: NONE

CALIFORNIA PROPOSITION 65: THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND/OR REPRODUCTIVE HARM.

---

#### **NOTICE**

SHAW INDUSTRIES EXPRESSLY DISCLAIMS ALL EXPRESS OR APPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WITH RESPECT TO THE PRODUCT OR INFORMATION PROVIDED HEREIN. ALL INFORMATION APPEARING HEREIN IS BASED UPON A DATA OBTAINED FROM THE MANUFACTURER AND/OR RECOGNIZED TECHNICAL SOURCES. WHILE THE INFORMATION IS BELIEVED TO BE ACCURATE, SHAW INDUSTRIES MAKES NO REPRESENTATIONS AS TO ITS ACCURACY OR EFFICIENCY. CONDITIONS OF USE ARE BEYOND SHAW'S CONTROL AND THEREFOR USERS ARE RESPONSIBLE TO VERIFY THIS DATA UNDER THEIR OWN OPERATING CONDITIONS TO DETERMINE WHETHER THE PRODUCT IS SUITABLE FOR THEIR PARTICULAR PURPOSES AND THEY ASSUME ALL RISKS OF THEIR USE, HANDLING, AND DISPOSAL OF THE PRODUCT, OR FROM PUBLICATION OF USE OF, OR RELIANCE UPON, INFORMATION CONTAINED HEREIN. THIS INFORMATION RELATES ONLY TO THE PRODUCT DESIGNATED HEREIN, AND DOES NOT RELATE TO ITS USE IN COMBINATION WITH ANY OTHER MATERIAL OR IN ANY PROCESS.

---