

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION.**W. F. Taylor Co., Inc.**11545 Pacific Avenue
Fontana, CA 92337-8228
951/360-6677

CHEMICAL EMERGENCY HOTLINE 1-800-535-5053

PRODUCT NAME: **SUBSET 4000 LATEX SEAM ADHESIVE**
ITEM NUMBER: 4000-04
ITEM DESCRIPTION: Shaw 4000 Subset Seam Sealer Qts
PRODUCT DESCRIPTION: LATEX BASED ADHESIVE
CHEMICAL FAMILY: LATEX POLYMER MIXTURE
REVISION DATE: 01/02/14 REVIEW DATE: / / PRINT DATE: 07/25/14 PRINT TIME: 13:08
MANUFACTURED FOR: SHAW INDUSTRIES
ADDRESS: P.O. DRAWER 2128
DALTON, GA 30722
PHONE NO.: (800) 441 - 7429
EMERGENCY PHONE NO.: (800) 535 - 5053
PRODUCT CLASS: WATER BASE SEAM ADHESIVE
MANUFACTURER'S CODE IDENTIFICATION: 4000
CHEMICAL NAMES, COMMON NAMES: LATEX, POLYMER MIXTURE

HMIS HAZARD RATING

LEAST: 0	HEALTH: 1
SLIGHT: 1	FLAMMABLE: 0
MODERATE: 2	REACTIVITY: 0
HIGH: 3	
EXTREME: 4	

PREPARED BY: ROBERT DDAMULIRA
PREEMPTS PREVIOUS MSDS SHEETS

SECTION II HAZARDOUS INGREDIENTS

No Hazardous ingredients per current OSHA regulations.

SECTION III PHYSICAL DATA

<u>Hazard</u>	<u>CAS #</u>	<u>WT/Wt % Less Than</u>
NO HAZARDOUS INGREDIENTS PER CURRENT OSHA REGULATIONS		
BOILING POINT:	212 DEGREES F	
LBS / GALLON:	8.3 - 8.6	
EVAPORATION RATE:	SAME AS WATER	
VAPOR DENSITY:	SAME AS WATER	
VAPOR PRESSURE:	SAME AS WATER	
PERCENT VOLATILE:	46 - 50 (BY WEIGHT)	
COLOR:	OFF WHITE	
ODOR:	SLIGHT AMMONIA-LIKE ODOR	

SECTION IV FIRE AND EXPLOSION HAZARD DATA

PRODUCT NAME: **SUBSET 4000 LATEX SEAM ADHESIVE**
 ITEM NUMBER: 4000-04
 ITEM DESCRIPTION: Shaw 4000 Subset Seam Sealer Qts
 REVISION DATE: 01/02/14 REVIEW DATE: / / PRINT DATE:07/25/14 PRINT TIME:13:08

DOT CATEGORY: NOT REGULATED
 FLASH POINT: NONE LEL: NA
 EXTINGUISHING MEDIA: NONE REQUIRED
 UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE
 SPECIAL FIRE FIGHTING PROCEDURES: NONE

SECTION V HEALTH HAZARD IDENTIFICATION

SYMPTOMS OF OVER EXPOSURE:
 INHALATION: NONE KNOWN
 EYES: MAY CAUSE MILD IRRITATION
 SKIN: NONE KNOWN
 INGESTION: NONE KNOWN

FIRST AID PROCEDURES:
 EYES: FLUSH WITH WATER
 SKIN: WASH WITH SOAP AND WATER
 INHALATION: REMOVE TO FRESH AIR IF NEEDED

INGESTION: DO NOT INDUCE VOMITING. CALL PHYSICIAN IMMEDIATELY.

SECTION VI REACTIVITY DATA

STABILITY: STABLE
 CONDITIONS TO AVOID: NONE KNOWN
 INCOMPATIBILITY-MATERIALS TO AVOID: NONE KNOWN
 HAZARDOUS DECOMPOSITION PRODUCTS: NONE KNOWN
 HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION VII SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED
 KEEP OUT OF SEWER SYSTEMS TO PREVENT BLOCKAGE DUE TO POLYMER DEPOSITS. USE ABSORBENT MATERIAL TO COLLECT AND/OR SCRAPE UP EXCESS AND PLACE INTO CLOSED DOT APPROVED CONTAINERS FOR DISPOSAL.

WASTE DISPOSAL: ABIDE BY ALL STATE, FEDERAL AND LOCAL REGULATIONS.

SECTION VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: NONE NEEDED
 VENTILATION: LOCAL EXHAUST
 PROTECTIVE GLOVES: NONE REQUIRED
 EYES: GOGGLES
 OTHER PROTECTIVE EQUIPMENT: NONE

SECTION IX SPECIAL PRECAUTIONS

PRECAUTION FOR HANDLING AND STORING: DO NOT PUNCTURE.
 KEEP OUT OF THE REACH OF CHILDREN.
 PROTECT FROM FREEZING
 CAUTION: DO NOT TAKE INTERNALLY. IF SWALLOWED, DO NOT INDUCE VOMITING, CALL PHYSICIAN IMMEDIATELY.

SECTION X TOXICOLOGICAL PROPERTIES

PRODUCT NAME: **SUBSET 4000 LATEX SEAM ADHESIVE**
ITEM NUMBER: 4000-04
ITEM DESCRIPTION: Shaw 4000 Subset Seam Sealer Qts
REVISION DATE: 01/02/14 REVIEW DATE: / / PRINT DATE:07/25/14 PRINT TIME:13:08

CHRONIC/SUBCHRONIC DATA:

FORMALDEHYDE IS A MINOR VOLATILE COMPONENT OF THIS PRODUCT. RECENT TEST RESULTS HAVE SHOWN FORMALDEHYDE TO CAUSE CANCER IN LABORATORY ANIMALS. FORMALDEHYDE IS READILY DETECTED BY ITS IRRITANT PROPERTIES. THE ODOR DETECTION LEVEL VARIES WITH INDIVIDUALS BETWEEN 0.2 PPM TO 1 PPM. ALSO ACCLIMATION OCCURS FROM REPEATED EXPOSURE BUT SENSITIVITY RETURNS FOLLOWING REST PERIODS AWAY FROM ATMOSPHERES CONTAINING FORMALDEHYDE. WHETHER RISK EXISTS AT LEVELS BELOW THE ODOR THRESHOLD HAS NOT BEEN DETERMINED.

SECTION XI REGULATORY INFORMATION

OSHA HAZARD COMMUNICATION STANDARD(29CFR 1910.1200)HAZARD CLASS(ES): NONE
SARA TITLE III SECTION 312 HAZARD CLASS: NONE
EPA SARA TITLE III SECTION 313: NONE

ALL COMPONENTS OF THIS PRODUCT ARE EITHER LISTED OR EXEMPT IN THE US EPA TSCA LIST

CALIFORNIA PROPOSITION 65: THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND/OR REPRODUCTIVE HARM.

NOTICE

SHAW INDUSTRIES EXPRESSLY DISCLAIMS ALL EXPRESS OR APPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WITH RESPECT TO THE PRODUCT OR INFORMATION PROVIDED HEREIN. ALL INFORMATION APPEARING HEREIN IS BASED UPON A DATA OBTAINED FROM THE MANUFACTURER AND/OR RECOGNIZED TECHNICAL SOURCES. WHILE THE INFORMATION IS BELIEVED TO BE ACCURATE, SHAW INDUSTRIES MAKES NO REPRESENTATIONS AS TO ITS ACCURACY OR EFFICIENCY. CONDITIONS OF USE ARE BEYOND SHAW'S CONTROL AND THEREFOR USERS ARE RESPONSIBLE TO VERIFY THIS DATA UNDER THEIR OWN OPERATING CONDITIONS TO DETERMINE WHETHER THE PRODUCT IS SUITABLE FOR THEIR PARTICULAR PURPOSES AND THEY ASSUME ALL RISKS OF THEIR USE, HANDLING, AND DISPOSAL OF THE PRODUCT, OR FROM PUBLICATION OF USE OF, OR RELIANCE UPON, INFORMATION CONTAINED HEREIN. THIS INFORMATION RELATES ONLY TO THE PRODUCT DESIGNATED HEREIN, AND DOES NOT RELATE TO ITS USE IN COMBINATION WITH ANY OTHER MATERIAL OR IN ANY PROCESS.
