



# Shield AW46 MVI Anti Wear Hydraulic Fluid

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier
- Product form : Mixture
- Product name : Shield AW46 MVI Anti Wear Hydraulic Fluid
- 1.2. Relevant identified uses of the substance or mixture and uses advised against
- Use of the substance/mixture : Hydraulic oil
- 1.3. Details of the supplier of the safety data sheet
- Old World Industries, LLC  
4065 Commercial Ave.  
Northbrook, IL 60062 - USA  
T (847) 559-2000  
[www.oldworldind.com](http://www.oldworldind.com)
- 1.4. Emergency telephone number
- Emergency number : (800) 424-9300; (703) 527 3887 (International)  
Chemtrec

### SECTION 2: Hazards identification

- 2.1. Classification of the substance or mixture
- GHS-US classification  
Not classified
- 2.2. Label elements
- GHS-US labelling
- Signal word (GHS-US) : None
- Hazard statements (GHS-US) : None
- Precautionary statements (GHS-US) : P273 - Avoid release to the environment  
P501 - Dispose of contents/container, in a safe manner, to appropriate waste disposal facility, in accordance with local/regional/national/international regulations
- 2.3. Other hazards
- Other hazards not contributing to the classification : Avoid prolonged or repeated contact with used fluid. The mixture consists of substances capable of producing an aspiration hazard. Aspiration may result in chemical pneumonia (fluid in the lungs), severe lung damage, respiratory failure, and even death. 9.73 percent of the mixture consists of ingredient(s) of unknown acute toxicity.
- 2.4. Unknown acute toxicity (GHS US)
- No data available

### SECTION 3: Composition/information on ingredients

- 3.1. Substance  
Not applicable

3.2. Mixture

Name	Product identifier	% by wt	GHS-US classification
distillates (petroleum), solvent-dewaxed heavy paraffinic	(CAS No) 64742-65-0	64 - 95	Not classified
distillates (petroleum), hydrotreated heavy paraffinic	(CAS No) 64742-54-7	0 - 17	Acute Tox. 3 (Inhalation:vapor), H331 Acute Tox. 4 (Inhalation:vapor), H332
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	(CAS No) 68649-42-3	0.7 - 2.7	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 2, H401 Aquatic Chronic 2, H411

# Shield AW46 MVI Anti Wear Hydraulic Fluid

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse immediately with plenty of water for 15 minutes, lifting lower and upper lids. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
First-aid measures after ingestion	: Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.
4.2. Most important symptoms and effects, both acute and delayed	
Symptoms/injuries after inhalation	: ON CONTINUOUS EXPOSURE/CONTACT: May cause respiratory irritation.
Symptoms/injuries after skin contact	: Contact during a long period may cause slight irritation.
Symptoms/injuries after eye contact	: Direct contact with the eyes is likely to be irritating.
Symptoms/injuries after ingestion	: Ingestion is likely to be harmful or have adverse effects.
4.3. Indication of any immediate medical attention and special treatment needed	
Aspiration during swallowing or vomiting may severely damage the lungs. If evacuation of stomach contents is necessary, use method least likely to cause aspiration.	
SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	: Do not use a heavy water stream. Will float and can be reignited on water surface.
5.2. Special hazards arising from the substance or mixture	
Fire hazard	: Not flammable. Promotes combustion.
Explosion hazard	: Not applicable.
Reactivity	: No dangerous reactions known under normal conditions of use.
5.3. Advice for firefighters	
Firefighting instructions	: Cool tanks/drums with water spray/remove them into safety. Fight fire with normal precautions from a reasonable distance. Under fire conditions, hazardous fumes will be present.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
Special protective equipment for fire fighters	: Protective fire fighting clothing (includes fire-fighting helmet, coat, pants, boots and gloves). Wear positive pressure self-contained breathing apparatus (SCBA).
SECTION 6: Accidental release measures	
6.1. Personal precautions, protective equipment and emergency procedures	
General measures	: Avoid contact with skin, eyes and clothing. Avoid breathing vapors, mist, spray.
6.1.1. For non-emergency personnel	
Protective equipment	: Use appropriate personal protection equipment (PPE).
Emergency procedures	: Evacuate unnecessary personnel.
6.1.2. For emergency responders	
Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Stop leak if safe to do so. Ventilate area.
6.2. Environmental precautions	
Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.	
6.3. Methods and material for containment and cleaning up	
For containment	: Contain leaking substance. Plug the leak, cut off the supply. Take up mechanically (sweeping, shovelling) and collect in suitable container for disposal.
Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage.

# Shield AW46 MVI Anti Wear Hydraulic Fluid

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 6.4. Reference to other sections

No additional information available

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling

Hygiene measures

- : Any proposed use of this product in elevated-temperature processes should be thoroughly evaluated to assure that safe operating conditions are established and maintained. Practice good housekeeping - spillage can be slippery on smooth surface either wet or dry.
- : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke when using this product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures

Storage conditions

- : Comply with applicable regulations.
- : Store in a dry place. Store in a well-ventilated place. Keep cool. Keep container closed when not in use. Protect from sunlight. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not store near food, foodstuffs, drugs or potable water supplies.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (Mineral oil, pure, highly and severely refined; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Inhalable fraction)
OSHA	Not applicable	

### 8.2. Exposure controls

Appropriate engineering controls

Personal protective equipment

- : Ensure good ventilation of the work station.
- : Protective goggles. Gloves.



Hand protection

Eye protection

Skin and body protection

Respiratory protection

- : Wear suitable gloves resistant to chemical penetration.
- : Chemical goggles or safety glasses.
- : Wear suitable protective clothing.
- : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state

Color

Odor

Odor threshold

Relative evaporation rate (butylacetate=1)

Freezing point

Boiling point

Flash point

Auto-ignition temperature

Decomposition temperature

Flammability (solid, gas)

Vapor pressure

Relative vapor density at 20 °C

- : Liquid
- : amber
- : petroleum-like odor
- : No data available
- : No data available
- : No data available
- : No data available
- : 204 °C (400 °F) [Method used: Cleveland Open Cup]
- : No data available
- : No data available
- : No data available
- : No data available
- : No data available

# Shield AW46 MVI Anti Wear Hydraulic Fluid

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Specific Gravity	: 0.85
Density	: 0.85 kg/l (7.09 lbs/gal)
Solubility	: Water: Negligible
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Not applicable.
Oxidizing properties	: No data available
Explosive limits	: No data available
9.2. Other information	
VOC content	: 0.00 %

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No dangerous reactions known under normal conditions of use.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

#### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Keep away from open flames, hot surfaces and sources of ignition.

#### 10.5. Incompatible materials

Keep away from strong acids, strong bases and oxidizing agents.

#### 10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide. hydrocarbons.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Not classified

#### distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LD50 oral rat	> 5,000.00 mg/kg bodyweight (Rat; OECD 401: Acute Oral Toxicity; Experimental value)
LD50 dermal rabbit	> 5,000.00 mg/kg bodyweight (Rabbit; Experimental value; Equivalent or similar to OECD 402)
LC50 inhalation rat (mg/l)	> 5.53 mg/l/4h (Rat; Experimental value)
ATE US (vapors)	3.00 mg/l/4h

#### distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

LD50 oral rat	> 5,000.00 mg/kg (Rat; Literature study)
LD50 dermal rabbit	> 5,000.00 mg/kg bodyweight (Rabbit; Literature study)
LC50 inhalation rat (mg/l)	> 5.00 mg/l/4h (Rat; Literature study)

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified

# Shield AW46 MVI Anti Wear Hydraulic Fluid

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: ON CONTINUOUS EXPOSURE/CONTACT: May cause respiratory irritation.
Symptoms/injuries after skin contact	: Contact during a long period may cause slight irritation.
Symptoms/injuries after eye contact	: Direct contact with the eyes is likely to be irritating.
Symptoms/injuries after ingestion	: Ingestion is likely to be harmful or have adverse effects.

### SECTION 12: Ecological information

#### 12.1. Toxicity

<b>distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>	
LC50 fish 1	> 100.00 mg/l (LL50; OECD 203: Fish, Acute Toxicity Test; 96 h; Pimephales promelas; Static system; Fresh water; Experimental value)
Threshold limit algae 1	>= 100 mg/l (NOEL; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Experimental value)
<b>Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)</b>	
LC50 fish 1	1 - 5 mg/l Exposure time: 96 h - Species: Pimephales promelas [static]
EC50 Daphnia 1	1 - 1.5 mg/l Exposure time: 48 h - Species: Daphnia magna
LC50 fish 2	10 - 35 mg/l Exposure time: 96 h - Species: Pimephales promelas [semi-static]

#### 12.2. Persistence and degradability

<b>distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>	
Persistence and degradability	Not readily biodegradable in water. Adsorbs into the soil.
<b>distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)</b>	
Persistence and degradability	Contains non readily biodegradable component(s). Adsorbs into the soil. Low potential for mobility in soil.

#### 12.3. Bioaccumulative potential

<b>distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>	
Bioaccumulative potential	No bioaccumulation data available.
<b>distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)</b>	
Log Pow	> 6.00 (Conclusion by analogy)
Bioaccumulative potential	Contains bioaccumulative component(s).

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

Effect on ozone layer

: No known effect on the ozone layer

Effect on global warming

: No known ecological damage caused by this product.  
No additional information available

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste disposal recommendations

: Dispose of contents/container, in a safe manner, to appropriate waste disposal facility, in accordance with local/regional/national/international regulations.

### SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not a dangerous good in sense of transport regulations

TDG

Refer to current TDG Canada for further Canadian regulations

# Shield AW46 MVI Anti Wear Hydraulic Fluid

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Transport by sea

No additional information available

Air transport

No additional information available

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

Shield AW46 MVI Anti Wear Hydraulic Fluid		
EPA TSCA Regulatory Flag	Toxic Substances Control Act (TSCA):	The intentional ingredients of this product are listed
<b>distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
<b>distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)</b>		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
<b>Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)</b>		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		

#### 15.2. International regulations

CANADA

WHMIS Classification

Uncontrolled product according to WHMIS classification criteria

<b>distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>		
Listed on the Canadian DSL (Domestic Substances List)		
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria	
<b>distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)</b>		
Listed on the Canadian DSL (Domestic Substances List)		
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria	
<b>Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)</b>		
Listed on the Canadian DSL (Domestic Substances List)		
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects	

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

No additional information available

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

National regulations

No additional information available

#### 15.3. US State regulations

### SECTION 16: Other information

# Shield AW46 MVI Anti Wear Hydraulic Fluid

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Full text of H-statements:


Acute Tox. 3 (Inhalation:vapor)	Acute toxicity (inhalation:vapor) Category 3
Acute Tox. 4 (Inhalation:vapor)	Acute toxicity (inhalation:vapor) Category 4
Aquatic Acute 2	Hazardous to the aquatic environment — Acute Hazard, Category 2
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
H315	Causes skin irritation
H318	Causes serious eye damage
H331	Toxic if inhaled
H332	Harmful if inhaled
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects

### NFPA health hazard

### NFPA fire hazard

### NFPA reactivity

- : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.
- : 1 - Must be preheated before ignition can occur.
- : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



### HMIS III Rating

### Health

### Flammability

### Physical

### Personal Protection

- : 1 Slight Hazard - Irritation or minor reversible injury possible
  - : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 °F (93 °C). (Class IIIB)
  - : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.
- B - Safety glasses, Gloves

### SDS GHS US (GHS HazCom 2012) OWI

*Old World Industries, LLC makes no warranty, representation or guarantee as to the accuracy, sufficiency or completeness of the material set forth herein. It is the user's responsibility to determine the safety, toxicity and suitability of his own use, handling and disposal of this product. Since actual use by others is beyond our control, no warranty, expressed or implied, is made by Old World Industries, LLC as to the effects of such use, the results to be obtained or the safety and toxicity of this product, nor does Old World Industries, LLC assume liability arising out of the use by others of this product referred to herein. The data in this SDS relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.*