**** MATERIAL SAFETY DATA SHEET ****

Version Date...........10/28/10 SOLAR FLUX TYPE B A=SILICA, CRYSTALLINE ______ PRODUCT IDENTIFICATION SECTION 1 COMPANY NAME WHO SENT MSDS..... Harris Products Group COMPANY ADDRESS..... 4501 QUALITY PLACE MASON, OHIO 45040 (513) 754-2000 (800) 424-9300 EMERGENCY PHONE NUMBER..... MSDS VERSION NUMBER..... SOLAR FLUX TYPE B TRADE NAME....... HAZARD RATING (HMIS)..... HEALTH-3 FLAMMABILITY-0 REACTIVITY-0 OTHER-1 4-SEVERE HAZARD HMIS DESIGNATION KEY..... 3-SERIOUS HAZARD 2-MODERATE HAZARD 1-SLIGHT HAZARD 0-MINIMAL HAZARD ___________ HAZARDOUS COMPONENTS SECTION 2 MATERIAL % BY WEIGHT CAS NUMBER OSHA PEL ACGIH TLV (Mg/M3) SEC 313 6-12 14808-60-7 0.1MG/M3 (1) NA FREE CRYSTALLINE SILICA NON - HAZARDOUS INGREDIENTS _________ PHYSICAL PROPERTIES SECTION 3 BOILING POINT..... 3060 F MELTING POINT..... NA VAPOR PRESSURE..... NA VAPOR DENSITY (AIR = 1).....NA SOLUBILITY IN WATER..... % BY WT. 4.2 GM/ML SPECIFIC GRAVITY..... (H20 = 1) 2.2EVAPORATION RATE..... ZERO APPEARANCE AND ODOR...... DARK GRAY POWDER, ODORLESS ________ SECTION 4 FIRE AND EXPLOSION DATA FLASH POINT.....

SOLAR FLUX TYPE B A=SILICA, CRYSTALLINE

SECTION 4	FIRE AND EXPLOSION DATA	CONT'D
EXTINGUISING MEDIA SPECIAL PROCEDURES UNUSUAL HAZARDS	NONE	
SECTION 5	REACTIVITY DATA	
STABILITY	NA	

HEALTH HAZARD DATA SECTION 6 ROUTES OF ENTRY..... SKIN CONTACT, EYE, INHALATION, INGESTION= OF NUISANCE DUST. HEALTH HAZARDS..... SKIN AND EYE CONTACT - WASH WITH SOAP AND WATER. IF IRRITATION OCCURS AND PERSISTS SEE A DOCTOR. INHALATION - KEEP AREA WELL VENTILATED TO PREVENT INHALING DUST, NO SPECIAL AID PRO-CEDURES REQUIRED UNLESS ENORMOUS QUAN-TITIES INHALED. INGESTION - DRINK PLENTY OF WATER & INDUCE VOMITING. SEE A DOCTOR. CARCINOGENICITY..... THE STATE OF CALIFORNIA REQUIRES THE FOL-LOWING INFORMATION: WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER. SIGNS & SYMPTOMS OF EXPOSURE.... REPEATED INHALATION AND PROLONGED OVER MEDICAL CONDITIONS FROM EXPOSURE EXPOSURE ABOVE TLV COULD RESULT IN DELAYED LUNG INJURY (SILICOSIS). EMERGENCY & FIRST AID..... SEEK MEDICAL ATTENTION IF NEEDED.

SOLAR FLUX TYPE B A=SILICA, CRYSTALLINE

HEALTH HAZARD DATA SECTION 6

CONT'D

SEE 29 CFR 1910.1200.

ADDITIONAL INFORMATION..... SOLAR FLUX CONTAINS 6-12% CRYSTALLINE

SILICA, WHICH IS A FIBROGENIC MATERIAL WHICH CAN CAUSE A DISABLING PULMONARY FIBROSIS KNOWN AS SILICOSIS AFTER PRO-

LONGED INHALATION OF THE DUST.

PRECAUTIONS FOR SAFE HANDLING AND USE SECTION 7

SPILL AND LEAK PROCEDURES..... INERT DRY POWDER. SWEEP UP AND DISCARD IN

SOLID WASTE.

WASTE AND DISPOSAL METHOD..... DISPOSE OF IN ACCORDANCE WITH FEDERAL,

STATE, AND LOCAL REGULATIONS.

NOT CLASSIFIED AS TOXIC WASTE.

HANDLING AND STORING PRECAUTIONS LABEL ALL CONTAINERS ACCORDINGLY.

OTHER PRECAUTIONS.....

USE IN WELL VENTILATED AREA.

SECTION 8 CONTROL MEASURES

RESPIRATORY MEASURES..... STANDARD FOR WELDING

WELL VENTILATED AREA. LOCAL EXHAUST. VENTILATION.....

STANDARD FOR WELDING

PROTECTIVE GLOVES..... STANDARD FOR WELDING

EYE PROTECTION..... STANDARD FOR WELDING

OTHER PROTECTIVE EQUIPMENT..... REFER TO 29 CFR 1910.1200 FOR ALL PROTECT-

IVE CLOTHING/EQUIPMENT THAT IS REQUIRED.

WORK/HYGIENIC PRACTICES...... FOR MAXIMUM SAFETY: BE CERTIFIED FOR, AND

WEAR A RESPIRATOR AT ALL TIMES WHEN WELD-

ING AND OR BRAZING.

SECTION 9 **DISCLAIMER**

THIS DATA IS BELIEVED TO BE ACCURATE. HARRIS WELC

SECTION 10 ADDITIONAL INFORMATION

NA= NOT APPLICABLE

SOLAR FLUX TYPE B A=SILICA, CRYSTALLINE

ADDITIONAL INFORMATION SECTION 10

CONT'D

CARCINOGENITY INFORMATION: SILICA, CRYST-ALLINE (AIRBORNE PARTICLES OF RESPIRABLE SIZE) ARE REQUIRED BY OSHA TO BE CONSIDER-ED CARCINOGENIC.

SECTION 11

ADDITIONAL INFORMATION