

# Specshield 35% H<sub>2</sub>, Ar

PRODUCT: SPECSHIELD 35% H<sub>2</sub>, Ar MSDS NR: 302-10-0004 BOC VERSION: 1.02 DATE: 20/03/02 PAGE: 1/1  
FORMERLY: PURESIELD P2 AND ARGON/HYDROGEN MIXTURES CONTAINING MORE THAN 11% HYDROGEN

## 1 IDENTIFICATION OF THE SUBSTANCE/ PREPARATION AND OF THE COMPANY

<b>Product name</b>	Specshield 35% H <sub>2</sub> , Ar
<b>Company identification</b>	see end of page 2
<b>Emergency phone Nos</b>	see end of page 2

## 2 COMPOSITION/INFORMATION ON INGREDIENTS

<b>Substance/ Preparation</b>	Preparation
<b>Components/Impurities</b>	
Specshield 35% H <sub>2</sub> , Ar	35% H <sub>2</sub> balance Ar
<b>EEC Nr (from EINECS)</b>	Not applicable for preparations

## 3 HAZARDS IDENTIFICATION

<b>Hazards identification</b>	Extremely flammable Compressed gas.
-------------------------------	--

## 4 FIRST AID MEASURES

<b>Inhalation</b>	In high concentrations may cause asphyxiation and death. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
<b>Ingestion</b>	Ingestion is not considered a potential route of exposure.

## 5 FIRE FIGHTING MEASURES

<b>Specific hazards</b>	Exposure to fire may cause containers to rupture/explode. Inform Fire Brigade.
<b>Hazardous combustion products</b>	None.
<b>Suitable extinguishing media</b>	All known extinguishants can be used.
<b>Specific methods</b>	If possible, stop flow of product. Move away from container and cool with water from a protected position. Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive re-ignition may occur. Extinguish any other fire.
<b>Special protective equipment for fire fighters</b>	In confined space use self-contained breathing apparatus.

## 6 ACCIDENTAL RELEASE MEASURES

<b>Personal precautions</b>	Evacuate area. Ensure adequate air ventilation. Eliminate ignition sources. Post warning signs (including no smoking).
<b>Leak not ignited</b>	Extinguish all sources of ignition in the immediate area. Close the cylinder valve. If necessary tighten the gland nut.  If leak continues, evacuate the area, and avoiding sources of ignition and minimising personal risk move the leaking cylinder to a safe outside area. Notify BOC Gases. Post warning notices and prevent access to the area.  Do not attempt to tighten the cylinder valve in the body of the cylinder.  Do not tamper with the safety devices.
<b>Leak Ignited</b>	Raise fire alarm.  Close cylinder valve if safe to do so. Call fire brigade. Evacuate the area. If possible apply copious quantities of water from a hose to the affected cylinder(s) from a protected position until the cylinder(s) are cold.  Do not move cylinders until cold.
<b>Environmental precautions</b>	Try to stop release if safe to do so.
<b>Clean up methods</b>	Ventilate area.

## 7 HANDLING AND STORAGE

<b>Handling and storage</b>	Ensure equipment is adequately earthed. Close cylinder valve when not in use to prevent contamination of the cylinder. Purge air from system before introducing gas. Do not allow backfeed into the container. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact BOC if in doubt. Keep away from heat and ignition sources (including static discharges). Segregate from oxidant gases and other oxidants in store. Refer to BOC container handling instructions. Keep container below 50°C in a well ventilated place.
-----------------------------	--

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

<b>Personal protection</b>	Ensure adequate ventilation. Do not smoke while handling product.
----------------------------	---

## 9 PHYSICAL AND CHEMICAL PROPERTIES

<b>Relative density, gas</b>	Lighter or similar to air.
<b>Solubility mg/l water</b>	Not known.
<b>Appearance/Colour</b>	Colourless gas
<b>Odour</b>	None

# SAFETY DATA SHEET

## 10 STABILITY AND REACTIVITY

**Stability and reactivity** Can form explosive mixture with air. May react violently with oxidants.

## 11 TOXICOLOGICAL INFORMATION

**General** No known toxicological effects from this product.

## 12 ECOLOGICAL INFORMATION

**General** No ecological damage caused by this product

## 13 DISPOSAL CONSIDERATIONS

**General** Do not discharge into areas where there is a risk of forming an explosive mixture with air. Waste gas should be flared through a suitable burner with flash back arrestor. Do not discharge into any place where its accumulation could be dangerous. Contact BOC if guidance is required.

## 14 TRANSPORT INFORMATION

**Proper shipping name** Flammable gas, compressed, N.O.S. (hydrogen, argon)

**UN Nr** 1954

**Class/Div** 2.1

**ADR/RID Classification Code** 1F

**ADR/RID Hazard Nr** 23

**Labelling ADR** Label 3: flammable gas.

### Other transport information

Avoid transport on vehicles where the load space is not separated from the driver's compartment.

Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.

Before transporting product containers ensure that they are firmly secured and:

- cylinder valve is closed and not leaking.
- valve outlet cap nut or plug (where provided) is correctly fitted.
- valve protection device (where provided) is correctly fitted
- adequate ventilation.
- compliance with applicable regulations.

## CYLINDER CHARACTERISTICS

Cylinder Size	Maximum Filled Pressure at 15° C (bar)	Approx. Dimensions incl. valve and guard where supplied (mm)	Approx. Full Cylinder weight (kg)	Manifolded cylinder Pallets (MCP's)	Maximum Filled Pressure at 15° C (bar)	Approx. Dimensions incl. cylinders (mm)	Max. Gross weight (kg)
N	200	230 x 1460	82	WVN (15xN)	200	1290 x 1810 x 840	1500

**OUTLET CONNECTION:** 5/8" BSP female left hand cone recessed.



A member of The BOC Group  
The stripe symbol and the word BOC and Specshield are BOC Group trademarks.  
© The BOC Group 2004

## For product and safety enquiries please phone

**In the United Kingdom:**  
**0800 111 333**

**BOC Customer Service Centre**  
**Priestley Road, Worsley**  
**Manchester M28 2UT**  
**Fax: 0800 111 555**

**In the Republic of Ireland:**  
**Dublin 1850 333 435**

**BOC Ireland**  
**P.O. Box 201, Bluebell**  
**Dublin 12**  
**Fax: 01 409 1801**

SFT/007277/APUK/1204/1M

## 15 REGULATORY INFORMATION

**Number in Annex I of Dir 67/548** Not applicable for preparations

**EC Classification** F+;R12.

### Labelling of cylinders

- **Symbols** Label 3: flammable gas.
- **Risk phrases** R12 Extremely flammable.
- **Safety phrases** S9 Keep container in well ventilated place.  
S16 Keep away from ignition sources – No smoking.  
S33 Take precautionary measures against static discharges.

## 16 OTHER INFORMATION

Ensure all national/local regulations are observed.

Ensure operators understand the flammability hazard.

The hazard of asphyxiation is often overlooked and must be stressed during operator training.

Users of breathing apparatus must be trained.

This Safety Data Sheet has been established in accordance with the applicable European Directives and applies to all countries that have translated the Directives in their national laws.

Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Although this shielding gas alone does not exhibit toxic/harmful effects, the fumes generated from a welding process can be hazardous to health.

Always leak check cylinders when first collected, delivered or used, using an approved leak detection fluid.

Details given in this document are believed to be correct at the time of going to press.

Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

For further safety information please refer to "Safety Under Pressure" and "Safe handling, storage and transport of industrial gas cylinders", both of which are available from your local BOC outlet.