

Stainshield-TIG

PRODUCT: STAINSHIELD-TIG MSDS NR: 300-15-0001 BOC VERSION : 2.02 DATE : 17/08/06 PAGE : 1/2
FORMERLY: PURESIELD P1 AND ARGON HYDROGEN MIXTURES CONTAINING LESS THAN 2%
HYDROGEN, INCLUDING HYLITE

1 IDENTIFICATION OF THE SUBSTANCE/ PREPARATION AND OF THE COMPANY

Product name Stainshield-TIG.
Company identification see end of page 2.
Emergency phone Nos see end of page 2.

2 COMPOSITION/INFORMATION ON INGREDIENTS

Substance/Preparation Preparation.
Components/Impurities
Stainshield-TIG 1.5% H₂ balance Ar.
EEC Nr (from EINECS) Not applicable for preparation.

3 HAZARDS IDENTIFICATION

In high concentrations may cause asphyxiation.
Compressed gas.

4 FIRST AID MEASURES

Inhalation In high concentrations may cause asphyxiation and death. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

Ingestion Ingestion is not considered a potential route of exposure.

5 FIRE FIGHTING MEASURES

Specific hazards Exposure to fire may cause containers to rupture/explode. Inform Fire Brigade. Non flammable.

Hazardous combustion products None.

Suitable extinguishing media All known extinguishants can be used.

Specific methods If possible, stop flow of product. Move away from container and cool with water from a protected position.

Special protective equipment for fire fighters In confined space use self-contained breathing apparatus.

6 ACCIDENTAL RELEASE MEASURES

Personal precautions Evacuate area. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Ensure adequate air ventilation. Post warning notices.

Environmental precautions

Try to stop release.
Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

Clean up methods Ventilate area.

7 HANDLING AND STORAGE

Suck back of water into the container must be prevented. Do not allow backfeed into the container. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact BOC if in doubt. Refer to BOC container handling instructions. Keep container below 50°C in a well ventilated place.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Personal protection Ensure adequate ventilation.

9 PHYSICAL AND CHEMICAL PROPERTIES

Relative density, gas Heavier than air.
Solubility mg/l water Not known.
Appearance/Colour Colourless gas.
Odour None.
Other data Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level. Will displace oxygen when ventilation is at a high point only.

10 STABILITY AND REACTIVITY

Stability and reactivity Stable under normal conditions.

11 TOXICOLOGICAL INFORMATION

General No known toxicological effects from this product.

12 ECOLOGICAL INFORMATION

General No ecological damage caused by this product.

13 DISPOSAL CONSIDERATIONS

General Do not discharge into any place where its accumulation could be dangerous. Contact BOC if guidance is required.

SAFETY DATA SHEET

14 TRANSPORT INFORMATION

Proper Shipping Name	Compressed gas N.O.S. (argon, hydrogen).
UN Nr	1956.
Class/Div	2.2.
ADR/RID	
Classification Code	1A.
ADR/RID Hazard Nr	20.
Labelling ADR	Label 2.2: non flammable non toxic gas.
Other transport information	Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured and: - cylinder valve is closed and not leaking. - valve outlet cap nut or plug (where provided) is correctly fitted. - valve protection device (where provided) is correctly fitted. - adequate ventilation. - compliance with applicable regulations.

15 REGULATORY INFORMATION

Number in Annex I of Dir 67/548	Not applicable for preparations.
EC Classification	Not classified as dangerous substance.
Labelling of cylinders – Symbols	Label 2.2: non flammable non toxic gas.

16 OTHER INFORMATION

Ensure all national/local regulations are observed.
Asphyxiant in high concentrations.
Keep container in well ventilated place.
Do not breathe the gas.
The hazard of asphyxiation is often overlooked and must be stressed during operator training.
Users of breathing apparatus must be trained.
This Safety Data Sheet has been established in accordance with the applicable European Directives and applies to all countries that have translated the Directives into their national laws.
Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Although this shielding gas alone does not exhibit toxic/harmful effects, the fumes generated from a welding process can be hazardous to health.
Always leak check cylinders when first collected, delivered or used, using an approved leak detection fluid.
Details given in this document are believed to be correct at the time of going to press.
Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.
For further safety information please refer to Safe Under Pressure and Guidance for carriage of gas cylinders on vehicles, both of which are available from your local BOC.

CYLINDER DIMENSIONS AND WEIGHTS

Cylinder Size	Max Fill Pressure at 15°C (Bar)	Approx. Dimensions including valve and guard where supplied (mm)	Approx. Full Cylinder Weight (Kg)	Manifold Cylinder Pallets (MCP)	Max Fill Pressure at 15°C (Bar)	Approx. Dimensions including valve and guard where supplied (mm)	Approx. Full Cylinder Weight (Kg)
N	200	1460 x 230	82	WN (15 x N)	200	1290 x 1810 x 840	1500
V	200	940 x 140	19				

NOTE: Not all cylinder and MCP sizes are available at all locations.
OUTLET CONNECTION: 5/8" BSP female right hand cone recessed.



A member of The BOC Group
The stripe symbol and the word BOC are BOC Group trademarks.
© The BOC Group 2006

All BOC Safety Data Sheets are available online at www.boc.com/uk/sds

For product and safety enquiries please phone

In the United Kingdom:
0800 111 333

BOC Customer Service Centre
Priestley Road, Worsley
Manchester M28 2UT
Fax: 0800 111 555

In the Republic of Ireland:
1850 333 435

BOC Ireland
P.O. Box 201
Bluebell, Dublin 12
Fax: 01 409 1801