




**CCI MANUFACTURING IL CORPORATION**

 15550 Canal Bank Rd., P.O. Box 339, Lemont, IL 60439 U.S.A.  
 TEL +1-630-739-0606 FAX +1-630-739-1116

**Safety Data Sheet**

SDS No. 128524

Subaru Long Life Super Coolant 50/50 Prediluted Antifreeze and Engine

Date : October 20, 2015

Coolant

**Subaru Long Life Super Coolant 50/50 Prediluted Antifreeze and Engine Coolant**

Flammable aerosols	-
Oxidizing gases	-
Gases under pressure	-
Flammable liquids	Not Classified
Flammable solids	-
Self-reactive chemicals	-
Pyrophoric liquids	Not Classified
Pyrophoric solids	-
Self-heating chemicals	Classification Not Possible
Chemicals which, in contact with water, emit flammable gases	-
Oxidizing liquids	Classification Not Possible
Oxidizing solids	-
Organic peroxides	-
Corrosive to metals	Not Classified

**2.2 Label elements**
**Hazard Pictograms**


Signal word

Danger

**Hazard statements**

Causes serious eye irritation

Causes skin irritation

May cause an allergic skin reaction

Causes damage to organs (Central nerves, Kidney).

May cause damage to organs (Blood, Kidney, Liver) through prolonged or repeated exposure.

May cause respiratory irritation

**Precautionary statements**
**Prevention**

Wash contact areas thoroughly after handling.

Wear eye protection/face protection.

Avoid breathing mist/vapors/spray.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves.

Do not breathe mist/vapors/spray.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

**Response**

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.






**CCI MANUFACTURING IL CORPORATION**

 15550 Canal Bank Rd., P.O. Box 339, Lemont, IL 60439 U.S.A.  
 TEL +1-630-739-0606 FAX +1-630-739-1116

## Safety Data Sheet

SDS No. 128524 Subaru Long Life Super Coolant 50/50 Prediluted Antifreeze and Engine  
 Date : October 20, 2015 Coolant

### Subaru Long Life Super Coolant 50/50 Prediluted Antifreeze and Engine Coolant

#### 7.1 Precautions and safe handling

- Do not expose children and pets to this material.
- After handling product, wash thoroughly with soap and water before drinking, eating, or smoking.
- Keep away from open flames.

#### 7.2 Conditions for safe storage, including any incompatibilities

- To prevent possible storage container rupture, do not permit to freeze. Incompatible with strong acids, oxidizers, bases and chromium trioxide, potassium permanganate, and sodium peroxide.

#### 7.3 Specific end use(s)

The identified uses for this product are detailed in section 1.2.

### SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

Component	CAS No.	Source	Exposure Limit	Notes
Ethylene glycol	107-21-1	US OSHA	None	None
		US ACGIH	100 mg/m <sup>3</sup> TLV	Ceiling Limit for Aerosols Only; A4 - Not classifiable as a human carcinogen
Diethylene Glycol	111-46-6	US OSHA	None	None
		US ACGIH	None	None
		US AIHA (WEEL)	10 mg/m <sup>3</sup>	TWA

#### 8.2 Exposure controls

- Control Measures : Handle in the presence of adequate ventilation. Engineering controls should be used whenever feasible to maintain concentrations below acceptable exposure criteria, including enclosures and local exhaust ventilation.
- Respiratory Protection : Where exposure is likely to exceed acceptable criteria and engineering controls are not feasible, use NIOSH/MSHA approved respiratory protection equipment. Respirators should be selected based on the form and concentration of contaminants in air and in accordance with OSHA (29 CFR 1910.134)
- Protective Clothing : Wear gloves and protective clothing which are impervious to the product for the duration of exposure if there is potential for skin contact.









