# MATERIAL SAFETY DATA SHEET

#### **SECTION I - IDENTIFICATION**

PRODUCT NAME:	Super	Dri S	pecial
I KODUCI NAME.	Duper		pecia

HAZARDOUS INGREDIENT

PRODUCT TYPE:.....Liquid Cationic Drying Agent

# **SECTION II - HAZARDOUS INGREDIENTS**

CAS NUMBER

PEL

**PERCENT** 

Water	7732-18-5	No limits established	Not
			Listed
Mixed Petroleum Hydrocarbons	64741-44-2	5mg/m3 PEL	
Dialkyl Quaternary Ammonium Chloride	61789-77-3	No limits established	
2-Butoxy Ethanol	111-76-2	20 ppm TLV, 25 ppm	
•		PEL	
Ethoxylated Tallow Amine	68155-39-5	No limits established	

## **SECTION III - PHYSICAL DATA**

APPEARANCE: Light golden transparent liquid. Slight solvent odor.

BOILING POINT: 210 degrees F. VAPOR PRESSURE: N/A VAPOR DENSITY: Greater than 1. SPECIFIC GRAVITY: 0.982

PH: 6.5-7.5 SOLUBILITY IN WATER: Completely soluble.

## **SECTION IV - FIRE AND EXPLOSION DATA**

FLASHPOINT:This product is non-flammable.				
EXTINGUISHING MEDIA:Water fog or fine spray. Carbon dioxide, Dry chemical,				
or Alcohol resistant foam.				
SPECIAL FIRE FIGHTING PROCEDURES: Firefighters working in areas				
where this product is present should be equipped with an approved, fully enclosed SCBA.				
UNUSUAL FIRE AND EXPLOSION HAZARDS:None known.				
SECTION V - REACTIVITY DATA				
STABILITY:Stable under normal conditions.				
HAZARDOUS POLYMERIZATION: This product not known to polymerize.				
INCOMPATIBILITY:				
HAZARDOUS BYPRODUCTS:Carbon monoxide, carbon dioxide.				
SECTION VI - HEALTH DATA				

STABILITY:Stable under normal conditions.				
HAZARDOUS POLYMERIZATION: This product not known to polymerize.				
INCOMPATIBILITY:Do not mix with other chemicals.				
HAZARDOUS BYPRODUCTS:Carbon monoxide, carbon dioxide.				
SECTION VI - HEALTH DATA				
ROUTE(S) OF ENTRY:Inhalation, skin absorption, or ingestion.				
LISTED CARCINOGEN:Not listed by IARC, NTP or OSHA.				
MEDICAL CONDITION AGGRAVATED: May aggravate pre-existing				
dermatitis.				
INHALATION:Not likely to be inhaled in hazardous amounts. Avoid				
exposure to mists or vapors. Maintain adequate ventilation in the work area.				
INGESTION:This material can cause irritation or damage to stomach				
and esophagus.				
EYES:Undiluted product will cause burns or eye irritation, or				
possibly permanent damage.				
SKIN (DERMAL): This product may cause irritation if not removed from				
the skin. Chronic overexposure may cause injury to blood, liver & kidneys.				

#### SECTION VILEIRST AID

SECTION VIII	INOI AID
BREATHING (INHALATION): If victim sl	nows signs of discomfort or irritation, remov
o fresh air. If symptoms persist, get immediate medi	
SWALLOWING (INGESTION):DO NOT I	NDUCE VOMITING! Drink a large quantit
of water or milk. Do not attempt to give liquids to an	
attention!	•
EYES: Flush eyes	with a large quantity of fresh water for at
east 15 minutes. If irritation persists, consult a phys	
SKIN (DERMAL):Flush fron	
vater. If irritation persists, consult physician. Wash	
SECTION VIII EMPLOY	
RESPIRATORY PROTECTION:Not usuall	
ise an OSHA approved respirator.	,
PROTECTIVE CLOTHING:Nitrile or 1	PVC gloves, and chemical splash goggles.
ADDITIONAL MEASURES: Do not pla	
Keep away from children! Spilled material is slipper	
SECTION IX - SPILL AN	D DISDOSAL DATA
SPILL: Dike to pro	event spinage into streams or sewer systems.
Consult local, state and federal authorities.	
WASTE DISPOSAL:As recomm	
HANDLING & STORAGE PRECAUTIONS	Store in a cool, well ventilated
area. Avoid overheating or freezing.	ATORY INFORMATION
SECTION X -OTHER REGU	
PROPER SHIPPING NAME: Not D.O.T. regulated.	
CONSTITUENT:	NFPA FLAMMABILITY: 1
HAZARD CLASS AND LABEL:	NFPA REACTIVITY: 0
D NUMBER:	NFPA OTHER: None
PACKING GROUP:	

#### SECTION XI - PRECAUTIONARY STATEMENTS