

Safety Data Sheet THREAD-EZE ULTRA AEROSOL

Supersedes Date 09/27/2013

Issuing Date 04/05/2016

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name THREAD-EZE ULTRA AEROSOL
Recommended use Lubricant
Information on Manufacturer
CHEMSEARCH DIV. OF NCH CORP.
BOX 152170
IRVING, TX 75015

Product Code 5588
Chemical nature Petroleum distillates Mixture
Emergency Telephone Number

Telephone inquiry
972-579-2477

2. HAZARD IDENTIFICATION

Color White - off-white

Physical state Liquid

Odor Petroleum

GHS

Classification

Physical Hazards

Flammable Aerosols
Gases under pressure

Category 1
Liquefied gas

Health Hazard

Aspiration Toxicity
Skin Corrosion/Irritation
Specific target organ systemic toxicity (single exposure)

Category 1
Category 2
Category 3

Other hazards

None

Labeling

Signal Word

DANGER



Hazard statements

H220 - Extremely flammable gas
H336 - May cause drowsiness or dizziness
H315 - Causes skin irritation
H304 - May be fatal if swallowed and enters airways
H280 - Contains gas under pressure; may explode if heated

Precautionary Statements

P210 - Keep away from heat, sparks, open flames or hot surfaces.
P211 - Do not spray on an open flame or other ignition source
P251 - Pressurized container: Do not pierce or burn, even after use
P261 - Avoid breathing vapor, mist or gas
P271 - Use in a well-ventilated area.
P280 - Wear protective gloves, protective clothing and eye protection.
P264 - Wash face, hands and any exposed skin thoroughly after handling
P270 - Do not eat, drink or smoke when using this product.
P304 + P340 - IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.
P312 - Call a physician if unwell.
P302 + P352 - IF ON SKIN: Wash with plenty of soap and water
P332 + P313 - If skin irritation occurs, get medical attention.
P362 - Take off contaminated clothing and wash before reuse
P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. DO NOT induce vomiting. Call a physician if unwell.
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed
P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
P233 - Keep container tightly closed
P501 - Dispose of contents and container in accordance with applicable local regulations.

2 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION / INFORMATION ON INGREDIENTS

Component	CAS No.	Weight % *
White mineral oil, solvent refined	8042-47-5	30-60
Heptane (n-)	142-82-5	15-40
Calcium carbonate	471-34-1	10-30
Isobutane	75-28-5	5-10
Propane	74-98-6	5-10
Zinc oxide	1314-13-2	3-7
Oxaluminum Benzoate/Stearate	151911-66-9	1-5

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

General advice	Avoid breathing vapors, mist, or gas. Avoid contact with skin, eyes and clothing.
Eye Contact	Rinse thoroughly with plenty of water, also under the eyelids. Get medical attention if irritation develops and persists.
Skin Contact	Wash off with soap and plenty of water. Get medical attention if irritation develops and persists.
Inhalation	If inhaled, remove to fresh air. Get medical attention if symptoms occur.
Ingestion	Drink 1 or 2 glasses of water. Do NOT induce vomiting. Get medical attention if symptoms occur.
Notes to physician	Aspiration hazard if swallowed - can enter lungs and cause damage. May be fatal if swallowed and enters airways.

5. FIRE-FIGHTING MEASURES

Flash Point 73 °F / 23 °C	Method Setaflash Closed Cup ASTM E502	
Flammability Limits in Air %: Mixture.	Upper: 9.5	Lower: 1
Suitable Extinguishing Media		
Carbon dioxide (CO ₂). Dry chemical. Water spray. Foam. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.		
Specific hazards arising from the chemical		
Extremely flammable. Solvent vapors are heavier than air and may spread along floors. Vapors may ignite and explode. Flame extension: >30 inches / >76 cm and Burnback: 6 inch / 15 cm. Material can create slippery conditions.		
Protective Equipment and Precautions for Firefighters		
As in any fire, wear self-contained breathing apparatus pressure-demand, NOHSC (approved or equivalent) and full protective gear.		
Aerosol Level (NFPA 30B) -	3	
NFPA	Health 2	Flammability 4
HMIS	Health 2	Flammability 4
		Instability 0
		Instability 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Use personal protective equipment. Ensure adequate ventilation. Take precautionary measures against static discharges. Remove all sources of ignition. Material can create slippery conditions.
Environmental Precautions	Do not flush into surface water or sanitary sewer system.
Methods for Containment	Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).
Methods for Cleaning Up	Use clean non-sparking tools to collect absorbed material. Pick up and transfer to properly labeled containers.
Neutralizing Agent	Not applicable.

7. HANDLING AND STORAGE

Handling	Keep away from open flames, hot surfaces and sources of ignition. Avoid breathing vapors, mist or gas. Avoid contact with skin, eyes and clothing.			
Storage	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition. Store in original container.			
Storage Temperature	Minimum	35 °F / 2 °C	Maximum	125 °F / 52 °C
Storage Conditions	Indoor	X	Outdoor	Heated Refrigerated

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH
White mineral oil, solvent refined	5 mg/m ³	5 mg/m ³	STEL 10 mg/m ³ TWA: 5 mg/m ³
Heptane (n-)	TWA: 400 ppm	TWA: 500 ppm	750 ppm

	STEL: 500 ppm	TWA: 2000 mg/m ³	Ceiling: 440 ppm Ceiling: 1800 mg/m ³ TWA: 85 ppm TWA: 350 mg/m ³
Calcium carbonate	No data available	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Isobutane	STEL: 1000 ppm	No data available	TWA: 800 ppm TWA: 1900 mg/m ³
Propane	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m ³	2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³
Zinc oxide	TWA: 2 mg/m ³ respirable fraction STEL: 10 mg/m ³	TWA: 5 mg/m ³ fume TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction	500 mg/m ³ Ceiling: 15 mg/m ³ STEL 10 mg/m ³ TWA: 5 mg/m ³ dust and fume

Engineering Measures Ensure adequate ventilation, especially in confined areas. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

Personal Protective Equipment

Eye/Face Protection

Safety glasses with side-shields.

Skin Protection

Wear suitable protective clothing, Impervious gloves.

Respiratory Protection

In case of inadequate ventilation wear respiratory protection. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

General Hygiene Considerations

Ensure that eyewash stations and safety showers are close to the workstation location. Remove and wash contaminated clothing before re-use. Wear protective gloves/clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid	Viscosity	Viscous
Color	White - off-white	Odor	Petroleum
Odor Threshold	Not applicable	Appearance	Opaque
pH	Not applicable	Specific Gravity	0.872
Evaporation Rate	29.77 (Butyl acetate=1)	Percent Volatile (Volume)	55.2
VOC Content (%)	39.9	VOC Content (g/L)	348
Vapor Pressure	1647 mm Hg	Vapor Density	1.4 (Air = 1.0)
Solubility	Not applicable	n-Octanol/Water Partition	No data available
Melting Point/Range	No data available	Decomposition Temperature	No data available
Boiling Point/Range	No data available	Flammability (solid, gas)	No data available
Flash Point	73 °F / 23 °C	Method	Setaflash Closed Cup ASTM E502
Autoignition Temperature	No information available.		
Flammability Limits in Air %:	Mixture	Upper: 9.5 Lower: 1	

10. STABILITY AND REACTIVITY

Chemical Stability	Stable. Hazardous polymerization does not occur.
Conditions to Avoid	Keep away from open flames, hot surfaces, and sources of ignition.
Incompatible Products	Strong oxidizing agents, Acids, Bases.
Decomposition Temperature	No data available
Hazardous Decomposition Products	No information available.
Possibility of Hazardous Reactions	None under normal processing.

11. TOXICOLOGICAL INFORMATION

Product Information No information available.

The following values are calculated based on chapter 3.1 of the GHS document

Oral LD50 No information available

Dermal LD50 No information available

Inhalation LC50

Gas No information available

Mist No information available

Vapor No information available

Principle Route of Exposure

Eye contact, Skin contact, Inhalation.

Primary Routes of Entry

Skin contact, Eye contact, Inhalation, Ingestion.

Acute Effects:

Eyes May cause eye irritation.

Skin Causes skin irritation.

Inhalation

Causes respiratory tract irritation. May cause central nervous system depression. Inhalation may cause central nervous system effects. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Ingestion

May be harmful if swallowed. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. Aspiration hazard if swallowed - can enter lungs and cause damage.

Chronic Toxicity**Target Organ Effects**

Causes damage to organs through prolonged or repeated exposure if inhaled.

Aggravated Medical Conditions

Central nervous system, Respiratory system, Skin, Eyes.

Component Information

Neurological disorders, Skin disorders, Respiratory disorders.

Acute Toxicity

Component	Oral LD50	Dermal LD50	Inhalation LC50	Draize Test	Other
White mineral oil, solvent refined 8042-47-5	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	no data available	no data available	no data available
Heptane (n-) 142-82-5	no data available	= 3000 mg/kg (Rabbit)	= 103 g/m ³ (Rat) 4 h	no data available	no data available
Calcium carbonate 471-34-1	= 6450 mg/kg (Rat)	no data available	no data available	no data available	no data available
Isobutane 75-28-5	no data available	no data available	= 658 mg/L (Rat) 4 h	no data available	no data available
Propane 74-98-6	no data available	no data available	= 658 mg/L (Rat) 4 h	no data available	no data available
Zinc oxide 1314-13-2	> 5000 mg/kg (Rat)	no data available	no data available	no data available	no data available

Component	Mutagenicity	Sensitization	Developmental Toxicity	Reproductive Toxicity	Target Organ Effects
White mineral oil, solvent refined 8042-47-5	no data available	no data available	no data available	no data available	Skin Eyes Respiratory system
Heptane (n-) 142-82-5	no data available	no data available	no data available	no data available	Skin Central nervous system Respiratory system
Calcium carbonate 471-34-1	no data available	no data available	no data available	no data available	Skin Eyes Respiratory system
Isobutane 75-28-5	no data available	no data available	no data available	no data available	Central nervous system
Propane 74-98-6	no data available	no data available	no data available	no data available	Central nervous system
Zinc oxide 1314-13-2	no data available	no data available	no data available	no data available	Respiratory system

Carcinogenicity

There are no known carcinogenic chemicals in this product.

12. ECOLOGICAL INFORMATION

Product Information

No information available.

Component Information

Component	Toxicity to Algae	Toxicity to Fish	Microtox	Crustacea	log Pow
White mineral oil, solvent refined	No information available.	LC50 > 10000 mg/L Lepomis macrochirus 96 h	No information available	No information available.	6.006
Heptane (n-)	No information available.	LC50 = 375.0 mg/L Cichlid fish 96 h	No information available	No information available.	4.66
Isobutane	No information available.	No information available.	No information available	No information available.	2.88
Propane	No information available.	No information available.	No information available	No information available.	2.3

Persistence and Degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

13. DISPOSAL CONSIDERATIONS

Product Disposal

Dispose of in accordance with local regulations.

Container Disposal

Contents under pressure. Do not puncture. Empty remaining contents. Empty containers should be taken for local recycling, recovery, or waste disposal.

14. TRANSPORT INFORMATION

DOT**Proper Shipping Name**

Consumer commodity

Hazard Class

ORM-D

Description Consumer commodity ,ORM-D,

TDG

Proper shipping name Aerosols
Hazard Class 2.1
UN-No UN1950
Description AEROSOLS,2.1,UN1950 LTD. QTY.

ICAO

UN-No DO NOT SHIP AIR

IATA

UN-No DO NOT SHIP AIR

IMDG/IMO

Proper Shipping Name Aerosols
Hazard Class 2.1
UN-No UN1950
EmS No. F-D, S-U
Description UN1950, Aerosols,2.1 LIMITED QUANTITIES

15. REGULATORY INFORMATION

Inventories

TSCA Complies
DSL Complies

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Component	CAS No.	Weight % *	SARA 313 - Threshold Values
Zinc oxide	1314-13-2	3-7	1.0

SARA 311/312 Hazardous Categorization

Acute Health Hazard	Chronic Health Hazard	Fire Hazard	Sudden Release of Pressure Hazard	Reactive Hazard
Yes	No	Yes	Yes	No

CERCLA

16. OTHER INFORMATION

Prepared By Samantha Purvis
Supersedes Date 09/27/2013
Issuing Date 04/05/2016
Reason for Revision No information available.
Glossary No information available.
List of References. No information available.

CHEMSEARCH DIV. OF NCH CORP. assumes no responsibility for personal injury or property damage caused by the use, storage, or disposal of the product in a manner not recommended on the product label. Users assume all risks associated with such unrecommended use, storage or disposal of the product. The information provided on this document is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.