

REVISION DATE 15/01/2013

## MATERIAL SAFETY DATA SHEET

### TOKUYAMA M-Bond Primer B

#### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME	TOKUYAMA M-Bond Primer B		
PRODUCT USE	Dental Cement, a component of kit. For dental professionals only.		
SUPPLIER	Tokuyama Dental America Inc. Tel: (877) 378 3548 (Toll-Free)	MANUFACTURER	Tokuyama Dental Corporation 38-9, Taitou 1-chome, Taitou-ku, Tokyo, Japan TEL: +81-3-3835-7201
CONTACT PERSON	<a href="http://www.tokuyama-dental.com/contact.htm">http://www.tokuyama-dental.com/contact.htm</a>		
EMERGENCY TELEPHONE	<p>Washington National Capital Poison Center 3201 New Mexico Avenue, Suite 310 Washington, DC 20016 Telephone: +1 202 362 3867 Emergency telephone: 1 800 222 1222 Fax: +1 202 362 8377 E-mail: <a href="mailto:pc@poison.org">pc@poison.org</a> Web site: <a href="http://www.poison.org">http://www.poison.org</a></p> <p>San Francisco California Poison Control System at San Francisco General Hospital University of California San Francisco, Box 1369 1001 Potrero Avenue, Bldg 5 Rm 2A21 San Francisco, California 94143-1369 Telephone: +1 415 643 3200 Emergency telephone: 1 800 222 1222 Fax: +1 415 502 6010 E-mail: <a href="mailto:coadmin@calpoison.org">coadmin@calpoison.org</a> Web site: <a href="http://www.calpoison.org">http://www.calpoison.org</a></p> <p><a href="http://www.who.int/ipcs/poisons/centre/en/">http://www.who.int/ipcs/poisons/centre/en/</a></p>		

#### 2 HAZARDS IDENTIFICATION

#### POTENTIAL HEALTH EFFECTS

##### INHALATION

Irritating to respiratory system. Vapors may cause drowsiness and dizziness.

##### INGESTION

Slightly irritating. : DIGESTIVE SYSTEM.

##### SKIN CONTACT

Slightly irritating. Product has a defatting effect on skin. Prolonged and frequent contact may cause redness and irritation.

##### EYE CONTACT

Irritating and may cause redness and pain.

#### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content %
ACETONE	200-662-2	67-64-1	30-60%
Water	231-791-2	7732-18-5	30-60%

#### 4 FIRST-AID MEASURES

##### GENERAL INFORMATION

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

##### INHALATION

Move the exposed person to fresh air at once.

REVISION DATE 15/01/2013

**TOKUYAMA M-Bond Primer B****INGESTION**

Immediately rinse mouth and drink plenty of water (200-300 ml). Get medical attention if any discomfort continues.

**SKIN CONTACT**

Wash the skin immediately with soap and water.

**EYE CONTACT**

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Contact physician if irritation persists.

**5 FIRE-FIGHTING MEASURES****EXTINGUISHING MEDIA**

Fire can be extinguished using: Foam. Carbon dioxide or dry powder.

**SPECIAL FIRE FIGHTING PROCEDURES**

Avoid breathing fire vapors.

**SPECIFIC HAZARDS**

When heated and in case of fire, irritating vapours/gases may be formed.

**PROTECTIVE MEASURES IN FIRE**

Wear full protective clothing.

FLASH POINT (°C) -9.5°C

**6 ACCIDENTAL RELEASE MEASURES****PERSONAL PRECAUTIONS**

Wear protective clothing as described in Section 8 of this material safety data sheet.

**ENVIRONMENTAL PRECAUTIONS**

Do not allow to enter drains, sewers or watercourses.

**SPILL CLEAN UP METHODS**

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb in vermiculite, dry sand or earth and place into containers. Do not contaminate water sources or sewer.

**7 HANDLING AND STORAGE****HANDLING**

All handling to take place in well-ventilated area.

**STORAGE**

Store under refrigerated conditions at temperatures between 0 to 10°C (32 to 50°F). Keep away from heat, direct sunlight, sparks and open flames.

**STORAGE CLASS**

Flammable liquid storage.

**8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

COMPONENT	STD	TWA (8-hrs)		STEL (15 min)		Notes
ACETONE	PEL	1000 ppm	2400 mg/m <sup>3</sup>			
ACETONE	ACGIH	500 ppm		750 ppm		A4
COMPONENT						IDLH
ACETONE						2500 ppm

ACGIH=American Conference of Governmental Industrial Hygienists.

A4: Not Classifiable as a Human Carcinogen.

**PROTECTIVE EQUIPMENT**

REVISION DATE 15/01/2013

**TOKUYAMA M-Bond Primer B****ENGINEERING MEASURES**

Provide adequate general and local exhaust ventilation.

**HAND PROTECTION**

Wear protective gloves.

**EYE PROTECTION**

Wear approved safety goggles.

**OTHER PROTECTION**

Wear appropriate clothing to prevent any possibility of skin contact.

**HYGIENE MEASURES**

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap & water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

**9 PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE	Clear liquid
COLOR	Colorless
ODOR	Characteristic
pH-VALUE, CONC. SOLUTION	7
FLASH POINT (°C)	-9.5°C

**10 STABILITY AND REACTIVITY****STABILITY**

HIGHLY FLAMMABLE!

**CONDITIONS TO AVOID**

Keep away from heat, sparks and open flame. Protect against direct sunlight.

**MATERIALS TO AVOID**

Strong oxidizing agents.

**HAZARDOUS DECOMPOSITION PRODUCTS**

Toxic gases are generated when heated.

**11 TOXICOLOGICAL INFORMATION****TOXICOLOGICAL INFORMATION**

No data on possible toxic effects have been found.

**12 ECOLOGICAL INFORMATION****ECOTOXICITY**

No data on possible environmental effects have been found.

**13 DISPOSAL CONSIDERATIONS****DISPOSAL METHODS**

Dispose of waste and residues in accordance with local authority requirements.

**14 TRANSPORT INFORMATION**

DOT PROPER SHIPPING NAME	ADHESIVES, CONTAINING A FLAMMABLE LIQUID
TDG SHIPPING NAME	ADHESIVES, CONTAINING A FLAMMABLE LIQUID
IDENTIFICATION No.	1133

REVISION DATE 15/01/2013

**TOKUYAMA M-Bond Primer B**

TUNNEL RESTRICTION CODE	(D/E)
CEPIC TEC(R) NO.	30GF1-I+II, 30GF1-sp
DOT HAZARD CLASS	3
DOT PACKING GROUP	II
U.S DOT HAZARD LABEL	Flammable Liquid
UN NO. SEA	1133
IMDG CLASS	3
IMDG PACK GR.	II
EMS	F-E, S-D
UN NO. AIR	1133
ICAO CLASS	3
AIR PACK GR.	II
TDG CLASS	3
TDG LABEL(S)	3
TDG PACKING GROUP	II

**15 REGULATORY INFORMATION**

## INVENTORIES

COMPONENT	CAN	US	EU	AUS	JAP	KOR	CHN	PHLP
ACETONE	DSL	Yes.						
Water	No.	No.	EINECS					

COMPONENT	TSCA 12(b) Export Notification
ACETONE	Yes.
Water	No.

## US FEDERAL REGULATIONS

COMPONENT	SARA 302-TPQ	CERCLA-RQ	SARA 313
ACETONE	Not Listed	5 000 lbs	No.

## CLEAN AIR ACT

COMPONENT	CAA Accidental Release Prevention
ACETONE	Not Listed

## US STATE REGULATIONS

COMPONENT	CAS	CA	FL	MA	MN	NJ	PA	RI
ACETONE	67-64-1	Not Listed	Yes.	Yes.	Yes.	Yes.	Yes.	Yes.

## REGULATORY REFERENCES

29 CFR 1910. 1200(g) Federal Regulations (OSHA Standard).

**16 OTHER INFORMATION**

REVISION DATE

15/01/2013

## DISCLAIMER

The information which is contained in this document is based on available data. However, as such has been obtained from various sources, including independent laboratories, it is given without warranty or representation that is complete, accurate and can be relied upon. Tokuyama Dental Corp. has not attempted to conceal in any way the deleterious aspects of the product listed herein, but makes no warranty as to such.