

---

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

---

### 1.1 Product identifier

**Product name** TWO COMPONENT MIXTURE (H<sub>2</sub>S, BALANCE ARGON)  
**Synonym(s)** 2496 - SDS NUMBER • SPECIAL GAS MIXTURE

### 1.2 Uses and uses advised against

**Use(s)** CALIBRATION • INDUSTRIAL APPLICATIONS

### 1.3 Details of the supplier of the product

**Supplier name** BOC LIMITED (AUSTRALIA)  
**Address** 10 Julius Avenue, North Ryde, NSW, 2113, AUSTRALIA  
**Telephone** 131 262, (02) 8874 4400  
**Fax** 132 427 (24 hours)  
**Website** <http://www.boc.com.au>

### 1.4 Emergency telephone number(s)

**Emergency** 1800 653 572 (24/7) (Australia only)

---

## 2. HAZARDS IDENTIFICATION

---

### 2.1 Classification of the substance or mixture


CLASSIFIED AS HAZARDOUS ACCORDING TO AUSTRALIAN WHS REGULATIONS

**GHS classification(s)** Aquatic Toxicity (Acute): Category 1  
Gases Under Pressure: Compressed gas  
Flammable Gases: Category 1  
Acute Toxicity: Inhalation: Category 4

### 2.2 Label elements

**Signal word** DANGER

**Pictogram(s)**



**Hazard statement(s)**

H220 Extremely flammable gas.  
H280 Contains gas under pressure; may explode if heated.  
H332 Harmful if inhaled.  
H400 Very toxic to aquatic life.

**Prevention statement(s)**

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P271 Use only outdoors or in a well-ventilated area.  
P273 Avoid release to the environment.

**PRODUCT NAME TWO COMPONENT MIXTURE (H2S, BALANCE ARGON)****Response statement(s)**

P304 + P340 IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.  
P312 Call a POISON CENTER or doctor/physician if you feel unwell.  
P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.  
P381 Eliminate all ignition sources if safe to do so.  
P391 Collect spillage.

**Storage statement(s)**

P410 + P403 Protect from sunlight. Store in a well-ventilated place.

**Disposal statement(s)**

P501 Dispose of contents/container in accordance with relevant regulations.

**2.3 Other hazards**

Asphyxiant. Effects are proportional to oxygen displacement.

---

**3. COMPOSITION/ INFORMATION ON INGREDIENTS**

---

**3.1 Substances / Mixtures**

Ingredient	CAS Number	EC Number	Content (v/v)
HYDROGEN SULPHIDE	7783-06-4	231-977-3	5%
ARGON	7440-37-1	231-147-0	Remainder

---

**4. FIRST AID MEASURES**

---

**4.1 Description of first aid measures**

**Eye** If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.

**Inhalation** If inhaled, remove from contaminated area. To protect rescuer, use an Air-line respirator or Self Contained Breathing Apparatus (SCBA). Apply artificial respiration if not breathing. Give oxygen if breathing is difficult. Seek immediate medical attention. For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor.

**Skin** If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water.

**Ingestion** Due to product form and application, ingestion is considered unlikely.

**First aid facilities** No information provided.

**4.2 Most important symptoms and effects, both acute and delayed**

In high concentrations may cause asphyxiation. Symptoms may include loss of mobility / consciousness. Victim may not be aware of asphyxiation. Inhalation of high levels of hydrogen sulphide may be fatal. Chronic exposure may result in nerve paralysis/damage, heart damage and neurological effects.

**4.3 Immediate medical attention and special treatment needed**

If inhalation has occurred observe for premonitory signs of pulmonary oedema. Otherwise, treatment is symptomatic and supportive.

---

**5. FIRE FIGHTING MEASURES**

---

**5.1 Extinguishing media**

Stop flow of gas if safe to do so, such as by slowly closing the cylinder valve.

**5.2 Special hazards arising from the substance or mixture**

Extremely flammable. May evolve toxic gases (carbon/ sulphur oxides, sulphides, hydrocarbons) when heated to decomposition. Eliminate all ignition sources including cigarettes, open flames, spark producing switches/tools, heaters, naked lights, pilot lights, mobile phones etc. when handling.

**5.3 Advice for firefighters**

Temperatures in a fire may cause cylinders to rupture and internal pressure relief devices to be activated. Cool cylinders or containers exposed to fire by applying water from a protected location. Do not approach cylinders or containers suspected of being hot. This material is capable of forming explosive mixtures in air.

## PRODUCT NAME TWO COMPONENT MIXTURE (H2S, BALANCE ARGON)

### 5.4 Hazchem code

2SE  
2 Fine Water Spray.  
S Risk of violent reaction or explosion. Wear full fire kit and breathing apparatus. Dilute spill and run-off.  
E Evacuation of people in and around the immediate vicinity of the incident should be considered.

## 6. ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

If the cylinder is leaking, evacuate area of personnel. Inform manufacturer/supplier of leak. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Ensure adequate air ventilation. Eliminate all sources of ignition. Consider the risk of potentially explosive atmospheres.

### 6.2 Environmental precautions

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

### 6.3 Methods of cleaning up

Carefully move material to a well ventilated remote area, then allow to discharge if safe to do so. Do not attempt to repair leaking valve or cylinder safety devices.

### 6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

## 7. HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Do not drag, drop, slide or roll cylinders. The uncontrolled release of a gas under pressure may cause physical harm. Use a suitable hand truck for cylinder movement.

### 7.2 Conditions for safe storage, including any incompatibilities

Do not store near incompatible substances and sources of ignition. Replace outlet seals after use. Cylinders should be stored: upright, prevented from falling, in a secure area; below 45°C, in a dry, well ventilated area constructed of non-combustible material with firm level floor (preferably concrete), away from areas of heavy traffic and emergency exits.

### 7.3 Specific end use(s)

No information provided.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1 Control parameters

#### Exposure standards

Ingredient	Reference	TWA		STEL	
		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Argon	SWA (AUS)	Asphyxiant			
Hydrogen sulfide	SWA (AUS)	10	14	15	21

### Biological limits

No biological limit values have been entered for this product.

### 8.2 Exposure controls

#### Engineering controls

Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical explosion proof extraction ventilation is recommended. Flammable or explosive vapours may accumulate in confined or poorly ventilated areas. Vapours may travel some distance to an ignition source and flash back. Maintain atmospheric levels below the recommended exposure standard.

**PRODUCT NAME TWO COMPONENT MIXTURE (H2S, BALANCE ARGON)**

**PPE**

<b>Eye / Face</b>	Wear safety glasses.
<b>Hands</b>	Wear rubber gloves.
<b>Body</b>	Wear safety boots.
<b>Respiratory</b>	Wear Self Contained Breathing Apparatus (SCBA) or an Air-line respirator.



---

**9. PHYSICAL AND CHEMICAL PROPERTIES**

---

**9.1 Information on basic physical and chemical properties**

<b>Appearance</b>	COLOURLESS GAS OR LIQUID
<b>Odour</b>	ROTTEN EGG ODOUR
<b>Flammability</b>	EXTREMELY FLAMMABLE
<b>Flash point</b>	-82°C (Hydrogen sulphide)
<b>Boiling point</b>	-60.3°C (Hydrogen sulphide)
<b>Melting point</b>	NOT AVAILABLE
<b>Evaporation rate</b>	NOT APPLICABLE
<b>pH</b>	NOT APPLICABLE
<b>Vapour density</b>	1.2 (Air =1) (Hydrogen sulphide)
<b>Specific gravity</b>	NOT APPLICABLE
<b>Solubility (water)</b>	2.3 L/L (Hydrogen sulphide)
<b>Vapour pressure</b>	NOT AVAILABLE
<b>Upper explosion limit</b>	45 % (Hydrogen sulphide)
<b>Lower explosion limit</b>	2.7 % (Hydrogen sulphide)
<b>Partition coefficient</b>	NOT AVAILABLE
<b>Autoignition temperature</b>	NOT AVAILABLE
<b>Decomposition temperature</b>	NOT AVAILABLE
<b>Viscosity</b>	NOT AVAILABLE
<b>Explosive properties</b>	NOT AVAILABLE
<b>Oxidising properties</b>	NOT AVAILABLE
<b>Odour threshold</b>	NOT AVAILABLE

**9.2 Other information**

<b>Critical temperature</b>	100.4°C (Hydrogen sulphide)
<b>Critical pressure</b>	9,010 kPa (Hydrogen sulphide)
<b>% Volatiles</b>	100 %

---

**10. STABILITY AND REACTIVITY**

---

**10.1 Reactivity**

Carefully review all information provided in sections 10.2 to 10.6.

**10.2 Chemical stability**

Stable under recommended conditions of storage.

**10.3 Possibility of hazardous reactions**

Polymerization will not occur.

**10.4 Conditions to avoid**

Avoid heat, sparks, open flames and other ignition sources.

**10.5 Incompatible materials**

Incompatible with oxidising agents (e.g. hypochlorites), metals, metal oxides, nitrogen trichloride, alkalis (e.g. sodium hydroxide), heat and ignition sources.

**10.6 Hazardous decomposition products**

May evolve toxic gases (carbon/ sulphur oxides, sulphides, hydrocarbons) when heated to decomposition.

## 11. TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects

<b>Acute toxicity</b>	Harmful if inhaled. Exposure may cause irritation to respiratory tract, runny nose, cough, hoarseness, shortness of breath and pneumonia, followed by severe irritation, headache, nausea, vomiting and dizziness. Severe exposure may result in pulmonary oedema.
	HYDROGEN SULPHIDE LC50 (Inhalation): 444 ppm / 4 hours (rat)
<b>Skin</b>	Not classified as a skin irritant.
<b>Eye</b>	Not classified as an eye irritant. However, contact may result in mild irritation, lacrimation, pain and redness.
<b>Sensitization</b>	Not classified as causing skin or respiratory sensitisation.
<b>Mutagenicity</b>	Not classified as a mutagen.
<b>Carcinogenicity</b>	Not classified as a carcinogen.
<b>Reproductive</b>	Not classified as a reproductive toxin.
<b>STOT – single exposure</b>	Over exposure may result in central nervous system and respiratory system effects. Symptoms include headaches, dizziness, unconsciousness and build-up of fluid in the lungs (pulmonary oedema).
<b>STOT – repeated exposure</b>	Long-term exposure to low concentrations damages the respiratory and central nervous system. Symptoms include pulmonary irritation, headaches, dizziness, muscular fatigue, weakness and occasional, transient tremors.
<b>Aspiration</b>	Not classified as causing aspiration.

## 12. ECOLOGICAL INFORMATION

### 12.1 Toxicity

Very toxic to aquatic organisms.

### 12.2 Persistence and degradability

No information provided.

### 12.3 Bioaccumulative potential

No information provided.

### 12.4 Mobility in soil

No information provided.

### 12.5 Other adverse effects

Microorganisms in soil and water are involved in oxidation-reduction reactions which oxidise hydrogen sulphide to elemental sulphur. Not anticipated to bioaccumulate or concentrate in the food chain.

## 13. DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods

<b>Waste disposal</b>	Return to manufacturer/supplier where possible for recycling/ reuse. Contact Waste Disposal Authorities in your State for further details and required approvals.
<b>Legislation</b>	Dispose of in accordance with relevant local legislation.

## 14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



**PRODUCT NAME TWO COMPONENT MIXTURE (H2S, BALANCE ARGON)**

	<b>LAND TRANSPORT (ADG)</b>	<b>SEA TRANSPORT (IMDG / IMO)</b>	<b>AIR TRANSPORT (IATA / ICAO)</b>
<b>14.1 UN Number</b>	1954	1954	1954
<b>14.2 Proper Shipping Name</b>	COMPRESSED GAS, FLAMMABLE, N.O.S. (contains hydrogen sulphide)	COMPRESSED GAS, FLAMMABLE, N.O.S. (contains hydrogen sulphide)	COMPRESSED GAS, FLAMMABLE, N.O.S. (contains hydrogen sulphide)
<b>14.3 Transport hazard class</b>	2.1	2.1	2.1
<b>14.4 Packing Group</b>	None Allocated	None Allocated	None Allocated

**14.5 Environmental hazards** No information provided

**14.6 Special precautions for user**

**Hazchem code** 2SE  
**GTEPG** 2A1  
**EMS** F-D, S-U

**Other information** Ensure cylinder is separated from driver and foodstuffs. Refer to Commonwealth, State and Territory Dangerous Goods Legislation which contain requirements which affect gas storage and transport.

**15. REGULATORY INFORMATION****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Poison schedule** Classified as a Schedule 7 (S7) Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

**Classifications** Safework Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals.  
The classifications and phrases listed below are based on the Approved Criteria for Classifying Hazardous Substances [NOHSC: 1008(2004)].

**Hazard codes** F+ Extremely flammable  
N Dangerous for the environment  
Xn Harmful

**Risk phrases** R12 Extremely Flammable.  
R20 Harmful by inhalation.  
R50 Very toxic to aquatic organisms.

**Safety phrases** S1/2 Keep locked up and out of reach of children.  
S9 Keep container in a well ventilated place.  
S16 Keep away from sources of ignition - No smoking.  
S36 Wear suitable protective clothing.  
S38 In case of insufficient ventilation, wear suitable respiratory equipment.  
S45 In case of accident or if you feel unwell seek medical advice immediately (show the label where possible).  
S61 Avoid release to the environment. Refer to special instructions/safety data sheets.

**Inventory listing(s)** **AUSTRALIA: AICS (Australian Inventory of Chemical Substances)**  
All components are listed on AICS, or are exempt.

**16. OTHER INFORMATION**

**Additional information** The storage of significant quantities of gas cylinders must comply with AS4332 The storage and handling of gases in cylinders.

APPLICATION METHOD: Gas withdrawal: Gas regulator of suitable pressure and flow rating fitted to cylinder or manifold with low pressure gas distribution to equipment.

**PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:**

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

**PRODUCT NAME TWO COMPONENT MIXTURE (H2S, BALANCE ARGON)**

**HEALTH EFFECTS FROM EXPOSURE:**

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a ChemAlert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

**Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists
CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
CNS	Central Nervous System
EC No.	EC No - European Community Number
EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
GHS	Globally Harmonized System
GTEPG	Group Text Emergency Procedure Guide
IARC	International Agency for Research on Cancer
LC50	Lethal Concentration, 50% / Median Lethal Concentration
LD50	Lethal Dose, 50% / Median Lethal Dose
mg/m <sup>3</sup>	Milligrams per Cubic Metre
OEL	Occupational Exposure Limit
pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
ppm	Parts Per Million
STEL	Short-Term Exposure Limit
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
SWA	Safe Work Australia
TLV	Threshold Limit Value
TWA	Time Weighted Average

**Report status**

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

**Prepared by**

Risk Management Technologies  
5 Ventnor Ave, West Perth  
Western Australia 6005  
Phone: +61 8 9322 1711  
Fax: +61 8 9322 1794  
Email: info@rmt.com.au  
Web: www.rmt.com.au.

**[ End of SDS ]**