

Material Safety Data Sheet

Trifluoroacetic Acid in Acetonitrile Blend



1 . Product and company identification

Product name	: Trifluoroacetic Acid in Acetonitrile Blend
Product code	: TX1277P
Supplier	: EMD Chemicals Inc. 480 S. Democrat Rd. Gibbstown, NJ 08027 856-423-6300 Technical Service Monday-Friday: 8:00 -5:00 PM
Synonym	: None.
Material uses	: Other non-specified industry: Analytical reagent.
Validation date	: 8/26/2009.
In case of emergency	: 800-424-9300 CHEMTRAC (USA) 613-996-6666 CANUTEC (Canada) 24 Hours/Day: 7 Days/Week

2 . Hazards identification

Emergency overview	: DANGER! POISON! HARMFUL IF INHALED, ABSORBED THROUGH SKIN OR SWALLOWED. CAUSES EYE IRRITATION. FLAMMABLE LIQUID AND VAPOR. VAPOR MAY CAUSE FLASH FIRE. MAY CAUSE RESPIRATORY TRACT AND SKIN IRRITATION. CONTAINS MATERIAL WHICH MAY CAUSE DAMAGE TO THE FOLLOWING ORGANS: KIDNEYS, LIVER, CARDIOVASCULAR SYSTEM, RESPIRATORY TRACT, SKIN, CENTRAL NERVOUS SYSTEM, EYE, LENS OR CORNEA. BREATHING HIGH VAPOR CONCENTRATIONS MAY CAUSE CYANIDE POISONING. Keep away from heat, sparks and flame. Do not breathe vapor or mist. Do not ingest. Do not get in eyes or on skin or clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.
Physical state	: Liquid.
OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Potential acute health effects	
Inhalation	: Toxic by inhalation. May cause respiratory irritation. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
Ingestion	: Toxic if swallowed.
Skin	: Toxic in contact with skin. May cause skin irritation.
Eyes	: Irritating to eyes.
Potential chronic health effects	
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.
Target organs	: Contains material which may cause damage to the following organs: kidneys, liver, cardiovascular system, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.
Medical conditions aggravated by over- exposure	: Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

2 . Hazards identification

See toxicological information (section 11)

3 . Composition/information on ingredients

Name	CAS number	% by weight
Acetonitrile	75-05-8	99.8
Trifluoroacetic Acid	76-05-1	0.2

4 . First aid measures

- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.
- Skin contact** : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.
- Inhalation** : Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.
- Ingestion** : Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

5 . Fire-fighting measures

- Flammability of the product** : Flammable liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.
- Extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Not suitable** : Do not use water jet.
- Special exposure hazards** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6 . Accidental release measures

- Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for cleaning up

6 . Accidental release measures

Spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container.

7 . Handling and storage

Handling

: Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Storage

: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container, protected from direct sunlight. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

8 . Exposure controls/personal protection

Ingredient	Exposure limits
Acetonitrile	<p>ACGIH (United States, 1996). STEL: 101 mg/m³ TWA: 67 mg/m³</p> <p>OSHA (United States, 1989). STEL: 105 mg/m³ TWA: 70 mg/m³</p> <p>ACGIH TLV (United States, 1/2008). Absorbed through skin. TWA: 20 ppm 8 hour(s).</p> <p>OSHA PEL 1989 (United States, 3/1989). TWA: 40 ppm 8 hour(s). TWA: 70 mg/m³ 8 hour(s). STEL: 60 ppm 15 minute(s). STEL: 105 mg/m³ 15 minute(s).</p> <p>NIOSH REL (United States, 6/2008). TWA: 20 ppm 10 hour(s). TWA: 34 mg/m³ 10 hour(s).</p> <p>OSHA PEL (United States, 11/2006). TWA: 40 ppm 8 hour(s). TWA: 70 mg/m³ 8 hour(s).</p>

Consult local authorities for acceptable exposure limits.

Engineering measures

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

8 . Exposure controls/personal protection

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Personal protection	
Respiratory	: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Hands	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Recommended: nitrile rubber
Eyes	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. Recommended: splash goggles
Skin	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: lab coat
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9 . Physical and chemical properties

Physical state	: Liquid.
Flash point	: Closed cup: 13.333°C (56°F)
Odor	: Not available.
pH	: Not available.
Boiling/condensation point	: Not available.
Melting/freezing point	: Not available.
Relative density	: Not available.
Vapor pressure	: Not available.
Vapor density	: Not available.
Odor threshold	: Not available.
Evaporation rate	: Not available.

10 . Stability and reactivity

Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Hazardous polymerization	: Under normal conditions of storage and use, hazardous polymerization will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Materials to avoid	: Highly reactive or incompatible with the following materials: oxidizing materials, reducing materials, acids and alkalis.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Conditions of reactivity	: Highly flammable in the presence of the following materials or conditions: open flames, sparks and static discharge, heat, shocks and mechanical impacts and oxidizing materials.

10 . Stability and reactivity

Highly explosive in the presence of the following materials or conditions: open flames, sparks and static discharge, heat, shocks and mechanical impacts and oxidizing materials.

11 . Toxicological information

Acute toxicity

Product/ingredient name	Test	Route	Species	Result
Acetonitrile	LD50	Dermal	Rabbit	980 mg/kg
	LD50		Rat	850 mg/kg
		Intraperitoneal		
	LD50	Intravenous	Rat	1680 mg/kg
	LD50	Oral	Rat	2460 mg/kg
	LD50	Oral	Guinea pig	177 mg/kg
	LD50	Oral	Rabbit	50 mg/kg
	LD50	Parenteral	Rat	1100 mg/kg
	LD50		Rat	1900 mg/kg
		Subcutaneous		
	TDLo		Rat	1520 mg/kg
		Subcutaneous		
	LC50	Inhalation Gas.	Rat	17100 ppm
	LC50	Inhalation Gas.	Rat	7551 ppm

Carcinogenicity

Classification

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
Acetonitrile	A4	-	-	None.	-	-

No known significant effects or critical hazards.

Mutagenicity

No known significant effects or critical hazards.

Teratogenicity

No known significant effects or critical hazards.

12 . Ecological information

Aquatic ecotoxicity

Product/ingredient name	Result	Species	Exposure
Acetonitrile	Acute LC50 1640 mg/L	Fish	96 hours
	Acute LC50 >100 mg/L	Daphnia	96 hours
	Acute LC50 >100 mg/L	Fish	96 hours
	Acute LC50 1640000 to 1690000 ug/L Fresh water	Fish - Fathead minnow - Pimephales promelas - 26 to 31 days - 21.1 mm - 0.165 g	96 hours
	Acute LC50 1000000 ug/L Fresh water	Fish - Fathead minnow - Pimephales promelas - 5.1 to 6.4 cm - 1.5 g	96 hours
	Acute LC50 >100000 ug/L Fresh water	Fish - Fathead minnow - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling) - 0.2 to 0.5 g	96 hours
	Acute LC50 3600000 ug/L Fresh water	Daphnia - Water flea - Daphnia magna - <24 hours	48 hours
	Acute LC50 1850000 ug/L Fresh water	Fish - Bluegill - Lepomis macrochirus - 3.8 to 5.1 cm - 2 g	96 hours
	Acute LC50 1650000 ug/L	Fish - Guppy - Poecilia	96 hours

15 . Regulatory information

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

Connecticut Carcinogen Reporting	: None of the components are listed.
Connecticut Hazardous Material Survey	: None of the components are listed.
Florida substances	: None of the components are listed.
Illinois Chemical Safety Act	: None of the components are listed.
Illinois Toxic Substances Disclosure to Employee Act	: None of the components are listed.
Louisiana Spill	: None of the components are listed.
Louisiana Reporting	: None of the components are listed.
Massachusetts Spill	: None of the components are listed.
Massachusetts Substances	: The following components are listed: Acetonitrile
Minnesota Hazardous Substances	: None of the components are listed.
Michigan Critical Material	: None of the components are listed.
New Jersey Toxic Catastrophe Prevention Act	: None of the components are listed.
New Jersey Spill	: None of the components are listed.
New Jersey Hazardous Substances	: The following components are listed: Acetonitrile
New York Toxic Chemical Release Reporting	: None of the components are listed.
New York Acutely Hazardous Substances	: The following components are listed: Acetonitrile
Pennsylvania RTK Hazardous Substances	: The following components are listed: Acetonitrile
Rhode Island Hazardous Substances	: None of the components are listed.
Canada	
WHMIS (Canada)	: Class B-2: Flammable liquid Class D-1A: Material causing immediate and serious toxic effects (Very toxic). Class D-2B: Material causing other toxic effects (Toxic).
Canadian lists	: CEPA Toxic substances: None of the components are listed. Canadian ARET: None of the components are listed. Canadian NPRI: The following components are listed: Acetonitrile Alberta Designated Substances: None of the components are listed. Ontario Designated Substances: None of the components are listed. Quebec Designated Substances: None of the components are listed.
CEPA DSL / CEPA NDSL	: All components are listed or exempted.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

EU regulations

Hazard symbol or symbols	:	 
---------------------------------	---	---

15 . Regulatory information


- Risk phrases** : R11- Highly flammable.
R20/21/22- Harmful by inhalation, in contact with skin and if swallowed.
R36- Irritating to eyes.
- Safety phrases** : S2- Keep out of the reach of children.
S36/37- Wear suitable protective clothing and gloves.
S46- If swallowed, seek medical advice immediately and show this container or label.

International regulations

- International lists** : **Australia inventory (AICS)**: All components are listed or exempted.
China inventory (IECSC): All components are listed or exempted.
Japan inventory (ENCS): All components are listed or exempted.
Japan inventory (ISHL): Not determined.
Korea inventory (KECI): All components are listed or exempted.
New Zealand Inventory of Chemicals (NZIoC): Not determined.
Philippines inventory (PICCS): All components are listed or exempted.

16 . Other information

National Fire Protection Association (U.S.A.) :



Notice to reader

The statements contained herein are based upon technical data that EMD Chemicals Inc. believes to be reliable, are offered for information purposes only and as a guide to the appropriate precautionary and emergency handling of the material by a properly trained person having the necessary technical skills. Users should consider these data only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use, storage and disposal of these materials and the safety and health of employees and customers and the protection of the environment. EMD CHEMICALS INC. MAKES NO REPRESENTATION OR WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE, WITH RESPECT TO THE INFORMATION HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS.