THINNER 3A Version Number: 3

# SAFETY DATA SHEET

## SECTION 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: THINNER 3A

Other Names:

Recommended Use: Paint thinner

Company Name: Resene Paints Limited New Zealand Address: 32-50 Vogel Street, Naenae, Wellington, NEW ZEALAND

P O Box 38242, Wellington Mail Centre

**Phone:** (04) 577 0500 Fax: (04) 577 0600

Resene Paints Limited Australia Address 7 Production Avenue, Molendinar, Queensland 4214

P O Box 785, Ashmore City, Queensland 4214

AUSTRALIA

Phone 1800 738 383

**Emergency Telephone:** 

New Zealand 0800 737 363 Available Monday - Friday 8.00am - 4.30pm

New Zealand Poisons Centre: 0800 764 766

Australia 1800 738 383

**Australian Poisons Centre: 131 126** 

SECTION 2. HAZARDS IDENTIFICATION

Hazard Classificaton HAZARDOUS according to NZ HSNO Regulations

Regulated under NZS5433 for land transportation

Risk Phrases Safety Phrases

Substance Classification 3.1B 6.1D 6.3A 6.4A 6.8B 6.9B 9.1D 9.3C

Hazard Statements Highly flammable liquid and vapour

Harmful if swallowed Causes skin irritation Causes eye irritation

Suspected of damaging fertility or the unborn child.

May cause damage to organs through prolonged or repeated

exposure.

May cause long lasting harmful effects to aquatic life

Harmful to terrestrial vertebrates

# SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

| Ingredients            | %     | CAS No    | TWA                   |                   |
|------------------------|-------|-----------|-----------------------|-------------------|
| Dimethylbenzene        | 30-60 | 1330-20-7 | 217 mg/m <sup>3</sup> | NZ OSH (WES) 2002 |
| Methyl Isobutyl Ketone | 30-60 | 108-10-1  | 205 mg/m <sup>3</sup> | NZ OSH (WES) 2002 |
| isopropanol            | 30-60 | 67-63-0   | 983 mg/m <sup>3</sup> | NZ OSH (WES) 1994 |

#### SECTION 4. FIRST AID MEASURES

**Eyes** Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so.

Continue rinsing. If eye irritation persists get medical attention/advice.

Swallowed: Call a POISON CENTRE (NZ 0800 764766) or Australia (131 126) or doctor/physician if you feel

ınwell.

Skin IF ON SKIN: Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF skin irritation occurs: Get medical advice/attention.

Inhaled

Aggravated medical conditions caused by exposure

**Chronic Health Effects** 

### SECTION 5. FIRE FIGHTING MEASURES

**Extinguisher** Foam, Carbon Dioxide, Dry Chemical

**Hazards from** 

combustion products

Special protective precautions and equipment for firefighters

Fire/Explosion Hazard Auto Ingnition Temperature Lower Explosion Limit Upper Explosion Limit

Hazchem Code Flash Point

3[Y]E -7°C

## SECTION 6. ACCIDENTAL RELEASE MEASURES

#### **Emergency Procedures**

Keep spectators away and avoid breathing dust or vapours

#### Methods and materials for containment and clean up

Minor Spills Clean up spills immediately.

Wear protective clothing and breathing apparatus.

Use absorbent clean up materials, such as fire retardant treated sawdust or diatomaceous earth.

Keep spills (and as much as possible cleaning runoffs) out of municipal sewers and waterways.

Sweep up.

Place in separate container for disposal or recovery.

Major Spills Restrict access to area. No smoking or naked lights.

Alert Fire Brigade and tell them location and nature of hazard.

Consider evacuation (or protect in place).

Clear area of personnel and move upwind.

Dike and contain spill with inert materials (eg. Sand).

Stop leak if safe to do so.

Keep spills (and as much as possible cleaning runoffs) out of municipal sewers and open bodies of water.

Collect recoverable product into labelled containers for recycling.

# SECTION 7. HANDLING AND STORAGE

Precautions for safe handling Avoid damaging containers. Keep lids on containers when not in use

#### Conditions for safe storage including any incompatibilities

Storage Temperatures Min 1°C Max 40°C

# SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

National exposure

No exposure standards has been established for this product

standards for mixture Component Pigments

Breathing Zone ppm Breathing Zone mg/m<sup>3</sup>

#### **Personal Protection**

**Eye:** Safety eyewear with splash guards or side shields to prevent eye contact is recommended when

using any paint.

Hands/Feet Protective clothing. Gloves of neoprene or nitrile rubber - Industrial weight lined

gauntlet recommended.

Other Overalls, impervious clothing, barrier cream, eyewash unit, skin cleansing cream.

Practice good caution and personal cleanliness to avoid skin contact. Avoid breathing vapours of

heated materials. Wash hands thoroughly before handling food.

Respirator

# SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Clear liquid

Odour pH Vapour Pressure Vapour Density Boiling Point Melt Freeze Solubility Volatile by Weigl Immiscible 100

SECTION 10. STABILITY AND ACTIVITY

THINNER 3A Page 2 of 4 Resene Paints Limited

Chemical Stability Product is considered stable under normal storage and handling conditions.

Conditions to Avoid Freezing, excessive heat and changes in temperature Incompatible Material

Hazardous decomposition product Oxides of carbon and nitrogen

Hazardous reactions Hazardous polymerisation will not occur.

#### THINNER 3A

### SECTION 11. TOXICOLOGICAL INFORMATION

No data available for this product

Refer to individual raw materials

### SECTION 12. HAZARDS IDENTIFICATION

No data available for this product

Do not allow the product to enter the environment

### SECTION 13. DISPOSAL CONSIDERATIONS

Special precautions for landfill or incineratio

Consult manufacturer for recycling options and recycle where possible

Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed

### SECTION 14. TRANSPORT INFORMATION

UN Number 1263

UN Proper

Paint related product

shipping

Subsidiary risk

Poison Schedule HAZCHEM Code 3[Y]E

Packing Group: Class 3

### Special precautions for user

## SECTION 15. REGULATORY INFORMATION

Group Standard HSR002662 Surface Coatings & Colourants (Flammable)

Approved Handler Class 3.1B required for quantities greater than 250Lt (containers greater than 5Lt

capacity) or greater than 500Lt (containers less than 5Lt capacity)

### SECTION 16. OTHER INFORMATION

Date of Preparation 1/02/2009

Literature references MSDS's for individual raw material

Abbreviations:

NOHSC National Occupational Health and Safety Commissio

TLV Time weighted averag
STEL Short term exposure limit

CAS Numbe Chemical Abstract Service registry numbe

TWA Threshold limit valu

Marine Pollutant Marine Pollutant

#### Safety data sheets are updated frequently. Please ensure that you have a current copy

The information contained herein is based on data considered accurate and reliable to the best of our knowledge and belief as of the date compiled. However no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use hereof. Resene Paints (New Zealand) Limited assumes no responsibility for personal injury or property damage to vendors, users or third parties caused by the material. Such users or vendors assume all risks associated with the use of the material. It is the users responsibility to satisfy themselves as to the suitability and completeness of the information for their own particular use. The users must determine whether the use of the information and data is in accordance with local laws and regulations.