

MATERIAL SAFETY DATA SHEET

Section 1: IDENTIFICATION

TUNG OIL SEAL

Recommended Use: Timber floor sealer. **Product Code:** 200094 (2x10L).



Whiteley Industrial

A division of Whiteley Corporation Pty Ltd (A.C.N. 000 906 678) Postal Address: P. O. Box 1076 North Sydney NSW 2059 Telephone Number: (02) 9929 9155 Facsimile: (02) 9929 9077

Web: www.whiteley.com.au

Emergency Telephone Number: Poisons Information Centre (National) 131126

Section 2: HAZARDS

Classified as hazardous by the criteria of Safe Work Australia.

R10: Flammable

R36/37/38: Irritating to eyes, respiratory system and skin. R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness or dizziness. S9: Keep container in a well ventilated place.

S16: Keep away from sources of ignition – No smoking.

S23: Do not breathe vapour.

S24/25: Avoid contact with skin and eyes.

S36/37/39: Wear suitable protective clothing, gloves and eye/face protection.

S62: If swallowed, do not induce vomiting; seek medical advice immediately and show this

container or label.

Section 3: COMPOSITION INFORMATION

IngredientCAS NoProportionIngredients deemed not to be hazardousNot applicableTo 100%Mineral turpentine64742-95-630-60%Synthetic resinNot available10-<30%</td>

Section 4: FIRST AID

Eye (Contact) Hold eyelids apart and flush the eye continuously with running water.

Continue flushing until advised to stop by the Poisons Information Centre or

a doctor, or for at least 15 minutes.

Skin (Contact) If skin or hair contact occurs, remove contaminated clothing and flush skin

and hair with running water. Continue flushing with water until advised to

Issue No. 8 Page 1 of 5

stop by the Poisons Information Centre or a doctor.

Inhalation(Breathing) If inhaled, remove from contaminated area. Apply artificial respiration if not

breathing.

Ingestion (Swallowing) DO NOT induce vomiting. For advice, contact a Poisons Information

Centre (Phone 131126) or a doctor.

Advice to Doctor Treat symptomatically for solvent based solution.

First Aid Facilities Ensure an eye bath and safety shower are available and ready for use.

Additional Information No aggravated medical conditions are known to be caused by exposure to

this product.

Section 5: FIREFIGHTING MEASURE

Suitable Extinguishing Media Use dry chemical powder, foam or CO₂ extinguishers.

Hazards From Combustion

Products

Toxic and/or irritating fumes including carbon monoxide and carbon

dioxide may be emitted.

Precautions For Fire Fighters and Special Protective

Equipment

Firefighters should wear self-contained breathing apparatus (SCBA)

and complete protective clothing.

Vapours are heavier than air and will 'travel' to low-level areas

and/or spread fires. Water may be used to cool containers.

Additional Information Hazchem Code – 3[Y]

Section 6: ACCIDENTAL RELEASE MEASURES

Emergency Procedure

SAA/SNZ HB76: Dangerous Goods - Initial Emergency Response Guide

- 14.

Eliminate all sources of ignition. Ventilate area thoroughly and wear a suitable respirator if necessary to minimise inhalation. Wear suitable personal protective equipment such as protective gloves to prevent skin

contact.

Spills / Clean up Eliminate all sources of ignition. Stop leak if safe to do so.

For larger spills (greater than 1L) – contain spill by placing inert, non-combustible absorbent material such as vermiculite, sand or dirt onto spill.

For small spills (less than 1L) – can be wiped up using clean rags.

Collect material using non-sparking tools and place into a suitable container for disposal according to local regulations. Do not flush to drains or sewers. Clean area by working from the periphery to the centre

of spill or from the edge of the room to the centre.

Section 7: HANDLING AND STORAGE

Precautions for Safe Handling

Contact Whiteley Corporation sales representative for advice when using this product for any application other than that

outlined on the label or technical bulletin.

Any non-intended or non-authorised use of this product may result in personal injury or damage to equipment and goods.

Store product in original container.

Wash hands and face thoroughly after handling and before work

breaks, eating, drinking, smoking and using toilet facilities.

Issue No. 8 Page 2 of 5

Conditions for Safe Storage Store as Class 3 Flammable Liquid in accordance with Australian

Standard 1940, The storage and handling of flammable and combustible liquids. Store in a cool, dry, well ventilated area away from sources of ignition. Store away from heat, naked flames or sparks. Keep container tightly sealed and store away

from incompatible materials.

Section 8: EXPOSURE CONTROL/PERSONAL PROTECTION

National Exposure Standards – Source: National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003].

IngredientCAS NoES-TWAES-STELMineral turpentine64742-95-6480mg/m³Not available

Biological Limit Values Not known.

Engineering Controls When used in confined spaces respiratory protection may be

required, see Personal Protective Equipment.

Personal Protective Equipment Eye/face protection - Safety glasses or chemical resistant

goggles should be worn to prevent eye contact.

Skin protection – Use suitable protective clothing, such as impervious gloves, apron, face shield and chemical resistant

safety shoes to prevent skin contact.

Respiratory protection - If necessary, use a respirator with

organic vapour filters.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance Clear brown liquid Boiling Point greater than 100°C

Odour Solvent Freezing Point less than 0°C

pH Not applicable **Solubility** Slightly soluble in water.

Specific Gravity 0.85 Flash Point 60°C – Method: ASTM D-92

Vapour Pressure Not Available. Upper and Lower Flammability limits (in air) Not Available.

Vapour Density Not Available. **Ignition Temperature** Not Available.

Section 10: STABILITY AND REACTIVITY

Chemical Stability Stable under normal ambient storage conditions.

Conditions to avoid Avoid high temperatures (store below 30°C). Protect

against physical damage. Store away from sources of

ignition.

agents.

Hazardous decomposition products Not known.

Hazardous reactions Not known.

Issue No. 8 Page 3 of 5

Section 11: TOXICOLOGICAL INFORMATION

HEALTH EFFECTS

Acute

Swallowed Considered an unlikely route of entry in commercial / industrial environments. May

cause gastric irritation. Aspiration may cause lung damage.

Eye Liquid and vapour may cause eye irritation. Liquid may cause damage to eye if not

treated immediately.

Skin Mildly irritating.

Inhaled Vapour or mists may be irritating to respiratory system.

Chronic

Swallowed None known.

Eye None known.

Skin None known.

Inhalation None known.

TOXICITY DATA

Mineral turpentine LD₅₀ 8400mg/kg (oral, rat) RTECS WF3400000

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity Not known.

Persistence and degradability Not known.

Mobility Not known.

Section 13: DISPOSAL CONSIDERATIONS

Disposal method Refer to State/Territory Land Waste Management Authority. Dispose of

material through a licensed waste contractor. Rinse empty containers with t mineral turpentine thoroughly before disposing to an authorised landfill.

Special precautions None known.

Section 14: TRANSPORT INFORMATION

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG

Code).

UN Number 1866

UN Proper Shipping Name RESIN SOLUTION, flammable

Class and subsidiary risk 3 - Flammable

Packing Group 2

Special precautions for user None known

Hazchem Code 3[Y]

Section 15: REGULATORY INFORMATION

Poisons Schedule (SUSDP): Schedule 5 – CAUTION.

All ingredients are listed in the Australia Inventory of Chemical Substances (AICS).

Issue No. 8 Page 4 of 5

Section 16: OTHER INFORMATION

Date of review: 17th September 2013

© This document remains property of Whiteley Corporation Pty Ltd. Alterations are not permitted without prior written authorisation from Whiteley Corporation Pty Ltd.

Issue No. 8 Page 5 of 5