



Material Safety Data Sheet

Material Name: ULTRABOND ECO 190

ID: NDM0011

*** Section 1 - Chemical Product and Company Identification ***

Material Name: ULTRABOND ECO 190

Product Use

Flooring adhesive

Manufacturer Information

USA and Puerto Rico

MAPEI

1144 East Newport Center Drive

Deerfield Beach, FL 33442

Phone: 1-954-246-8888

Canada

MAPEI

2900 Francis-Hughes Avenue

Laval, QC H7L 3J5

Phone: 1-450-662-1212

IN THE EVENT OF A CHEMICAL EMERGENCY INVOLVING A SPILL, LEAK, FIRE, EXPLOSION, EXPOSURE OR ACCIDENT, CONTACT THE FOLLOWING NUMBERS:

Emergency 24 hour numbers:

(USA) CHEMTREC 1-800-424-9300

(Canada) CANUTEC 1-631-996-6666

*** Section 2 - Hazards Identification ***

Emergency Overview

This product has been evaluated using criteria specified in 29CFR 1910.1200 (Hazard Communication Standard). Irritating to eyes. This product contains trace levels (<0.03%) of fungicides.

Hazard Statements

CAUTION! Irritating to eyes. Wear suitable gloves and eye/face protection. Keep out of the reach of children.

Potential Health Effects: Eyes

This product is irritating to the eyes.

Potential Health Effects: Skin

This product may cause irritation to the skin.

Potential Health Effects: Ingestion

Acute ingestion may result in mild gastrointestinal distress.

Potential Health Effects: Inhalation

This product may cause irritation to the respiratory system.

Medical Conditions Aggravated by Exposure

Hypersensitivity to product, allergies, and skin or respiratory disorders

Potential Environmental Effects

None identified.

HMIS Ratings: Health: 1 Fire: 0 Reactivity: 0 Pers. Prot.: safety glasses, gloves

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

*** Section 3 - Composition / Information on Ingredients ***

CAS #	Component	Percent
1332-58-7	Kaolin	15-40
1317-65-3	Limestone	10-30
64742-52-5	Naphthenic Oil	7-13

Component Related Regulatory Information

This product may be regulated, have exposure limits or other information identified as the following: Calcium carbonates.

Material Safety Data Sheet

Material Name: ULTRABOND ECO 190

ID: NDM0011

Component Information/Information on Non-Hazardous Components

*** Section 4 - First Aid Measures ***

First Aid: Eyes

Immediately flush eyes with plenty of water for at least 15 minutes. If irritation persists get medical attention.

First Aid: Skin

For skin contact, flush with large amounts of water. If irritation persists, get medical attention.

First Aid: Ingestion

For ingestion, flush out mouth with water. If ingestion of a large amount does occur, seek medical attention. Do not induce vomiting.

First Aid: Inhalation

If inhaled, immediately remove the affected person to fresh air. If the affected person is not breathing, apply artificial respiration. If symptoms persist, get medical attention.

First Aid: Notes to Physician

Provide general supportive measures and treat symptomatically.

*** Section 5 - Fire Fighting Measures ***

General Fire Hazards

See Section 9 for Flammability Properties.

This product is combustible at high temperatures.

Hazardous Combustion Products

Irritating and toxic gases or fumes may be released during a fire. Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

Extinguishing Media

Dry chemical (preferred), foam, water.

Fire Fighting Equipment/Instructions

Firefighters should wear full protective clothing including self contained breathing apparatus.

NFPA Ratings: Health: 1 Fire: 0 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

*** Section 6 - Accidental Release Measures ***

Personal Precautions

Wear appropriate protective equipment and clothing during clean-up.

Containment Procedures

Dike the spilled material, where this is possible. Absorb with inert absorbent such as dry clay, sand or diatomaceous earth, commercial sorbents, or recover using pumps. Scoop up used absorbent into drums or other appropriate container.

Environmental Precautions

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

Clean-Up Procedures

Attempt to reclaim the free product, if this is possible. Shovel the material into waste container. Thoroughly wash the area with water after a spill or leak clean-up. Wear appropriate protective equipment and clothing during clean-up.

Evacuation Procedures

None identified.

Special Procedures

Regulations vary. Consult local authorities before disposal.

Material Safety Data Sheet

Material Name: ULTRABOND ECO 190

ID: NDM0011

*** Section 7 - Handling and Storage ***

Handling Procedures

Avoid getting this material into contact with your skin and eyes. Avoid breathing vapors or mists of this product. Use this product with adequate ventilation. Wash hands after handling and before eating. Keep out of the reach of children.

Storage Procedures

Store at ambient temperature and atmospheric pressure. Store away from strong oxidizers.

*** Section 8 - Exposure Controls / Personal Protection ***

A: Component Exposure Limits

Kaolin (1332-58-7)

ACGIH:	2 mg/m3 TWA (respirable fraction, particulate matter containing no asbestos and <1% crystalline silica)
OSHA	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
(Final):	
OSHA	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
(Vacated):	
NIOSH:	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)
Alberta:	2 mg/m3 TWA (respirable particulate)
British	2 mg/m3 TWA (respirable, particulate matter containing no asbestos and less than 1%
Columbia:	crystalline silica)
Manitoba:	2 mg/m3 TWA (respirable fraction, particulate matter containing no asbestos and <1% crystalline silica)
New	2 mg/m3 TWA (particulate matter containing no asbestos and < 1% crystalline silica,
Brunswick:	respirable fraction)
NW	5 mg/m3 TWA (respirable mass); 10 mg/m3 TWA (total mass)
Territories:	
Nova Scotia:	2 mg/m3 TWA (respirable fraction, particulate matter containing no asbestos and <1% crystalline silica)
Nunavut:	5 mg/m3 TWA (respirable mass); 10 mg/m3 TWA (total mass)
Ontario:	2 mg/m3 TWAEV (respirable, containing no asbestos and less than 1% crystalline silica)
Quebec:	5 mg/m3 TWAEV (respirable dust, containing no asbestos and less than 1% crystalline silica)
Saskatchewan	2 mg/m3 TWA (respirable fraction)
n:	4 mg/m3 STEL (respirable fraction)
Yukon:	30 mppcf TWA; 10 mg/m3 TWA
	20 mg/m3 STEL

Material Safety Data Sheet

Material Name: ULTRABOND ECO 190

ID: NDM0011

Limestone (1317-65-3)

OSHA 15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
(Final):
OSHA 15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
(Vacated):
NIOSH: 10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)
Alberta: 10 mg/m3 TWA
British 10 mg/m3 TWA (total dust); 3 mg/m3 TWA (respirable fraction)
Columbia: 20 mg/m3 STEL (total dust)
New 10 mg/m3 TWA (particulate matter containing no asbestos and < 1% crystalline silica)
Brunswick:
NW 5 mg/m3 TWA (respirable mass); 10 mg/m3 TWA (total mass)
Territories:
Nunavut: 5 mg/m3 TWA (respirable mass); 10 mg/m3 TWA (total mass)
Quebec: 10 mg/m3 TWAEV (total dust, containing no asbestos and less than 1% crystalline silica)
Saskatchewan 10 mg/m3 TWA
n: 20 mg/m3 STEL
Yukon: 30 mppcf TWA; 10 mg/m3 TWA
20 mg/m3 STEL

Engineering Controls

Use general ventilation.

PERSONAL PROTECTIVE EQUIPMENT

Personal Protective Equipment: Eyes/Face

Wear safety glasses with side shields.

Personal Protective Equipment: Skin

The use of nitrile-latex gloves is recommended.

Personal Protective Equipment: Respiratory

Not normally needed. If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection.

Personal Protective Equipment: General

Launder contaminated clothing before reuse. Use good industrial hygiene practices in handling this material.

*** Section 9 - Physical & Chemical Properties ***

Appearance:	Creamy Paste	Odor:	Slight Hydrocarbon Odor
Physical State:	Paste	pH:	7-11
Vapor Pressure:	None Identified	Vapor Density:	None Identified
Boiling Point:	None Identified	Melting Point:	None Identified
Solubility (H2O):	None Identified	Specific Gravity:	1.2- 1.5
Evaporation Rate:	None Identified	VOC:	43 g/L
Octanol/H2O Coeff.:		Flash Point:	>200F
Flash Point Method:	Closed cup	Upper Flammability Limit (UFL):	None Identified
Lower Flammability Limit (LFL):	None Identified	Burning Rate:	None Identified
Auto Ignition:	None Identified		

Physical Properties: Additional Information

The data provided in this section is to be used for product safety handling purposes. Please refer to Product Data Sheets, Certificates of Conformity or Certificates of Analysis for chemical and physical data for determinations of quality and for formulation purposes.

Material Safety Data Sheet

Material Name: ULTRABOND ECO 190

ID: NDM0011

*** Section 10 - Chemical Stability & Reactivity Information ***

Chemical Stability

This is a stable material.

Chemical Stability: Conditions to Avoid

Do not freeze.

Incompatibility

This product may react with strong oxidizing agents.

Hazardous Decomposition

Irritating and/or toxic fumes and gases may be emitted upon the product's decomposition. Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

Possibility of Hazardous Reactions

Will not occur.

*** Section 11 - Toxicological Information ***

Acute Dose Effects

A: General Product Information

No information available for the product.

B: Component Analysis - LD50/LC50

Petroleum distillates, hydrotreated heavy naphthenic (64742-52-5)

Inhalation LC50 Rat: 2.18 mg/L/4H; Oral LD50 Rat:>5000 mg/kg; Dermal LD50 Rabbit:>2000 mg/kg

Carcinogenicity

A: General Product Information

No information available for the product.

B: Component Carcinogenicity

Kaolin (1332-58-7)

ACGIH: A4 - Not Classifiable as a Human Carcinogen

Sensitization

No information available for the product.

*** Section 12 - Ecological Information ***

Ecotoxicity

A: General Product Information

No information available for the product.

B: Component Analysis - Ecotoxicity - Aquatic Toxicity

Petroleum distillates, hydrotreated heavy naphthenic (64742-52-5)

Test & Species

Conditions

96 Hr LC50 Pimephales promelas >5000 mg/L

48 Hr EC50 Daphnia magna >1000 mg/L

*** Section 13 - Disposal Considerations ***

US EPA Waste Number & Descriptions

A: General Product Information

No additional information available.

B: Component Waste Numbers

No EPA Waste Numbers are applicable for this product's components.

Disposal Instructions

Waste must be handled in accordance with all federal, state, provincial, and local regulations. Consult authorities before disposal.

See Section 7 for Handling Procedures. See Section 8 for Personal Protective Equipment recommendations.

Material Safety Data Sheet

Material Name: ULTRABOND ECO 190

ID: NDM0011

*** Section 14 - Transportation Information ***

International Transportation Regulations

Not regulated as dangerous goods.

*** Section 15 - Regulatory Information ***

US Federal Regulations

A: General Product Information

All components are on the U.S. EPA TSCA Inventory List. All components of this product are included, or are exempt from inclusion, in the Canadian Domestic Substance List unless otherwise noted.

B: Component Analysis

None of this products components are listed under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), or CERCLA (40 CFR 302.4).

State Regulations

A: General Product Information

Other state regulations may apply. Check individual state requirements.

B: Component Analysis - State

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA	RI
Kaolin	1332-58-7	No	Yes	Yes	Yes	Yes	Yes
Limestone	1317-65-3	No	Yes	Yes	Yes	Yes	Yes

Canadian WHMIS Information

A: General Product Information

Not regulated

B: Component Analysis - WHMIS IDL

No components are listed in the WHMIS IDL.

WHMIS Classification: Not Regulated

Additional Regulatory Information

A: General Product Information

Supplier(s) of proprietary component(s) state that these components are contained on the TSCA inventory.

B: Component Analysis - Inventory

Component	CAS #	TSCA	CAN	EEC
Kaolin	1332-58-7	Yes	DSL	EINECS
Limestone	1317-65-3	Yes	NDSL	EINECS
Petroleum distillates, hydrotreated heavy naphthenic	64742-52-5	Yes	DSL	EINECS

*** Section 16 - Other Information ***

Other Information

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. However, no warranty, expressed or implied, is given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

Material Safety Data Sheet

Material Name: ULTRABOND ECO 190

ID: NDM0011

Key/Legend

NA = Not available or Not Applicable. NFPA = National Fire Protection Association. HMIS = Hazardous Material Information System. CFR = Code of Federal Regulations. EPA = Environmental Protection Agency; TSCA = Toxic Substance Control Act; ACGIH = American Conference of Governmental Industrial Hygienists; IARC = International Agency for Research on Cancer; NIOSH = National Institute for Occupational Safety and Health; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration., NJTSR = New Jersey Trade Secret Registry.

Contact: Product Safety Specialist

Contact Phone: 1-954-246-8888

End of Sheet NDM0011