

Material Name: Ultralite Mortar ID: SAH00320

* * * Section 1 - Chemical Product and Company Identification * * *

Material Name: Ultralite Mortar

Product Use Mortar

Manufacturer Information

USA and Puerto Rico MAPEI

1144 East Newport Center Drive 2900 Francis-Hughes Avenue Deerfield Beach, FL 33442 Laval, QC H7L 3J5

Phone: 1-954-246-8888 Phone: 1-450-662-1212

IN THE EVENT OF A CHEMICAL EMERGENCY INVOLVING A SPILL, LEAK, FIRE, EXPLOSION, EXPOSURE OR ACCIDENT, CONTACT THE FOLLOWING NUMBERS:

Canada

MAPEI

Emergency 24 hour numbers:

(USA) CHEMTREC 1-800-424-9300 (Canada) CANUTEC 1-631-996-6666

* * * Section 2 - Hazards Identification * * *

Emergency Overview

This product has been evaluated using criteria specified in 29CFR 1910.1200 (Hazard Communication Standard). Causes burns to the skin and eyes when mixed with water.

Hazard Statements

DANGER! CORROSIVE. Causes burns to the skin and eyes when mixed with water. May be harmful or fatal if swallowed. Wear suitable gloves, eye/face protection, and respiratory protection. Keep out of the reach of children.

Potential Health Effects: Eyes

This product is irritating to the eyes. Symptoms can include irritation, redness, scratching of the cornea, and tearing.

Potential Health Effects: Skin

This product is irritating to the skin. Mechanical rubbing may increase skin irritation.

Potential Health Effects: Ingestion

This product may be harmful if it is swallowed. Ingestion of this product may cause nausea, vomiting and diarrhea.

Potential Health Effects: Inhalation

This product is irritating to the respiratory system. Inhalation of dusts produced during cutting, grinding or sanding of this product may cause irritation of the respiratory tract.

Medical Conditions Aggravated by Exposure

Hypersensitivity to product, allergies, and skin or respiratory disorders

Potential Environmental Effects

None identified.

HMIS Ratings: Health: 1 Fire: 0 Reactivity: 0 Pers. Prot.: Safety glasses, gloves, and N95 respirator if dust exposure exceeds TLV values

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

* * * Section 3 - Composition / Information on Ingredients * * *

CAS#	Component	Percent
65997-15-1	Portland cement	30-60
1344-95-2	Calcium silicate	5-10

Material Name: Ultralite Mortar ID: SAH00320

12042-78-3	Tricalcium aluminate	5-10
68683-26-1	Vinyl versatate polymer	1-5
7778-18-9	Calcium sulfate	3-7
544-17-2	Calcium formate	1-5
1309-48-4	Magnesium oxide fume	1-5

* * * Section 4 - First Aid Measures * * *

First Aid: Eyes

In case of contact, immediately flush eyes with large amounts of water, continuing to flush for 15 minutes. If irritation persists get medical attention.

First Aid: Skin

For skin contact, flush with large amounts of water. If irritation persists, get medical attention.

First Aid: Ingestion

For ingestion, flush out mouth with water. If ingestion of a large amount does occur, seek medical attention. Do not induce vomiting.

First Aid: Inhalation

If inhaled, immediately remove the affected person to fresh air. If the affected person is not breathing, apply artificial respiration. If symptoms persist, get medical attention.

First Aid: Notes to Physician

Provide general supportive measures and treat symptomatically.

* * * Section 5 - Fire Fighting Measures * * *

General Fire Hazards

See Section 9 for Flammability Properties.

As with all dry powders, it is advisable to ground mechanical equipment in contact with dry material to dissipate the potential buildup of static electricity.

Hazardous Combustion Products

Irritating and toxic gases or fumes may be released during a fire. Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

Extinguishing Media

Dry chemical (preferred), foam, water.

Fire Fighting Equipment/Instructions

Firefighters should wear full protective clothing including self contained breathing apparatus.

NFPA Ratings: Health: 1 Fire: 0 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

* * * Section 6 - Accidental Release Measures * * *

Personal Precautions

Avoid the generation of dusts during clean-up. Wear appropriate protective equipment and clothing during clean-up.

Containment Procedures

Contain the discharged material.

Environmental Precautions

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

Clean-Up Procedures

Attempt to reclaim the free product, if this is possible. Shovel the material into waste container. Thoroughly wash the area with water after a spill or leak clean-up. Wear appropriate protective equipment and clothing during clean-up. Keep out of the reach of children.

Evacuation Procedures

None identified.

Special Procedures

Wear a dust mask if dust is generated above exposure limits.

Material Name: Ultralite Mortar ID: SAH00320

* * * Section 7 - Handling and Storage * * *

Handling Procedures

Avoid getting this material into contact with your skin and eyes. Avoid breathing dusts from this material. Wash hands after handling and before eating. Keep out of the reach of children.

Storage Procedures

Store in a cool, dry, well-ventilated area. Keep the container tightly closed. Do not freeze.

* * * Section 8 - Exposure Controls / Personal Protection * * *

A: Component Exposure Limits

Portland cement (65997-15-1)

i Ortiana cent	311t (00007-10-1)
ACGIH:	10 mg/m3 TWA particulate matter containing no asbestos and <1% crystalline silica
OSHA (Final):	15 mg/m3 TWA total dust; 5 mg/m3 TWA respirable fraction
NIOSH:	10 mg/m3 TWA total dust; 5 mg/m3 TWA respirable dust
Alberta:	10 mg/m3 TWA
British Columbia:	10 mg/m3 TWA particulate total particulate matter containing no asbestos and less than 1% crystalline silica; 3 mg/m3 TWA respirable particulate particulate matter containing no asbestos and less than 1% crystalline silica
Manitoba:	10 mg/m3 TWA particulate matter containing no asbestos and <1% crystalline silica
New Brunswick:	10 mg/m3 TWA particulate matter containing no asbestos and < 1% crystalline silica
NW Territories:	5 mg/m3 TWA respirable mass; 10 mg/m3 TWA total mass
Nova Scotia:	10 mg/m3 TWA particulate matter containing no asbestos and <1% crystalline silica
Nunavut:	5 mg/m3 TWA respirable mass; 10 mg/m3 TWA total mass
Ontario:	10 mg/m3 TWAEV total dust, containing no asbestos and less than 1% crystalline silica
Quebec:	10 mg/m3 TWAEV total dust, containing no asbestos and less than 1% crystalline silica; 5 mg/m3 TWAEV respirable dust, containing no asbestos and less than 1% crystalline silica
Saskatchewan:	10 mg/m3 TWA
	20 mg/m3 STEL
Yukon:	30 mppcf TWA; 10 mg/m3 TWA
	20 mg/m3 STEL

Calcium silicate (1344-95-2)

Calcium Sinca	ne (1344-93-2)
ACGIH:	10 mg/m3 TWA particulate matter containing no asbestos and <1% crystalline silica
OSHA (Final):	15 mg/m3 TWA total dust; 5 mg/m3 TWA respirable fraction
NIOSH:	10 mg/m3 TWA total dust; 5 mg/m3 TWA respirable dust
Alberta:	10 mg/m3 TWA (nonfibrous)
British Columbia:	10 mg/m3 TWA particulate total particulate matter containing no asbestos and less than 1% crystalline silica;
	3 mg/m3 TWA respirable particulate particulate matter containing no asbestos and less than 1% crystalline
	silica
Manitoba:	10 mg/m3 TWA nonfibrous particulate matter containing no asbestos and <1% crystalline silica
New Brunswick:	10 mg/m3 TWA particulate matter containing no asbestos and < 1% crystalline silica
NW Territories:	5 mg/m3 TWA respirable mass; 10 mg/m3 TWA total mass
Nova Scotia:	10 mg/m3 TWA nonfibrous, particulate matter containing no asbestos and <1% crystalline silica synthetic
Nunavut:	5 mg/m3 TWA respirable mass; 10 mg/m3 TWA total mass
Ontario:	10 mg/m3 TWAEV total dust
Quebec:	10 mg/m3 TWAEV total dust, containing no asbestos and less than 1% crystalline silica
Saskatchewan:	10 mg/m3 TWA (nonfibrous)
	20 mg/m3 STEL (nonfibrous)
Yukon:	30 mppcf TWA; 10 mg/m3 TWA

Material Name: Ultralite Mortar ID: SAH00320

Calcium sulfate (7778-18-9)

ACGIH:	10 mg/m3 TWA inhalable fraction
OSHA (Final):	15 mg/m3 TWA total dust; 5 mg/m3 TWA respirable fraction
NIOSH:	10 mg/m3 TWA total dust; 5 mg/m3 TWA respirable dust
Alberta:	10 mg/m3 TWA
British Columbia:	10 mg/m3 TWA inhalable
Manitoba:	10 mg/m3 TWA inhalable fraction
New Brunswick:	10 mg/m3 TWA particulate matter containing no asbestos and < 1% crystalline silica
Nova Scotia:	10 mg/m3 TWA inhalable fraction
Ontario:	10 mg/m3 TWAEV inhalable
Quebec:	10 mg/m3 TWAEV total dust, containing no asbestos and less than 1% crystalline silica; 5 mg/m3 TWAEV
	respirable dust, containing no asbestos and less than 1% crystalline silica
Saskatchewan:	10 mg/m3 TWA
	20 mg/m3 STEL

Magnesium oxide fume (1309-48-4)

	due faine (1000 40 4)
ACGIH:	10 mg/m3 TWA inhalable fraction
OSHA (Final):	15 mg/m3 TWA fume, total particulate
Alberta:	10 mg/m3 TWA (fume)
British Columbia:	10 mg/m3 TWA Mg fume, inhalable; 3 mg/m3 TWA Mg respirable dust and fume
	10 mg/m3 STEL Mg respirable dust and fume
Manitoba:	10 mg/m3 TWA inhalable fraction
New Brunswick:	10 mg/m3 TWA fume
NW Territories:	10 mg/m3 TWA Mg fume
	20 mg/m3 STEL Mg fume
Nova Scotia:	10 mg/m3 TWA inhalable fraction
Nunavut:	10 mg/m3 TWA Mg fume
	20 mg/m3 STEL Mg fume
Ontario:	10 mg/m3 TWAEV inhalable
Quebec:	10 mg/m3 TWAEV Mg fume
Saskatchewan:	10 mg/m3 TWA (inhalable fraction)
	20 mg/m3 STEL (inhalable fraction)
Yukon:	10 mg/m3 TWA (Mg, fume)
	10 mg/m3 STEL (Mg, fume)

Engineering Controls

Use general ventilation.

PERSONAL PROTECTIVE EQUIPMENT

Personal Protective Equipment: Eyes/Face

Wear safety glasses with side shields.

Personal Protective Equipment: Skin

The use of nitrile-latex gloves is recommended.

Personal Protective Equipment: Respiratory

If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection.

Personal Protective Equipment: General

Launder contaminated clothing before reuse. Use good industrial hygiene practices in handling this material.

* * * Section 9 - Physical & Chemical Properties * * *

Appearance:	White or gray powder	Odor:	Cement odor
Physical State:	Solid	pH:	11.0 - 13.0
Vapor Pressure:	N/A	Vapor Density:	N/A
Boiling Point:	N/A	Melting Point:	N/A
Solubility (H2O):	Soluble	Specific Gravity:	2.0 - 2.3
Evaporation Rate:	N/A	VOC:	0 g/L
Octanol/H2O Coeff.:	N/A	Flash Point:	N/A
Flash Point Method:	N/A	Upper Flammability Limit (UFL):	N/A
Lower Flammability Limit (LFL):	N/A	Burning Rate:	N/A
Auto Ignition:	N/A		

Material Name: Ultralite Mortar ID: SAH00320

Physical Properties: Additional Information

The data provided in this section is to be used for product safety handling purposes. Please refer to Product Data Sheets, Certificates of Conformity or Certificates of Analysis for chemical and physical data for determinations of quality and for formulation purposes.

* * * Section 10 - Chemical Stability & Reactivity Information * * *

Chemical Stability

Stable under normal conditions.

Chemical Stability: Conditions to Avoid

Keep away from heat, ignition sources and incompatible materials.

Incompatibility

This product may react with strong acids, bases and oxidizing agents.

Hazardous Decomposition

Irritating and/or toxic fumes and gases may be emitted upon the product's decomposition. Upon decomposition, this product may emit fumes of carbon monoxide, carbon dioxide, oxides of nitrogen, and other organic compounds.

Possibility of Hazardous Reactions

Will not occur.

* * * Section 11 - Toxicological Information * * *

Acute Dose Effects

A: General Product Information

No information available for the product.

B: Component Analysis - LD50/LC50

Calcium silicate (1344-95-2)

Oral LD50 Rat 3400 mg/kg

Calcium sulfate (7778-18-9)

Oral LD50 Rat >3000 mg/kg

Calcium formate (544-17-2)

Oral LD50 Rat 2650 mg/kg

Carcinogenicity

A: General Product Information

No information available for the product.

B: Component Carcinogenicity

Calcium silicate (1344-95-2)

ACGIH: A4 - Not Classifiable as a Human Carcinogen (synthetic nonfibrous)

Magnesium oxide fume (1309-48-4)

ACGIH: A4 - Not Classifiable as a Human Carcinogen

Sensitization

No information available for the product.

* * * Section 12 - Ecological Information * * *

Ecotoxicity

A: General Product Information

No information available for the product.

B: Component Analysis - Ecotoxicity - Aquatic Toxicity

Calcium sulfate (7778-18-9)

Test & Species		Conditions	
96 Hr LC50 Lepomis macrochirus	2980 mg/L	[static]	
96 Hr LC50 Pimephales promelas	>1970 mg/L	[static]	
120 Hr EC50 Nitscheria linearis	3200 mg/L		<u> </u>

Page 5 of 7 Issue Date: 10 August 2009 Revision: 1.0000 Print Date: 11/2/2009

Material Name: Ultralite Mortar ID: SAH00320

Calcium formate (544-17-2)

Test & Species		Conditions
96 Hr LC50 Brachydanio rerio	>=1000 mg/L	[static]

* * * Section 13 - Disposal Considerations * * *

US EPA Waste Number & Descriptions

A: General Product Information

No additional information available.

B: Component Waste Numbers

No EPA Waste Numbers are applicable for this product's components.

Disposal Instructions

Waste must be handled in accordance with all federal, state, provincial, and local regulations. Consult authorities before disposal.

See Section 7 for Handling Procedures. See Section 8 for Personal Protective Equipment recommendations.

* * * Section 14 - Transportation Information * * *

International Transportation Regulations

Not regulated as dangerous goods.

* * * Section 15 - Regulatory Information * * *

US Federal Regulations

A: General Product Information

All components are on the U.S. EPA TSCA Inventory List. All components of this product are included, or are exempt from inclusion, in the Canadian Domestic Substance List unless otherwise noted.

B: Component Analysis

None of this products components are listed under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), or CERCLA (40 CFR 302.4).

State Regulations

A: General Product Information

Other state regulations may apply. Check individual state requirements.

B: Component Analysis - State

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA	RI
Portland cement	65997-15-1	No	Yes	Yes	Yes	Yes	Yes
Calcium silicate	1344-95-2	No	Yes	Yes	Yes	Yes	Yes
Calcium sulfate	7778-18-9	No	Yes	Yes	Yes	Yes	No
Magnesium oxide fume	1309-48-4	Yes	Yes	Yes	Yes	Yes	Yes

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING! This product contains a chemical known to the state of California to cause cancer.

Canadian WHMIS Information

A: General Product Information



Page 6 of 7 Issue Date: 10 August 2009 Revision: 1.0000 Print Date: 11/2/2009

Material Name: Ultralite Mortar ID: SAH00320

B: Component Analysis - WHMIS IDL

The following components are identified under the Canadian Hazardous Products Act Ingredient Disclosure List:

Component	CAS#	Minimum Concentration
Calcium formate	544-17-2	1 %
Magnesium oxide fume	1309-48-4	1 %

Additional Regulatory Information

A: General Product Information

Supplier(s) of proprietary component(s) state that these components are contained on the TSCA inventory.

B: Component Analysis - Inventory

ponone / maryolo mivomory				
Component	CAS#	TSCA	CAN	EEC
Portland cement	65997-15-1	Yes	DSL	EINECS
Calcium silicate	1344-95-2	Yes	DSL	EINECS
Tricalcium aluminate	12042-78-3	Yes	DSL	EINECS
Vinyl versatate polymer	68683-26-1	Yes	DSL	No
Calcium sulfate	7778-18-9	Yes	DSL	EINECS
Calcium formate	544-17-2	Yes	DSL	EINECS
Magnesium oxide fume	1309-48-4	Yes	DSL	EINECS

* * * Section 16 - Other Information * * *

Reference

15-2624-09

Other Information

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

Key/Legend

NA = Not available or Not Applicable. ACGIH = American Conference of Governmental Industrial Hygienists. NFPA = National Fire Protection Association. EPA = Environmental Protection Agency; TSCA = Toxic Substance Control Act; ACGIH = American Conference of Governmental Industrial Hygienists; IARC = International Agency for Research on Cancer; NIOSH = National Institute for Occupational Safety and Health; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration., NJTSR = New Jersey Trade Secret Registry.

Contact: Product Safety Specialist Contact Phone: 1-954-246-8888

End of Sheet SAH00320

Page 7 of 7 Issue Date: 10 August 2009 Revision: 1.0000 Print Date: 11/2/2009