

Page 01 of 08



# Gas Line Antifreeze

# **SECTION 1. IDENTIFICATION**

Product Identifier Gas Line Antifreeze

Other Means of 15-355, 15-356, 35-351SO, 35-355C, 35-355H, 35-355WM, 35-356CHR, 35-356CQ,

Identification 35-356LAU, 35-356PC, 35-356SO, 35-356SS

Other Identification Methyl Hydrate

**Recommended Use** Please refer to Product label.

**Restrictions on Use** None known.

Manufacturer / Recochem Inc., 850 Montee de Liesse, Montreal, QC, H4T 1P4, Compliance and Regulatory

**Supplier** Department, 905-878-5544, www.recochem.com

Emergency Phone No. CANUTEC, 613-996-6666, 24 Hours

**SDS No.** 1605

#### **SECTION 2. HAZARDS IDENTIFICATION**

#### **GHS Classification**

Flammable liquid - Category 2; Acute toxicity (Oral) - Category 3; Acute toxicity (Dermal) - Category 3; Acute toxicity (Inhalation) - Category 3; Specific target organ toxicity (single exposure) - Category 1

#### **GHS Label Elements**







Signal Word: Danger

### Hazard Statement(s):

H225 Highly flammable liquid and vapour.

H301 Toxic if swallowed.
H311 Toxic in contact with skin.

H331 Toxic if inhaled.

H370 Causes damage to organs (eyes) if swallowed.

#### Precautionary Statement(s):

#### Prevention:

P210 Keep away from heat, sparks, open flames, and hot surfaces. – No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical, ventilating, lighting, and other equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe fume, mist, vapours, spray.
P264 Wash hands and skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.

Product Identifier: Gas Line Antifreeze

SDS No.: 1605

P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/protective clothing.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTRE/doctor.

P330 Rinse mouth.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P312 Call a POISON CENTRE/doctor if you feel unwell.

P363 Wash contaminated clothing before reuse.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTRE/doctor if you feel unwell.

P321 Specific treatment (see supplemental first aid instruction on this label).

P370 + P378 In case of fire: Use appropriate foam, carbon dioxide, dry chemical powder, water spray or fog to

extinguish.

#### Storage:

Store in a well ventilated place. Keep cool. Keep container tightly closed. Store locked up.

#### Disposal:

Dispose of contents/container in accordance with applicable regional, national and local laws and regulations.

#### Other Hazards

None known.

### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### Substance:

Chemical Name	CAS No.	%	Other Identifiers
Methanol	67-56-1	60-100	

#### **SECTION 4. FIRST-AID MEASURES**

#### **First-aid Measures**

#### Inhalation

Take precautions to ensure your own safety before attempting rescue (e.g. wear appropriate protective equipment). Remove source of exposure or move to fresh air. Keep at rest in a position comfortable for breathing. If breathing has stopped, trained personnel should begin rescue breathing. If the heart has stopped, trained personnel should start cardiopulmonary resuscitation (CPR) or automated external defibrillation (AED). Avoid mouth-to-mouth contact by using a barrier device. Get medical advice/attention if you feel unwell or are concerned.

# **Skin Contact**

Avoid direct contact. Wear chemical protective clothing if necessary. Take off immediately contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Wash gently and thoroughly with lukewarm, gently flowing water and mild soap for 5 minutes. Get medical advice/attention if you feel unwell or are concerned. Thoroughly clean clothing, shoes and leather goods before reuse or dispose of safely.

# **Eye Contact**

Avoid direct contact. Wear chemical protective gloves if necessary. Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for at least 30 minutes, while holding the eyelid(s) open. If eye irritation persists, get medical advice/attention.

#### Ingestion

Rinse mouth with water. Never give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Do not induce vomiting. If vomiting occurs naturally, lie on your side in the recovery position. Rinse

Product Identifier: Gas Line Antifreeze

SDS No.: 1605 Page 02 of 08

mouth with water again. If breathing has stopped, trained personnel should immediately begin rescue breathing. If the heart has stopped, trained personnel should start cardiopulmonary resuscitation (CPR) or automated external defibrillation (AED). Avoid mouth-to-mouth contact by using a barrier device. Immediately call a Poison Centre or doctor. Treatment is urgently required.

### Most Important Symptoms and Effects, Acute and Delayed

No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

# **Immediate Medical Attention and Special Treatment**

### **Target Organs**

Eyes, liver, nervous system.

#### **Special Instructions**

Acute exposure to methanol, either through ingestion or breathing high airborne concentrations can result in symptoms appearing between 40 minutes and 72 hours after exposure. Symptoms and signs are usually limited to CNS, eyes and gastrointestinal tract. Because of the initial CNS's effects of headache, vertigo, lethargy and confusion, there may be an impression of ethanol intoxication. Blurred vision, decreased acuity and photophobia are common complaints. Treatment with ipecac or lavage is indicated in any patient presenting within two hours of ingestion. A profound metabolic acidosis occurs in severe poisoning and serum bicarbonate levels are a more accurate measure of severity than serum methanol levels. Treatment protocols are available from most major hospitals and early collaboration with appropriate hospitals is recommended.

### **Medical Conditions Aggravated by Exposure**

Respiratory conditions, dermatitis, eye conditions.

# **SECTION 5. FIRE-FIGHTING MEASURES**

### **Extinguishing Media**

#### Suitable Extinguishing Media

Carbon dioxide, dry chemical powder or appropriate foam. Special "alcohol resistant fire-fighting foams".

### **Unsuitable Extinguishing Media**

Water is not effective for extinguishing a fire. It may not cool product below its flash point.

### Specific Hazards Arising from the Chemical

Highly flammable liquid and vapour. Can ignite at room temperature. Releases vapour that can form explosive mixture with air. Can be ignited by static discharge. Can accumulate static charge by flow, splashing or agitation. Even dilute solutions in water may be flammable. May travel a considerable distance to a source of ignition and flash back to a leak or open container. See Section 9 (Physical and Chemical Properties) for flash point and explosive limits. Burns with an invisible flame. May accumulate in hazardous amounts in low-lying areas especially inside confined spaces, resulting in a fire hazard.

In a fire, the following hazardous materials may be generated: toxic chemicals; very toxic carbon monoxide, carbon dioxide; very toxic, flammable formaldehyde.

### **Special Protective Equipment and Precautions for Fire-fighters**

Review Section 6 (Accidental Release Measures) for important information on responding to leaks/spills. See Skin Protection in Section 8 (Exposure Controls/Personal Protection) for advice on suitable chemical protective materials.

# **SECTION 6. ACCIDENTAL RELEASE MEASURES**

#### Personal Precautions, Protective Equipment, and Emergency Procedures

Evacuate the area immediately. Isolate the hazard area. Keep out unnecessary and unprotected personnel. Evacuate downwind locations. Use the personal protective equipment recommended in Section 8 of this safety data sheet. Increase ventilation to area or move leaking container to a well-ventilated and secure area. Eliminate all ignition sources. Use grounded, explosion-proof equipment. May accumulate in hazardous amounts in low-lying areas especially inside confined spaces, if ventilation is not sufficient. Distant ignition and flashback are possible.

### **Environmental Precautions**

Product Identifier: Gas Line Antifreeze

SDS No.: 1605

Date of Preparation: November 09, 2015

Page 03 of 08

Do not allow into any sewer, on the ground or into any waterway.

### Methods and Materials for Containment and Cleaning Up

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

# **SECTION 7. HANDLING AND STORAGE**

# **Precautions for Safe Handling**

Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

### **Conditions for Safe Storage**

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Control Parameters**

	ACGIH TLV®		OSHA PEL		AIHA WEEL	
Chemical Name	TWA	STEL	TWA	Ceiling	8-hr TWA	TWA
Methanol	200 ppm	250 ppm	200 ppm	250 ppm		

#### **Appropriate Engineering Controls**

General ventilation is usually adequate. For large scale use of this product: do not allow product to accumulate in the air in work or storage areas, or in confined spaces. Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air. Use non-sparking ventilation systems, approved explosion-proof equipment and intrinsically safe electrical systems in areas where this product is used and stored. Control static electricity discharges which includes bonding of equipment to ground. Use only non-combustible, compatible materials for walls, floors, ventilation system, air cleaning devices, pallets, shelving. Provide safety shower in work area, if contact or splash hazard exists.

### **Individual Protection Measures**

# **Eye/Face Protection**

Wear chemical safety goggles.

#### **Skin Protection**

Wear chemical protective clothing e.g. gloves, aprons, boots.

Nitrile rubber.

#### **Respiratory Protection**

Not normally required if product is used as directed. For non-routine or emergency situations: wear a NIOSH approved air-purifying respirator with an organic vapour cartridge.

Product Identifier: Gas Line Antifreeze

SDS No.: 1605

Date of Preparation: November 09, 2015

Page 04 of 08

### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

**Basic Physical and Chemical Properties** 

**Appearance** Clear colourless liquid.

**Odour** Pungent

**Odour Threshold** 4.2 - 5960 ppm (5.5 - 7794.2 mg/m3)

**pH** Not available

Melting Point/Freezing Point -97.7 °C (-143.9 °F) (melting); -97.7 °C (-143.9 °F) (freezing)

**Initial Boiling Point/Range** 64.7 °C (148.5 °F)

Flash Point 11 °C (52 °F) (closed cup)
Evaporation Rate 4.1 (n-butyl acetate = 1)

Flammability (solid, gas) Not applicable

Upper/Lower Flammability or

36% (upper); 6% (lower)

Explosive Limit Vapour Pressure

96.0 mm Hg (12.8 kPa) at 20 °C

Vapour Density (air = 1) 1.1

Relative Density (water = 1) 0.791 at 25 °C

**Solubility** Soluble in water; Soluble in all proportions in alcohols (e.g. ethanol).

Partition Coefficient, -0.77 at 20 °C

n-Octanol/Water (Log Kow)

**Auto-ignition Temperature** 464 °C (867 °F) **Decomposition Temperature** Not available

Viscosity 0.686 - 0.699 mm2/s at 25 °C (kinematic); 0.54 - 0.55 mPa.s at 20 °C (dynamic)

Other Information

Physical State Liquid Molecular Weight 32.04

# **SECTION 10. STABILITY AND REACTIVITY**

# Reactivity

None known.

### **Chemical Stability**

Normally stable.

#### **Possibility of Hazardous Reactions**

None known.

### **Conditions to Avoid**

Heat. Open flames, sparks, static discharge, heat and other ignition sources. Temperatures above 11.0 °C (51.8 °F)

#### **Incompatible Materials**

Reacts violently with: reacts explosively with: strong oxidizing agents (e.g. perchloric acid).

Highly reactive. Strong acids (e.g. hydrochloric acid).

### **Hazardous Decomposition Products**

Very toxic carbon monoxide, carbon dioxide; very toxic, flammable formaldehyde.

# **SECTION 11. TOXICOLOGICAL INFORMATION**

### **Likely Routes of Exposure**

Ingestion; eye contact; skin contact; inhalation.

**Acute Toxicity** 

Product Identifier: Gas Line Antifreeze

SDS No.: 1605 Page 05 of 08

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Methanol	83867.5 mg/m3 (rat) (4-hour exposure)	5628 mg/kg (rat)	15800 mg/kg (rabbit)

LC50: Not applicable.

LD50 (oral): Not applicable. LD50 (dermal): Not applicable.

Skin Corrosion/Irritation

Human experience shows very mild irritation.

### Serious Eye Damage/Irritation

Animal tests show serious eye irritation.

# STOT (Specific Target Organ Toxicity) - Single Exposure

#### Inhalatior

May be harmful based on human experience and animal tests. Depression of the central nervous system. Symptoms may include headache, nausea, dizziness, drowsiness and confusion. A severe exposure can cause unconsciousness.

Toxic, can cause death based on human experience. At high concentrations.

# **Skin Absorption**

Harmful based on human experience. Can cause effects as described for inhalation. Depression of the central nervous system. Symptoms may include headache, nausea, dizziness, drowsiness and confusion. A severe exposure can cause unconsciousness.

### Ingestion

Toxic, can cause death depression of the central nervous system, impaired vision and blindness. In some cases, there may be delayed effects on the nervous system. Symptoms may include headache, nausea, vomiting, dizziness, drowsiness and confusion. A severe exposure may cause stomach pain, muscle pain, difficult breathing and coma. Vision can be impaired and permanent blindness can result. There may be other permanent effects on the nervous system e.g. tremor, seizures.

### **Aspiration Hazard**

Not known to be an aspiration hazard.

#### STOT (Specific Target Organ Toxicity) - Repeated Exposure

May cause damage to organs based on limited evidence. If inhaled: effects on the central nervous system. Symptoms may include restlessness, reduced ability to think, muscle tremors, memory loss and personality changes. effects similar to STOT (Specific Target Organ Toxicity) - Single Exposure, as described above.

May cause Following skin contact: dermatitis. Symptoms may include dry, red, cracked skin (dermatitis). effects similar to STOT (Specific Target Organ Toxicity) - Single Exposure, as described above.

May cause If inhaled: at high concentrations visual distubances, cataracts, opacities.

May cause If inhaled: at high concentrations harmful effects on the liver.

### Respiratory and/or Skin Sensitization

Not known to be a respiratory sensitizer. Not known to be a skin sensitizer.

### Carcinogenicity

Chemical Name	IARC	ACGIH®	NTP	OSHA
Methanol	Not Listed	Not designated	Not Listed	Not Listed

Product Identifier: Gas Line Antifreeze

SDS No.: 1605

Date of Preparation: November 09, 2015

Page 06 of 08

### **Reproductive Toxicity**

### **Development of Offspring**

Animal studies show effects on the offspring. If inhaled: known to cause: decreased weight, birth defects. Teratogenic(external, soft tissue and skeletal defects) embryotoxic (late resorptions).

# **Sexual Function and Fertility**

Not known to cause effects on sexual function or fertility.

#### Effects on or via Lactation

May cause effects on or via lacation. Can transfer to mother's milk.

#### **Germ Cell Mutagenicity**

Conclusions cannot be drawn from the limited studies available.

#### Interactive Effects

No information was located.

# **SECTION 12. ECOLOGICAL INFORMATION**

# **Toxicity**

### **Acute Aquatic Toxicity**

Chemical Name	LC50 Fish	EC50 Crustacea	ErC50 Aquatic Plants	ErC50 Algae
Methanol	15400 mg/L (Lepomis macrochirus (bluegill); 96-hour)	10000 mg/L (Daphnia magna (water flea); 48-hour)		

### **Chronic Aquatic Toxicity**

Chemical Name	NOEC Fish	EC50 Fish	NOEC Crustacea	EC50 Crustacea
Methanol	7900 mg/L (Lepomis			
	macrochirus			
	(bluegill); 200-hrs)			

### Persistence and Degradability

Degrades rapidly based on quantitative tests.

#### **Bioaccumulative Potential**

This product and its degradation products are not expected to bioaccumulate.

#### **Mobility in Soil**

No information was located.

#### **Other Adverse Effects**

There is no information available.

# **SECTION 13. DISPOSAL CONSIDERATIONS**

### **Disposal Methods**

The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Product Identifier: Gas Line Antifreeze

SDS No.: 1605

Date of Preparation: November 09, 2015

Page 07 of 08

#### **SECTION 14. TRANSPORT INFORMATION**

Regulation	UN No.	Proper Shipping Name	Transport Hazard Class(es)	Packing Group
Canadian TDG	1230	METHANOL	3 (6.1)	П
US DOT	1230	METHANOL	3 (6.1)	П

Environmental

**Hazards** 

Not applicable

**Special Precautions** 

Please note: In containers of 1 L (1Kg) capacity or less this product is classified as a "Limited Quantities" "Consumer Commodity" under TDG regulations.

for User

In containers of 1 L (1Kg) this product is qualified as a "consumer commodity" ORM-D under

DOI

Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

### **SECTION 15. REGULATORY INFORMATION**

Safety, Health and Environmental Regulations

Canada

Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)

All ingredients are listed on the DSL/NDSL.

USA

Toxic Substances Control Act (TSCA) Section 8(b)

All ingredients are listed on the TSCA Inventory.

**Additional USA Regulatory Lists** 

California Proposition 65: WARNING: This product contains chemicals known to the State of California to cause birth defects.

### **SECTION 16. OTHER INFORMATION**

SDS Prepared By Compliance and Regulatory Department

Phone No. 905-878-5544 **Date of Preparation** November 09, 2015

Additional Information We are committed to uphold the Industry Consumer Ingredient Communication Voluntary

Initiative.

Please send us your request by visiting our website at www.recochem.com.

Ingredients present (intentionally added ingredients) at a concentration of greater than one percent (1%) shall be listed in descending order of predominance. Ingredients present at a concentration of not more than one percent shall be listed but may be disclosed without

respect to order of predominance.

**Disclaimer** Notice to reader: To the best of our knowledge, the information contained herein is accurate.

However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are

described herein, we cannot guarantee that these are the only hazards that exist.

Product Identifier: Gas Line Antifreeze

SDS No.: 1605 Page 08 of 08

