

	Page: 1
SAFETY DATA SHEET	Revision Date: 05/22/2017
	Print Date: 10/30/2017
	SDS Number: R0382635
Valvoline™ ATF+4® FULL Synthetic Automatic Transmission Fluid VV346	Version: 1.5

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Valvoline™ ATF+4® FULL
Synthetic Automatic Transmission Fluid

Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Engine, gear & lubricating oil.

Details of the supplier of the safety data sheet Valvoline LLC 100 Valvoline Way Lexington, KY 40509 United States of America (USA) 1-800-TEAMVAL	Emergency telephone number 1-800-VALVOLINE (1-800-825-8654) Regulatory Information Number 1-800-TEAMVAL Product Information 1-800-TEAMVAL
---	---

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Skin sensitization : Category 1

GHS label elements

Hazard pictograms :



Signal Word : Warning

Hazard Statements : May cause an allergic skin reaction.

Precautionary Statements : If medical advice is needed, have product container or label at hand.
Keep out of reach of children.
Read label before use.

Prevention:

Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves.

Response:

SAFETY DATA SHEET

Revision Date: 05/22/2017

Print Date: 10/30/2017

SDS Number: R0382635

Valvoline™ ATF+4® FULL Synthetic Automatic Transmission Fluid

Version: 1.5

VV346

IF ON SKIN: Wash with plenty of soap and water.
If skin irritation or rash occurs: Get medical advice/ attention.
Wash contaminated clothing before reuse.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).	59.3321
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	Asp. Tox. 1; H304	25.6673
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	Asp. Tox. 1; H304	3.2526
Mineral Oil		Asp. Tox. 1; H304	3.1046
BENZENE, POLYPROPENE DERIVATIVES, SULFONATED, CALCIUM SALTS		Eye Irrit. 2A; H319 Skin Sens. 1; H317	0.7703
DODECYL HYDROXYPROPYL SULFIDE	67124-09-8	Skin Sens. 1; H317	0.7703
C14-C18 alpha-olefin epoxide, reaction products with boric acid		Skin Sens. 1; H317	0.3813

SECTION 4. FIRST AID MEASURES

	Page: 3
SAFETY DATA SHEET	Revision Date: 05/22/2017
	Print Date: 10/30/2017
	SDS Number: R0382635
Valvoline™ ATF+4® FULL Synthetic Automatic Transmission Fluid VV346	Version: 1.5

General advice	: Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: If breathed in, move person into fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	: Remove contaminated clothing. If irritation develops, get medical attention. If on skin, rinse well with water. First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water. Wash contaminated clothing before re-use.
In case of eye contact	: Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. If eye irritation persists, consult a specialist.
If swallowed	: Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	: Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities. Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: acne stomach or intestinal upset (nausea, vomiting, diarrhea) irritation (nose, throat, airways) May cause an allergic skin reaction.
Notes to physician	: No hazards which require special first aid measures.

SAFETY DATA SHEET

Revision Date: 05/22/2017

Print Date: 10/30/2017

SDS Number: R0382635

Valvoline™ ATF+4® FULL Synthetic Automatic Transmission Fluid

Version: 1.5

VV346

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide
Hydrocarbons
Aldehydes
- Specific extinguishing methods :

Product is compatible with standard fire-fighting agents.
- Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.
- Other information : Comply with all applicable federal, state, and local regulations.

SAFETY DATA SHEET

Revision Date: 05/22/2017

Print Date: 10/30/2017

SDS Number: R0382635

Valvoline™ ATF+4® FULL Synthetic Automatic Transmission Fluid

Version: 1.5

VV346

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Do not breathe vapours/dust.
Do not smoke.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Container hazardous when empty.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0

SAFETY DATA SHEET

Revision Date: 05/22/2017

Print Date: 10/30/2017

SDS Number: R0382635

Valvoline™ ATF+4® FULL Synthetic Automatic Transmission Fluid

Version: 1.5

VV346

		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL

Hazardous components without workplace control parameters

Components	CAS-No.
Mineral Oil	
BENZENE, POLYPROPENE DERIVATIVES, SULFONATED, CALCIUM SALTS	
DODECYL HYDROXYPROPYL SULFIDE	67124-09-8
C14-C18 alpha-olefin epoxide, reaction products with boric acid	

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Hand protection

Remarks

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection

: Wear as appropriate:
Impervious clothing
Safety shoes
Choose body protection according to the amount and

SAFETY DATA SHEET

Revision Date: 05/22/2017

Print Date: 10/30/2017

SDS Number: R0382635

Valvoline™ ATF+4® FULL Synthetic Automatic Transmission Fluid

Version: 1.5

VV346

concentration of the dangerous substance at the work place.
Discard gloves that show tears, pinholes, or signs of wear.
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures : Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Physical state	: liquid
Colour	: red
Odour	: No data available
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: > 390 °F / > 199 °C Method: Cleveland open cup
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: 6 %(V) Calculated Explosive Limit
Lower explosion limit	: 1 %(V) Calculated Explosive Limit
Vapour pressure	: 0.0133333 hPa (21.11 °C) Calculated Vapor Pressure
Relative vapour density	: No data available
Relative density	: 0.854 (15.6 °C)
Density	: 0.8508 g/cm ³ (15.56 °C)
Solubility(ies)	
Water solubility	: negligible

SAFETY DATA SHEET

Revision Date: 05/22/2017

Print Date: 10/30/2017

SDS Number: R0382635

Valvoline™ ATF+4® FULL Synthetic Automatic Transmission Fluid

Version: 1.5

VV346

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : < 10,000 mPa.s Method: Brookfield

Viscosity, kinematic : ca. 34 mm²/s (40 °C)

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Product will not undergo hazardous polymerization.

Conditions to avoid : excessive heat

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : carbon dioxide and carbon monoxide
Hydrocarbons

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

**SAFETY DATA SHEET**

Revision Date: 05/22/2017

Print Date: 10/30/2017

SDS Number: R0382635

Valvoline™ ATF+4® FULL Synthetic Automatic Transmission Fluid

Version: 1.5

VV346

DODECYL HYDROXYPROPYL SULFIDE:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
GLP: yes

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: Not classified as acutely toxic by dermal absorption under GHS.

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks: May cause skin irritation in susceptible persons.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Slight, transient irritation

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Result: Slight, transient irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Slight, transient irritation

BENZENE, POLYPROPENE DERIVATIVES, SULFONATED, CALCIUM SALTS:

Result: Slight, transient irritation

DODECYL HYDROXYPROPYL SULFIDE:

Species: Rabbit

Result: No skin irritation

C14-C18 alpha-olefin epoxide, reaction products with boric acid:

Result: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Result: Slight, transient irritation

Remarks: Expected based on components.

Remarks: Unlikely to cause eye irritation or injury.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Slight, transient irritation

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Result: No eye irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

	Page: 10
SAFETY DATA SHEET	Revision Date: 05/22/2017
	Print Date: 10/30/2017
	SDS Number: R0382635
Valvoline™ ATF+4® FULL Synthetic Automatic Transmission Fluid VV346	Version: 1.5

Result: Slight, transient irritation

BENZENE, POLYPROPENE DERIVATIVES, SULFONATED, CALCIUM SALTS:
Result: Irritating to eyes.

DODECYL HYDROXYPROPYL SULFIDE:
Species: Rabbit
Result: No eye irritation

C14-C18 alpha-olefin epoxide, reaction products with boric acid:
Result: No eye irritation

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.
Respiratory sensitisation: Not classified based on available information.

Components:

BENZENE, POLYPROPENE DERIVATIVES, SULFONATED, CALCIUM SALTS:
Assessment: May cause sensitisation by skin contact.

DODECYL HYDROXYPROPYL SULFIDE:
Test Type: Local lymph node assay
Species: Guinea pig
Assessment: May cause sensitisation by skin contact.
Method: OECD Test Guideline 429

C14-C18 alpha-olefin epoxide, reaction products with boric acid:
Assessment: May cause sensitisation by skin contact.

Germ cell mutagenicity
Not classified based on available information.

Components:

DODECYL HYDROXYPROPYL SULFIDE:
Genotoxicity in vitro : Test Type: Ames test
Test species: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

SAFETY DATA SHEET

Revision Date: 05/22/2017

Print Date: 10/30/2017

SDS Number: R0382635

Valvoline™ ATF+4® FULL Synthetic Automatic Transmission Fluid

Version: 1.5

VV346

May be fatal if swallowed and enters airways.

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

Mineral Oil:

May be fatal if swallowed and enters airways.

Further information
Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION
Ecotoxicity
Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Acute aquatic toxicity Category 3; Harmful to aquatic life.

Chronic aquatic toxicity : Chronic aquatic toxicity Category 3; Harmful to aquatic life with long lasting effects.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Toxicity to fish : LL50 (Fish): > 100 mg/l

Toxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10,000 mg/l

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l

Toxicity to fish (Chronic toxicity) : NOEC (Fish): 10 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Aquatic invertebrates): 10 mg/l

DODECYL HYDROXYPROPYL SULFIDE:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.75 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: OECD Test Guideline 203
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 0.58 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: WAF

SAFETY DATA SHEET

Revision Date: 05/22/2017

Print Date: 10/30/2017

SDS Number: R0382635

Valvoline™ ATF+4® FULL Synthetic Automatic Transmission Fluid

Version: 1.5

VV346

Toxicity to algae : EL50 (Desmodesmus subspicatus (green algae)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: WAF

M-Factor (Acute aquatic toxicity) : 1

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL (Daphnia magna (Water flea)): 0.32 mg/l
Exposure time: 21 d
Test Type: semi-static test
Method: OECD Test Guideline 211
GLP: yes

M-Factor (Chronic aquatic toxicity) : 1

Persistence and degradability

DODECYL HYDROXYPROPYL SULFIDE:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 5 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

No data available

Bioaccumulative potential

DODECYL HYDROXYPROPYL SULFIDE:

Partition coefficient: n-octanol/water : log Pow: 4.7 - 6.5

No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS
Disposal methods

General advice : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and

**SAFETY DATA SHEET**

Revision Date: 05/22/2017

Print Date: 10/30/2017

SDS Number: R0382635

Valvoline™ ATF+4® FULL Synthetic Automatic Transmission Fluid

Version: 1.5

VV346

federal regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste
handling site for recycling or disposal.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION**International transport regulations****REGULATION**

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

TDG_INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

**SAFETY DATA SHEET**

Revision Date: 05/22/2017

Print Date: 10/30/2017

SDS Number: R0382635

Valvoline™ ATF+4® FULL Synthetic Automatic Transmission Fluid

Version: 1.5

VV346

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

***ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant

no

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know Act
CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
BENZENE	71-43-2	10	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
SULFUR DIOXIDE	7446-09-5	500	*
SULFUR DIOXIDE	7446-09-5		*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards : Acute Health Hazard**SARA 313**

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop 65

Proposition 65 warnings are not required for this product based on the results of a risk assessment.

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : Not in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

SAFETY DATA SHEET

Revision Date: 05/22/2017

Print Date: 10/30/2017

SDS Number: R0382635

Valvoline™ ATF+4® FULL Synthetic Automatic Transmission Fluid

Version: 1.5

VV346

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TSCA : On TSCA Inventory


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 05/22/2017

NFPA:	HMIS III:						
Flammability Health Instability Special hazard. 	<table border="1"> <tr> <td>HEALTH</td><td>2</td></tr> <tr> <td>FLAMMABILITY</td><td>1</td></tr> <tr> <td>PHYSICAL HAZARD</td><td>0</td></tr> </table> 0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic	HEALTH	2	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	2						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements

H304 May be fatal if swallowed and enters airways.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

	Page: 16
SAFETY DATA SHEET	Revision Date: 05/22/2017
	Print Date: 10/30/2017
	SDS Number: R0382635
Valvoline™ ATF+4® FULL Synthetic Automatic Transmission Fluid VV346	Version: 1.5

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists
 BEI : Biological Exposure Index
 CAS : Chemical Abstracts Service (Division of the American Chemical Society).
 CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
 FG : Food grade
 GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
 H-statement : Hazard Statement
 IATA : International Air Transport Association.
 IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization
 ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
 IMDG : International Maritime Code for Dangerous Goods
 ISO : International Organization for Standardization
 logPow : octanol-water partition coefficient
 LCxx : Lethal Concentration, for xx percent of test population
 LDxx : Lethal Dose, for xx percent of test population.
 ICxx : Inhibitory Concentration for xx of a substance
 Ecxx : Effective Concentration of xx
 N.O.S.: Not Otherwise Specified
 OECD : Organization for Economic Co-operation and Development
 OEL : Occupational Exposure Limit
 P-Statement : Precautionary Statement
 PBT : Persistent , Bioaccumulative and Toxic
 PPE : Personal Protective Equipment
 STEL : Short-term exposure limit
 STOT : Specific Target Organ Toxicity
 TLV : Threshold Limit Value
 TWA : Time-weighted average
 vPvB : Very Persistent and Very Bioaccumulative
 WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
 DOT : Department of Transportation
 FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
 HMIRC : Hazardous Materials Information Review Commission
 HMIS : Hazardous Materials Identification System
 NFPA : National Fire Protection Association
 NIOSH : National Institute for Occupational Safety and Health
 OSHA : Occupational Safety and Health Administration
 PMRA : Health Canada Pest Management Regulatory Agency
 RTK : Right to Know
 WHMIS : Workplace Hazardous Materials Information System

	Page: 17
SAFETY DATA SHEET	Revision Date: 05/22/2017
	Print Date: 10/30/2017
	SDS Number: R0382635
Valvoline™ ATF+4® FULL Synthetic Automatic Transmission Fluid VV346	Version: 1.5