		Page: 1
<b>SAFETY DATA SHEET</b>		Revision Date: 05/19/2017
		Print Date: 4/25/2018
		SDS Number: R0076416
Valvoline™ Multi-Vehicle Multi-Purpose Grease ™ Trademark, Valvoline or its subsidiaries, registered in various countries VV633		Version: 1.2

29 CFR 1910.1200 (OSHA HazCom 2012)

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

**Product identifier**

Trade name : Valvoline™ Multi-Vehicle Multi-Purpose Grease  
™ Trademark, Valvoline or its subsidiaries, registered in various countries

<b>Details of the supplier of the safety data sheet</b> Valvoline LLC 100 Valvoline Way Lexington, KY 40509 United States of America (USA) 1-800-TEAMVAL	<b>Emergency telephone number</b> 1-800-VALVOLINE (1-800-825-8654)  <b>Regulatory Information Number</b> 1-800-TEAMVAL  <b>Product Information</b> 1-800-TEAMVAL
---	---

**SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification**

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

**GHS label elements**

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Hazardous components**

Chemical name	CAS-No.	Classification	Concentration (%)
RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED	64742-01-4	This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).	50.00



**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 4/25/2018

SDS Number: R0076416


Version: 1.2

Valvoline™ Multi-Vehicle Multi-Purpose Grease  
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries  
 VV633

Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).	50.00
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHT	64742-52-5	This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).	9.9999
MOLYBDENUM DISULFIDE	1317-33-5	Not a hazardous substance or mixture.	2.4999

**SECTION 4. FIRST AID MEASURES**

- General advice : No hazards which require special first aid measures.
- If inhaled : If breathed in, move person into fresh air.  
 If unconscious, place in recovery position and seek medical advice.  
 If symptoms persist, call a physician.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Remove contact lenses.  
 Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.  
 Never give anything by mouth to an unconscious person.  
 If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes

	Page: 3
<b>SAFETY DATA SHEET</b>	Revision Date: 05/19/2017
	Print Date: 4/25/2018
	SDS Number: R0076416
Valvoline™ Multi-Vehicle Multi-Purpose Grease ™ Trademark, Valvoline or its subsidiaries, registered in various countries VV633	Version: 1.2

appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:  
 stomach or intestinal upset (nausea, vomiting, diarrhea)  
 irritation (nose, throat, airways)

Notes to physician : No hazards which require special first aid measures.

---

#### SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
 Water spray  
 Foam  
 Carbon dioxide (CO<sub>2</sub>)  
 Dry chemical
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide  
 Hydrocarbons  
 Aldehydes  
 Ketones  
 Nitrogen oxides (NO<sub>x</sub>)  
 Sulphur oxides
- Specific extinguishing methods :  
  
 Product is compatible with standard fire-fighting agents.
- Further information : Standard procedure for chemical fires.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

---

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 4/25/2018

SDS Number: R0076416

Version: 1.2

Valvoline™ Multi-Vehicle Multi-Purpose Grease  
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries  
 VV633

emergency procedures

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
 Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

**SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Smoking, eating and drinking should be prohibited in the application area.  
 For personal protection see section 8.

Materials to avoid : No materials to be especially mentioned.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED	64742-01-4	ST ESL	1,000 µg/m3	TX ESL
		AN ESL	100 µg/m3	TX ESL
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHT	64742-52-5	PEL	5 mg/m3 particulate	CAL PEL
		TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3	ACGIH

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 4/25/2018

SDS Number: R0076416

Version: 1.2

Valvoline™ Multi-Vehicle Multi-Purpose Grease  
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries  
 VV633

			Inhalable fraction	
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL
MOLYBDENUM DISULFIDE	1317-33-5	TWA	15 mg/m3 total dust (Molybdenum)	OSHA Z-1
		TWA	10 mg/m3 Inhalable fraction (Molybdenum)	ACGIH
		TWA	3 mg/m3 Respirable fraction (Molybdenum)	ACGIH
		TWA	10 mg/m3 Total dust (Molybdenum)	OSHA P0
		PEL	10 mg/m3 Total dust (Molybdenum)	CAL PEL
		PEL	3 mg/m3 respirable dust fraction (Molybdenum)	CAL PEL

**Engineering measures** : General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

**Personal protective equipment**

Respiratory protection : No personal respiratory protective equipment normally required.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Wear as appropriate:  
 Safety shoes  
 Wear resistant gloves (consult your safety equipment supplier).

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 4/25/2018

SDS Number: R0076416

Version: 1.2

Valvoline™ Multi-Vehicle Multi-Purpose Grease  
™ Trademark, Valvoline or its subsidiaries, registered in various  
countries  
VV633

Hygiene measures : General industrial hygiene practice.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : paste

Physical state : liquid

Colour : grey

Odour : hydrocarbon-like

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : 640 °F / 338 °C

Flash point : 500 °F / 260 °C

Evaporation rate :  
No data available

Flammability (solid, gas) : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure :  
No data available

Relative vapour density :  
No data available

Relative density : No data available

Density : 0.94 g/cm<sup>3</sup> (20 °C)

Solubility(ies)  
Water solubility : negligible

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 4/25/2018

SDS Number: R0076416

Version: 1.2

Valvoline™ Multi-Vehicle Multi-Purpose Grease  
™ Trademark, Valvoline or its subsidiaries, registered in various  
countries  
VV633

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : > 315 °C

Thermal decomposition : No data available

Viscosity  
Viscosity, dynamic : No data available

Viscosity, kinematic : > 20.5 mm<sup>2</sup>/s (40 °C)

Oxidizing properties : No data available

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Product will not undergo hazardous polymerization.

Conditions to avoid : None known.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : carbon dioxide and carbon monoxide  
Hydrocarbons

**SECTION 11. TOXICOLOGICAL INFORMATION**

Information on likely routes of exposure : Inhalation  
Skin contact  
Eye Contact  
Ingestion

**Acute toxicity**

Not classified based on available information.

**Product:**

Acute oral toxicity : LD50 (Rat): 6,477 mg/kg  
Method: Acute toxicity estimate

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 4/25/2018

SDS Number: R0076416

Version: 1.2

Valvoline™ Multi-Vehicle Multi-Purpose Grease  
™ Trademark, Valvoline or its subsidiaries, registered in various  
countries  
VV633

Acute dermal toxicity : LD50 (Rabbit): 169,492 mg/kg  
Method: Acute toxicity estimate

**Components:****RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Remarks: Information given is based on data obtained from  
similar substances.

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Assessment: Not classified as acutely toxic by inhalation  
under GHS.  
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: No adverse effect has been observed in acute  
dermal toxicity tests.

**Distillates (petroleum), solvent-dewaxed heavy paraffinic:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHT:**

Acute oral toxicity : LD50 (Rat): > 5 g/kg

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Assessment: Not classified as acutely toxic by inhalation  
under GHS.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Assessment: Not classified as acutely toxic by dermal  
absorption under GHS.  
Remarks: No mortality observed at this dose.

**MOLYBDENUM DISULFIDE:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 2.82 mg/l

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 4/25/2018

SDS Number: R0076416

Version: 1.2

Valvoline™ Multi-Vehicle Multi-Purpose Grease  
™ Trademark, Valvoline or its subsidiaries, registered in various  
countries  
VV633

Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: No adverse effect has been observed in acute  
inhalation toxicity tests.

**Skin corrosion/irritation**

Not classified based on available information.

**Components:**

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:

Species: Rabbit

Result: No skin irritation

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Result: Slight, transient irritation

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHT:

Species: Rabbit

Result: No skin irritation

MOLYBDENUM DISULFIDE:

Result: No skin irritation

**Serious eye damage/eye irritation**

Not classified based on available information.

**Product:**

Remarks: Unlikely to cause eye irritation or injury.

**Components:**

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:

Species: Rabbit

Result: Slight, transient irritation

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Result: Slight, transient irritation

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHT:

Species: Rabbit

Result: Slight, transient irritation

MOLYBDENUM DISULFIDE:

Result: No eye irritation

**Respiratory or skin sensitisation**

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.


**Components:**

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:

Test Type: Buehler Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

	Page: 10
<b>SAFETY DATA SHEET</b>	Revision Date: 05/19/2017
	Print Date: 4/25/2018
	SDS Number: R0076416
Valvoline™ Multi-Vehicle Multi-Purpose Grease ™ Trademark, Valvoline or its subsidiaries, registered in various countries VV633	Version: 1.2

Method: OECD Test Guideline 406

Distillates (petroleum), solvent-dewaxed heavy paraffinic:  
Test Type: Buehler Test  
Species: Guinea pig  
Assessment: Does not cause skin sensitisation.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHT:  
Species: Guinea pig  
Assessment: Does not cause skin sensitisation.  
Method: OECD Test Guideline 406

Germ cell mutagenicity  
Not classified based on available information.

**Components:**

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:

Genotoxicity in vitro : Test Type: Ames test  
Test species: Salmonella typhimurium  
Metabolic activation: with and without metabolic activation  
Result: negative

**Carcinogenicity**

Not classified based on available information.

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

Not classified based on available information.

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**Product:**

No aspiration toxicity classification

**Components:**

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:

No aspiration toxicity classification

Distillates (petroleum), solvent-dewaxed heavy paraffinic:  
No aspiration toxicity classification

**Further information**

**Product:**

Remarks: No data available

**Carcinogenicity:**

**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 4/25/2018

SDS Number: R0076416

Version: 1.2

 Valvoline™ Multi-Vehicle Multi-Purpose Grease  
 ™ Trademark, Valvoline or its subsidiaries, registered in various  
 countries  
 VV633

human carcinogen by IARC.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

---

**SECTION 12. ECOLOGICAL INFORMATION**
**Ecotoxicity**
**Product:**

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

**Components:**

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:

 Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
 Exposure time: 96 h  
 Test Type: static test  
 Test substance: WAF  
 Method: OECD Test Guideline 203

 Toxicity to daphnia and other aquatic invertebrates : EL50 (Scud (Gammarus pulex)): > 10,000 mg/l  
 Exposure time: 48 h  
 Test Type: semi-static test  
 Method: OECD Test Guideline 202

 Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l  
 End point: Growth inhibition  
 Exposure time: 72 h  
 Test Type: static test  
 Test substance: WAF  
 Method: OECD Test Guideline 201

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

 Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
 Exposure time: 96 h  
 Test Type: static test  
 Test substance: WAF

 Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l  
 Exposure time: 48 h

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 4/25/2018

SDS Number: R0076416

Version: 1.2

Valvoline™ Multi-Vehicle Multi-Purpose Grease  
 ™ Trademark, Valvoline or its subsidiaries, registered in various  
 countries  
 VV633

Test Type: static test  
 Test substance: WAF

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (algae)): >= 100 mg/l  
 End point: Growth inhibition  
 Exposure time: 72 h  
 Test Type: static test  
 Test substance: WAF

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHT:**

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
 Exposure time: 96 h  
 Test Type: static test  
 Test substance: WAF  
 Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l  
 Exposure time: 48 h  
 Test Type: static test  
 Test substance: WAF  
 Method: OECD Test Guideline 202

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l  
 End point: Growth inhibition  
 Exposure time: 72 h  
 Test Type: static test  
 Test substance: WAF  
 Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL (Daphnia (water flea)): 10 mg/l  
 Exposure time: 21 d  
 Test Type: semi-static test  
 Test substance: WAF  
 Method: OECD Test Guideline 211

**Persistence and degradability****Components:****RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:**

Biodegradability : Result: Not readily biodegradable.  
 Biodegradation: 2 - 4 %  
 Exposure time: 28 d  
 Method: OECD Test Guideline 301B  
 Remarks: Information given is based on data obtained from similar substances.

Distillates (petroleum), solvent-dewaxed heavy paraffinic:  
 Biodegradability : Result: Inherently biodegradable.  
 Method: OECD Test Guideline 301F



**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 4/25/2018

SDS Number: R0076416

Version: 1.2

Valvoline™ Multi-Vehicle Multi-Purpose Grease  
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries  
 VV633

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHT:  
 Biodegradability : Result: Inherently biodegradable.  
 Biodegradation: 31 %  
 Exposure time: 28 d  
 Method: OECD Test Guideline 301F

No data available

**Bioaccumulative potential**

**Components:**

No data available

**Mobility in soil**

**Components:**

No data available

**Other adverse effects**

No data available

**Product:**

Additional ecological information : No data available

**Components:**

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods**

General advice : Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.

**SECTION 14. TRANSPORT INFORMATION**

**International transport regulations**

**REGULATION**

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

**U.S. DOT - ROAD**

Not dangerous goods
---------------------

**CFR\_RAIL\_C**

Not dangerous goods
---------------------

**U.S. DOT - INLAND WATERWAYS**

Not dangerous goods
---------------------



**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 4/25/2018

SDS Number: R0076416

Version: 1.2

Valvoline™ Multi-Vehicle Multi-Purpose Grease  
™ Trademark, Valvoline or its subsidiaries, registered in various countries  
VV633

**TDG\_ROAD\_C**

Not dangerous goods

**TDG\_RAIL\_C**

Not dangerous goods

**TDG\_INWT\_C**

Not dangerous goods

**INTERNATIONAL MARITIME DANGEROUS GOODS**

Not dangerous goods

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO**

Not dangerous goods

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER**

Not dangerous goods

**MX\_DG**

Not dangerous goods

**\*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

**SECTION 15. REGULATORY INFORMATION**

**EPCRA - Emergency Planning and Community Right-to-Know Act  
CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : No SARA Hazards

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 4/25/2018

SDS Number: R0076416

Version: 1.2

Valvoline™ Multi-Vehicle Multi-Purpose Grease  
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries  
 VV633

**SARA 313**

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**California Prop 65**

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

**The components of this product are reported in the following inventories:**

- DSL : All components of this product are on the Canadian DSL
- AICS : On the inventory, or in compliance with the inventory
- ENCS : Not in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory
- TSCA : On TSCA Inventory


**Inventories**

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)


**SECTION 16. OTHER INFORMATION**

**Further information**

Revision Date: 05/19/2017

<p><b>NFPA:</b></p> <div style="text-align: center;"> <p>Flammability</p>  <p>Health      Instability</p> <p>Special hazard.</p> </div>	<p><b>HMIS III:</b></p> <table border="1" style="width: 100%;"> <tr> <td style="background-color: blue; color: white;"><b>HEALTH</b></td> <td style="text-align: center;"><b>0</b></td> </tr> <tr> <td style="background-color: red; color: white;"><b>FLAMMABILITY</b></td> <td style="text-align: center;"><b>1</b></td> </tr> <tr> <td style="background-color: yellow;"><b>PHYSICAL HAZARD</b></td> <td style="text-align: center;"><b>0</b></td> </tr> </table> <p>0 = not significant, 1 =Slight,                  2 = Moderate, 3 = High                  4 = Extreme, * = Chronic</p>	<b>HEALTH</b>	<b>0</b>	<b>FLAMMABILITY</b>	<b>1</b>	<b>PHYSICAL HAZARD</b>	<b>0</b>
<b>HEALTH</b>	<b>0</b>						
<b>FLAMMABILITY</b>	<b>1</b>						
<b>PHYSICAL HAZARD</b>	<b>0</b>						

**NFPA Flammable and Combustible Liquids Classification**

	Page: 16
<b>SAFETY DATA SHEET</b>	Revision Date: 05/19/2017
	Print Date: 4/25/2018
	SDS Number: R0076416
Valvoline™ Multi-Vehicle Multi-Purpose Grease ™ Trademark, Valvoline or its subsidiaries, registered in various countries VV633	Version: 1.2

Combustible Liquid Class IIIB

### Full text of H-Statements

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit


P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

	Page: 17
<b>SAFETY DATA SHEET</b>	Revision Date: 05/19/2017
	Print Date: 4/25/2018
	SDS Number: R0076416
Valvoline™ Multi-Vehicle Multi-Purpose Grease ™ Trademark, Valvoline or its subsidiaries, registered in various countries VV633	Version: 1.2

TLV : Threshold Limit Value  
TWA : Time-weighted average  
vPvB : Very Persistent and Very Bioaccumulative  
WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act  
DOT : Department of Transportation  
FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act  
HMIRC : Hazardous Materials Information Review Commission  
HMIS : Hazardous Materials Identification System  
NFPA : National Fire Protection Association  
NIOSH : National Institute for Occupational Safety and Health  
OSHA : Occupational Safety and Health Administration  
PMRA : Health Canada Pest Management Regulatory Agency  
RTK : Right to Know  
WHMIS : Workplace Hazardous Materials Information System