

Valvoline™ HEAVY DUTY SYNTHETIC SAE 50 MANUAL TRANSMISSION FLUID

Version: 1.5 Revision Date: 03/10/2022 Print Date: 05/02/2023

29 CFR 1910.1200 (OSHA HazCom 2012)

# **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

**Product identifier** 

Trade name : Valvoline™ HEAVY DUTY SYNTHETIC SAE 50 MANUAL

TRANSMISSION FLUID

Product code : VV70601

Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Transmission Fluid

Details of the supplier of the safety data sheet

Valvoline LLC 100 Valvoline Way Lexington, KY 40509

United States of America (USA) 1-800-TEAMVAL (1-800-832-6825)

SDS@valvoline.com

Emergency telephone number 1-800-VALVOLINE (1-800-825-8654)

Regulatory Information Number 1-800-TEAMVAL (1-800-832-6825)

**Product Information** 

1-800-TEAMVAL (1-800-832-6825)

#### **SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification** 

Not a hazardous substance or mixture.

**GHS** label elements

Not a hazardous substance or mixture.

Other hazards

None known.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

Chemical nature : Defatter

**Hazardous components** 

Chemical name	CAS-No.	Classification	Concentration (%)
Distillates (Petroleum),	64742-54-7	Asp. Tox. 1; H304	>=50.00 - < 60.00



Valvoline™ HEAVY DUTY SYNTHETIC SAE 50 MANUAL TRANSMISSION FLUID

Version: 1.5 Revision Date: 03/10/2022 Print Date: 05/02/2023

Hydrotreated Heavy Paraffinic			
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC		Not a hazardous substance or mixture.	>=5.00 - < 10.00
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	=	Not a hazardous substance or mixture.	>=1.50 - < 5.00

Actual concentration is withheld as a trade secret

### **SECTION 4. FIRST AID MEASURES**

General advice : Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Induce vomiting immediately and call a physician.

Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

: No symptoms known or expected.

Notes to physician : No hazards which require special first aid measures.

Treat symptomatically.

#### **SECTION 5. FIREFIGHTING MEASURES**

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion : carbon dioxide and carbon monoxide



Valvoline™ HEAVY DUTY SYNTHETIC SAE 50 MANUAL TRANSMISSION FLUID

Version: 1.5 Revision Date: 03/10/2022 Print Date: 05/02/2023

products

Specific extinguishing

Further information

methods

: Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

: Wipe up with absorbent material (e.g. cloth, fleece). Keep in suitable, closed containers for disposal.

# **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Electrical installations / working materials must comply with

the technological safety standards.

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type	Control	Basis
		(Form of	parameters /	
		exposure)	Permissible	
			concentration	



Valvoline™ HEAVY DUTY SYNTHETIC SAE 50 MANUAL TRANSMISSION FLUID

Version: 1.5 Revision Date: 03/10/2022 Print Date: 05/02/2023

Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	TWA	5 mg/m3 Mist	OSHA Z-1
, , ,		TWA	5 mg/m3 Inhalable particulate matter	ACGIH
		PEL	5 mg/m3 particulate	CAL PEL
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC		TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable particulate matter	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable particulate matter	ACGIH
		PEL	5 mg/m3 particulate	CAL PEL

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally

required.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.



Valvoline™ HEAVY DUTY SYNTHETIC SAE 50 MANUAL TRANSMISSION FLUID

Version: 1.5 Revision Date: 03/10/2022 Print Date: 05/02/2023

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Colour : amber

Odour : mild

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : No data available

Flash point :  $> 376 \, ^{\circ}\text{F} \, / > 191 \, ^{\circ}\text{C}$ 

Method: closed cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Self-ignition : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : 0.8610 g/cm3 (68 °F / 20 °C)

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available



Valvoline™ HEAVY DUTY SYNTHETIC SAE 50 MANUAL TRANSMISSION FLUID

Version: 1.5 Revision Date: 03/10/2022 Print Date: 05/02/2023

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 135.31 mm2/s (104 °F / 40 °C)

Oxidizing properties : No data available

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Conditions to avoid : None known.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products No hazardous decomposition products are known.

### **SECTION 11. TOXICOLOGICAL INFORMATION**

#### **Acute toxicity**

Not classified based on available information.

**Product:** 

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Components:

**Distillates (Petroleum), Hydrotreated Heavy Paraffinic:**Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

#### **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

Skin corrosion/irritation

Not classified based on available information.

# Valvoline,

#### SAFETY DATA SHEET

Valvoline™ HEAVY DUTY SYNTHETIC SAE 50 MANUAL TRANSMISSION FLUID

Version: 1.5 Revision Date: 03/10/2022 Print Date: 05/02/2023

**Components:** 

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:
Assessment : Slight, transient irritation
Result : Slight, transient irritation

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Assessment : Slight, transient irritation Result : Slight, transient irritation

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Assessment : Slight, transient irritation Result : Slight, transient irritation

Serious eye damage/eye irritation

Not classified based on available information.

**Components:** 

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Result : No eye irritation
Assessment : No eye irritation

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Result : Slight, transient irritation
Assessment : Slight, transient irritation

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:** 

Result : No eye irritation Assessment : No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

**Components:** 

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:** 

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

IARC Group 1: Carcinogenic to humans

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC

64742-65-0

(Mineral oils, untreated or mildly treated)

# Valvoline,

# SAFETY DATA SHEET

Valvoline™ HEAVY DUTY SYNTHETIC SAE 50 MANUAL TRANSMISSION FLUID

Version: 1.5 Revision Date: 03/10/2022 Print Date: 05/02/2023

**OSHA**No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP Known to be human carcinogen

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC

64742-65-0

(Mineral Oils: Untreated and Mildly Treated)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

**Aspiration toxicity** 

Not classified based on available information.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

May be fatal if swallowed and enters airways.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

No aspiration toxicity classification

**Further information** 

Product:

Remarks : No data available

# **SECTION 12. ECOLOGICAL INFORMATION**

Ecotoxicity Product:

Frouuct.

Toxicity to fish : LC50 (Fish): > 10 - 100 mg/l

Ecotoxicology Assessment

Short-term (acute) aquatic

hazard

: Acute aquatic toxicity Category 3; Harmful to aquatic life.

Long-term (chronic) aquatic

hazard

: Chronic aquatic toxicity Category 3; Harmful to aquatic life

with long lasting effects.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Toxicity to fish : LL50 (Fish): > 100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

: EL50 (Aquatic invertebrates): > 10,000 mg/l

Exposure time: 48 h

# Valvoline...

# SAFETY DATA SHEET

Valvoline™ HEAVY DUTY SYNTHETIC SAE 50 MANUAL TRANSMISSION FLUID

Version: 1.5 Revision Date: 03/10/2022 Print Date: 05/02/2023

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l

Exposure time: 72 h

Toxicity to fish (Chronic

toxicity)

: NOEC (Fish): 10 mg/l

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEC (Aquatic invertebrates): 10 mg/l

Ecotoxicology Assessment

Short-term (acute) aquatic

hazard

: Not classified based on available information.

Long-term (chronic) aquatic

hazard

: Not classified based on available information.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Toxicity to fish

: LL50 (Fish): > 100 mg/l Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EL50 (Aquatic invertebrates): > 10,000 mg/l

Exposure time: 48 h

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l

Exposure time: 72 h

Toxicity to fish (Chronic

toxicity)

: NOEC (Fish): 10 mg/l

aquatic invertebrates (Chronic toxicity)

Toxicity to daphnia and other : NOEC (Aquatic invertebrates): 10 mg/l

Ecotoxicology Assessment

Short-term (acute) aquatic

hazard

: Not classified based on available information.

Long-term (chronic) aquatic

hazard

: Not classified based on available information.

Persistence and degradability

**Components:** 

No data available

Bioaccumulative potential

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Partition coefficient: n-

octanol/water

: log Pow: Expected > 7



Valvoline™ HEAVY DUTY SYNTHETIC SAE 50 MANUAL TRANSMISSION FLUID

Version: 1.5 Revision Date: 03/10/2022 Print Date: 05/02/2023

No data available

Mobility in soil

Components:

No data available

Other adverse effects

No data available

**Product:** 

Remarks

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I Substances This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act

Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological

information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life

with long lasting effects.

# Components:

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

#### Disposal methods

General advice : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

#### **SECTION 14. TRANSPORT INFORMATION**

#### International Regulations

#### **UNRTDG**

Not regulated as a dangerous good

#### IATA-DGR

Not regulated as a dangerous good

#### **IMDG-Code**

Not regulated as a dangerous good

# Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

# **National Regulations**



Valvoline™ HEAVY DUTY SYNTHETIC SAE 50 MANUAL TRANSMISSION FLUID

Version: 1.5 Revision Date: 03/10/2022 Print Date: 05/02/2023

#### **CFR ROAD**

Not regulated as a dangerous good

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

#### **SECTION 15. REGULATORY INFORMATION**

## **EPCRA - Emergency Planning and Community Right-to-Know Act**

#### **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

# SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : No SARA Hazards

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

#### **Clean Water Act**

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

#### The components of this product are reported in the following inventories:

TCSI : Not in compliance with the inventory



Valvoline™ HEAVY DUTY SYNTHETIC SAE 50 MANUAL TRANSMISSION FLUID

Version: 1.5 Revision Date: 03/10/2022 Print Date: 05/02/2023

TSCA : All substances listed as active on the TSCA inventory

AIIC : Not in compliance with the inventory

DSL : All components of this product are on the Canadian DSL

ENCS : On the inventory, or in compliance with the inventory

ISHL : Not in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

TECI: Not in compliance with the inventory

## **TSCA list**

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

#### **Inventories**

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

#### **SECTION 16. OTHER INFORMATION**


#### **Further information**

Internal information: R0284085



Valvoline™ HEAVY DUTY SYNTHETIC SAE 50 MANUAL TRANSMISSION FLUID

Version: 1.5 Revision Date: 03/10/2022 Print Date: 05/02/2023



NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

#### **Full text of H-Statements**

H304 May be fatal if swallowed and enters airways.

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet:

ACGIH: American Conference of Industrial Hygienists

BEI: Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization



Valvoline™ HEAVY DUTY SYNTHETIC SAE 50 MANUAL TRANSMISSION FLUID

Version: 1.5 Revision Date: 03/10/2022 Print Date: 05/02/2023

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx: Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV : Threshold Limit Value TWA : Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

DOT: Department of Transportation

FIFRA: Federal Insecticide, Fungicide, and Rodenticide Act HMIRC: Hazardous Materials Information Review Commission

HMIS: Hazardous Materials Identification System NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety and Health Administration

PMRA: Health Canada Pest Management Regulatory Agency

RTK: Right to Know

WHMIS: Workplace Hazardous Materials Information System