ASHLAND,	Page: 1
SAFETY DATA SHEET	Revision Date: 05/23/2015
	Print Date: 5/28/2015
	SDS Number: R0172170
Valvoline™ GM MULTIPURPOSE GREASE	Version: 1.0
VV615	

29 CFR 1910.1200 (OSHA HazCom 2012)

# **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

**Product identifier** 

Trade name

: Valvoline™ GM MULTIPURPOSE

**GREASE** 

# Recommended use of the chemical and restrictions on use

Details of the supplier of the safety data	Emergency telephone number
sheet	1-800-ASHLAND (1-800-274-5263)
Ashland	, , ,
P.O. Box 2219	Regulatory Information Number
Columbus, OH 43216	1-800-325-3751
United States of America	
	Product Information
	614-790-3333
EHS Customer Requests@ashland.com	
, <u>-</u>	

# **SECTION 2. HAZARDS IDENTIFICATION**

# **GHS Classification**

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

### **GHS Label element**

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

# Other hazards

None known.

# **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture

: Mixture

Chemical nature

: Defatter

## **Hazardous components**

Chemical Name	CAS-No.	Classification	Concentration (%)
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0	Asp. Tox. 1; H304	74.99
ASPHALT	8052-42-4	Not a hazardous	24.99

ASHLAND.	Page: 3
SAFETY DATA SHEET	Revision Date: 05/23/2015
	Print Date: 5/28/2015
	SDS Number: R0172170
Valvoline™ GM MULTIPURPOSE GREASE	Version: 1.0
VV615	

# **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray Foam

Carbon dioxide (CO2)

Dry chemical

Specific hazards during

firefighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

carbon dioxide and carbon monoxide

sulfur oxides Hydrocarbons Aldehydes Ketones

Nitrogen oxides (NOx)

Sulphur oxides

Specific extinguishing

methods

٠

Product is compatible with standard fire-fighting agents.

Further information : Standard procedure for chemical fires.

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

ASHLAND	Page: 5
SAFETY DATA SHEET	Revision Date: 05/23/2015
	Print Date: 5/28/2015
	SDS Number: R0172170
Valvoline™ GM MULTIPURPOSE GREASE	Version: 1.0
VV615	

## Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally

required.

Eye protection : Not required under normal conditions of use. Wear splash-

proof safety goggles if material could be misted or splashed

into eyes.

Skin and body protection : Wear as appropriate:

Safety shoes

Wear resistant gloves (consult your safety equipment

supplier).

Hygiene measures : General industrial hygiene practice.

# **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : gel

Physical state : liquid

Colour : red

Odour : No data available

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

: 640 °F / 338 °C

Flash point : 471 °F / 244 °C

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : < 0.01 mmHg (20 °C)

Relative vapour density : No data available

Relative density : 0.95 (15.6 °C)

ASHLAND.	Page: 7
SAFETY DATA SHEET	Revision Date: 05/23/2015
	Print Date: 5/28/2015
	SDS Number: R0172170
Valvoline™ GM MULTIPURPOSE GREASE	Version: 1.0
VV615	

Acute oral toxicity Acute toxicity estimate (Rat): 3,019 mg/kg

Acute dermal toxicity 
Acute toxicity estimate (Rabbit): 169,492 mg/kg

**Components:** 

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Acute oral toxicity : LD 50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD 50 (Rabbit): > 5,000 mg/kg

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA:

Acute oral toxicity : LD 50 (Rat): > 5 g/kg

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: OECD Test Guideline 403

Assessment: Not classified as acutely toxic by inhalation

under GHS.

Acute dermal toxicity : LD 50 (Rabbit): > 2,000 mg/kg

Assessment: Not classified as acutely toxic by dermal

absorption under GHS.

Remarks: No mortality observed at this dose.

### Skin corrosion/irritation

Not classified based on available information.

**Product:** 

Result: Not irritating to skin

Result: Repeated exposure may cause skin dryness or cracking.

# **Components:**

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Result: Mildly irritating to skin

**ASPHALT:** 

Result: Not irritating to skin

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA:

Species: Rabbit

Result: Not irritating to skin

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Result: Not irritating to eyes

Remarks: Unlikely to cause eye irritation or injury.

Components:

ASHLAND.	Page: 9
SAFETY DATA SHEET	Revision Date: 05/23/2015
	Print Date: 5/28/2015
	SDS Number: R0172170
Valvoline™ GM MULTIPURPOSE GREASE	Version: 1.0
VV615	

### **SECTION 12. ECOLOGICAL INFORMATION**

## **Ecotoxicity**

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA:

Toxicity to fish

: LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h
Test Type: static test
Test substance: WAF

Method: OECD Test Guideline 203

Toxicity to daphnia and other

aquatic invertebrates

: EL50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 48 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 202

Toxicity to algae

: NOEL (Pseudokirchneriella subcapitata (green algae)): >=

100 mg/l

End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 201

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEL (Daphnia (water flea)): 10 mg/l

Exposure time: 21 d Test Type: semi-static test Test substance: WAF

Method: OECD Test Guideline 211

## Persistence and degradability

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA:

Biodegradability

Result: Inherently biodegradable

Biodegradation: 31 % Exposure time: 28 d

Method: OECD Test Guideline 301F

# **Bioaccumulative potential**

No data available

Mobility in soll
No data available

Other adverse effects

No data available

**Product:** 

Additional ecological

information

: No data available

ASHLAND.	Page: 11
SAFETY DATA SHEET	Revision Date: 05/23/2015
	Print Date: 5/28/2015
	SDS Number: R0172170
Valvoline™ GM MULTIPURPOSE GREASE	Version: 1.0
VV615	

INTERNATIONAL	AID	TRANSPORT	ACCOCIATION	DASSENCED
INTERNATIONAL	AIR	TRANSPORT	ASSOCIATION :	- PASSENGER

Not dangerous goods

# MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

Not dangerous goods

## \*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

#### SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards

: No SARA Hazards

**SARA 313** 

Component(s)SARA 313

: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop 65

Proposition 65 warnings are not required for this product

based on the results of a risk assessment.

The components of this product are reported in the following inventories:

**TSCA** 

: On TSCA Inventory

**AUSTR** 

: On the inventory, or in compliance with the inventory

**D\$L** 

: All components of this product are on the Canadian DSL.

**ENCS** 

: On the inventory, or in compliance with the inventory

**KECL** 

: On the inventory, or in compliance with the inventory

**PICCS** 

: On the inventory, or in compliance with the inventory

.\_\_\_\_

**IECSC** 

: On the inventory, or in compliance with the inventory

#### **Inventories**

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

ASHLAND.	Page: 13
SAFETY DATA SHEET	Revision Date: 05/23/2015
	Print Date: 5/28/2015
	SDS Number: R0172170
Valvoline™ GM MULTIPURPOSE GREASE	Version: 1.0
VV615	

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx: Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment STEL : Short-term exposure limit STOT : Specific Target Organ Toxicity

TLV: Threshold Limit Value TWA: Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

**DOT**: Department of Transportation

FIFRA: Federal Insecticide, Fungicide, and Rodenticide Act HMIRC: Hazardous Materials Information Review Commission

HMIS: Hazardous Materials Identification System NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety and Health Administration PMRA: Health Canada Pest Management Regulatory Agency

RTK: Right to Know

WHMIS: Workplace Hazardous Materials Information System