

Code

# MATERIAL SAFETY DATA SHEET

### Volvo Automatic Transmission Fluid AT102

15142868

## 1. Product and company identification

Trade name : Volvo Automatic Transmission Fluid

AT102

: 15142868

Material uses : Industrial applications: oil

Supplier : Volvo Construction Equipment North

America, Inc. 312 Volvo Way

Shippensburg, PA 17257

**United States** 

**Telephone no.** : + 1 (877) 823-1111

### 2. Hazards identification

Physical state : Liquid.

Odor : Characteristic.

Emergency overview : PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION.

Keep out of the reach of children. If ingested, do not induce vomiting. Seek medical advice immediately. Minimise skin contact. Protect the environment. Dispose of used oil

In case of emergency

1-800-535-5053

at designated sites. Do not mix used oil with solvents, brake fluids or coolants.

Routes of entry : Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects

**Inhalation** ; Slightly irritating to the respiratory system. Can enter lungs and cause damage.

Skin : Slightly irritating to the skin.

Eyes : Slightly irritating to the eyes.

**Ingestion**: Ingestion may cause gastrointestinal irritation and diarrhea.

Potential chronic health effects

Chronic effects : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or

dermatitis.

Medical conditions

aggravated by over-

exposure

: Pre-existing skin disorders may be aggravated by over-exposure to this product.

Over-exposure signs/

symptoms

: Skin inflammation is characterized by itching, scaling, reddening or, occasionally,

blistering.skin lesion/eczema

Environmental effects : Ecotoxicological data on the substances included in this product show that the product is not classified as harmful to the environment. Oils are in general persistent in the

is not classified as harmful to the environment. Oils are in general persistent in the environment. Upon release the oil spreads on the soil or water surface and can affect

the area for a long time.

See toxicological information (Section 11)

# 3. Composition/information on ingredients

Name Mineral Oil, Solvent refined CAS number 60 - 100

Methacrylate copolymer 1 - 5

### 4. First aid measures

Inhalation : If inhaled, remove to fresh air. Get medical attention if symptoms occur.

Eye contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.

Get medical attention if symptoms occur.

**Skin contact**: Wash with soap and water. Get medical attention if symptoms occur.

**Ingestion**: If swallowed, do not induce vomiting unless directed to do so by medical personnel. Get

medical attention.

### 5. Fire-fighting measures

**Flammability of the product**: No specific fire or explosion hazard.

**Extinguishing media** 

Suitable : Recommended: alcohol-resistant foam CO<sub>2</sub> powders .

Not suitable : Do not use water jet.

Hazardous combustion

products

: Aldehydes, Carbon dioxide (CO<sub>2</sub>)., sulfur oxides (SO<sub>2</sub>, SO<sub>3</sub> etc.)

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing

apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### 6. Accidental release measures

Personal precautions

: Refer to protective measures listed in sections 7 and 8.

**Environmental precautions** 

 Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental

pollution (sewers, waterways, soil or air).

Spill

: Absorb with an inert material and transfer the spilled material and absorbent to an appropriate waste disposal container. Waste must be disposed of in accordance with federal, state and local environmental control regulations.

# 7. Handling and storage

Handling

: Wash thoroughly after handling.

Storage

: Keep container tightly closed in a cool, well-ventilated place. To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. Do not store in unlabeled containers.

# 8. Exposure controls/personal protection

Product name Exposure limits

No exposure limit value known.

Engineering measures

: Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits.

Personal protection

Eyes : Use safety eyewear designed to protect against splash of liquids.

**Skin** : Protective clothing

**Respiratory**: Wear appropriate respirator when ventilation is inadequate.

**Hands** : Chemical-resistant gloves.

**Hygiene measures**: Wash hands, forearms and face thoroughly after handling chemical products, before

eating, smoking and using the lavatory and at the end of the working period.

2/4

Date of issue : 2013-10-01.

#### Physical and chemical properties 9.

Physical state : Liquid. Color Red.

Odor : Characteristic.

Flash point : Open cup: >180°C (>356°F) [Cleveland.]

Flammable limits : Lower: 0,9%

Upper: 7%

: >316°C (>600,8°F) Boiling/condensation point

Relative density : 0,846

Vapor pressure : 0,013 kPa (0,1 mm Hg)

Vapor density : 2 [Air = 1]

: Kinematic (40°C (104°F)): 0,3 cm<sup>2</sup>/s (30 cSt) **Viscosity** 

Solubility : Insoluble in the following materials: cold water and hot water.

### 10 . Stability and reactivity

Stability : Stable under recommended storage and handling conditions (see Section 7).

Conditions to avoid : heat. Keep away from sources of ignition.

Materials to avoid : Reactive or incompatible with the following materials:

oxidizing materials

Hazardous decomposition

products

: Aldehydes, Carbon dioxide (CO<sub>2</sub>)., sulfur oxides (SO<sub>2</sub>, SO<sub>3</sub> etc.)

Hazardous polymerization **Conditions of reactivity** 

: Under normal conditions of storage and use, hazardous polymerization will not occur. : Flammable in the presence of the following materials or conditions: open flames, sparks

and static discharge and heat.

### **Toxicological information**

**Acute toxicity** 

Product/ingredient name Result **Species** Dose **Exposure** 

Not applicable.

Carcinogenicity

**ACGIH IARC EPA NIOSH** NTP **OSHA** Product/ingredient name

Not applicable.

Other toxic effects on : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or

dermatitis. humans

# 12. Ecological information

**Environmental effects** 

Ecotoxicological data on the substances included in this product show that the product is not classified as harmful to the environment. Oils are in general persistent in the environment. Upon release the oil spreads on the soil or water surface and can affect the area for a long time.

### 13. Disposal considerations

Waste disposal : Waste must be disposed of in accordance with federal, state and local environmental

control regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

3/4

#### Volvo Automatic Transmission Fluid AT102

### 14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	Not regulated.	-	-	-		
TDG Classification	Not regulated.	-	-	-		
IMDG Class	Not regulated.	-	-	-		-
IATA-DGR Class	Not regulated.	-	-	-		

PG\*: Packing group

# 15. Regulatory information

WHMIS (Canada)Canada inventoryNot controlled under WHMIS (Canada).This product is in compliance with DSL.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

### 16. Other information

Emergency overview (label) : PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION.

Keep out of the reach of children. If ingested, do not induce vomiting. Seek medical advice immediately. Minimise skin contact. Protect the environment. Dispose of used oil

at designated sites. Do not mix used oil with solvents, brake fluids or coolants.

Date of issue : 2013-10-01.

Date of previous issue : 2013-03-11.

Indicates information that has changed from previously issued version.

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.