

# **Material Safety Data Sheet**

Revision Date: 29-Apr-2014 Revision Number: 13

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name ben PREMIUM INTERIOR LATEX FLAT FINISH

Product Code W625

Product Class WATER THINNED PAINT

**Color** All

Manufacturer Emergency Telephone Number(s)

Benjamin Moore & Co. CHEMTREC: 800-424-9300
101 Paragon Drive

Montvale, NJ 07645 Phone: 855-724-6802 www.benjaminmoore.com

# 2. COMPOSITION INFORMATION ON COMPONENTS

**Hazardous Components** 

Chemical Name	CAS-No	Weight % (max)
Limestone	1317-65-3	30
Nepheline syenite	37244-96-5	30
Titanium dioxide	13463-67-7	20
Kaolin	1332-58-7	5
Diatomaceous earth	61790-53-2	5
Silica, amorphous	7631-86-9	5
Aluminum hydroxide	21645-51-2	5
Distillates, petroleum, hydrotreated heavy paraffinic	64742-54-7	1
Distillates (petroleum), solvent-dewaxed heavy	64742-65-0	1
paraffinic		
Distillates, petroleum, solvent-refined heavy paraffinic	64741-88-4	0.5

# 3. HAZARDS IDENTIFICATION

### **Emergency Overview**

Vapors may be irritating to eyes, nose, throat, and lungs. May cause skin irritation and/or dermatitis.

Appearance liquid Odor little or no odor

**Potential Health Effects** 

**Principal Routes of Exposure** Eye contact, skin contact and inhalation.

**Acute Effects** 

**Eyes** May cause slight irritation.

**Skin Inhalation**Substance may cause slight skin irritation.
May cause irritation of respiratory tract.

**Ingestion** Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

**Chronic Effects** Repeated contact may cause allergic reactions in very susceptible persons.

See Section 11 for additional Toxicological information.

Aggravated Medical Conditions None known

HMIS Health: 1\* Flammability: 0 Reactivity: 0 PPE: -

#### **HMIS Legend**

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- \* Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special"

handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

### 4. FIRST AID MEASURES

**General Advice** No hazards which require special first aid measures.

**Eye Contact** Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

**Skin Contact**Wash off immediately with soap and plenty of water removing all contaminated

clothes and shoes.

**Inhalation** Move to fresh air. If symptoms persist, call a physician.

**Ingestion** Clean mouth with water and afterwards drink plenty of water. Consult a physician if

necessary.

Notes To Physician Treat symptomatically

### 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Revision Date: 29-Apr-2014

Protective Equipment And Precautions For Firefighters As in any fire, wear self-contained breathing apparatus

pressure-demand, MSHA/NIOSH (approved or equivalent)

Revision Date: 29-Apr-2014

and full protective gear.

Specific Hazards Arising From The Chemical Closed containers may rupture if exposed to fire or extreme

heat.

No

Sensitivity To Mechanical Impact No

Flash Point Data

Flash Point (°F)

Flash Point (°C)

Flash Point Method

Not applicable
Not applicable

Flammability Limits In Air

**Sensitivity To Static Discharge** 

Lower Explosion LimitNot applicableUpper Explosion LimitNot applicable

NFPA Health: 1 Flammability: 0 Instability: 0 Special: Not Applicable

#### **NFPA Legend**

- 0 Not Hazardous
- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

#### 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

**Environmental Precautions** Prevent further leakage or spillage if safe to do so.

**Methods For Clean-Up**Soak up with inert absorbent material. Sweep up and shovel into suitable containers

for disposal.

Other Information None known

### 7. HANDLING AND STORAGE

**Handling** Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or

sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.

**Storage** Keep container tightly closed. Keep out of the reach of children.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### **Exposure Limits**

Revision Date: 29-Apr-2014

**Hazardous Components** 

Chemical Name	ACGIH	OSHA
Limestone	N/E	15 mg/m <sup>3</sup> - TWA total
		5 mg/m³ - TWA
Nepheline syenite	N/E	5 mg/m <sup>3</sup> - TWA (nuisance dust)
Titanium dioxide	10 mg/m³ - TWA	15 mg/m <sup>3</sup> - TWA
Kaolin	2 mg/m³ - TWA	15 mg/m³ - TWA total 5 mg/m³ - TWA
Diatomaceous earth	N/E	- (80)/(% SiO2) mg/m³ TWA 20 mppcf - TWA
Silica, amorphous	N/E	- (80)/(% SiO2) mg/m³ TWA 20 mppcf - TWA
Aluminum hydroxide	1 mg/m³ - TWA	N/E
Distillates, petroleum, hydrotreated heavy paraffinic	N/E	N/E
Distillates (petroleum), solvent-dewaxed heavy paraffinic	N/E	N/E
Distillates, petroleum, solvent-refined heavy paraffinic	N/E	N/E

### Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits

OSHA - Occupational Safety & Health Administration Exposure Limits

N/E - Not Established

**Engineering Measures** Ensure adequate ventilation, especially in confined areas.

**Personal Protective Equipment** 

**Eye/Face Protection** Safety glasses with side-shields.

**Skin Protection** Protective gloves and impervious clothing

**Respiratory Protection** In case of insufficient ventilation wear suitable respiratory equipment.

Hygiene Measures Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing

before re-use. Wash thoroughly after handling.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid

Odor little or no odor Density (lbs/gal) 10.3 - 11.7 **Specific Gravity** 1.23 - 1.40 pН Not available **Evaporation Rate** Not available **Vapor Pressure** Not available **Vapor Density** Not available Wt. % Solids 40 - 60 Vol. % Solids 30 - 45 Wt. % Volatiles 40 - 60 Vol. % Volatiles 55 - 70 **VOC Regulatory Limit (g/L)** < 50 **Boiling Point (°F)** 212 **Boiling Point (°C)** 100

\_\_\_\_\_

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Revision Date: 29-Apr-2014

Freezing Point (°F) 32 Freezing Point (°C) 0

Flash Point (°F)

Flash Point (°C)

Flash Point Method

Upper Explosion Limit

Lower Explosion Limit

Not applicable

Not applicable

Not applicable

# 10. STABILITY AND REACTIVITY

Chemical Stability Stable under normal conditions.

Conditions To Avoid Prevent from freezing

**Incompatible Materials**No materials to be especially mentioned.

Hazardous Decomposition Products

None under normal use.

Possibility Of Hazardous Reactions

None under normal conditions of use.

#### 11. TOXICOLOGICAL INFORMATION

### **Acute Toxicity**

#### **Product**

No information available

#### Component

#### Limestone

LD50 Oral: 6,450 mg/kg (Rat) vendor data Sensitization: No sensitizing effects known.

#### Nepheline syenite

Sensitization: No sensitizing effects known.

#### Titanium dioxide

LD50 Oral: > 10000 mg/kg (Rat)

LD50 Dermal: > 10000 mg/m<sup>3</sup> (Rabbit)

LC50 Inhalation (Dust): > 6.82 mg/L (Rat, 4 hr.)

#### Kaolin

LD50 Oral: > 5000 mg/kg (Rat)

#### Silica, amorphous

LD50 Oral: > 5000 mg/kg (Rat) LD50 Dermal: 2,000 mg/kg (Rabbit) LC50 Inhalation (Dust): > 2 mg/L

Revision Date: 29-Apr-2014

Distillates, petroleum, solvent-refined heavy paraffinic

LD50 Oral: > 5,000 mg/kg (Rat) LD50 Dermal: > 2,000 mg/kg

LC50 Inhalation (Vapor): > 3.9 mg/L (Rat, 4 hr.)

#### **Chronic Toxicity**

#### Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:

Chemical Name	ACGIH	IARC	NTP	OSHA Carcinogen
Titanium dioxide		2B - Possible Human Carcinogen		Listed
Distillates, petroleum, hydrotreated heavy paraffinic		1 - Human Carcinogen		
Distillates (petroleum), solvent-dewaxed heavy paraffinic		1 - Human Carcinogen		
Distillates, petroleum, solvent-refined heavy paraffinic		1 - Human Carcinogen		

 Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists

IARC - International Agency for Research on Cancer

NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

# 12. ECOLOGICAL INFORMATION

## **Ecotoxicity Effects**

### **Product**

Acute Toxicity to Fish

No information available

### **Acute Toxicity to Aquatic Invertebrates**

No information available

### **Acute Toxicity to Aquatic Plants**

No information available

### Component

### 12. ECOLOGICAL INFORMATION

# **Acute Toxicity to Fish**

Titanium dioxide

LC50: >1000 mg/L (Fathead Minnow - 96 hr.)

#### **Acute Toxicity to Aquatic Invertebrates**

No information available

#### **Acute Toxicity to Aquatic Plants**

No information available

### 13. DISPOSAL CONSIDERATIONS

Waste Disposal Method Dispose of in accordance with federal, state, and local regulations. Dry, empty

containers may be recycled in a can recycling program. Local requirements may vary, consult your sanitation department or state-designated environmental

Revision Date: 29-Apr-2014

protection agency for more disposal options.

# 14. TRANSPORT INFORMATION

**DOT** Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

### 15. REGULATORY INFORMATION

#### **International Inventories**

United States TSCA Yes - All components are listed or exempt.

Canada DSL Yes - All components are listed or exempt.

### **Federal Regulations**

# SARA 311/312 hazardous categorization

Acute Health Hazard No
Chronic Health Hazard Yes
Fire Hazard No
Sudden Release of Pressure Hazard No
Reactive Hazard No

\_\_\_\_\_

Revision Date: 29-Apr-2014

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

This product may contain trace amounts of (other) SARA reportable chemicals. Contact the preparer for further information.

### Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

This product may contain trace amounts of (other) HAPs chemicals. Contact the preparer for further information.

## State Regulations

### **California Proposition 65**

This product may contain small amounts of materials known to the state of California to cause cancer or reproductive harm.

### State Right-to-Know

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Louisiana	Rhode Island
Limestone	X	X	X		X
Titanium dioxide	Х	Х	X		Х
Kaolin	Х	X	X		X
Diatomaceous earth		X			Х
Silica, amorphous	X	X	X		

#### Legend

X - Listed

### 16. OTHER INFORMATION

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Prepared By Product Stewardship Department

Benjamin Moore & Co. 101 Paragon Drive Monvale, NJ 07645 855-724-6802

**Revision Date:** 29-Apr-2014 **Revision Summary** Not available

\_\_\_\_\_

Revision Date: 29-Apr-2014

#### Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

**End of MSDS**