

**MATERIAL SAFETY DATA SHEET**

---

**SECTION 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**

---

**LUBRIPLATE® Lubricants Co.**  
**129 Lockwood St.**  
**Newark, NJ 07105**

**Emergency Telephone Number:**  
**1-800-255-3924-CHEM-TEL (24 hour)**  
**Telephone Number for information:**  
**1-973-589-9150**

**SUBSTANCE: LUBRIPLATE X-357 (Aerosol)**

**MSDS No. - 0892150149063**

**TRADE NAMES/SYNONYMS:**

**PRODUCT USE:** Petroleum lubricating grease

**CREATION DATE:** 11/05/2007

**REVISION DATE:** 10/11/2012

---

**SECTION 2 COMPOSITION/INFORMATION ON INGREDIENTS**

---

**COMPONENT:** Light hydrotreated naphthenic distillates (petroleum)

**CAS NUMBER:** 64742-53-6

**EC NUMBER (EINECS):** 265-156-6

**PERCENTAGE:** 30-35

**COMPONENT:** Heptane

**CAS NUMBER:** 142-82-5

**EC NUMBER (EINECS):** 205-563-8

**PERCENTAGE:** 20-25

**COMPONENT:** Liquefied petroleum gas

**CAS NUMBER:** 68476-85-7

**EC NUMBER (EINECS):** 270-704-2

**PERCENTAGE:** 15-20

**COMPONENT:** Heavy hydrotreated naphthenic distillates (petroleum)

**CAS NUMBER:** 64742-52-5

**EC NUMBER (EINECS):** 265-155-0

**PERCENTAGE:** 15-20

**COMPONENT:** Zinc oxide

**CAS NUMBER:** 1314-13-2

**EC NUMBER (EINECS):** 215-222-5

**PERCENTAGE:** 5-10

**COMPONENT:** 12 hydroxystearic acid

**CAS NUMBER:** 106-14-9

**EC NUMBER (EINECS):** 203-366-1

**PERCENTAGE:** 2-5

**COMPONENT:** Antimony 0,0-dipropylphosphorodithionate

**CAS NUMBER:** 15874-48-3

**EC NUMBER (EINECS):** 240-001-5

**PERCENTAGE:** 2-5

**COMPONENT:** Carbon black

**CAS NUMBER:** 1333-86-4

**EC NUMBER (EINECS):** 215-609-9

**PERCENTAGE:** 0-2

**COMPONENT:** Inedible animal grease

**CAS NUMBER:** 68153-81-1

**EC NUMBER (EINECS):** 268-896-8

**PERCENTAGE:** 0-1

**COMPONENT:** Lithium hydroxide monohydrate

**CAS NUMBER:** 1310-66-3

**EC NUMBER (EINECS):** not assigned

**PERCENTAGE:** 0-1

**COMPONENT:** Butyl zimate

**CAS NUMBER:** 136-23-2

**EC NUMBER (EINECS):** 205-232-8

**PERCENTAGE:** 0-1

**COMPONENT:** Molybdenum disulfide

**CAS NUMBER:** 1317-33-5

**EC NUMBER (EINECS):** 215-263-9

**PERCENTAGE:** 0-1

**COMPONENT:** Petroleum hydrocarbon

**CAS NUMBER:** 64742-58-1

**EC NUMBER (EINECS):** 265-161-3

**PERCENTAGE:** 0-1

**COMPONENT:** Hydroxyalkyl carboxylic ester

**CAS NUMBER:** NA

**EC NUMBER (EINECS):** NA

**PERCENTAGE:** 0-1

**COMPONENT:** Alkyl thiadiazole mixture

**CAS NUMBER:** NA

**EC NUMBER (EINECS):** NA

**PERCENTAGE:** 0-1

**NOTE:** The IP 346 value of the mineral oil is less than 3%

---

**SECTION 3 HAZARDS IDENTIFICATION**

---

**POTENTIAL HEALTH EFFECTS:****INHALATION:****SHORT TERM EXPOSURE:** Irritation**LONG TERM EXPOSURE:** Lung damage**SKIN CONTACT:****SHORT TERM EXPOSURE:** Irritation**LONG TERM EXPOSURE:** Irritation, skin disorders**EYE CONTACT:****SHORT TERM EXPOSURE:** Irritation**LONG TERM EXPOSURE:** No information available**INGESTION:****SHORT TERM EXPOSURE:** Diarrhea, difficulty breathing**LONG TERM EXPOSURE:** no information on significant adverse effects

**Effects of Overexposure:** Inhalation is the most likely method of exposure. Minimal effects are expected at levels below the TLV of components. Dizziness, drowsiness, coughing, nasal or throat irritations may occur at higher levels. LPG may act as a simple asphyxiant without other significant physiologic effects if the oxygen content is low. It is reported that overexposure can cause liver abnormalities, kidney, lung and spleen damage in test animals.

**HAZARDOUS MATERIAL IDENTIFICATION SYSTEM (HMIS):**

Health – 1

Flammability – 4

Reactivity – 0

**Not a Controlled Product under (WHMIS) – Canada****Special Protection: See Section 8**

---

**SECTION 4 FIRST AID MEASURES**

---

**INHALATION:** Remove to fresh air. If breathing has stopped, administer artificial respiration. Get medical help immediately.

**SKIN CONTACT:** Remove any contaminated clothing and wash with soap and warm water.

**EYE CONTACT:** Flush with clear water for 15 minutes or until irritation subsides. If irritation persists, consult a physician.

**INGESTION:** If ingested, call a physician immediately. Do not induce vomiting.

---

**SECTION 5 FIRE FIGHTING MEASURES**

---

**FIRE AND EXPLOSION HAZARDS:** Flammable

**EXTINGUISHING MEDIA:** Foam, Dry Chemical, Carbon Dioxide or Water Spray (Fog)

**SPECIAL FIRE FIGHTING PROCEDURES:** Cool exposed containers with water. Use air-supplied breathing equipment for enclosed or confined spaces. Use shielding to protect personnel against bursting containers

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Do not spray near open flame. At elevated temperatures (over 54 C), aerosol containers may vent, burst, or rupture.

---

## SECTION 6 ACCIDENTAL RELEASE MEASURES

---

**OCCUPATIONAL RELEASE:** Remove sources of ignition, ventilate area. Use appropriate safety equipment to enter area. Allow time for vapors to be below their TLV. Add oil absorbent and clean area. Keep petroleum products out of sewers and water courses.

---

## SECTION 7 HANDLING AND STORAGE

---

**STORAGE:** Store in cool, dry area out of direct sunlight. Do not puncture or incinerate, or heat full or empty containers above 54 C.

---

## SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

---

**EXPOSURE LIMITS:**

**OIL MIST IN AIR (Not Encountered in Normal Usage):**

5 mg/m<sup>3</sup> UK OES TWA

10mg/m<sup>3</sup> UK OES STEL

**HEPTANE:**

400 ppm PEL

**LIQUEFIED PETROLEUM GAS:**

1,000 mg/m<sup>3</sup> PEL

**VENTILATION:** Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

**EYE PROTECTION:** Wear splash resistant safety goggles. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

**CLOTHING:** Wear appropriate chemical resistant clothing.

**GLOVES:** Wear appropriate chemical resistant (nitrile) gloves.

**RESPIRATOR:** Need approved organic vapor mask if TLV is exceeded.

---

**SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**

---

**PHYSICAL STATE:** aerosol  
**APPEARANCE:** smooth  
**COLOUR:** black  
**PHYSICAL FORM:** mist  
**ODOR:** solvent odor  
**BOILING POINT:** NA (aerosol)  
**FREEZING POINT:** Not available  
**FLASH POINT:** <-18 C  
**LOWER FLAMMABLE LIMIT:** not determined  
**UPPER FLAMMABLE LIMIT:** not determined  
**AUTO IGNITION:** not available  
**VAPOUR PRESSURE:** aerosol at 54 C – 115 psig  
**VAPOR DENSITY (air=1):** >1  
**SPECIFIC GRAVITY (water=1):** 0.97 (of product)  
**DENSITY:** not available  
**WATER SOLUBILITY:** insoluble  
**pH:** not available  
**VOLATILITY:** not available  
**ODOR THRESHOLD:** not available  
**EVAPORATION RATE (Butyl acetate = 1):** faster  
**VISCOSITY:** not available  
**COEFFICIENT OF WATER/OIL DISTRIBUTION:** not available

---

**SECTION 10 STABILITY AND REACTIVITY**

---

**REACTIVITY:** Stable at normal temperatures and pressures

**CONDITIONS TO AVOID:** Avoid spraying into open flame or onto red-hot surfaces.

**INCOMPATIBLES:** Strong oxidizers

**HAZARDOUS DECOMPOSITION:**  
Thermal decomposition products or combustion: may form carbon monoxide

**POLYMERISATION:** Will not polymerise.

---

**SECTION 11 TOXICOLOGICAL INFORMATION**

---

**Light hydrotreated naphthenic distillates (petroleum):****TOXICITY DATA:**

Low order of dermal and oral toxicity

**Heptane:****TOXICITY DATA:**

No data available

**Liquefied petroleum gas:**

**TOXICITY DATA:**

No data available

**Heavy hydrotreated naphthenic distillates (petroleum):**

**TOXICITY DATA:**

Low order of dermal and oral toxicity

**Zinc oxide:**

**TOXICITY DATA:**

No data available

**12 hydroxystearic acid:**

**TOXICITY DATA:**

Greater than 5 g/kg oral-rat LD50

**Antimony 0,0-dipropylphosphorodithionate:**

**TOXICITY DATA:**

4,695 mg/kg oral-rat LD50

**Carbon black:**

**TOXICITY DATA:**

Greater than 8,000 mg/kg oral-rat LD50

**Inedible animal grease:**

**TOXICITY DATA:**

No data available

**Lithium hydroxide monohydrate:**

**TOXICITY DATA:**

Greater than 8 g/kg oral-rat LD50

**Molybdenum disulfide:**

**TOXICITY DATA:**

No data available

**Butyl zimate:**

**TOXICITY DATA:**

Greater than 16,000 mg/kg oral-rat LD50

**Petroleum hydrocarbon:**

**TOXICITY DATA:**

No data available

**Hydroxyalkyl carboxylic ester:**

**TOXICITY DATA:**

Between 2,000 and 5,000 mg/kg oral-rat LD50

**Alkyl thiadiazole mixture:**

**TOXICITY DATA:**

Greater than 10,000 mg/kg oral-rat LD50

---

**SECTION 12 ECOLOGICAL INFORMATION**

---

Not available

---

**SECTION 13 DISPOSAL CONSIDERATIONS**

---

Dispose in accordance with all applicable regulations.

---

**SECTION 14 TRANSPORT INFORMATION**

---

**LAND TRANSPORT ADR:** No classification assigned.

**LAND TRANSPORT RID:** No classification assigned.

**AIR TRANSPORT IATA:** ID 8000, CONSUMER COMMODITY, Class 9, Packing Instructions – Y963

**AIR TRANSPORT ICAO:** ID 8000, CONSUMER COMMODITY, Class 9, Packing Instructions – Y963

**MARITIME TRANSPORT IMDG:** UN 1950, AEROSOLS (Ltd. Qty.), Class 2.1, EmS No. F-D, S-U, ERG No. 126

---

**SECTION 15 REGULATORY INFORMATION**

---

EUROPEAN REGULATIONS:

EC CLASSIFICATION (CALCULATED): N

Risk Phrases: R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SARA/TITLE III, Section 313 Status – Zinc Compounds <8%, Antimony Compounds <3%

---

**SECTION 16 OTHER INFORMATION**

---

**The above information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of LUBRIPLATE Lubricants Company. The data on these sheets relates only to the specific material designated herein. LUBRIPLATE Lubricants Company assumes no legal responsibility for use or reliance upon this data.**