


MATERIAL SAFETY DATA SHEET

Used to comply with OSHA's Hazard
Communication Standard, 29 CFR 1910.1200

NFPA HAZARD RATING



SECTION I - NAME AND PRODUCT

FLEXOVIT USA, INC. 1305 Eden Evans Center Rd, Angola, NY 14006 Phone: (716) 549-5100 Fax: (716) 549-5455

Product: ZIRCOTEX Flap Discs Updated: 5/1/09. Contact: Technical Director

SECTION II - COMPOSITION

Ingredient	% By Weight	OSHA Regulate	C.A.S. #	OSHA PEL	ACGIH TLV	Other Limits	Carcinogen
Aluminum Oxide	15-30%	No	1344-28-1	15mg/m3	10 mg/m3	N/A	No
Zirconium Oxide	0 - 15%	No	1314-23-4	5mg/m3	10 mg/m3	N/A	No
Cotton Cloth	13-17%	No	N/A	N/A	N/A	N/A	No
Cured Epoxy Resin	15-20%	No	68609-97-2	N/A	N/A	N/A	No
Fiberglass Backing	39-50%	No	65997-17-3	15mg/m3	10 mg/m3	N/A	No
Plastic or Aluminum Backing	39-50%	No	N/A	N/A	N/A	N/A	No

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point	N/A	Specific Gravity (H2O=1)	2-4
Vapor Pressure (mm Hg)	N/A	Melting Point	N/A
Vapor Density (Air=1)	N/A	Evaporation Rate (Butyl Acetate=1)	N/A
Solubility in Water	N/A	Appearance/Odor	Abrasive Sheets on backing; odorless

SECTION IV - FIRE AND EXPLOSION DATA

Flash Point	N/A	Lower Explosion Limit	N/A
Flammable Limits	N/A	Upper Explosion Limit	N/A
Special Fire Fighting Procedures	N/A	Unusual Fire or Explosion Hazards	N/A

SECTION V - REACTIVITY DATA

Stable - Avoid excessive moisture, high relative humidity, temperature extremes and contact with acids or solvents

Not incompatible with any materials

Hazardous Polymerization will not occur

Dust and organic fumes are generated in use. Do not exceed TLV's.

SECTION VI - HEALTH HAZARD DATA

Route(s) of Entry	Signs and Symptoms of Exposure	Emergency and First-Aid procedures
Dust Inhalation	May cause coughing and shortness of breath during grinding. May affect breathing capacity.	Terminate exposure and remove to fresh air. Obtain medical assistance.
Ingestion	No known adverse effects, but not recommended.	Obtain medical assistance.
Absorption	Not absorbed through skin.	N/A
Skin contact	Grinding wheel may cause abrasions. Dust may cause skin irritation.	Terminate exposure and remove to fresh air. Obtain medical assistance.
Eye	Dust or fumes may cause eye irritation.	Fresh air and medical assistance.
Other	Excessive noise levels may exist in use.	Cease use. Obtain medical assistance.

Medical conditions such as emphysema and asthma may be aggravated during grinding.

SECTION VII - STORAGE, HANDLING AND USE PROCEDURES

Handling and storage procedures - Avoid damage to discs. Do not use a disc that has been damaged. Avoid excessive temperatures in storage. Always handle in accordance with ANSI B7.1.

Normal clean up procedures should be used if material is released.

Dispose of waste in a sanitary landfill in accordance with state, local and federal regulations.

Always use in accordance with OSHA 1910.215. Do not use damaged discs. Do not use without machine guard in place. Do not exceed maximum RPM on disc.

SECTION VIII - CONTROL MEASURES

Protection	Requirements and Referrals
Respiratory	OSHA or NIOSH approved respirator if TLV's exceeded. See OSHA 29 CFR 1910.134
Ventilation	Local and mechanical exhaust recommended. Refer to OSHA 29 CFR 1910.94.
Protective Gloves	Not required but use if desired.
Eye Protection	Required. Refer to OSHA 29 CFR 1910.133.
Hearing Protection	Required. Refer to OSHA 29 CFR 1910.95.
Other	Apron and/or face shield if desired. Covering exposed skin is recommended.
Hygienic Practices	Wash with soap and water after handling and grinding.

SECTION IX - MSDS PREPARATION

The information and recommendations set forth herein are taken from sources and references believed to be accurate and complete as of the date hereof. However, FLEXOVIT USA, Inc. makes no expressed or implied warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.