

MATERIAL SAFETY DATA SHEET

COMPLIES WITH OSHA'S 29 CFR 1910, 1200 AND STATE HAZARD COMMUNICATION STANDARD

A BRITE COMPANY
3217 WOOD DRIVE
GARLAND, TEXAS 75041
214-291-0400

24 HOUR EMERGENCY PHONE NUMBER 1-800-424-9300 (CHEMTREC)

SECTION 1: PRODUCT IDENTIFICATION

TRADE NAME: Albond CL
GENERAL OR GENERIC ID: Zincating solution
DATE PREPARED: 2/10/97
LATEST REVISION DATE: 9/13/04
NFPA/HMIS HAZARD CODES
(minimal = 0; slight = 1; moderate = 2; serious = 3; severe = 4)
HEALTH: 3/3 FIRE: 0/0 REACTIVITY: 0/0 SPECIAL: NA

SECTION 2: HAZARDOUS INGREDIENTS IDENTITY INFORMATION

HAZARDOUS COMPONENTS	CAS #	OSHA PEL	ACGIH TLV	IDLH LEVEL	% /WT
Sodium Hydroxide	310-73-2	2mg/m ³	2mg/m ³	250mg/m ³	<30
*Zinc Oxide	67-51-1	5mg/m ³	5mg/m ³	N/A	5

*= Reportable under SARA Title III

SECTION 3: PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: >212°F
VAPOR PRESSURE: N/A
SOLUBILITY IN WATER: Complete
pH: 13.98
APPEARANCE AND COLOR: Clear straw to pale yellow liquid with slight soapy and alcohol smell.

SPECIFIC GRAVITY: 1.44
VAPOR DENSITY: >1
EVAPORATION RATE: Slower than ether

SECTION 4: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: not flammable
EXTINGUISHING MEDIA: Water fog, carbon dioxide, alcohol foam, dry chemical and Halon.
SPECIAL FIRE FIGHTING PROCEDURES: Pressure demand, self contained respiratory protection and protective clothing should be worn by firefighters in areas where products containing caustic soda or caustic soda mixtures are stored.
UNUSUAL FIRE AND EXPLOSION HAZARDS: Non combustible material, liquid form in contact with water may generate sufficient heat to ignite combustible or flammable materials. Contact with white metals such as zinc, aluminum, tin or alloys of these metals can generate explosive hydrogen gas.

SECTION 5: REACTIVITY DATA

STABILITY: Stable
HAZARDOUS POLYMERIZATION: Will not occur
INCOMPATIBILITY: Acids, metals such as zinc, aluminum, tin or alloys of these metals. Flammable liquids, organic halogens, nitromethane or nitro compounds.
CONDITIONS TO AVOID: Splashing or dropping of water or strong acids on product. Spilling of liquid product on white metals.
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon dioxide and or carbon monoxide or hydrogen gas may evolve.

SECTION 6: HEALTH HAZARD DATA

ROUTES OF ENTRY /SIGNS AND SYMPTOMS OF EXPOSURE:
ACUTE: Corrosive to eyes and skin, concentrated solutions may destroy tissue on contact. Can cause blindness.
INGESTION: Harmful if swallowed. Can cause severe burns and complete perforation of mucous membranes to the mouth, throat, esophagus and stomach if swallowed.
INHALATION: Mist or dust at high levels may cause irritation to the nose, throat and lungs. May cause damage to the upper respiratory tract.
CHRONIC EFFECTS: None known
CARCINOGENS: None under OSHA, IARC or NTP.
MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None known.
EMERGENCY AND FIRST AID PROCEDURES:
EYES: Immediately flush with plenty of water for 15 minutes. See a physician.
SKIN: Wash with soap and water. Remove contaminated clothing. See a physician if irritation occurs.
INHALATION: Remove to fresh air. If breathing has stopped start artificial respiration. See a physician.
INGESTION: Call a physician immediately, **DO NOT INDUCE VOMITING DILUTE BY DRINKING WATER (MILK IF AVAILABLE) NEVER GIVE LIQUIDS TO AN UNCONSCIOUS PERSON.**

SECTION 7: PRECAUTIONS FOR SAFE HANDLING AND USE

SPILL OR LEAK PROCEDURES:
SMALL SPILLS: Flush to treatment system with large amounts of water.
LARGE SPILLS: Sweep into suitable containers. Keep out of fish bearing waters.
WASTE DISPOSAL METHOD: Dump to waste water treatment system, observe local, state and federal regulations. Product is hazardous waste, EPA Code (c,R), EPA Hazardous Waste Numbers D002, D003, due to pH.

SECTION 8: TRANSPORTATION AND LABELING

REGULATORY INFORMATION:
DOT HAZARD CLASS: 8
SHIPPING NAME: Corrosive, liquid, basic, inorganic, n.o.s. (Sodium Hydroxide)
ID NUMBER: UN 3266
PACKING GROUP: II
LABELS: 8
TSCA: All components included in the inventory.

SECTION 9: HANDLING AND STORAGE

HANDLING AND STORING: Keep container closed when not in use.
OTHER PRECAUTIONS: Keep out of reach of children. Store in proper chemical storage area.
If water pollution occurs, notify the proper authorities.

SECTION 10: CONTROL MEASURES

RESPIRATORY PROTECTION: Use NIOSH approved respiratory equipment for dust and mist.
VENTILATION: Local exhaust to maintain air contamination below TLV limit.
GLOVES: Rubber gloves, neoprene, or synthetic rubber required.
EYE PROTECTION: Safety glasses or goggles required.
OTHER PROTECTIVE EQUIPMENT: As needed to prevent prolonged or repeated skin contact. Eye wash fountain and safety shower in work area.
WORK /HYGIENIC PRACTICES: Launder contaminated clothing before reuse.

THE INFORMATION WAS COMPILED FROM CURRENT, RELIABLE SOURCES AND IS BELIEVED TO BE CORRECT. AS DATA, AND OR REGULATIONS CHANGE, AND CONDITION OF USE AND HANDLING ARE BEYOND OUR CONTROL, NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE AS TO COMPLETENESS OR CONTINUING ACCURACY OF THIS INFORMATION. SELLER ASSUMES NO RESPONSIBILITY FOR INJURY TO BUYER OR TO THIRD PERSONS OR FOR ANY DAMAGE TO ANY PROPERTY AND BUYER ASSUMES ALL SUCH RISKS.