

MATERIAL SAFETY DATA SHEET

PETROFERM INC.

Lambent Technologies Plant
3938 Porett Drive
Gurnee, IL 60031
(800) 432-7187
www.petroferm.com

CHEMTREC 24-HOUR EMERGENCY RESPONSE
TOLL FREE NUMBER: (800) 424-9300
INTERNATIONAL CALLS: COLLECT (703) 527-3887
CHEMTREC should only be contacted in the event of chemical emergencies involving a spill, leak, fire, exposure, or accident involving chemicals.

1. PRODUCT NAME

AXAREL[®] 2200 Cleaner

2. HAZARDOUS INGREDIENTS

	CAS Number	Weight %	OSHA PEL	ACGIH TLV
Isoparaffinic hydrocarbon (C ₉₋₁₂ isoalkanes)	90622-57-4	30 - 60	Not est.	Not est.

3. HAZARDS IDENTIFICATION

SYMPTOMS/EFFECTS OF OVEREXPOSURE

- Inhalation:** May cause irritation of the upper respiratory passages with coughing and shortness of breath, headaches, and confusion.
- Ingestion:** May cause severe irritation of the gastrointestinal tract with nausea, vomiting, abdominal cramps, and diarrhea.
- Skin:** Contact of several hours may cause mild to moderate local redness and swelling.
- Eyes:** Liquid vapor contact may cause eye irritation with tearing or blurring of vision.
- Listed Carcinogens:** None

4. FIRST AID MEASURES

- Inhalation:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Consult a physician.
- Ingestion:** Do not induce vomiting. Seek medical attention.
- Skin:** Remove contaminated clothing. Thoroughly wash affected area with soap and water; use skin cream if irritation is severe.
- Eyes:** Immediately flush eyes with water for 15 minutes. Call a physician if irritation persists.

5. FIRE FIGHTING MEASURES

- Extinguishing Media:** Chemical foam, dry chemical, carbon dioxide. Class BC, ABC fire extinguisher.
- Special Fire Fighting Procedures:** Self-contained positive pressure breathing apparatus and protective clothing should be worn in fighting fires involving chemicals.
- Unusual Fire and Explosions Hazard:** None known.

6. ACCIDENTAL RELEASE MEASURES

Absorb spill with inert material, then place in chemical waste container. For large spills, dike for later disposal. Observe government regulations.

7. HANDLING AND STORAGE

Store in original container, preferably in a cool, ventilated, fire-resistant building. Avoid overheating or freezing. Since empty containers may retain product residues (vapor, liquid, or solid) all label precautions must be observed.

8. EXPOSURE CONTROLS - PERSONAL PROTECTION

- Respiratory:** Use NIOSH/MSHA approved respirator if ventilation is not sufficient and if mists are generated.
- Ventilation:** If desirable to reduce odor, mechanical (general) ventilation should have an airflow of 55 CFM. Local exhaust can also be effective in minimizing odor.
- Clothing/Glove:** Chemically resistant gloves should be used with all industrial chemicals.
- Eye Protection:** Safety glasses/goggles are recommended. Provide eye bath near work site.

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point (780 mm Hg):	> 305°F (> 152°C)	Vapor Density (Air = 1):	5
% Volatile (By Weight):	Not determined.	Evaporation Rate (BUAC = 1):	< 1
Specific Gravity (H ₂ O = 1):	0.82 @ 77°F (25°C)	Solubility in Water:	7% by weight
Vapor Pressure (20°C):	3.54 mm Hg @ (68°F)	Appearance and Odor:	Colorless liquid with an alcohol odor.
Flash Point:	111°F (44°C) (ASTM D93-85, Pensky-Martens Closed Cup)	Flammable Limits (% By Volume in Air):	Not determined

10. STABILITY AND REACTIVITY

- Stability:** AXAREL 2200 is stable.
- Conditions to Avoid:** Temperatures above 305°F (152°C).
- Incompatibility:** Strong oxidizing agents, strong acids, strong bases.
- Hazardous Decomposition Products:** None, other than normal products of combustion.
- Hazardous Polymerization:** Will not occur.

11. TOXICOLOGICAL INFORMATION

Isoparaffinic hydrocarbon (C₉₋₁₂ isoalkanes)
 LD50/oral/rat = > 10,000 mg/kg
 LD50/dermal/rabbit = > 3,200 mg/kg

12. ECOLOGICAL INFORMATION

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treat or incinerate used material in compliance with all applicable government regulations

14. TRANSPORT INFORMATION UN-No.: 3295

IATA

UN/ID No.: 3295	Class: 3
Packaging group: III	ICAO-Label: Flammable liquid
Proper shipping name:	Hydrocarbons, Liquid, N.O.S.

14. TRANSPORT INFORMATION UN-No.: 3295 (Continued)

IMO

Class: 3	IMDG Page: 171
Packaging group: III	IMO-Label: Flammable liquid
Proper shipping name:	Hydrocarbons, Liquid, N.O.S.

15. REGULATORY INFORMATION

None of the components of AXAREL 2200 appears on any of the EPA's lists of toxic or hazardous substances, or on the SARA 313 toxic chemicals list (40 CFR 372.65).

None of the components of this product is listed in the Threshold Limit Values and Biological Exposure Indices compiled by the American Conference of Governmental Industrial Hygienists.

None of the components of this product is listed in California's Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition as a chemical known to cause cancer, birth defects, or other reproductive harm.

All the components of this product are listed on the TSCA inventory.

Canadian WHMIS Classification: Class B Division 3 - Combustible liquid.
Class D Division 2 Subdivision B - Toxic material.

16. OTHER INFORMATION

NFPA Codes: Health: 1 Fire: 2 Reactivity: 0

<p>We believe that the information contained herein is current as of the date of this Material Safety Data Sheet. Since the use of this information and of these opinions and the conditions of use of the product are not within the control of Petroferm Inc., it is the user's obligation to determine the conditions of safe use of the product.</p>
--