



MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product number 926-004
Product name **Moisture Out Penetrating Oil**
Effective date 03-Jan-2012
Company information Claire Manufacturing Co.
1005 S. Westgate Drive
Addison, IL 60101 United States
Company phone General Assistance 630-543-7600
Emergency telephone US 800-424-9300
Version # 09
Supersedes date 26-Feb-2011

2. Hazards Identification

Emergency overview Aerosol. CONTENTS UNDER PRESSURE.
Cancer hazard. Irritating to skin. Irritating to eyes. Irritating to respiratory system.

Potential health effects

Routes of exposure Inhalation. Eye contact. Skin contact. Ingestion.

Eyes Causes eye irritation.

Skin Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. Irritating to skin.

Inhalation Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Irritating to respiratory system. Prolonged inhalation may be harmful.

Ingestion Exposure by ingestion of an aerosol is unlikely. May cause delayed lung damage. Components of the product may be absorbed into the body by ingestion.

Target organs Central nervous system. Lungs.

Chronic effects May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion and blurred vision) and/or damage. May cause delayed lung injury.

Signs and symptoms Discomfort in the chest. Narcosis. Coughing. Jaundice. Defatting of the skin. Skin irritation.

3. Composition / Information on Ingredients

Components	CAS #	Percent
Perchloroethylene	127-18-4	50 - 60
Deodorized Kerosene	64742-47-8	30 - 40
Carbon Dioxide	124-38-9	1 - 3
Non-hazardous and other components below reportable levels		2.5 - 10

4. First Aid Measures

First aid procedures

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Skin contact Remove and isolate contaminated clothing and shoes. Wash off with warm water and soap. Get medical attention if irritation develops and persists. For minor skin contact, avoid spreading material on unaffected skin.

Inhalation If symptoms develop move victim to fresh air. Oxygen or artificial respiration if needed. Get medical attention immediately.

Ingestion Do not induce vomiting without advice from poison control center. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately.

Notes to physician

In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

5. Fire Fighting Measures

Flammable properties	NFPA Rating Fire = 2. Materials that must be moderately heated or exposed to relative high ambient temperatures before ignition can occur. Runoff to sewer may cause fire or explosion hazard.
Extinguishing media	
Suitable extinguishing media	Water.
Protection of firefighters	
Specific hazards arising from the chemical	Fire may produce irritating, corrosive and/or toxic gases.
Protective equipment and precautions for firefighters	In case of fire and/or explosion do not breathe fumes. Containers should be cooled with water to prevent vapor pressure build up. Cool containers with flooding quantities of water until well after fire is out. Move containers from fire area if you can do so without risk. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

6. Accidental Release Measures

Methods for containment	Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk.
Methods for cleaning up	Should not be released into the environment. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. After removal flush contaminated area thoroughly with water.

7. Handling and Storage

Handling	Pressurized container: Do not pierce or burn, even after use. Do not smoke while using or until sprayed surface is thoroughly dry. Do not use if spray button is missing or defective. Do not re-use empty containers. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin. Avoid contact with eyes. Wear personal protective equipment.
Storage	Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Do not handle or store near an open flame, heat or other sources of ignition. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Avoid exposure to long periods of sunlight. Keep out of the reach of children. Level 1 Aerosol (NFPA 30B)

8. Exposure Controls / Personal Protection

Exposure limits**ACGIH**

Components	CAS #	TWA	STEL	Ceiling
Perchloroethylene	127-18-4	25 ppm	100 ppm	Not established
Carbon Dioxide	124-38-9	5000 ppm	30000 ppm	Not established

OSHA

Components	CAS #	TWA	STEL	Ceiling
Perchloroethylene	127-18-4	100 ppm	Not established	200 ppm
Carbon Dioxide	124-38-9	5000 ppm	Not established	Not established

Personal protective equipment

Eye / face protection	Chemical goggles are recommended.
Skin protection	Wear appropriate chemical resistant clothing.
Respiratory protection	Wear positive pressure self-contained breathing apparatus (SCBA). If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

9. Physical & Chemical Properties

Appearance	Aerosol.
Boiling point	294.8 °F (146.1 °C) estimated
Color	clear brown
Density	1.1953 g/cm ³ estimated
Flammability (HOC)	15.0356 kJ/g estimated
Flash back	No
Flash point	159 °F (70.6 °C) CONCENTRATE
Form	Aerosol.
Freezing point	Not available
Odor	Solvent.
pH	Not applicable
Physical state	Liquid.
Pressure	70 - 90 psig @70F
Solubility	None
Specific gravity	1.1954

10. Chemical Stability & Reactivity Information

Chemical stability	Risk of ignition.
Conditions to avoid	Heat, flames and sparks.
Hazardous decomposition products	May include oxides of sulphur. Hydrogen chloride.

11. Toxicological Information

Acute effects	Acute LD50: 6002 mg/kg estimated, Rat, Dermal	
Component analysis - LD50		
Toxicology Data - Selected LD50s and LC50s		
Deodorized Kerosene	64742-47-8	Inhalation LC50 Rat >5.2 mg/L 4 h; Oral LD50 Rat >5000 mg/kg; Dermal LD50 Rabbit >2000 mg/kg
Perchloroethylene	127-18-4	Inhalation LC50 Rat 4000 ppm 4 h; Oral LD50 Rat 2629 mg/kg; Dermal LD50 Mouse 2800 mg/kg
Sensitization	Not expected to be hazardous by OSHA criteria.	
Carcinogenicity	Hazardous by OSHA criteria. Risk of cancer cannot be excluded with prolonged exposure.	
IARC - Group 2A (Probably Carcinogenic to Humans)		
Perchloroethylene	127-18-4	Monograph 63 [1995]; Supplement 7 [1987]
Teratogenicity	Not expected to be hazardous by OSHA criteria.	

12. Ecological Information

Ecotoxicity	LC50 8.42 mg/L estimated, Fish, 96.00 Hours, EC50 12.84 mg/L estimated, Daphnia, 48.00 Hours, Components of this product are hazardous to aquatic life.
--------------------	---

13. Disposal Considerations

Waste codes	D039: Waste Tetrachloroethylene
Disposal instructions	Contents under pressure. Do not puncture, incinerate or crush. Dispose of this material and its container to hazardous or special waste collection point. Do not allow this material to drain into sewers/water supplies.

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name Aerosols
 Hazard class 2.2
 UN number UN1950

Additional information:

Special provisions 153
 Packaging exceptions LTD QTY
 Packaging non bulk None
 Packaging bulk None



IMDG

Basic shipping requirements:

Proper shipping name AEROSOLS
 Hazard class 2.2
 Subsidiary hazard class 6.1
 UN number 1950
 Marine pollutant Tetrachloroethylene

Additional information:

Packaging exceptions Not a LTD QTY
 Labels required 2.2, 6.1



IATA

Basic shipping requirements:

Proper shipping name Aerosols, non-flammable, containing substances in Division 6.1, Packing Group III
 Hazard class 2.2
 Subsidiary hazard class 6.1
 UN number 1950

Additional information:

Packaging exceptions LTD QTY
 Labels required 2.2, 6.1



15. Regulatory Information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

Perchloroethylene 127-18-4 0.1 % de minimis concentration

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous chemical Yes

CERCLA (Superfund) reportable quantity

Perchloroethylene: 100.0000

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 302 extremely hazardous substance No

Section 311 hazardous chemical Yes

Hazard categories (311/312) Immediate Hazard - Yes
 Delayed Hazard - Yes
 Fire Hazard - Yes
 Pressure Hazard - Yes
 Reactivity Hazard - No

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of New and Existing Chemicals (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations

WARNING: This product contains a chemical known to the State of California to cause cancer.

U.S. - Pennsylvania - RTK (Right to Know) List

Carbon Dioxide	124-38-9	Present
Deodorized Kerosene	64742-47-8	Present
Perchloroethylene	127-18-4	Environmental hazard; Special hazardous substance

16. Other Information**Further information**

HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings

Health: 2*
 Flammability: 2
 Physical hazard: 0

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

MSDS sections updated

Transport Information: Product Shipping Name/Packing Group

Prepared by

Regulatory Compliance