

Firestone Building Products Company, LLC

Material Safety Data Sheet

August 6, 2013

Page: 1

SECTION 1: PRODUCT IDENTIFICATION

Product Name: Enverge™ Air & Vapor Barrier SA Membrane and Enverge™ Thru-Wall Flashing SA (Self-Adhered Membrane)

Chemical Name / Synonym: SBEPro Thru Wall Flashing & SBEPPro Air and Vapor Barrier SA Membrane

Chemical Family: Mixture

24-Hour Emergency Phone: (800) 424-9300 CHEMTREC

Manufacturer's Name: Firestone Building Products Company, LLC

Manufacturer's Address: 250 West 96th Street, Indianapolis, IN 46260

NFPA Hazard Rating: Health 1, Flammability 1, Reactivity 0

HMS Hazard Rating: Health 0, Flammability 1, Reactivity 0

SECTION 2: CHEMICAL COMPOSITION

| Chemical Name: | Common Name: | CAS #: | % (by wt) | Exposure Limits: |
|---------------------------------------|--------------|---------------------|-----------|------------------|
| Nonhazardous as per 29 CFR 1910.1200. | None | EPA TSCA Registered | 100 | None Established |

SECTION 3: HAZARD IDENTIFICATION

Primary Route of Exposure: None

Signs and Symptoms of Exposure: No known adverse effects.

Medical Conditions Aggravated by Exposure: None known.

Chronic Effects: No known adverse effects.

Carcinogenicity: None

SECTION 4: FIRST AID MEASURES

First Aid Procedures: No special action necessary.

SECTION 5: FIRE FIGHTING PROCEDURES

Suitable Extinguishing Media: Alcohol foam, carbon dioxide, or dry chemical.

Hazardous Combustion Products: Carbon dioxide, carbon monoxide and partially burned carbon.

Recommended Fire Fighting Procedures: Wear impermeable protective clothing and self-contained breathing apparatus as toxic fumes and vapors may be evolved.

Unusual Fire and Explosion Hazards: Combustion of this product causes dense black smoke. Water may cause frothing.

Firestone Building Products Company, LLC

Material Safety Data Sheet

August 6, 2013

Page: 2

SECTION 6: PRECAUTIONS FOR SAFE HANDLING AND USE

| | |
|--|--|
| Steps to Be Taken in Case Material is Released or Spilled: | Not Applicable |
| Precautions to Be Taken in Handling and Storing: | Keep away from heat, sparks, and open flames. Store in a clean, dry area in its original unopened packaging at temperatures of 50° F (10° C) – 140° F (60° C), so that it will be 50° F (10° C) or above at the time of application. Storage area should be well ventilated. |

SECTION 7: EXPOSURE CONTROLS / PERSONAL PROTECTION

| | |
|----------------------------|---|
| Ventilation: | Use in well ventilated area. |
| Respiratory Protection: | None required. |
| Eye Protection: | Safety glasses with side shields may be needed as determined by end-user. |
| Skin Protection: | Leather or cotton gloves may be required for direct handling. |
| Other: | None recommended |
| Work / Hygienic Practices: | Wash exposed skin prior to eating, drinking or smoking and at the end of each shift. Wash contaminated clothing prior to reuse. |

SECTION 8: PHYSICAL AND CHEMICAL PROPERTIES

| | | | |
|-------------------------|---|------------------------|---------|
| Appearance and Odor: | Black solid membrane with asphalt odor. | | |
| Flash Point: | Not Applicable | Lower Explosive Limit: | None |
| Method Used: | Not Applicable | Upper Explosive Limit: | None |
| Evaporation Rate: | Not Applicable | Boiling Point: | None |
| pH (undiluted product): | Not Applicable | Melting Point: | Unknown |
| Solubility in Water: | Insoluble | Specific Gravity: | Varies |
| Vapor Density: | Not Applicable | Percent Volatile: | Unknown |
| Vapor Pressure: | Not Applicable | | |

SECTION 9: STABILITY AND REACTIVITY

| | |
|---------------------------|--------------------------------|
| Thermal Stability: | Stable |
| Hazardous Polymerization: | Will not occur |
| Conditions to Avoid: | Heat, sparks, and open flames. |

SECTION 10: TRANSPORTATION

| | |
|------------------------|----------------|
| Regulatory Agency: | Not Regulated |
| Proper Shipping Name: | Not Applicable |
| Hazard Classification: | Not Applicable |
| Identification Number: | Not Applicable |
| Labels Required: | Not Applicable |

Firestone Building Products Company, LLC

Material Safety Data Sheet

August 6, 2013

Page: 3

Other Requirements: Not Applicable

SECTION 11: MISCELLANEOUS INFORMATION

Additional Comments: This product is considered to be a finished article as per 29 CFR 1910.1200 (C) and is, therefore, exempt from the requirements of the Hazard Communication standard.

Date of Previous MSDS: May 22, 2013

Changes Since Previous MSDS: Added a synonym name to section 1.

Telephone Number for Additional Information: (317) 575-7190

DISCLAIMER

The information contained herein is based on data considered accurate which has been obtained from other companies and organizations. However, no warranty or representation is expressed or implied that the information, is accurate, complete or representative. Firestone Building Products Company, LLC assumes no responsibility for injury to the buyer, the buyer's employees, or any third persons, if reasonable safety procedures are not followed. Additionally, Firestone Building Products Company assumes no responsibility for injury to buyer, the buyer's employees, or any third persons caused by abnormal use of this material, even if reasonable safety procedures are followed.