



The Clorox Pet Products Company

1221 Broadway
Oakland, CA 94612
Tel. 1-510-271-7000

**Material Safety
Data Sheet**

I Product: EVER CLEAN® CLUMPING CAT LITTER - MULTIPLE CAT													
Description: LIGHT AND DARK GRAY CLAY GRANULES WITH BLUE SPECKLES AND A FLORAL, LAVENDER ODOR													
Other Designations	Distributor												
	The Clorox Sales Company 1221 Broadway Oakland, CA 94612												
Emergency Telephone Nos.													
For Medical Emergencies, call 1-800-446-1014. For Transportation Emergencies, call 1-800-424-9300 (Chemtrec).													
II Health Hazard Data	III Hazardous Ingredients												
Inhalation of dust may irritate nose and throat. Cat feces can sometimes transmit a disease called toxoplasmosis. Pregnant women and immunosuppressed persons are most susceptible. Always remember to wash hands thoroughly after handling used cat litter. Unused cat litter poses no toxoplasmosis threat. Used cat litter is not recommended for use in the garden. No medical conditions are known to be aggravated by exposure to this product. FIRST AID: INHALATION: Remove to fresh air. If breathing problems develop, call a doctor. EYE CONTACT: Flush eyes with plenty of water for 15 minutes. If irritation persists, call a doctor. SKIN CONTACT: Wash skin with water. INGESTION: Drink a glassful of water. Call a doctor or poison control center.	<table border="1"> <thead> <tr> <th>Ingredient</th> <th>Concentration</th> <th>Worker Exposure Limit</th> </tr> </thead> <tbody> <tr> <td>Bentonite clay CAS # 1302-78-9</td> <td>> 80%</td> <td>Not established.</td> </tr> <tr> <td>Calcium carbonate CAS # 1317-65-3</td> <td>3 - 7%</td> <td>10 mg/m³ - TLV-TWA^a (total dust) 15 mg/m³ - PEL-TWA^b (total dust) 5 mg/m³ - PEL-TWA^b (respirable fraction)</td> </tr> <tr> <td>Crystalline silica (quartz) CAS # 14808-60-7</td> <td>< 6%</td> <td>0.05 mg/m³ - TLV-TWA^a (respirable fraction)</td> </tr> </tbody> </table> <p>^aTLV-TWA = ACGIH Threshold Limit Value - Time Weighted Average ^bPEL-TWA = OSHA Permissible Exposure Limit - Time Weighted Average</p> <p>IARC Monographs (Volume 68, 1997) state that there is sufficient evidence of the carcinogenicity of inhaled crystalline silica (quartz) from occupational sources in humans. IARC classification - Group 1.</p> <p>None of the other materials in this product are on the IARC, OSHA, or NTP carcinogen lists.</p>	Ingredient	Concentration	Worker Exposure Limit	Bentonite clay CAS # 1302-78-9	> 80%	Not established.	Calcium carbonate CAS # 1317-65-3	3 - 7%	10 mg/m ³ - TLV-TWA ^a (total dust) 15 mg/m ³ - PEL-TWA ^b (total dust) 5 mg/m ³ - PEL-TWA ^b (respirable fraction)	Crystalline silica (quartz) CAS # 14808-60-7	< 6%	0.05 mg/m ³ - TLV-TWA ^a (respirable fraction)
Ingredient	Concentration	Worker Exposure Limit											
Bentonite clay CAS # 1302-78-9	> 80%	Not established.											
Calcium carbonate CAS # 1317-65-3	3 - 7%	10 mg/m ³ - TLV-TWA ^a (total dust) 15 mg/m ³ - PEL-TWA ^b (total dust) 5 mg/m ³ - PEL-TWA ^b (respirable fraction)											
Crystalline silica (quartz) CAS # 14808-60-7	< 6%	0.05 mg/m ³ - TLV-TWA ^a (respirable fraction)											
IV Special Protection and Precautions	V Transportation and Regulatory Data												
Hygienic Practices: Wash hands after direct contact. Engineering Controls: Use general ventilation to minimize exposure to dust. Personal Protective Equipment: In situations where exposure limits may be exceeded, a NIOSH-approved respirator is advised. Particles may scratch hard surfaces, such as vinyl flooring. Do not use this product as a traction aid because product becomes slippery and slick when wet.	DOT/IATA/IMDG: Not restricted. EPA - SARA Title III/CERCLA: This product is regulated under Sections 311/312. This product contains no chemicals regulated under Section 313 or under Section 304/CERCLA.												
VI Spill Procedures/Waste Disposal	VII Reactivity Data												
Spill Procedures: Vacuum sweep, if possible, to avoid generating airborne dust. Wash residual down to sanitary sewer. Contact the sanitary treatment facility in advance to assure ability to process washed-down material. Waste Disposal: Reclaim, if possible, since material may be used as an absorbent for liquid spills. Otherwise, dispose of in accordance with all applicable federal, state, and local regulations.	Stable under normal use and storage conditions.												
VIII Fire and Explosion Data	IX Physical Data												
Not flammable or explosive.	Bulk density (g/cm ³).....~1.1 Solubility in water.....Insoluble												