Material Safety Data Sheet

Floor Stripper

1. Product and company identification

Product nameFloor StripperIn case of emergencyCode17791, 17792, 1369149Validation dateMaterial usesFloor finish removerPrint date

2200 Kensington Court Oak Brook, IL 60523-2100 Phone: 630-990-6600

Ace Hardware Corp.

Hazardous Material Information System (U.S.A.)

riazar acac material micrimation cyclom (cicii a)					
Health	* 3	HAZARD RATING			
Flammability	0	4 = Extreme 3 = High			
Physical hazards	1	2 = Moderate 1 = Slight			
Personal protection	С	0 = Insignificant			

A = Goggles B = Goggles & Gloves C = Goggles, Gloves & Apron

2. Hazards identification

Emergency overview WARNING!

Manufacturer

HARMFUL IF ABSORBED THROUGH SKIN OR IF SWALLOWED. CONTAINS MATERIAL THAT MAY

CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA.

Harmful in contact with skin and if swallowed. Do not breathe vapor or mist. Do not ingest. Do not get in eyes or on skin or clothing. Contains material that may cause target organ damage, based on animal data. Wash thoroughly after handling.

Responsible name

1-800-843-6174

Regulatory Affairs Department

4/1/2011

4/1/2011.

Potential acute health effects due to overexposure

Inhalation Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following

exposure.

Ingestion May be toxic if swallowed.

Skin Corrosive to the skin. May cause severe burns.

Eyes No known significant effects or critical hazards.

Potential chronic health effects due to overexposure

CarcinogenicityNo known significant effects or critical hazards.MutagenicityNo known significant effects or critical hazards.TeratogenicityNo known significant effects or critical hazards.Developmental effectsNo known significant effects or critical hazards.Fertility effectsNo known significant effects or critical hazards.

See toxicological information (section 8)

3. Composition/information on ingredients

 Name
 CAS number
 %

 2-butoxyethanol
 111-76-2
 10 - 30

 2-aminoethanol
 141-43-5
 1 - 5

SARA 313 (Form R - Reporting requirements)

Product nameCAS numberConcentration2-butoxyethanol111-76-222.852

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

4. First aid measures

Eye contact Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes,

occasionally lifting the upper and lower eyelids. Get medical attention immediately.

Skin contact In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing

contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get

medical attention immediately.

Inhalation Move exposed person to fresh air. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical

attention immediately.

Ingestion Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Get

medical attention immediately.

Protection of first-aiders No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are

still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing

thoroughly with water before removing it, or wear gloves.

Notes to physician In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may

need to be kept under medical surveillance for 48 hours.

5. Fire-fighting measures

Flammability of the product In a fire or if heated, a pressure increase will occur and the container may burst.

Extinguishing media

Suitable Use an extinguishing agent suitable for the surrounding fire.

Special exposure hazards Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action

shall be taken involving any personal risk or without suitable training.

Hazardous thermal decomposition Decomposition products may include the following materials:

carbon dioxide

products

carbon monoxide nitrogen oxides

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA)

with a full face-piece operated in positive pressure mode.

6. Control and preventive measures

Storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Ingredient	Exposure limits
2-butoxyethanol	OSHA PEL 1989 (United States, 3/1989). Absorbed through skin. TWA: 25 ppm 8 hour(s). TWA: 120 mg/m³ 8 hour(s). NIOSH REL (United States, 12/2001). Absorbed through skin. TWA: 5 ppm 10 hour(s). TWA: 24 mg/m³ 10 hour(s). ACGIH TLV (United States, 1/2008). TWA: 20 ppm 8 hour(s). OSHA PEL (United States, 11/2006). Absorbed through skin. TWA: 50 ppm 8 hour(s). TWA: 240 mg/m³ 8 hour(s).
2-aminoethanol	ACGIH TLV (United States, 1/2008). TWA: 3 ppm 8 hour(s). OSHA PEL 1989 (United States, 3/1989). TWA: 3 ppm 8 hour(s). NIOSH REL (United States, 12/2001). TWA: 3 ppm 10 hour(s). OSHA PEL (United States, 11/2006). TWA: 3 ppm 8 hour(s). TWA: 6 mg/m³ 8 hour(s).

Personal protection

Skin

Odor

Respiratory None required. However, use of adequate ventilation is good industrial practice.

Hands Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when

handling chemical products if a risk assessment indicates this is necessary.

Personal protective equipment for the body should be selected based on the task being performed and the

risks involved and should be approved by a specialist before handling this product.

Eyes Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is

necessary to avoid exposure to liquid splashes, mists or dusts.

Methods for cleaning up

Small spill Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or

absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a

licensed waste disposal contractor.

Solvent (Delete)

Waste disposal Disposal of this product, solutions and any by-products should at all times comply with the requirements of

environmental protection and waste disposal legislation and any regional local authority requirements.

7. Physical and chemical properties

Physical stateLiquidBoiling/condensation point100°C (212°F)ColorRedMelting/freezing point0°C (32°F)

Vapor pressure <4 kPa (<30 mm Hg)

Vapor density <1 [Air = 1]

Weight per Gallon:

Specific Gravity: N.E.

pH 10.5 to 11.5 **1% pH:** 10.5 to 11.5 [Basic.]

Toxicological information 8.

Result	Species	Dose	Exposure
LD50 Dermal	Rabbit	220 mg/kg	- 1
LD50 Intraperitoneal	Rat	220 mg/kg	-
LD50 Intravenous	Rat	307 mg/kg	-
LD50 Oral	Rat	917 mg/kg	-
LD50 Oral	Rat	250 mg/kg	-
LD50 Unreported	Rat	917 mg/kg	-
LDLo Oral	Rat	1500 mg/kg	-
TDLo Oral	Rat	500 mg/kg	-
TDLo Unreported	Rat	250 mg/kg	-
LC50 Inhalation Vapor	Rat	2900 mg/m3	7 hours
LC50 Inhalation Gas.	Rat	450 ppm	4 hours
LD50 Oral	Rat	1720 mg/kg	-
	LD50 Dermal LD50 Intraperitoneal LD50 Intravenous LD50 Oral LD50 Oral LD50 Unreported LDL0 Oral TDL0 Oral TDL0 Unreported LC50 Inhalation Vapor LC50 Inhalation Gas.	LD50 Dermal Rabbit LD50 Intraperitoneal Rat LD50 Intravenous Rat LD50 Oral Rat LD50 Oral Rat LD50 Unreported Rat LDL0 Oral Rat TDL0 Oral Rat TDL0 Unreported Rat LC50 Inhalation Vapor LC50 Inhalation Gas. Rat	LD50 Dermal Rabbit 220 mg/kg LD50 Intraperitoneal Rat 220 mg/kg LD50 Intravenous Rat 307 mg/kg LD50 Oral Rat 917 mg/kg LD50 Oral Rat 250 mg/kg LD50 Unreported Rat 917 mg/kg LDLo Oral Rat 1500 mg/kg TDLo Oral Rat 500 mg/kg TDLo Unreported Rat 250 mg/kg LC50 Inhalation Vapor Rat 2900 mg/m3 LC50 Inhalation Gas. Rat 450 ppm

Conclusion/Summary Not available

Chronic toxicity

Conclusion/Summary Not available

9. Transport information						
Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	UN1719	Caustic alkali liquids, n.o.s. (2-aminoethanol)	8	III	CORROSIVE	-

PG* : Packing group