



**PLAINSMAN**  
 702 Wood Street, Medicine Hat, Alta.  
 Phone 403-527-8535 FAX 527-7508  
 http://www.plainsmanclays.com  
 plainsman@telus.net

# Material Safety Data Sheet

## Alberta Slip

1-800-4Laguna info@Lagunaclay.com

Further Physical Properties and Descriptive Literature is Available on Request or On Our Web Site

### Section 1 - Product Information

**Product Name:** Alberta Slip  
**Description:** Clay/Mineral blend used for Pottery (dry powder)  
**Product Use:** Pottery glaze ingredient  
**CEPA Status:** All ingredients listed on Canadian domestic substances list (DSL)

**WHMIS Class:**  
 No hazardous classes apply  
**EPA TSCA Status:**  
 All ingredients are included in the inventory

### Section 2 - Hazardous Ingredients

Hazardous Ingredient	%	CAS Number	OSHA PEL	ACGIH TLV
*Respirable Free Silica (Quartz)		14808-60-7	3 mg/m <sup>3</sup>	0.1 mg/m <sup>3</sup>
Powder minerals added to the blend are 7% Talc (Steatite CAS 14807-96-6), 10% Calcium Carbonate (CAS 1317-65-3), 15% Nepheline Syenite (Feldspar CAS 37244-96-5), 2% Iron Oxide (CAS 1317-61-9) (the clay component itself also contains amount of these minerals also)				

\*Note: Free Silica is not a hazard in moist or wet form, it is only a hazard if clay is dry and dust is generated.

### Section 3 - Physical Data

**Physical State:** Solid **Physical Properties Not Applicable:**

**Odour and Appearance:** Light brownish grey powder  
 \*'pugged' refers to the wet plastic material

Odour Threshold, Vapour Pressure & Density, Evaporation Rate, Boiling Point, Freezing Point, pH, Specific Gravity, Coeff. Water/Oil Dis.

### Section 4 - Fire and Explosion Data

**Flammability:**  Yes  No Consider dust as Non-Flammable and Non-Explosive

**Non-Applicable Data:** Means of Extinction, Flashpoint and Method, Autoignition Temperature, Upper Flammable Limit, Lower Flammable Limit, Hazardous Combustion Products, Sensitivity to Impact, Sensitivity to Static Discharge

**Products of Decomposition During Kiln Burning:** Carbon Monoxide, Carbon Dioxide and possible traces of Sulfur Dioxide. Vent kiln during firing.

### Section 5 - Reactivity Data

**Chemical Stability:**  Yes  No **Conditions of Instability:** None **Solubility in Water:** No

**Incompatibility with Other Substances:**  Yes  No **Incompatible Substances:** None

**Hazardous Decomposition Products:** See section 4

**Reactivity, and Under What Conditions:** Inert and Non-Reactive except for calcium carbonate which reacts with acids to liberate carbon dioxide

## Section 6 - Toxicological Properties

Route of Entry:  Skin Contact  Skin Absorption  Eye Contact  Inhalation  Ingestion

Effect of Acute Exposure to Product: A nuisance dust, heavy exposure may cause mechanical irritation of the respiratory tract.

Irritancy of Product: Mechanical Irritant Only

Non-Applicable Properties: Sensitization, Teratogenicity, Reproductive Toxicity, Mutagenicity

Effects of Chronic Exposure to Respirable Quartz Dust: IARC has found evidence for the carcinogenicity of crystalline quartz. Avoid prolonged or repeated inhalation of dust. Long term exposure may cause silicosis.

Exposure Limits to Quartz: TLV = 0.1 mg/m<sup>3</sup> respirable crystalline silica

Synergistic Products: Tobacco smoke will increase lung damage

## Section 7 - Preventive Measures

### Personal Protective Equipment

Gloves: Not Req'd

Special Clothing: Not Req'd

Eye: May cause mechanical irritation on direct contact or where contact lenses are worn in high dust conditions

Footwear: Not applicable unless wet material is a slip hazard

Respirator (Specify):  
Approved Respirator where TLV exceeded

Ventilation: Local exhaust or other ventilation that will reduce dust concentration to less than permissible exposure limits is recommended

Leak and Spill Procedure: Aqueous slurry is a slipping hazard. If dry minimize excessive dust generation, if sweeping use dust suppressant.

Skin Contact: Wash with water.

Waste Disposal at Landfill: Treat this as a blend of naturally occurring minerals.

Storage Requirements: No special requirements, store powders in dry area.

Special Shipping Information: Not required.

Education: Many governments require that personnel working with crystalline silica receive training in safe work habits, respiratory protection and health risks.

Clothing: Do not wear clothing dusted with this product in your home.

Laguna Clay Company    [www.Lagunaclay.com](http://www.Lagunaclay.com)    1-800-4Laguna    [info@Lagunaclay.com](mailto:info@Lagunaclay.com)

## Section 8 - First Aid Measures

Skin - Wash with water

Eyes - Flush with running water until material is removed

## Section 9 - Preparation Data of MSDS

Prepared by  
Plainsman Clays Limited

Date: January 1, 2012