



Material Safety Data Sheet

Gold Bond® BRAND eXP Interior Extreme Products

MSDS No: GB-1008

Date: Page 1 of 7
March 6, 2013
July 26, 2011

1. PRODUCT AND COMPANY INFORMATION

Manufacturer Information:

National Gypsum Company
2001 Rexford Road
Charlotte, NC 28211

For Emergency Product Information Call:

Director Quality Services
(704) 551-5820 - 24 Hour Emergency Response
Website: www.nationalgypsum.com

Product Name: **eXP Interior Extreme**
eXP Interior Extreme AR (Abuse Resistant)
eXP Interior Extreme IR (Impact Resistant)

Use: Interior building walls where moisture is a concern

Generic Descriptions: Article composite. **eXP Interior Extreme** gypsum panels consist of a fire resistant, moisture resistant gypsum core encased in a moisture resistant, coated fiberglass mat.

2. HAZARDS IDENTIFICATION

Appearance and Odor: A gypsum core wrapped with an off white coated fiberglass mat. Composite material provides mildew protection. No odor.

Contains no asbestos. HMIS Hazard Class No. 1, 0, 0.

Emergency Overview

eXP Interior Extreme panels do not present an inhalation, ingestion, or contact health hazard unless subjected to operations such as sawing, sanding or machining which results in the generation of airborne particulate. This product contains quartz (crystalline silica) as a naturally occurring contaminant. It is recommended that a NIOSH approved particulate respirator be worn whenever working with this product results in airborne dust exposure exceeding the prescribed limits.
(See Section 11 - Toxicological Information)

OSHA Regulatory Status

While this material is not considered hazardous by the OSHA Hazard Communication Standard (29CFR 1910.1200), this MSDS contains valuable information critical to the safe handling and proper use of the product. This MSDS should be retained and available for employees and other users of this product.

2. HAZARDS IDENTIFICATION (CONTINUED)**Potential Health Effects**

Primary Routes of Entry: Inhalation, Dermal contact

Target Organs: Respiratory system, skin, eyes.

Inhalation: Acute exposure to airborne dust concentrations in excess of the PEL/TLV may result in coughing, dyspnea, wheezing, general irritation of the nose, throat, and upper respiratory tract, and impaired pulmonary function. Chronic exposures may result in lung disease (silicosis and/or lung cancer). (See Section 11 - Toxicological Information)

Exposures to respirable crystalline silica have not been documented during normal use of this product. However, good housekeeping practices and industrial hygiene monitoring is recommended when the potential for significant exposure exists.

Skin Contact: Continued and prolonged contact may result in dry skin. Contact with dust or glass fibers may produce itching, rash and/or redness. Repeated or prolonged exposure may result in dermatitis.

Eye Contact: Direct contact may cause mechanical irritation.

Ingestion: No known adverse effects. May result in obstruction or temporary irritation of the digestive tract.

3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Component</u>	<u>CAS-Number</u>	<u>Weight Percent</u>
Calcium Sulfate Dihydrate (Gypsum)	10101-41-4	>91
Crystalline Silica (Quartz)	14808-60-7	varies
Vermiculite	1318-00-9	<2
Fiberglass, synthetic, vitreous, continuous	65997-17-3	<1%
Proprietary Additives*	NA	<5

* Note: No single proprietary ingredient is in excess of 1% (0.1% for carcinogens) of the mixture.

4. FIRST AID MEASURES

- **Inhalation:** Remove exposed individual to fresh air immediately. If breathing difficulty persists, seek medical attention.
- **Skin:** Flush and wash skin with soap and water. Utilize lotions to alleviate dryness if present. Seek medical attention if irritation persists.
- **Eye:** Immediately flush eyes with water for 15 minutes. Remove contact lenses (if applicable). Seek medical attention if irritation persists.
- **Ingestion:** Gypsum is non-hazardous and no harmful effects are expected upon ingestion of small amounts. Larger amounts may cause abdominal discomfort or possible obstruction of the digestive tract. Seek medical attention if problems persist.

5. FIRE FIGHTING MEASURES**Flammable Properties**

- Not flammable or combustible
- NFPA Hazard Class No: 1/0/0

Extinguishing media

- Dry chemical, foam, water, fog or spray

Protection of firefighters

- Standard protective equipment and precautions

Fire and Explosion Hazards

- None

Hazardous Combustion Products

- None
- Above 1450°C, material can decompose and release sulfur dioxide (SO₂) and oxides of carbon.

6. ACCIDENTAL RELEASE MEASURES

Not applicable, as product is an article composite.

General recommendations:

- Wear appropriate Personal Protective Equipment. (See Section 8)
- Maintain proper ventilation.
- Pick-up larger pieces to avoid a tripping hazard. Return large pieces of damaged/scraped material for recycling. Sweep or vacuum remaining material into a waste container for disposal. Use a light water spray to minimize dust generation.
- Waste material is not a hazardous waste. Dispose of in accordance with applicable federal, state, and local regulations.

7. HANDLING AND STORAGE

- Avoid contact with eyes, skin and clothing.
- Wear recommended personal protective equipment when handling. (See Section 8)
- Avoid breathing dust.
- Minimize generation of dust.
- Utilize proper lifting techniques when moving product and employ mechanical/ergonomic assistance when possible (i.e. move with forklifts, hold in place with lifts) to minimize the risk of back injury.
- Store material in a cool, dry, ventilated area.
- Store panels flat to minimize damage and warping.
- Do not stack panels too high when storing to minimize the risk of falling.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Exposure Guidelines**

Component	Exposure Limits	
	OSHA PEL (mg/m3)	ACGIH TLV (mg/m3)
Calcium Sulfate Dihydrate (Gypsum)	15 ^(T) 5 ^(R)	10 ^(T)
Crystalline Silica (Quartz)	0.1 ^(R)	0.025 ^(R)
Fiberglass, synthetic, vitreous, continuous	15 ^(T) 5 ^(R)	1 f/cc ^(R)
Proprietary Additives	NA	NA

T- Total Dust

R- Respirable Dust

Engineering Controls

- Work/Hygiene Practices: The score and snap method of cutting is recommended. Sawing, drilling or machining will produce dust.
- Ventilation: Provide local and general exhaust ventilation to maintain a dust level below the PEL/TLV.
- Utilize wet methods, when appropriate, to reduce generation of dust.

Personal Protective Equipment

- Respiratory Protection: A NIOSH approved particulate respirator is recommended in poorly ventilated areas or if the PEL/TLV is exceeded. OSHA's 29 CFR 1910.134 (Respiratory Protection Standard) must be followed whenever work conditions require respirator use.
- Eye Protection: Safety glasses or goggles.
- Skin: Gloves, protective clothing and/or barrier creams may be utilized if conditions warrant.

9. PHYSICAL AND CHEMICAL PROPERTIES**Appearance:** Coated gypsum boards with white/gray core**Odor:** None**Physical State:** Solid**Ph:** ~7**Solubility (H2O):** 2.1 g/L @ 20°C**Boiling, Freezing, Melting Point:** Not Applicable**Decomposition Temperature:** 1450°C**Vapor pressure:** Not Applicable**Vapor density:** Not Applicable**Volatile organic compounds (VOC) content:** None**Flammability:** Not Applicable**Flash Point:** Not Applicable**Upper/Lower explosive limits:** Not applicable**Auto-ignition temperature:** Not Applicable**Partition coefficient: n-octanol/water:** Not applicable**Evaporation rate:** Not Applicable**Molecular weight:** 172.2 grams**Molecular formula:** CaSO₄·2H₂O**Specific Gravity:** 2.31 g/cc**Bulk Density:** ~55 lb/ft³

10. STABILITY AND REACTIVITY

Chemical stability: Stable in dry environments.

Conditions to avoid: Contact with strong acids may result in generation of carbon dioxide.

Incompatibility: None

Hazardous decomposition: Above 1450°C gypsum will decompose to calcium oxide (CaO), with releases of sulfur dioxide (SO₂) and various oxides of carbon.

Hazardous polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Data presented is for the major component of this product: Gypsum (calcium sulfate dihydrate)

Human Data

There is no information on toxicokinetics, metabolism and distribution.

There have been reports of irritation to mucus membranes of the eyes and respiratory tract upon acute exposure to dusts in excess of the recommended limits.

Chronic exposure to crystalline silica (a naturally occurring contaminant in gypsum) in the respirable size has been shown to cause silicosis, a debilitating lung disease. In addition, the International Agency for Research on Cancer (IARC) classifies crystalline silica inhaled in the form of quartz or cristobalite from occupational sources as carcinogenic to humans, Group 1. The National Toxicology Program (NTP) classifies respirable crystalline silica as a substance which may be reasonably anticipated to be a carcinogen. OSHA does not regulate crystalline silica as a human carcinogen. Industrial hygiene monitoring to date has not identified any detectable respirable crystalline silica in dust sampling conducted during gypsum panel installation utilizing recommended procedures.

Animal Data

The acute oral toxicity study [OECD TG 420, Fixed dose procedure] of calcium sulfate dihydrate showed that this chemical did not cause any changes even at 2,000 mg/kg b.w. Therefore, the oral LD₅₀ value was more than 2,000-mg/kg b.w. for female rats (Sprague-Dawley).

Calcium sulfate, dihydrate was not irritating to the skin of rabbits at 1, 24, 48 and 72 hours after removal of test patches [OECD TG 404]. There is no indication of skin sensitization in guinea pigs [OECD TG 406].

In vivo and *In vitro* studies for mutagenicity were negative.

Reproduction/Developmental Toxicity Screening Tests were negative.

12. ECOLOGICAL INFORMATION

This product does not present an ecological hazard to the environment.

Ecotoxicological Information

Toxicity studies performed with fish, aquatic invertebrates and aquatic plants showed no toxic effect.

Environmental Fate

Gypsum is a naturally occurring mineral. Biodegradation and/or bioaccumulation potential is not applicable.

13. DISPOSAL CONSIDERATIONS

- Dispose of according to Local, State, Federal, and Provincial Environmental Regulations.
- Recycle if possible.

16. OTHER INFORMATION (CONTINUED)

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind expressed or implied is made with respect to the information contained herein. This material safety data sheet was prepared to comply with the OSHA Hazard Communication Standard (29 CFR 1910.1200) and with the Workplace Hazardous Materials Information System (WHMIS).

Disclaimer of Liability:

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of the material. Information contained herein is believed to be true and accurate, but all statements or suggestions are made without any warranty, express or implied, regarding accuracy of the information, the hazards connected with the use of the material, or the results to be obtained for the use thereof.