

# Firestone Building Products Company, LLC

## Material Safety Data Sheet

February 2, 2012

Page: 1

### SECTION 1: PRODUCT IDENTIFICATION

Product Name: AP Sealant  
 Chemical Name / Synonym: Sealant  
 Chemical Family: Mixture  
 24-Hour Emergency Phone: (800) 424-9300 CHEMTREC  
 Manufacturer's Name: Firestone Building Products Company, LLC  
 Manufacturer's Address: 250 West 96<sup>th</sup> Street, Indianapolis, IN 46260  
 NFPA Hazard Rating: Health 2, Flammability 2, Reactivity 0  
 HMIS Hazard Rating: Health 2, Flammability 2, Reactivity 0

### SECTION 2: CHEMICAL COMPOSITION

Chemical Name:	Common Name:	CAS #:	% (by wt)	Exposure Limits:
Calcium Carbonate	Limestone	1317-65-3	≤30	PEL 15 mg/m <sup>3</sup> (Total) PEL 5 mg/m <sup>3</sup> (Respirable)
Talc	Talcum	14807-96-6	≤7	TLV 2 mg/m <sup>3</sup> (Respirable) PEL 20 mppcf
Titanium Dioxide	None	13463-67-7	≤7	TLV 10 mg/m <sup>3</sup> PEL 15 mg/m <sup>3</sup>
Stoddard Solvent	White Spirits	8052-41-3	≤5	TLV 100 ppm PEL 500 ppm
Bis(2-propylheptyl) phthalate	None	53306-54-0	≤5	None Established
Calcium Oxide	Lime	1305-78-8	≤2	TLV 2 mg/m <sup>3</sup> PEL 5 mg/m <sup>3</sup>
Toluene-2,6-diisocyanate	TDI	91-08-7	≤1	TLV 0.005 ppm TLV-STEL 0.02 ppm PEL-C 0.02 ppm
Toluene-2,4-diisocyanate	TDI	584-84-9	≤1	TLV 0.005 ppm TLV-STEL 0.02 ppm PEL-C 0.02 ppm
Nonhazardous as per 29 CFR 1910.1200.	None	None	>42	None Established

### SECTION 3: HAZARD IDENTIFICATION

Primary Route of Exposure: Inhalation and skin  
 Signs and Symptoms of Exposure: Eye contact may cause eye irritation. Prolonged or repeated skin contact may cause irritation or sensitization. Inhalation of vapors associated with the solvent portion of this product may cause respiratory system irritation and central nervous system depression (narcosis) characterized by headache, dizziness, muscular weakness and fatigue. This product may

# Firestone Building Products Company, LLC

## Material Safety Data Sheet

February 2, 2012

Page: 2

---

	contain a small amount (<2%) of a respiratory sensitizer. Also, prolonged repeated exposure can lead to skin sensitization. For persons so sensitized, even brief exposures can produce reddening, swelling, rash, or blisters of the skin, or produce chemical asthma. Although ingestion is an unlikely route of exposure, doing so may cause irritation to the mouth, throat and stomach.
Medical Conditions Aggravated by Exposure:	Pre-existing respiratory or skin disorders may be aggravated by exposure to this material. Those with asthma or allergies to isocyanates should consult with their physician prior to use/exposure.
Chronic Effects:	Repeated, prolonged occupational over-exposure to the solvent portion of this product may cause kidney, liver, and central nervous system damage. This product contains a small percent ( $\leq 2\%$ ) of TDI, which is a respiratory sensitizer. It may cause allergic reaction leading to asthmatic-like response.
Carcinogenicity:	Titanium dioxide is classified by IARC as a group 2B, <i>possibly carcinogenic to humans</i> . TDI is classified by IARC as a group 2B, <i>possibly carcinogenic to humans</i> and by NTP as <i>reasonably anticipated to be a human carcinogen</i> .

---

### SECTION 4: FIRST AID MEASURES

---

First Aid Procedures:	If this material contacts the eyes, hold eyelids open and flush immediately with a gentle stream of water for at least 15 minutes, preferably at an eyewash fountain. Get medical attention. In case of skin contact, clean affected area immediately with soap and water. In case of inhalation, remove to fresh uncontaminated air. Administer oxygen if breathing is labored. Give artificial respiration if breathing has stopped. Get medical attention immediately if oxygen or artificial respiration is administered. In case of accidental ingestion, do NOT induce vomiting. Get medical attention and advise the physician of the nature of the material.
-----------------------	--

---

### SECTION 5: FIRE FIGHTING PROCEDURES

---

Suitable Extinguishing Media:	Carbon dioxide, dry chemical, alcohol foam or water fog.
Hazardous Combustion Products:	Carbon dioxide, carbon monoxide, isocyanates, and acrid smoke and irritating fumes.
Recommended Fire Fighting Procedures:	Wear impermeable protective clothing and self-contained breathing apparatus. Toxic fumes and vapors may be evolved.
Unusual Fire and Explosion Hazards:	Do not use a direct stream of water. Direct stream of water into hot burning material will cause splattering. Heat (from fire) builds up pressure in closed containers. Cool with water stream.

---

### SECTION 6: PRECAUTIONS FOR SAFE HANDLING AND USE

---

Steps to Be Taken in Case Material is Released or Spilled:	Remove ignition sources. Absorb on inert material. Use non-sparking tools. Place in secure containers for disposal.
Precautions to Be Taken in Handling and Storing:	Keep away from heat, sparks, and open flames. Keep containers closed, and stored at temperatures of 65° – 104° F. Use in a well-ventilated location. Do not cut, drill, grind, weld or perform similar operations on or near containers.

# Firestone Building Products Company, LLC

## Material Safety Data Sheet

February 2, 2012

Page: 3

---

### SECTION 7: EXPOSURE CONTROLS / PERSONAL PROTECTION

---

Ventilation:	Use in a well-ventilated location.
Respiratory Protection:	If personal exposure concentrations cannot be maintained below the appropriate exposure limits using engineering controls, a NIOSH-approved respirator may be appropriate based on employer-determined exposure levels.
Eye Protection:	Safety glasses with side shields or chemical splash goggles may be warranted if eye contact is likely when using this product.
Skin Protection:	Nitrile or polyvinyl alcohol gloves may be warranted for direct handling.
Other:	Not required.
Work / Hygienic Practices:	Wash exposed skin prior to eating, drinking and smoking and at the end of each work shift. Wash contaminated clothing prior to reuse. Avoid breathing vapors from heated material.

---

### SECTION 8: PHYSICAL AND CHEMICAL PROPERTIES

---

Appearance and Odor:	Grey paste with paint thinner odor.		
Flash Point:	192° F	Lower Explosive Limit:	Approx. 1.0% (based on solvent)
Method Used:	ASTM D3278	Upper Explosive Limit:	Approx. 6.0% (based on solvent)
Evaporation Rate:	Unknown	Boiling Point:	Not Applicable
pH:	Not Determined	Melting Point:	Not Applicable
Solubility in Water:	Insoluble	Specific Gravity:	Unknown
Vapor Density:	1.2	Volatile Organic Compounds:	Unknown
Vapor Pressure:	Not Determined		

---

### SECTION 9: STABILITY AND REACTIVITY

---

Thermal Stability:	Stable under normal storage conditions.
Hazardous Polymerization:	Will not occur under normal conditions.
Conditions to Avoid:	Avoid long-term exposure to elevated temperatures, strong bases, oxidizing agents, alcohols, moisture and water.

---

### SECTION 10: TRANSPORTATION

---

Regulatory Agency:	Not Regulated
Proper Shipping Name:	Not Applicable
Hazard Classification:	Not Applicable
Identification Number:	Not Applicable
Packing Group:	Not Applicable
Labels Required:	Not Applicable
Other Requirements:	Not Applicable

# Firestone Building Products Company, LLC

## Material Safety Data Sheet

February 2, 2012

Page: 4

---

### SECTION 11: MISCELLANEOUS INFORMATION

---

Additional Comments:	The solids of this product, listed in Section 2, are not expected to be released.
Date of Previous MSDS:	November 2, 2010
Changes Since Previous MSDS:	Chemical composition in section 2; additional information in section 5; physical property information in section 8; information in section 9; transportation information in section 10; company name.
Telephone Number for Additional Information:	(317) 575-7190

---

### DISCLAIMER

---

The information contained herein is based on data considered accurate which has been obtained from other companies and organizations. However, no warranty or representation is expressed or implied that the information, is accurate, complete or representative. Firestone Building Products Company, LLC assumes no responsibility for injury to the buyer, the buyer's employees, or any third persons, if reasonable safety procedures are not followed. Additionally, Firestone Building Products Company assumes no responsibility for injury to buyer, the buyer's employees, or any third persons caused by abnormal use of this material, even if reasonable safety procedures are followed.