

-----  
M A T E R I A L   S A F E T Y   D A T A   S H E E T  
-----

=====

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

=====

PRODUCT NAME : PROTECTO-FLEX 310BC COMP. B  
IDENTIFICATION NUMBER: PFL310BCB000000B PREPARE / REVISED: 08/07/06  
PRODUCT USE/CLASS : EPOXY HARDENER

SUPPLIER: Dudick, Inc. 1818 Miller Parkway Streetsboro, Ohio 44241	MANUFACTURER: Dudick, Inc. 1818 Miller Parkway Streetsboro, Ohio 44241
---	---

CHEM-TEL: 800-255-3924 24 HOURS A DAY	CHEM-TEL: 800-255-3924 24 HOURS A DAY
--	--

PREPARER: DUDICK, INC., PHONE: 800-322-1970

=====

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

=====

ITEM	CHEMICAL NAME	CAS NUMBER	WT/WT % LESS THAN
01	AMINO POLYAMIDE	UNKNOWN	30.0 %
02	BENZYL ALCOHOL	100-51-6	30.0 %
03	ISOPHORONE DIAMINE	2855-13-2	20.0 %
04	XYLENE, MIXED ISOMERS	1330-20-7	15.0 %
05	ETHYLBENZENE	100-41-4	10.0 %
06	2,4,6-TRI(DIMETHYLAMINOMETHYL)PHENOL	90-72-2	5.0 %
07	N-AMINOETHYLPIPERAZINE	140-31-8	5.0 %
08	PARATERTIARYBUTYLPHENOL	98-54-4	5.0 %

ITEM	EXPOSURE LIMITS				COMPANY	
	ACGIH TLV-TWA	ACGIH TLV-STEL	OSHA PEL-TWA	OSHA PEL-CEILING	TLV-TWA	SKIN
01	NO INFO	NO INFO	NO INFO	NO INFO	NE	YES
02	NO INFO	NO INFO	NO INFO	NO INFO	NE	NO
03	NE	NE	NE	NE	NE	YES
04	100PPM	150PPM	100PPM	NO INFO	NE	NO
05	100PPM	125PPM	100PPM	125PPM STEL	NE	YES
06	NE	NE	NE	NE	NE	YES
07	NE	NE	NE	NE	NE	YES
08	NO INFO	NO INFO	NO INFO	NO INFO	NO INFO	YES

(See Section 16 for abbreviation legend)

(Continued on Page 2)

=====

SECTION 3 - HAZARDS IDENTIFICATION

\*\*\* EMERGENCY OVERVIEW \*\*\*: DANGER!---CAUSES BURNS. WARNING!...FLAMMABLE. HARMFUL IF SWALLOWED. DO NOT GET IN EYES, ON SKIN, OR CLOTHING. DO NOT BREATH VAPORS OR MISTS.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: EYE CONTACT MAY CAUSE SEVERE IRRITATION WITH CORNEAL INJURY. MAY CAUSE BLINDNESS.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: SEVERE SKIN IRRITANT.

EFFECTS OF OVEREXPOSURE - INHALATION: MAY CAUSE IRRITATION OF THE NOSE, THROAT, AND LUNGS. THIS PRODUCT CONTAINS XYLENE WHICH AT HIGH VAPOR CONCENTRATIONS MAY CAUSE HEADACHE, DIZZINESS, ANESTHETIC EFFECTS AND MAY HAVE CENTRAL NERVOUS SYSTEM EFFECTS. CONCENTRATIONS OF 10,000 PPM OF XYLENE CAN BE IMMEDIATELY DANGEROUS TO LIFE AND HEALTH. VAPORS AND MISTS MAY BE CORROSIVE TO THE RESPIRATORY TRACT.

EFFECTS OF OVEREXPOSURE - INGESTION: INGESTION MAY CAUSE BURNS TO THE MOUTH, THROAT, AND ESOPHAGUS. INGESTION MAY CAUSE NAUSEA, CRAMPS, VOMITING, AND DIARRHEA.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: ALLERGIC REACTIONS MAY OCCUR IN SOME INDIVIDUALS. PREEXISTING SKIN AND EYE DISORDERS MAY BE AGGRAVATED BY THIS PRODUCT. MAY CAUSE SKIN SENSITIZATION.

PRIMARY ROUTE(S) OF ENTRY: SKIN CONTACT SKIN ABSORPTION INHALATION INGESTION EYE CONTACT

SECTION 4 - FIRST AID MEASURES

FIRST AID - EYE CONTACT: HOLD OPEN EYE LIDS AND FLUSH WITH COPIOUS AMOUNTS OF FLOWING WATER FOR AT LEAST 15 MINUTES. SEEK MEDICAL ATTENTION.

FIRST AID - SKIN CONTACT: WASH AFFECTED AREAS THOROUGHLY WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND WASH THOROUGHLY BEFORE REUSE.

FIRST AID - INHALATION: REMOVE VICTIM TO FRESH AIR. IF VICTIM IS NOT BREATHING, ARTIFICIAL RESPIRATION SHOULD BE ADMINISTERED BY QUALIFIED PERSONNEL. SUPPLEMENTAL OXYGEN MAY BE INDICATED. CALL A PHYSICIAN.

FIRST AID - INGESTION: IF SWALLOWED, CALL A PHYSICIAN IMMEDIATELY. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. GIVE VICTIM PLENTY OF WATER TO DRINK IF CONSCIOUS.

SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT: 106 F LOWER EXPLOSIVE LIMIT: 1.0 % (SETAFLASH CLOSED CUP) UPPER EXPLOSIVE LIMIT: 7.0 %

AUTOIGNITION TEMPERATURE: NE

(Continued on Page 3)





=====
SECTION 14 - TRANSPORTATION INFORMATION
=====

DOT TECHNICAL NAME: XYLENE,ISOPHORONEDIAMINE

DOT HAZARD CLASS: 3      HAZARD SUBCLASS: 8

DOT UN/NA NUMBER: UN 2924      PACKING GROUP: III      RESP. GUIDE PAGE: 132

=====
SECTION 15 - REGULATORY INFORMATION
=====

THE FOLLOWING COMPONENTS ARE NOT SUBJECT TO REPORTING IN SECTION 2:

----- CHEMICAL NAME ----- CAS NUMBER      WT/WT % IS LESS THAN
No non-hazardous components exist

U.S. FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

CERCLA - SARA HAZARD CATEGORY:
This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD      CHRONIC HEALTH HAZARD      FIRE HAZARD

SARA SECTION 313:
This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

Table with 3 columns: CHEMICAL NAME, CAS NUMBER, WT/WT % IS LESS THAN. Rows include XYLENE,MIXED ISOMERS (1330-20-7, 15.0 %) and ETHYLBENZENE (100-41-4, 10.0 %).

TOXIC SUBSTANCES CONTROL ACT:
The chemical substances in this product are not on the TSCA Section 8 Inventory.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

----- CHEMICAL NAME ----- CAS NUMBER
No information is available.

U.S. STATE REGULATIONS: AS FOLLOWS -

=====  
SECTION 15 - REGULATORY INFORMATION  
=====

NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product:

----- CHEMICAL NAME ----- CAS NUMBER  
No non-hazardous materials are among the top five ingredients.

PENNSYLVANIA RIGHT-TO-KNOW:

The following non-hazardous ingredients are present in the product at greater than 3%:

----- CHEMICAL NAME ----- CAS NUMBER  
No non-hazardous ingredients are present at greater than 3%.

CALIFORNIA PROPOSITION 65:

WARNING: The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm:

----- CHEMICAL NAME ----- CAS NUMBER  
No Proposition 65 chemicals exist in this product.

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: B, E

=====  
SECTION 16 - OTHER INFORMATION  
=====

HMIS RATINGS - HEALTH: 3\*      FLAMMABILITY: 2      REACTIVITY: 0

VOLATILE ORGANIC COMPOUNDS (VOCS): 1.48 lbs/gal,    178 grams/ltr

LEGEND: N.A. - Not Applicable, N.E. - Not Established,  
N.D. - Not Determined

=====

The information contained on this MSDS has been compiled from information obtained from raw material suppliers and is believed to be accurate. It is the responsibility of the user to comply with all Federal, State and Local Regulations.

=====

<END OF MSDS>