



The Clorox Pet Products Company
 1221 Broadway
 Oakland, CA 94612
 Tel. 1-510-271-7000

Material Safety Data Sheet

I Product: SCOOP AWAY® COMPLETE PERFORMANCE CLUMPING CAT LITTER													
Description: LIGHT AND DARK GRAY CLAY GRANULES WITH A FLORAL, LAVENDER ODOR													
Other Designations	Distributor												
	The Clorox Sales Company 1221 Broadway Oakland, CA 94612												
Emergency Telephone Nos.													
For Medical Emergencies, call 1-800-446-1014. For Transportation Emergencies, call 1-800-424-9300 (Chemtrec).													
II Health Hazard Data	III Hazardous Ingredients												
<p>Inhalation of dust may irritate nose and throat.</p> <p>Cat feces can sometimes transmit a disease called toxoplasmosis. Pregnant women and immunosuppressed persons are most susceptible. Always remember to wash hands thoroughly after handling used cat litter. Unused cat litter poses no toxoplasmosis threat.</p> <p>Used cat litter is not recommended for use in the garden.</p> <p>No medical conditions are known to be aggravated by exposure to this product.</p> <p>FIRST AID:</p> <p>INHALATION: Remove to fresh air. If breathing problems develop, call a doctor.</p> <p>EYE CONTACT: Flush eyes with plenty of water for 15 minutes. If irritation persists, call a doctor.</p> <p>SKIN CONTACT: Wash skin with water.</p> <p>INGESTION: Drink a glassful of water. Call a doctor or poison control center.</p>	<table border="1"> <thead> <tr> <th>Ingredient</th> <th>Concentration</th> <th>Worker Exposure Limit</th> </tr> </thead> <tbody> <tr> <td>Bentonite clay CAS # 1302-78-9</td> <td>> 80%</td> <td>Not established.</td> </tr> <tr> <td>Calcium carbonate CAS # 1317-65-3</td> <td>3 - 7%</td> <td>15 mg/m³ - PEL-TWA^a (total dust) 5 mg/m³ - PEL-TWA^a (respirable fraction)</td> </tr> <tr> <td>Crystalline silica (quartz) CAS # 14808-60-7</td> <td>< 6%</td> <td>0.05 mg/m³ - TLV-TWA^b (respirable fraction)</td> </tr> </tbody> </table> <p>^aPEL-TWA = OSHA Permissible Exposure Limit - Time Weighted Average ^bTLV-TWA = ACGIH Threshold Limit Value - Time Weighted Average</p> <p>IARC Monographs (Volume 68, 1997) state that there is sufficient evidence of the carcinogenicity of inhaled crystalline silica (quartz) from occupational sources in humans. IARC classification - Group 1.</p> <p>None of the other materials in this product are on the IARC, OSHA, or NTP carcinogen lists.</p>	Ingredient	Concentration	Worker Exposure Limit	Bentonite clay CAS # 1302-78-9	> 80%	Not established.	Calcium carbonate CAS # 1317-65-3	3 - 7%	15 mg/m ³ - PEL-TWA ^a (total dust) 5 mg/m ³ - PEL-TWA ^a (respirable fraction)	Crystalline silica (quartz) CAS # 14808-60-7	< 6%	0.05 mg/m ³ - TLV-TWA ^b (respirable fraction)
Ingredient	Concentration	Worker Exposure Limit											
Bentonite clay CAS # 1302-78-9	> 80%	Not established.											
Calcium carbonate CAS # 1317-65-3	3 - 7%	15 mg/m ³ - PEL-TWA ^a (total dust) 5 mg/m ³ - PEL-TWA ^a (respirable fraction)											
Crystalline silica (quartz) CAS # 14808-60-7	< 6%	0.05 mg/m ³ - TLV-TWA ^b (respirable fraction)											
IV Special Protection and Precautions	V Transportation and Regulatory Data												
<p>Hygienic Practices: Wash hands after direct contact.</p> <p>Engineering Controls: Use general ventilation to minimize exposure to dust.</p> <p>Personal Protective Equipment: In situations where exposure limits may be exceeded, a NIOSH-approved respirator is advised.</p> <p>Particles may scratch hard surfaces, such as vinyl flooring.</p> <p>Do not use this product as a traction aid because product becomes slippery and slick when wet.</p>	<p>DOT/IATA/IMDG: Not restricted.</p> <p>EPA - SARA Title III/CERCLA: This product is regulated under Sections 311/312. This product contains no chemicals regulated under Section 313 or under Section 304/CERCLA.</p>												
VI Spill Procedures/Waste Disposal	VII Reactivity Data												
<p>Spill Procedures: Vacuum sweep, if possible, to avoid generating airborne dust. Wash residual down to sanitary sewer. Contact the sanitary treatment facility in advance to assure ability to process washed-down material.</p> <p>Waste Disposal: Reclaim, if possible, since material may be used as an absorbent for liquid spills. Otherwise, dispose of in accordance with all applicable federal, state, and local regulations.</p>	<p>Stable under normal use and storage conditions.</p>												
VIII Fire and Explosion Data	IX Physical Data												
<p>Not flammable or explosive.</p>	<p>Bulk density (g/cm³)..... ~1.1</p> <p>Solubility in water..... Insoluble</p>												